




Features:

- Compact overcurrent protectors are designed to protect audio speaker systems, amplifiers and power supplies from internal overcurrents
- High current accuracy
- Protection against excessive temperature
- Snap action
- Automatic reset type
- Long life
- PBT resin enclosure
- Reliable
- Two mounting options

Specifications:

Voltage Rating	: 250V AC
No. of Poles	: 1
Breaking Capacity Current	: 20AAC
External Depth	: 6mm
External Length / Height	: 22mm
External Width	: 12.6mm
Fixing Centres L × W	: 7.5mm × 2.3mm
Mounting Type	: PCB
Overload Capability	: <7S
Pin Diameter	: 1mm
Trip Time	: 30s




Dimensions : Millimetres

Normal




Stage 1

Trip




Stage 2

Reset



Stage 3

Circuit Breaker



Part Number Table

Description	Rated Hold Current (A)	Max. Voltage (V)	Trip Time		Internal Resistance (mΩ)	Max. Interrupt Current (A)	Part Number
			200%	300%			
	AC at 25°C		Overload Current				
Circuit Breaker	1	250	Within 30Sec	Within 5Sec	<150	20	AN-101(FC67200)
	1.6				<0		AN-161(FC67203)
	2.5				<75	25	AN-251(FC67207)
	3				<35	30	AN-301(FC67209)
	5				<30	50	AN-501(FC67211)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.