

9773 Multi-Conductor - Audio, Control and Instrumentation Cable

**Description:**

18 AWG stranded (19x30) TC conductors, polypropylene insulation, twisted pairs, individually shielded w/Beldfoil® (100% coverage), 20 AWG stranded TC drain wire, PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
3	18	19x30	TC - Tinned Copper

Insulation**Insulation Material:**

Insulation Material
PP - Polypropylene

Inner Shield**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
20

Inner Shield Drain Wire Stranding: Stranded

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.404 in.

Pair**Pair Color Code Chart:**

Number	Color
1	Black & Red
2	Black & White
3	Black & Green

Pair Lay Length & Direction:

Lay Length (in.)
1.750

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +80°C

UL Temperature Rating: 80°C (UL AWM Style 2919)

Bulk Cable Weight: 83 lbs/1000 ft.

9773 Multi-Conductor - Audio, Control and Instrumentation Cable

Max. Recommended Pulling Tension:	177 lbs.
-----------------------------------	----------

Min. Bend Radius (Install)/Minor Axis:	3.750 in.
--	-----------

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2919 (30 V 80°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL 1685 UL Loading
----------------	--------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

Impedance (Ohm)

50

Nom. Inductance:

Inductance (μH/ft)

.18

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

30

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

55

Nominal Velocity of Propagation:

VP (%)

66

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.4

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C:	8.300 Ohm/1000 ft
---	-------------------

Max. Operating Voltage - UL:

Voltage

30 V RMS (UL AWM Style 2919)

300 V RMS (CM)

Max. Recommended Current:

Current

3.64 Amps per conductor @ 25°C

9773 Multi-Conductor - Audio, Control and Instrumentation Cable

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9773 060100	100 FT	9.400 LB	CHROME		3 FS PR #18 PP PVC
9773 0601000	1,000 FT	93.000 LB	CHROME	C	3 FS PR #18 PP PVC
9773 060500	500 FT	45.500 LB	CHROME	C	3 FS PR #18 PP PVC

Introduction

Belden® paired cable products are manufactured in a variety of gage sizes, dimensions, insulation materials, shielding configurations, and jacketing materials including Plenum and High-Temperature versions to meet the technical requirements of many different types of systems.

Paired cables allow balanced signal transmission, which results in lower crosstalk through common mode rejection. Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables.

As an aid to proper cable selection, both the suggested working voltages and the maximum temperature ratings are indicated for each applicable paired cable selection.


Most of our paired cables are available from stock. Many of these are available off the shelf from distributors. If you have a new or unusual application or you cannot find a paired cable in this catalog section that meets your technical requirements, contact Technical Support at 1-800-BELDEN-1.

Paired Cables Packaging


Belden's unique UnReel® cable dispenser is available for many of the paired cable products listed in this section. The letter "U" before the specified put-up length denotes UnReel packaging.

Individually Shielded

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
20 AWG Stranded (7x28) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 22 AWG Stranded TC Drain Wire																		
Polypropylene Insulation • Overall Chrome PVC Jacket																		
 Z-Fold®	9873	NEC:	3	See Chart 3 (Tech Info Section)	100	30.5	6.6	3.0	10.5Ω/M'	14.0Ω/M'	.341	8.66	50	66%	30	98	55	180
		CM			250	76.2	14.5	6.6	34.4Ω/km	45.9Ω/km								
		CEC:			500	152.4	32.5	14.8										
		CM			1000	304.8	58.0	26.3										
	9874	NEC:	6	See Chart 3 (Tech Info Section)	100	30.5	10.3	4.7	10.5Ω/M'	11.3Ω/M'	.445	11.30	50	66%	30	98	55	180
		CM			250	76.2	29.0	13.2	34.4Ω/km	37.1Ω/km								
		CEC:			500	152.4	56.5	25.7										
		CM			1000	304.8	113.0	51.3										
	9875	NEC:	9	See Chart 3 (Tech Info Section)	100	30.5	17.7	8.1	10.5Ω/M'	11.3Ω/M'	.555	14.10	50	66%	30	98	55	180
		CM			500	152.4	97.0	44.0	34.4Ω/km	37.1Ω/km								
CEC:		1000			304.8	187.0	88.4											
CM																		
9876	NEC:	11	See Chart 3 (Tech Info Section)	1000	304.8	220.0	100.0	10.5Ω/M'	11.3Ω/M'	.600	15.24	50	66%	30	98	55	180	
	CM																	
	CEC:																	
	CM																	
9877	NEC:	12	See Chart 3 (Tech Info Section)	100	30.5	22.1	10.1	10.5Ω/M'	11.3Ω/M'	.617	15.67	50	66%	30	98	55	180	
	CM			500	152.4	119.0	54.1	34.4Ω/km	37.1Ω/km									
	CEC:			1000	304.8	237.0	107.7											
	CM																	
9879	NEC:	15	See Chart 3 (Tech Info Section)	500	152.4	146.0	66.4	10.5Ω/M'	11.3Ω/M'	.689	17.50	50	66%	30	98	55	180	
	CM			1000	304.8	296.0	134.5	34.4Ω/km	37.1Ω/km									
	CEC:																	
	CM																	

18 AWG Stranded (19x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil (100% Coverage) • 20 AWG Stranded TC Drain Wire

Polypropylene Insulation • Chrome PVC Jacket																		
UL AWM Style 2919 (30V 80°C) 	9773	NEC:	3	See Chart 3 (Tech Info Section)	100	30.5	10.8	4.9	6.4 Ω /M'	8.3 Ω /M'	.404	10.26	50	66%	30	98	55	180
		CM			500	152.4	52.5	23.8	21.0 Ω /km	27.2 Ω /km								
		CEC:			1000	304.8	107.0	48.6										
		CM																
		NEC:			100	30.5	16.1	7.3	6.4 Ω /M'	8.3 Ω /M'	.560	14.22						
		CM			500	152.4	89.5	40.9	21.0 Ω /km	27.2 Ω /km								
	9774	CEC:			1000	304.8	176.0	80.8										
		CM																
	9775	NEC:	9	See Chart 3 (Tech Info Section)	100	30.5	25.8	11.7	6.4 Ω /M'	8.3 Ω /M'	.655	16.64	50	66%	30	98	55	180
		CM			500	152.4	123.0	55.8	21.0 Ω /km	27.2 Ω /km								
		CEC:			1000	304.8	241.0	109.4										
		CM																
		NEC:			100	30.5	31.6	14.4	6.4 Ω /M'	8.3 Ω /M'	.735	18.67						
		CM			500	152.4	151.5	69.0	21.0 Ω /km	27.2 Ω /km								
	9776	CEC:			1000	304.8	307.0	139.4										
		CM																
	9777	NEC:	15	See Chart 3 (Tech Info Section)	100	30.5	38.8	17.6	6.4 Ω /M'	8.3 Ω /M'	.819	20.80	50	66%	30	98	55	180
		CM			500	152.4	194.0	88.1	21.0 Ω /km	27.2 Ω /km								
		CEC:			1000	304.8	421.0	191.1										
		CM																
		NEC:																
		CM																

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.