


Date	Rev.	Description



F32 TYPE



ITEM NO.	AS SUPPLIED		AFTER SHRINKAGE	
	D	W	d	w
F32-1	1.4±0.2	0.2	0.5	0.33
F32-1.5	2.0±0.2	0.2	0.75	0.36
F32-2	2.5±0.2	0.2	1.0	0.44
F32-2.5	3.0±0.2	0.25	1.25	0.44
F32-3	3.5±0.3	0.25	1.5	0.44
F32-3.5	4.0±0.3	0.25	1.75	0.44
F32-4	4.5±0.3	0.25	2.0	0.44
F32-5	5.4±0.3	0.25	2.5	0.56
F32-6	6.4±0.4	0.25	3.0	0.56
F32-7	7.4±0.4	0.25	3.5	0.56
F32-8	8.4±0.4	0.25	4.0	0.56
F32-9	9.4±0.4	0.25	4.5	0.56
F32-10	10.4±0.4	0.25	5.0	0.56
F32-11	11.4±0.4	0.25	5.5	0.56
F32-12	12.4±0.4	0.25	6.0	0.56
F32-13	13.5±0.4	0.3	6.5	0.69
F32-14	14.5±0.4	0.3	7.0	0.69
F32-15	15.5±0.5	0.3	7.5	0.69
F32-16	16.8±0.5	0.3	8.0	0.69
F32-18	18.7±0.5	0.35	9.0	0.77
F32-20	21.2±0.6	0.35	10.0	0.77
F32-22	23.2±0.6	0.4	11.0	0.77
F32-25	26.1±0.8	0.4	12.5	0.87
F32-28	29.0±1.0	0.45	14.0	0.87
F32-30	32.0±1.0	0.5	15.0	0.87

DCC. NO.
A4 DRAWING NO.

MATERIAL		GOLDSUN ELECTRONICS CO., LTD.			
DRAWN: Kiki Chen		JAMECO NO. 645001		GOLDSUN NO. F32-15-BLK 100	
VERIFY PEOPLE: Ada Zheng , Ivy Lan		Description HEAT SHRINK , BLACK			Rev. 1
		UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No: