


# Thick Film Chip Resistors

## MCR Series < Automotive >

### ●Features

- 1) Full line up from ultra small size (01005) to 2512 with jumper type.
- 2) High reliability metal glazed thick film.
- 3) ROHM resistors have obtained ISO9001/ISO/TS16949 certification.
- 4) "Automotive" product is AEC-Q200 compliant.



| Part No. | Size |        | Type Code                                                                                    |                                        | Packing Specification                            | Quantity / Reel               |
|----------|------|--------|----------------------------------------------------------------------------------------------|----------------------------------------|--------------------------------------------------|-------------------------------|
|          | (mm) | (inch) | GENERAL PURPOSE                                                                              | AUTOMOTIVE<br>*Corresponds to AEC-Q200 |                                                  |                               |
| MCR004   | 0402 | 01005  | YZP                                                                                          | —                                      | Paper tape (2mm pitch)                           | 15,000                        |
|          |      |        | RZP                                                                                          | —                                      | Embossed tape (1mm pitch)                        | 40,000                        |
| MCR006   | 0603 | 0201   | YRT                                                                                          | YZP                                    | Paper tape (2mm pitch)                           | 15,000                        |
| MCR01    | 1005 | 0402   | MRT                                                                                          | MZP                                    |                                                  | 10,000                        |
|          |      |        | PZPI<br>(*For further information on datasheet, please refer to AUTOMOTIVE datasheet.)       |                                        | Bulk case                                        | 50,000                        |
| MCR03    | 1608 | 0603   | ERT                                                                                          | EZP                                    | Paper tape (4mm pitch)                           | 5,000                         |
|          |      |        | MZP / PZPI<br>(*For further information on datasheet, please refer to AUTOMOTIVE datasheet.) |                                        | MZP : Paper tape (2mm pitch)<br>PZPI : Bulk case | MZP : 10,000<br>PZPI : 25,000 |
| MCR10    | 2012 | 0805   | ERT                                                                                          | EZP                                    | Paper tape (4mm pitch)                           | 5,000                         |
| MCR18    | 3216 | 1206   | ERT                                                                                          | EZP                                    |                                                  |                               |
| MCR25    | 3225 | 1210   | JZH                                                                                          |                                        | Embossed tape (4mm pitch)                        | 4,000                         |
| MCR50    | 5025 | 2010   | JZH                                                                                          |                                        |                                                  |                               |
| MCR100   | 6432 | 2512   | JZH                                                                                          |                                        |                                                  |                               |

\*Please contact us for status of AEC-Q200 on "General purpose" products.

### ●Part Number Description

| Part No.                             | Size (mm [inch])                                                                                                                                                                     | Type Code | Resistance Tolerance                                                                        | Nominal Resistance                                                                                                                                                                                                                                                 |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>MCR</b><br>(Micro chip resistors) | 004 (0402 [01005])<br>006 (0603 [0201])<br>01 (1005 [0402])<br>03 (1608 [0603])<br>10 (2012 [0805])<br>18 (3216 [1206])<br>25 (3225 [1210])<br>50 (5025 [2010])<br>100 (6432 [2512]) | YRT<br>J  | D (±0.5%)<br>F (±1%)<br>FX (±1%) *Only MCR03EZP/MZP/PZPI<br>J (±5%) (Including jumper type) | Resistance code, 3 or 4 digits.<br>000 denotes jumper type.<br>Resistance tolerance<br>Resistance code<br>D, F : 4 digits<br>J : 3 digits<br>Ex.)<br>1Ω = 1R0 (±5%)<br>9.1Ω = 9R1 (±5%)<br>10Ω = 10R0 (±0.5%, ±1%)<br>100 (±5%)<br>2.2MΩ = 2204 (±1%)<br>225 (±5%) |

## ●Products List


| Part No.                                  | Type Code          | Rated Power<br>(70°C)<br>(W) | Limiting Element<br>Voltage<br>(V) | Maximum<br>Overload<br>Voltage<br>(V) | Temperature<br>Coefficient<br>(ppm / °C) | Resistance<br>Tolerance<br>(%) | Resistance Range                                               | Series  | Operating<br>Temperature<br>Range<br>(°C) |
|-------------------------------------------|--------------------|------------------------------|------------------------------------|---------------------------------------|------------------------------------------|--------------------------------|----------------------------------------------------------------|---------|-------------------------------------------|
| MCR006                                    | YZP                | 0.05                         | 25                                 | —                                     | +600 / -200<br>±250                      | J(±5%)                         | 1.0Ω to 9.1Ω<br>10Ω to 10MΩ                                    | E24     | -55 to +125                               |
|                                           |                    |                              |                                    |                                       | ±250                                     | F(±1%)                         | 10Ω to 10MΩ                                                    |         |                                           |
|                                           |                    |                              |                                    |                                       | ±200                                     | D(±0.5%)                       | 10Ω to 910Ω<br>1kΩ to 1MΩ                                      |         |                                           |
|                                           |                    |                              |                                    |                                       | ±100                                     |                                |                                                                |         |                                           |
| Jumper type : Rmax = 50m Ω / Imax. = 0.5A |                    |                              |                                    |                                       |                                          |                                |                                                                |         |                                           |
| MCR01                                     | MZP<br>PZPI        | 0.063                        | 50                                 | —                                     | +500 / -250<br>±200                      | J(±5%)                         | 1.0Ω to 9.1Ω<br>10Ω to 10MΩ                                    | E24     |                                           |
|                                           |                    |                              |                                    |                                       | ±100                                     | F(±1%)                         | 10Ω to 2.2MΩ                                                   | E24,E96 |                                           |
|                                           |                    |                              |                                    |                                       | ±100<br>±50                              | D(±0.5%)                       | 10Ω to 91Ω<br>100Ω to 1MΩ                                      | E24     |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 1A  |                                |                                                                |         |                                           |
| MCR03                                     | EZP<br>MZP<br>PZPI | 0.1                          | 50                                 | 100                                   | ±400<br>±200                             | J(±5%)                         | 1.0Ω to 9.1Ω<br>10Ω to 10MΩ                                    | E24     |                                           |
|                                           |                    |                              |                                    |                                       | ±100                                     | FX(±1%)                        | 10Ω to 10MΩ                                                    | E24,E96 |                                           |
|                                           |                    |                              |                                    |                                       | ±100<br>±50                              | D(±0.5%)                       | 10Ω to 91Ω<br>100Ω to 1MΩ                                      |         |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 1A  |                                |                                                                |         |                                           |
| MCR10                                     | EZP                | 0.125                        | 150                                | 200                                   | ±400<br>±200                             | J(±5%)                         | 1.0Ω to 9.1Ω<br>10Ω to 10MΩ                                    | E24     |                                           |
|                                           |                    |                              |                                    |                                       | ±100                                     | F(±1%)                         | 10Ω to 2.2MΩ                                                   | E24,E96 |                                           |
|                                           |                    | 0.1                          |                                    | 300                                   | ±100<br>±50                              | D(±0.5%)                       | 10Ω to 91Ω<br>100Ω to 1MΩ                                      |         |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 2A  |                                |                                                                |         |                                           |
| MCR18                                     | EZP                | 0.25                         | 200                                | 400                                   | ±400<br>±200                             | J(±5%)                         | 1.0Ω to 9.1Ω<br>10Ω to 10MΩ                                    | E24     | -55 to +155                               |
|                                           |                    |                              |                                    |                                       | ±100                                     | F(±1%)                         | 10Ω to 2.2MΩ                                                   | E24,E96 |                                           |
|                                           |                    | 0.125                        |                                    |                                       | ±100<br>±50                              | D(±0.5%)                       | 10Ω to 91Ω<br>100Ω to 1MΩ                                      |         |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 2A  |                                |                                                                |         |                                           |
| MCR25                                     | JZH                | 0.25                         | 200                                | 400                                   | 500±350<br>±500<br>±200                  | J(±5%)                         | 1.0Ω to 2.0Ω<br>2.2Ω to 5.1Ω<br>5.6Ω to 3.3MΩ                  | E24     |                                           |
|                                           |                    |                              |                                    |                                       | ±100                                     | F(±1%)                         | 10Ω to 1MΩ                                                     | E24,E96 |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 2A  |                                |                                                                |         |                                           |
|                                           |                    |                              |                                    |                                       |                                          |                                |                                                                |         |                                           |
| MCR50                                     | JZH                | 0.5                          | 200                                | 400                                   | 500±350<br>±500<br>±200<br>±350          | J(±5%)                         | 1.0Ω to 2.0Ω<br>2.2Ω to 9.1Ω<br>10Ω to 330kΩ<br>360kΩ to 560kΩ | E24     |                                           |
|                                           |                    |                              |                                    |                                       | ±100                                     | F(±1%)                         | 10Ω to 180kΩ                                                   | E24,E96 |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 3A  |                                |                                                                |         |                                           |
|                                           |                    |                              |                                    |                                       |                                          |                                |                                                                |         |                                           |
| MCR100                                    | JZH                | 1                            | 200                                | 400                                   | 500±350<br>±500<br>±350<br>±200          | J(±5%)                         | 1.0Ω to 2.0Ω<br>2.2Ω to 9.1Ω<br>10Ω to 22Ω<br>24Ω to 100kΩ     | E24     | -55 to +125                               |
|                                           |                    |                              |                                    |                                       | ±100                                     | F(±1%)                         | 10Ω to 82kΩ                                                    | E24,E96 |                                           |
|                                           |                    |                              |                                    |                                       | Jumper type : Rmax = 50m Ω / Imax. = 4A  |                                |                                                                |         |                                           |
|                                           |                    |                              |                                    |                                       |                                          |                                |                                                                |         |                                           |

\*Design and specifications are subject to change without notice. Carefully check the specification sheet supplied with the product before using or ordering it.

## ●Chip Resistor Dimensions and Markings

■ MCR004 / 006 / 01 / 03

■ MCR10 / 18 / 25 / 50 / 100



&lt;Marking method&gt;

There are three or four digits used for the calculation number according to IEC code and "R" is used for the decimal point.

(Unit : mm)

| Part No.      | Type Code          | (mm) | (inch) | L        | W        | t         | a        | b                                     | Marking existence |
|---------------|--------------------|------|--------|----------|----------|-----------|----------|---------------------------------------|-------------------|
| <b>MCR006</b> | YZP                | 0603 | 0201   | 0.6±0.03 | 0.3±0.03 | 0.23±0.03 | 0.1±0.05 | 0.15±0.05                             | No                |
| <b>MCR01</b>  | MZP<br>PZPI        | 1005 | 0402   | 1.0±0.05 | 0.5±0.05 | 0.35±0.05 | 0.2±0.1  | 0.25 <sup>+0.05</sup> <sub>-0.1</sub> | No                |
| <b>MCR03</b>  | EZP<br>MZP<br>PZPI | 1608 | 0603   | 1.6±0.1  | 0.8±0.1  | 0.45±0.1  | 0.3±0.2  | 0.3±0.2                               | Yes *             |
| <b>MCR10</b>  | EZP                | 2012 | 0805   | 2.0±0.1  | 1.25±0.1 | 0.55±0.1  | 0.4±0.2  | 0.4±0.2                               | Yes               |
| <b>MCR18</b>  | EZP                | 3216 | 1206   | 3.2±0.15 | 1.6±0.15 | 0.55±0.1  | 0.5±0.25 | 0.5±0.25                              | Yes               |
| <b>MCR25</b>  | JZH                | 3225 | 1210   | 3.2±0.15 | 2.5±0.15 | 0.55±0.15 | 0.5±0.25 | 0.5±0.25                              | Yes               |
| <b>MCR50</b>  | JZH                | 5025 | 2010   | 5.0±0.15 | 2.5±0.15 | 0.55±0.15 | 0.6±0.25 | 0.6±0.25                              | Yes               |
| <b>MCR100</b> | JZH                | 6432 | 2512   | 6.3±0.15 | 3.2±0.15 | 0.55±0.15 | 0.6±0.25 | 0.6±0.25                              | Yes               |

Marking method of jumper type

| Jumper type                 | Marking existence |
|-----------------------------|-------------------|
| MCR006 / 01 / 25 / 50 / 100 | No                |
| MCR03 / 10 / 18             | Yes               |

\*Marking method of MCR03

For MCR03 series resistors, the printing process restricts the marking to three digits/characters.

Consequently, 1% tolerance resistors with values from the E24 series will be marked the same as

5% resistors with the same value, but 1% tolerance resistors with values from the E96 series will not be marked.

Examples:

MCR03EZPJ243 (5% tolerance, E24 / 24 k Ω ) Marking = 243

MCR03EZPF2402 (1% tolerance, E24 / 24 k Ω ) Marking = 243


MCR03EZPF2432 (1% tolerance, E96 / 24.3 k Ω ) No Marking

MCR18EZPJ243 (5% tolerance, E24 / 24 k Ω ) Marking = 243

MCR18EZPF2402 (1% tolerance, E24 / 24 k Ω ) Marking = 2402

MCR18EZPF2432 (1% tolerance, E96 / 24.3 k Ω ) Marking = 2432

## ●Land pattern Example





(Unit : mm)

| Dimensions<br>Part No. | Type Code          | A   | B    | C    | D    |
|------------------------|--------------------|-----|------|------|------|
| <b>MCR006</b>          | YZP                | 0.3 | 0.84 | 0.3  | 0.27 |
| <b>MCR01</b>           | MZP<br>PZPI        | 0.5 | 1.3  | 0.5  | 0.4  |
| <b>MCR03</b>           | EZP<br>MZP<br>PZPI | 1.0 | 2.0  | 0.8  | 0.5  |
| <b>MCR10</b>           | EZP                | 1.2 | 2.6  | 1.15 | 0.7  |
| <b>MCR18</b>           | EZP                | 2.2 | 4.0  | 1.5  | 0.9  |
| <b>MCR25</b>           | JZH                | 2.2 | 4.0  | 2.3  | 0.9  |
| <b>MCR50</b>           | JZH                | 3.8 | 6.0  | 2.3  | 1.1  |
| <b>MCR100</b>          | JZH                | 5.1 | 8.1  | 3.0  | 1.5  |

## Derating Curve

When the ambient temperature exceeds 70°C, power dissipation must be adjusted according to the derating curves below.



## Characteristics

| Test Items                               | Guaranteed Value                                                                               |             | Test Conditions                                                                                                  |
|------------------------------------------|------------------------------------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------------------|
|                                          | Resistor Type                                                                                  | Jumper Type |                                                                                                                  |
| Resistance                               | See "Products List"                                                                            |             | 20°C                                                                                                             |
| Variation of resistance with temperature | See "Products List"                                                                            |             | Measurement : +20 / -55 / +20 / +125°C                                                                           |
| Overload                                 | ± (2.0%+0.1Ω)                                                                                  | Max. 50mΩ   | Rated voltage (current) ×2.5, 2s.<br>Maximum overload voltage                                                    |
| Solderability                            | A new uniform coating of minimum of 95% of the surface being immersed and no soldering damage. |             | Rosin-Ethanol : 25% (Weight)<br>Soldering condition : 235±5°C<br>Duration of immersion : 2.0±0.5s                |
| Resistance to soldering heat             | ± (1.0%+0.05Ω)<br>No remarkable abnormality on the appearance.                                 | Max. 50mΩ   | Soldering condition : 260±5°C<br>Duration of immersion : 10±1s                                                   |
| Rapid change of temperature              | ± (1.0%+0.05Ω)                                                                                 | Max. 50mΩ   | Test temp.<br>-55°C to +125°C 100cycle (MCR006 / 01 / 03)<br>-55°C to +125°C 5cycle (MCR10 / 18 / 25 / 50 / 100) |
| Damp heat, steady state                  | ± (3.0%+0.1Ω)                                                                                  | Max. 100mΩ  | 40°C, 93%RH (Relative Humidity)<br>Test time : 1,000h to 1,048h                                                  |
| Endurance at 70°C                        | ± (3.0%+0.1Ω)                                                                                  | Max. 100mΩ  | 70°C<br>Rated voltage (current)<br>1.5h : ON – 0.5h : OFF<br>Test time : 1,000h to 1,048h                        |
| Endurance                                | ± (3.0%+0.1Ω)                                                                                  | Max. 100mΩ  | 125°C (MCR006 / 25 / 50 / 100)<br>155°C (MCR01 / 03 / 10 / 18)<br>Test time : 1,000h to 1,048h                   |
| Resistance to solvent                    | ± (1.0%+0.05Ω)                                                                                 | Max. 50mΩ   | 23±5°C, Immersion cleaning, 5±0.5min<br>Solvent : 2-propanol                                                     |
| Bend strength of the end face plating    | ± (1.0%+0.05Ω)<br>Without mechanical damage such as breaks.                                    | Max. 50mΩ   | —                                                                                                                |


Compliance Standard(s) : IEC60115-8  
JISC 5201-8

## Technical data

| Parameter             | Unit  | MCR006<br>YZP | MCR01<br>MZP / PZPI | MCR03<br>EZP / MZP / PZPI | MCR10<br>EZP | MCR18<br>EZP | MCR25<br>JZH | MCR50<br>JZH | MCR100<br>JZH |
|-----------------------|-------|---------------|---------------------|---------------------------|--------------|--------------|--------------|--------------|---------------|
| Insulation resistance | MΩ    | 1000          | 1000                | 1000                      | 1000         | 1000         | 1000         | 1000         | 1000          |
| Failure rate          | Fit   | 0.0016        | 0.0002              | 0.0009                    | 0.0015       | 0.0018       | 0.0203       | 0.0201       | 0.0586        |
| Weight                | mg/pc | 0.157         | 0.70                | 2.12                      | 5.03         | 9.46         | 16.5         | 25.8         | 42.0          |

## ●Tape Dimensions

## ■ Paper Tape




(Unit : mm)

| Part No.      | Type Code | W       | F        | E        | A0                                    | B0                                    |
|---------------|-----------|---------|----------|----------|---------------------------------------|---------------------------------------|
| <b>MCR006</b> | YZP       | 8.0±0.2 | 3.5±0.05 | 1.75±0.1 | 0.38±0.03                             | 0.68±0.03                             |
| <b>MCR01</b>  | MZP       | 8.0±0.3 | 3.5±0.05 | 1.75±0.1 | 0.7±0.1                               | 1.2±0.1                               |
| <b>MCR03</b>  | EZP       | 8.0±0.3 | 3.5±0.05 | 1.75±0.1 | 1.1±0.1                               | 1.9±0.1                               |
| <b>MCR10</b>  | EZP       | 8.0±0.3 | 3.5±0.05 | 1.75±0.1 | 1.65 <sup>+0.2</sup> <sub>-0.1</sub>  | 2.4 <sup>+0.2</sup> <sub>-0.1</sub>   |
| <b>MCR18</b>  | EZP       | 8.0±0.3 | 3.5±0.05 | 1.75±0.1 | 1.95 <sup>+0.1</sup> <sub>-0.05</sub> | 3.5 <sup>+0.15</sup> <sub>-0.05</sub> |

| Part No.      | Type Code | D0                                | P0      | P1       | P2       | T2      |
|---------------|-----------|-----------------------------------|---------|----------|----------|---------|
| <b>MCR006</b> | YZP       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 2.0±0.05 | 2.0±0.05 | Max 0.5 |
| <b>MCR01</b>  | MZP       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 2.0±0.05 | 2.0±0.05 | Max 1.1 |
| <b>MCR03</b>  | EZP       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 4.0±0.1  | 2.0±0.05 | Max 1.1 |
| <b>MCR10</b>  | EZP       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 4.0±0.1  | 2.0±0.05 | Max 1.1 |
| <b>MCR18</b>  | EZP       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 4.0±0.1  | 2.0±0.05 | Max 1.1 |


## ■ Paper Tape (Narrow pitch taping)



(Unit : mm)

| Part No.     | Type Code | W                                 | F        | E        | A0       | B0      |
|--------------|-----------|-----------------------------------|----------|----------|----------|---------|
| <b>MCR03</b> | MZP       | 8.0±0.3                           | 3.5±0.05 | 1.75±0.1 | 1.1±0.1  | 1.9±0.1 |
|              |           | D0                                | P0       | P1       | P2       | T2      |
|              |           | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1  | 2.0±0.5  | 2.0±0.05 | Max 1.1 |

## ■ Embossed Tape




(Unit : mm)

| Part No.      | Type Code | W       | F        | E        | A0      | B0      |
|---------------|-----------|---------|----------|----------|---------|---------|
| <b>MCR25</b>  | JZH       | 8.0±0.3 | 3.5±0.05 | 1.75±0.1 | 3.0±0.1 | 3.5±0.1 |
| <b>MCR50</b>  | JZH       | 12±0.3  | 5.5±0.05 | 1.75±0.1 | 3.4±0.2 | 5.6±0.2 |
| <b>MCR100</b> | JZH       | 12±0.3  | 5.5±0.05 | 1.75±0.1 | 3.5±0.2 | 6.7±0.2 |

| Part No.      | Type Code | D0                                | P0      | P1      | P2       | T2      |
|---------------|-----------|-----------------------------------|---------|---------|----------|---------|
| <b>MCR25</b>  | JZH       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 4.0±0.1 | 2.0±0.05 | Max 1.1 |
| <b>MCR50</b>  | JZH       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 4.0±0.1 | 2.0±0.05 | Max 1.1 |
| <b>MCR100</b> | JZH       | φ1.5 <sup>+0.1</sup> <sub>0</sub> | 4.0±0.1 | 4.0±0.1 | 2.0±0.05 | Max 1.1 |

## ●Reel Dimensions




(Unit : mm)

| Part No. | Type Code | A                                                          | B                                                         | C                                                    | D                 |  |
|----------|-----------|------------------------------------------------------------|-----------------------------------------------------------|------------------------------------------------------|-------------------|--|
| MCR006   | YZP       | $\phi 180 \begin{smallmatrix} 0 \\ -1.5 \end{smallmatrix}$ | $\phi 60 \begin{smallmatrix} +1.0 \\ 0 \end{smallmatrix}$ | $9 \begin{smallmatrix} +1.0 \\ 0 \end{smallmatrix}$  | $\phi 13 \pm 0.2$ |  |
| MCR01    | MZP       |                                                            |                                                           |                                                      |                   |  |
| MCR03    | EZP       |                                                            |                                                           |                                                      |                   |  |
|          | MZP       |                                                            |                                                           |                                                      |                   |  |
| MCR10    | EZP       |                                                            |                                                           |                                                      |                   |  |
| MCR18    | EZP       |                                                            |                                                           |                                                      |                   |  |
| MCR25    | JZH       |                                                            |                                                           | $13 \begin{smallmatrix} +1.0 \\ 0 \end{smallmatrix}$ |                   |  |
| MCR50    | JZH       |                                                            |                                                           |                                                      |                   |  |
| MCR100   | JZH       |                                                            |                                                           |                                                      |                   |  |

## ●Bulk case Dimensions

- MCR01PZPI
- MCR03PZPI



## Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations.  
More detail product informations and catalogs are available, please contact us.

### ROHM Customer Support System

<http://www.rohm.com/contact/>

