


# Advantech WebAccess

## Browser-based HMI/SCADA Software



### Features

- View, control, configure system remotely over an intranet or the Internet using ordinary Web browser
- Supports vector-based graphics
- Use the Open standard programming TCL, JScript or VB script
- Control equipment based on pre-defined schedule (time, date and holiday)
- Distributed SCADA architecture
- Central Database Server
- Redundant SCADA and COM ports
- Global access to alarms & data
- Support LonWorks LNS and BACnet IP
- Email alarm, report and message
- Customized functional toolbox
- Video and audio with animation

### Introduction

Advantech WebAccess is browser-based software package for human-machine interfaces (HMI), and supervisory control and data acquisition (SCADA). All the features found in conventional HMI and SCADA software packages are available in an ordinary browser including Animated Graphics Displays, Real-time Data Control, Trends, Alarms and Logs. WebAccess is based on standard internet architecture, its basic component includes:

1. SCADA Node: it communicates in real-time with automation equipments and control the equipment via Serial, Ethernet or proprietary communications. The SCADA Node can provide supervisory control and data acquisition functions, includes supplying communication driver (Modbus, PLC, and I/O systems), real-time and historical trending. It also can monitor and log alarm and event. The SCADA Node has its own run-time database and all graphics.
2. Project Node: it is the developing platform for WebAccess, and all system configuration and project development is implemented on the Project Node. It is a web server for all Client and SCADA node to connect with.
3. Client: through an ActiveX control inside Internet Explorer Web browser, it has the ability to monitor and control the SCADA Node simultaneously. The Client connects to the Project Node only to get the address of the SCADA Node. The Client then communicates directly with the SCADA Node using proprietary communications over a TCP/IP network connection. Data is displayed in real-time with dynamically updated graphics, and user can monitor real-time and historical trending with alarm record. Besides, user can acknowledge alarms and change setpoints, status and other data.
4. Thin Client: The Thin Client interface is intended for use with PDA, Pocket PCs and Handheld computers. Other ASP enabled web browsers can view the thin client graphics. Thin Client interface supplies static snapshots of dynamic graphics as GIFs and JPEGs. No plug-in or ActiveX control is required. Real-time Data, Alarms and changes to data are through a text type interface. Thin Client has been tested with the iPAQ series of pocket PCs. The thin client does not communicate with the SCADA node directly. The Thin Client communicates directly to the Project Node (Web Server).

### Features

#### Web Browser Client to View and Control

Using a standard Web browser, users can view and control automation equipment used in industrial, manufacturing, process and building automation systems. Data is displayed to users in real-time with dynamically updated graphics using full-motion animation.

#### Powerful Remote Diagnose and Maintenance Functionality

The unique feature, which distinguishes WebAccess from the competition, is that all engineering project, configuration, graphics building (DRAW) and software management (download, start and restart remote nodes) is performed using a standard Web browser. If there is any troubleshooting needed, no matter wherever the operator is located, he can use the standard internet to operate the system. This can significantly increase the efficiency of maintenance operation and reduce the maintenance cost.

#### Vector-based Graphics

WebAccess features Vector-based graphics. Vector-based graphics provide smaller file sizes and faster download. Because Vector-based graphics use mathematic algorithm to save image, its file size is much smaller than Bitmap graphics. Therefore it is much faster to transfer Vector-based graphics on internet. Besides, WebAccess features user interface self-adaptive adjustment technology, no matter how user adjust the screen ratio of monitor, WebAccess can ensure all the user interface will be displayed on the screen. When the resolution of screen increases, the display performance will also become better respectively.

#### Import BMP, JPEG and GIF

Except Vector-based graphics, WebAccess also supports the most popular BMP, JPEG and GIF Bitmap format file, and user can zoom in or zoom out these image as well as animation configurations. WebAccess also provides build-in animation image libraries.

#### Import AutoCAD DXF

WebAccess environment is similar to AutoCAD, and this can make engineer who is familiar with AutoCAD get used to WebAccess in short time. Users can even import the DXF format file into WebAccess. Users can edit the imported data and decide the animation configuration.

#### Scripts Using TCL, Java Script or VB Script

Scripts in WebAccess use the open source programming languages TCL, Java Script or VB Script and allow users to develop customized actions, calculations and reports.

#### Scheduler

The Scheduler provides control and changes setpoint status based on time and date. Lights, Fans, and HVAC equipment are turned on and off based on the time, day of week and date. The Scheduler is also used in process control and manufacturing applications. All these schedule configurations can be modified remotely through internet.



### Central Database Server

## Redundant SCADA & COM Ports

## DDE, OPC and ODBC Interface

## Historical and Real-time Trend, Data and Centralized Logs

## Alarm

## Recipe Function

## Enhanced Security

## HTML Reports

## Excel Import/Export

## Email Alarms, Reports and Messages

## Customized Functional Toolbox

## Ordering Information

- **WAP-150-W60** WebAccess Win32 Professional V6.0 150 Tag
- **WAP-300-W60** WebAccess Win32 Professional V6.0 300 Tag
- **WAP-600-W60** WebAccess Win32 Professional V6.0 600 Tag
- **WAP-1200-W60** WebAccess Win32 Professional V6.0 1200 Tag
- **WAP-5000-W60** WebAccess Win32 Professional V6.0 5000 Tag
- **WAP-20K-W60** WebAccess Win32 Professional V6.0 20K Tag
- **WAP-99K-W60E** WebAccess Win32 Pro V6.0 99K Tag