

# LM3710/LM3711 Microprocessor Supervisory Circuits with Power Fail Input, Low Line Output, Manual Reset and Watchdog Timer

Check for Samples: [LM3710](#), [LM3711](#)


## FEATURES

- **Standard Reset Threshold Voltage: 3.08V**
- **Custom Reset Threshold Voltages: For other voltages between 2.2V and 5.0V in 10mV increments, contact TI**
- **No External Components Required**
- **Manual-Reset Input**
- **$\overline{\text{RESET}}$  (LM3710) or  $\overline{\text{RESET}}$  (LM3711) Outputs**
- **Precision Supply Voltage Monitor**
- **Factory Programmable Reset and Watchdog Timeout Delays**
- **Separate Power Fail Comparator**
- **Available in DSBGA Package for Minimum Footprint**
- **$\pm 0.5\%$  Reset Threshold Accuracy at Room Temperature**
- **$\pm 2\%$  Reset Threshold Accuracy Over Temperature Extremes**
- **Reset Assertion Down to 1V  $V_{CC}$  ( $\overline{\text{RESET}}$  Option Only)**
- **28  $\mu\text{A}$   $V_{CC}$  Supply Current**

## APPLICATIONS

- **Embedded Controllers and Processors**
- **Intelligent Instruments**
- **Automotive Systems**
- **Critical  $\mu\text{P}$  Power Monitoring**

## Typical Application



## DESCRIPTION

The LM3710/LM3711 series of microprocessor supervisory circuits provide the maximum flexibility for monitoring power supplies and battery controlled functions in systems without backup batteries. The LM3710/LM3711 series are available in VSSOP-10 and 9-bump DSBGA packages.

Built-in features include the following:

**Reset:** Reset is asserted during power-up, power-down, and brownout conditions.  $\overline{\text{RESET}}$  is ensured down to  $V_{CC}$  of 1.0V.

**Manual Reset Input:** An input that asserts reset when pulled low.

**Power-Fail Input:** A 1.225V threshold detector for power fail warning, or to monitor a power supply other than  $V_{CC}$ .

**Low Line Output:** This early power failure warning indicator goes low when the supply voltage drops to a value which is 2% higher than the reset threshold voltage.


**Watchdog Timer:** The WDI (Watchdog Input) monitors one of the  $\mu\text{P}$ 's output lines for activity. If no output transition occurs during the watchdog timeout period, reset is activated.




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

## Connection Diagram



**Figure 1. VSSOP-10**




**Figure 2. Top View  
(looking from the coating side)  
DSBGA 9 Bump Package**

## PIN DESCRIPTIONS

| Pin No. |       | Name                      | Function                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------|-------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DSBGA   | VSSOP |                           |                                                                                                                                                                                                                                                                                                                                                                                                             |
| A1      | 2     | $\overline{\text{MR}}$    | Manual-Reset input. When $\overline{\text{MR}}$ is less than $V_{\text{MRT}}$ (Manual Reset Threshold) $\overline{\text{RESET}}$ /RESET is engaged.                                                                                                                                                                                                                                                         |
| B1      | 1     | $V_{\text{CC}}$           | Power Supply input.                                                                                                                                                                                                                                                                                                                                                                                         |
| C1      | 10    | $\overline{\text{RESET}}$ | Reset Logic Output. Pulses low for $t_{\text{RP}}$ (Reset Timeout Period) when triggered, and stays low whenever $V_{\text{CC}}$ is below the reset threshold or when $\overline{\text{MR}}$ is below $V_{\text{MRT}}$ . It remains low for $t_{\text{RP}}$ after either $V_{\text{CC}}$ rises above the reset threshold, or after $\overline{\text{MR}}$ input rises above $V_{\text{MRT}}$ (LM3710 only). |
|         |       | RESET                     | Reset Logic Output. RESET is the inverse of $\overline{\text{RESET}}$ (LM3711 only).                                                                                                                                                                                                                                                                                                                        |
| C2      | 8     | $\overline{\text{PFO}}$   | Power-Fail Logic Output. When PFI is below $V_{\text{PFT}}$ , $\overline{\text{PFO}}$ goes low; otherwise, $\overline{\text{PFO}}$ remains high.                                                                                                                                                                                                                                                            |
| C3      | 7     | $\overline{\text{LLO}}$   | Low-Line Logic Output. Early Power-Fail warning output. Low when $V_{\text{CC}}$ falls below $V_{\text{LLOT}}$ (Low-Line Output Threshold). This output can be used to generate an NMI (Non-Maskable Interrupt) to provide an early warning of imminent power-failure.                                                                                                                                      |
| B3      | 5     | GND                       | Ground reference for all signals.                                                                                                                                                                                                                                                                                                                                                                           |
| A3      | 4     | WDI                       | Watchdog Input Transition Monitor: If no transition activity occurs for a period exceeding $t_{\text{WD}}$ (Watchdog Timeout Period), reset is engaged.                                                                                                                                                                                                                                                     |
| A2      | 3     | PFI                       | Power-Fail Comparator Input. When PFI is less than $V_{\text{PFT}}$ (Power-Fail Reset Threshold), the $\overline{\text{PFO}}$ goes low; otherwise, $\overline{\text{PFO}}$ remains high.                                                                                                                                                                                                                    |
| B2      | 6, 9  | NC                        | No Connect. Test input used at factory only. Leave floating.                                                                                                                                                                                                                                                                                                                                                |

## Block Diagram



## Table Of Functions

| Part Number | Active Low Reset | Active High Reset | Output (X = totem-pole) (Y = open-drain) | Reset Timeout Period | Watchdog Timeout Period | Manual Reset | Power Fail Comparator | Low Line Output |
|-------------|------------------|-------------------|------------------------------------------|----------------------|-------------------------|--------------|-----------------------|-----------------|
| LM3710      | x                |                   | X, Y <sup>(1)</sup>                      | Customized           | Customized              | x            | x                     | x               |
| LM3711      |                  | x                 | X                                        | Customized           | Customized              | x            | x                     | x               |

(1) Available upon request. Contact TI.



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

**Absolute Maximum Ratings**<sup>(1)(2)</sup>

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Supply Voltage (V <sub>CC</sub> ) | –0.3V to 6.0V                   |
| All Other Inputs                  | –0.3V to V <sub>CC</sub> + 0.3V |
| ESD Ratings <sup>(3)</sup>        |                                 |
| Human Body Model                  | 1.5kV                           |
| Machine Model                     | 150V                            |
| Power Dissipation                 | <sup>(4)</sup>                  |

- (1) **Absolute Maximum Ratings** indicate limits beyond which damage to the device may occur. **Operating Ratings** indicate conditions for which the device is intended to be functional, but do not ensure specific performance limits. For ensured specifications and test conditions, see the Electrical Characteristics. The ensured specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed conditions.
- (2) If Military/Aerospace specified devices are required, please contact the Texas Instruments Sales Office/Distributors for availability and specifications.
- (3) The Human Body model is a 100 pF capacitor discharged through a 1.5 kΩ resistor into each pin. The machine model is a 200pF capacitor discharged directly into each pin.
- (4) The maximum allowable power dissipation is a function of the maximum junction temperature, T<sub>J</sub>(MAX), the junction-to-ambient thermal resistance, θ<sub>J-A</sub>, and the ambient temperature, T<sub>A</sub>. The maximum allowable power dissipation at any ambient temperature is calculated using:
- $$P_{(MAX)} = \frac{T_J(MAX) - T_A}{\theta_{J-A}}$$

Where the value of θ<sub>J-A</sub> for the VSSOP-10 package is 195°C/W in a typical PC board mounting and the DSBGA package is 220°C/W.

**Operating Ratings**<sup>(1)</sup>

|                   |                               |
|-------------------|-------------------------------|
| Temperature Range | –40°C ≤ T <sub>J</sub> ≤ 85°C |
|-------------------|-------------------------------|

- (1) **Absolute Maximum Ratings** indicate limits beyond which damage to the device may occur. **Operating Ratings** indicate conditions for which the device is intended to be functional, but do not ensure specific performance limits. For ensured specifications and test conditions, see the Electrical Characteristics. The ensured specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed conditions.

**LM3710/LM3711 Series Electrical Characteristics**

Limits in the standard typeface are for T<sub>J</sub> = 25°C and limits in **boldface type** apply over full operating range. Unless otherwise specified: V<sub>CC</sub> = +2.2V to 5.5V.

| Symbol                 | Parameter                                | Conditions                                                                                                                                       | Min                                                | Typ                      | Max                                                | Units |
|------------------------|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|--------------------------|----------------------------------------------------|-------|
| <b>POWER SUPPLY</b>    |                                          |                                                                                                                                                  |                                                    |                          |                                                    |       |
| V <sub>CC</sub>        | Operating Voltage Range: V <sub>CC</sub> | LM3710                                                                                                                                           | <b>1.0</b>                                         |                          | <b>5.5</b>                                         | V     |
|                        |                                          | LM3711                                                                                                                                           | <b>1.2</b>                                         |                          | <b>5.5</b>                                         |       |
| I <sub>CC</sub>        | V <sub>CC</sub> Supply Current           | All inputs = V <sub>CC</sub> ; all outputs floating                                                                                              |                                                    | 28                       | <b>50</b>                                          | μA    |
| <b>RESET THRESHOLD</b> |                                          |                                                                                                                                                  |                                                    |                          |                                                    |       |
| V <sub>RST</sub>       | Reset Threshold                          | V <sub>CC</sub> falling                                                                                                                          | –0.5<br><b>–2</b>                                  | V <sub>RST</sub>         | +0.5<br><b>+2</b>                                  | %     |
|                        |                                          | V <sub>CC</sub> falling: T <sub>A</sub> = 0°C to 70°C                                                                                            | <b>–1.5</b>                                        |                          | <b>+1.5</b>                                        |       |
| V <sub>RSTH</sub>      | Reset Threshold Hysteresis               |                                                                                                                                                  |                                                    | 0.0032•V <sub>RST</sub>  |                                                    | mV    |
| t <sub>RP</sub>        | Reset Timeout Period                     | Reset Timeout Period = E, J, N, S<br>Reset Timeout Period = F, K, P, T<br>Reset Timeout Period = G, L, Q, U<br>Reset Timeout Period = H, M, R, V | <b>1</b><br><b>20</b><br><b>140</b><br><b>1120</b> | 1.4<br>28<br>200<br>1600 | <b>2</b><br><b>40</b><br><b>280</b><br><b>2240</b> | ms    |
| t <sub>RD</sub>        | V <sub>CC</sub> to Reset Delay           | V <sub>CC</sub> falling at 1mV/μs                                                                                                                |                                                    | 20                       |                                                    | μs    |
| <b>RESET (LM3711)</b>  |                                          |                                                                                                                                                  |                                                    |                          |                                                    |       |
| V <sub>OL</sub>        | RESET                                    | V <sub>CC</sub> > 2.25V, I <sub>SINK</sub> = 900μA                                                                                               |                                                    |                          | <b>0.3</b>                                         | V     |
|                        |                                          | V <sub>CC</sub> > 2.7V, I <sub>SINK</sub> = 1.2mA                                                                                                |                                                    |                          | <b>0.3</b>                                         |       |
|                        |                                          | V <sub>CC</sub> > 4.5V, I <sub>SINK</sub> = 3.2mA                                                                                                |                                                    |                          | <b>0.4</b>                                         |       |
| V <sub>OH</sub>        | RESET                                    | V <sub>CC</sub> > 1.2V, I <sub>SOURCE</sub> = 50μA                                                                                               | <b>0.8 V<sub>CC</sub></b>                          |                          |                                                    | V     |
|                        |                                          | V <sub>CC</sub> > 1.8V, I <sub>SOURCE</sub> = 150μA                                                                                              | <b>0.8 V<sub>CC</sub></b>                          |                          |                                                    |       |
|                        |                                          | V <sub>CC</sub> > 2.25V, I <sub>SOURCE</sub> = 300μA                                                                                             | <b>0.8 V<sub>CC</sub></b>                          |                          |                                                    |       |
|                        |                                          | V <sub>CC</sub> > 2.7V, I <sub>SOURCE</sub> = 500μA                                                                                              | <b>0.8 V<sub>CC</sub></b>                          |                          |                                                    |       |
|                        |                                          | V <sub>CC</sub> > 4.5V, I <sub>SOURCE</sub> = 800μA                                                                                              | <b>V<sub>CC</sub> – 1.5V</b>                       |                          |                                                    |       |

**LM3710/LM3711 Series Electrical Characteristics (continued)**

Limits in the standard typeface are for  $T_J = 25^\circ\text{C}$  and limits in **boldface type** apply over full operating range. Unless otherwise specified:  $V_{CC} = +2.2\text{V}$  to  $5.5\text{V}$ .

| Symbol                                    | Parameter                                                                            | Conditions                                                                                                                                                   | Min                        | Typ                         | Max                         | Units |
|-------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------|-----------------------------|-------|
| I <sub>LKG</sub>                          | Output Leakage Current                                                               | V <sub>RESET</sub> = 5.5V                                                                                                                                    |                            |                             | 1.0                         | μA    |
| RESET (LM3710)                            |                                                                                      |                                                                                                                                                              |                            |                             |                             |       |
| V <sub>OL</sub>                           | RESET                                                                                | V <sub>CC</sub> > 1.0V, I <sub>SINK</sub> = 50μA                                                                                                             |                            |                             | 0.3                         | V     |
|                                           |                                                                                      | V <sub>CC</sub> > 1.2V, I <sub>SINK</sub> = 100μA                                                                                                            |                            |                             | 0.3                         |       |
|                                           |                                                                                      | V <sub>CC</sub> > 2.25V, I <sub>SINK</sub> = 900μA                                                                                                           |                            |                             | 0.3                         |       |
|                                           |                                                                                      | V <sub>CC</sub> > 2.7V, I <sub>SINK</sub> = 1.2mA                                                                                                            |                            |                             | 0.3                         |       |
|                                           |                                                                                      | V <sub>CC</sub> > 4.5V, I <sub>SINK</sub> = 3.2mA                                                                                                            |                            |                             | 0.4                         |       |
| V <sub>OH</sub>                           | RESET                                                                                | V <sub>CC</sub> > 2.25V, I <sub>SOURCE</sub> = 300μA                                                                                                         | 0.8 V <sub>CC</sub>        |                             |                             |       |
|                                           |                                                                                      | V <sub>CC</sub> > 2.7V, I <sub>SOURCE</sub> = 500μA                                                                                                          | 0.8 V <sub>CC</sub>        |                             |                             |       |
|                                           |                                                                                      | V <sub>CC</sub> > 4.5V, I <sub>SOURCE</sub> = 800μA                                                                                                          | V <sub>CC</sub> – 1.5V     |                             |                             |       |
| WDI                                       |                                                                                      |                                                                                                                                                              |                            |                             |                             |       |
| WDI                                       | Watchdog Input Current                                                               |                                                                                                                                                              | –1                         |                             | +1                          | μA    |
| WDI <sub>T</sub>                          | Watchdog Input Threshold                                                             |                                                                                                                                                              | 0.2•V <sub>CC</sub>        | 1.225                       | 0.8•V <sub>CC</sub>         | V     |
| t <sub>WD</sub>                           | Watchdog Timeout Period                                                              | Watchdog Timeout Period = E, F, G, H<br>Watchdog Timeout Period = J, K, L, M<br>Watchdog Timeout Period = N, P, Q, R<br>Watchdog Timeout Period = S, T, U, V | 4.3<br>71<br>1120<br>17900 | 6.2<br>102<br>1600<br>25600 | 9.3<br>153<br>2400<br>38400 | ms    |
| PFI/MR                                    |                                                                                      |                                                                                                                                                              |                            |                             |                             |       |
| V <sub>PFT</sub>                          | PFI Input Threshold                                                                  |                                                                                                                                                              | 1.200                      | 1.225                       | 1.250                       | V     |
| V <sub>MRT</sub>                          | MR Input Threshold                                                                   | MR, Low                                                                                                                                                      |                            |                             | 0.8                         | V     |
|                                           |                                                                                      | MR, High                                                                                                                                                     | 2.0                        |                             |                             |       |
| V <sub>PFTH</sub> /<br>V <sub>MRT H</sub> | PFI/MR Threshold Hysteresis                                                          | PFI/MR falling: V <sub>CC</sub> = V <sub>RST</sub> MAX to 5.5V                                                                                               |                            | 0.0032•V <sub>RST</sub>     |                             | mV    |
| I <sub>PFI</sub>                          | Input Current (PFI only)                                                             |                                                                                                                                                              | –75                        |                             | 75                          | nA    |
| R <sub>MR</sub>                           | MR Pull-up Resistance                                                                |                                                                                                                                                              | 35                         | 56                          | 75                          | kΩ    |
| t <sub>MD</sub>                           | MR to Reset Delay                                                                    |                                                                                                                                                              |                            | 12                          |                             | μS    |
| t <sub>MR</sub>                           | MR Pulse Width                                                                       |                                                                                                                                                              | 25                         |                             |                             | μS    |
| PFO, LLO                                  |                                                                                      |                                                                                                                                                              |                            |                             |                             |       |
| V <sub>OL</sub>                           | PFO, LLO Output Voltage                                                              | V <sub>CC</sub> > 2.25V, I <sub>SINK</sub> = 900μA                                                                                                           |                            |                             | 0.3                         | V     |
|                                           |                                                                                      | V <sub>CC</sub> > 2.7V, I <sub>SINK</sub> = 1.2mA                                                                                                            |                            |                             | 0.3                         |       |
|                                           |                                                                                      | V <sub>CC</sub> > 4.5V, I <sub>SINK</sub> = 3.2mA                                                                                                            |                            |                             | 0.4                         |       |
| V <sub>OH</sub>                           |                                                                                      | V <sub>CC</sub> > 2.25V, I <sub>SOURCE</sub> = 300μA                                                                                                         | 0.8 V <sub>CC</sub>        |                             |                             |       |
|                                           |                                                                                      | V <sub>CC</sub> > 2.7V, I <sub>SOURCE</sub> = 500μA                                                                                                          | 0.8 V <sub>CC</sub>        |                             |                             |       |
|                                           |                                                                                      | V <sub>CC</sub> > 4.5V, I <sub>SOURCE</sub> = 800μA                                                                                                          | V <sub>CC</sub> – 1.5V     |                             |                             |       |
| LLO OUTPUT                                |                                                                                      |                                                                                                                                                              |                            |                             |                             |       |
| V <sub>LLOT</sub>                         | LLO Output Threshold (V <sub>LLO</sub> – V <sub>RST</sub> , V <sub>CC</sub> falling) |                                                                                                                                                              | 1.01•V <sub>RST</sub>      | 1.02•V <sub>RST</sub>       | 1.03•V <sub>RST</sub>       | V     |
| V <sub>LLOTH</sub>                        | Low-Line Comparator Hysteresis                                                       |                                                                                                                                                              |                            | 0.0032•V <sub>RST</sub>     |                             | mV    |
| t <sub>CD</sub>                           | Low-Line Comparator Delay                                                            | V <sub>CC</sub> falling at 1mV/μs                                                                                                                            |                            | 20                          |                             | μs    |

## Typical Performance Characteristics




Figure 3.




Figure 4.




Figure 5.




Figure 6.




Figure 7.

**Max. Transient Duration vs Reset Comparator Overdrive  
( $V_{CC} = 3.3V$ )**





Figure 8.


## Typical Performance Characteristics (continued)

**Watchdog Timeout Period vs Temperature**  
( $t_{WD}$  programmed as 6.2ms)



**Figure 9.**

**Low-Line Comparator Propagation Delay vs Temperature**



**Figure 10.**

## CIRCUIT INFORMATION

### RESET OUTPUT

The Reset input of a  $\mu\text{P}$  initializes the device into a known state. The LM3710/LM3711 microprocessor supervisory circuits assert a forced reset output to prevent code execution errors during power-up, power-down, and brownout conditions.

$\overline{\text{RESET}}$  is ensured valid for  $V_{\text{CC}} > 1\text{V}$ . Once  $V_{\text{CC}}$  exceeds the reset threshold, an internal timer maintains the output for the reset timeout period. After this interval, reset goes high. The LM3710 offers an active-low  $\overline{\text{RESET}}$ ; The LM3711 offers an active-high RESET.

Any time  $V_{\text{CC}}$  drops below the reset threshold (such as during a brownout), the reset activates. When  $V_{\text{CC}}$  again rises above the reset threshold, the internal timer starts. Reset holds until  $V_{\text{CC}}$  exceeds the reset threshold for longer than the reset timeout period. After this time, reset releases.

The Manual Reset input ( $\overline{\text{MR}}$ ) will initiate a forced reset also. See the [MANUAL RESET INPUT \( \$\overline{\text{MR}}\$ \)](#) section.

### RESET THRESHOLD

The LM3710/LM3711 family is available with a reset voltage of 3.08V. Other reset thresholds in the 2.20V to 5.0V range, in steps of 10 mV, are available; contact Texas Instruments for details.

### MANUAL RESET INPUT ( $\overline{\text{MR}}$ )

Many  $\mu\text{P}$ -based products require a manual reset capability, allowing the operator to initiate a reset. The  $\overline{\text{MR}}$  input is fully debounced and provides an internal 56 k $\Omega$  pull-up. When the  $\overline{\text{MR}}$  input is pulled below  $V_{\text{MRT}}$  (1.225V) for more than 25  $\mu\text{s}$ , reset is asserted after a typical delay of 12  $\mu\text{s}$ . Reset remains active as long as  $\overline{\text{MR}}$  is held low, and releases after the reset timeout period expires after  $\overline{\text{MR}}$  rises above  $V_{\text{MRT}}$ . Use  $\overline{\text{MR}}$  with digital logic to assert or to daisy chain supervisory circuits. It may be used as another low-line comparator by adding a buffer.

### POWER-FAIL COMPARATOR (PFI/ $\overline{\text{PFO}}$ )

The PFI is compared to a 1.225V internal reference,  $V_{\text{PFT}}$ . If PFI is less than  $V_{\text{PFT}}$ , the Power Fail Output  $\overline{\text{PFO}}$  drops low. The power-fail comparator signals a falling power supply, and is driven typically by an external voltage divider that senses either the unregulated supply or another system supply voltage. The voltage divider generally is chosen so the voltage at PFI drops below  $V_{\text{PFT}}$  several milliseconds before the main supply voltage drops below the reset threshold, providing advanced warning of a brownout.

The voltage threshold is set by  $R_1$  and  $R_2$  and is calculated as follows:

$$V_{\text{PFT}} = \left( \frac{R_1 + R_2}{R_2} \right) \times 1.225\text{V} \quad (1)$$

Note this comparator is completely separate from the rest of the circuitry, and may be employed for other functions as needed.

### LOW-LINE OUTPUT ( $\overline{\text{LLO}}$ )

The low-line output comparator is typically used to provide a non-maskable interrupt to a  $\mu\text{P}$  when  $V_{\text{CC}}$  begins falling.  $\overline{\text{LLO}}$  monitors  $V_{\text{CC}}$  and goes low when  $V_{\text{CC}}$  falls below  $V_{\text{LLOT}}$  (typically  $1.02 \cdot V_{\text{RST}}$ ) with hysteresis of  $0.0032 \cdot V_{\text{RST}}$ .

### WATCHDOG TIMER INPUT (WDI)

The watchdog timer input monitors one of the microprocessor's output lines for activity. Each time a transition occurs on this monitored line, the watchdog counter is reset. However, if no transition occurs and the timeout period is reached, the LM3710/LM3711 assumes that the microprocessor has locked up and the reset output is activated.

WDI is a high impedance input.

## SPECIAL PRECAUTIONS FOR THE DSBGA PACKAGE

As with most integrated circuits, the LM3710 and LM3711 are sensitive to exposure from visible and infrared (IR) light radiation. Unlike a plastic encapsulated IC, the DSBGA package has very limited shielding from light, and some sensitivity to light reflected from the surface of the PC board or long wavelength IR entering the die from the side may be experienced. This light could have an unpredictable affect on the electrical performance of the IC. Care should be taken to shield the device from direct exposure to bright visible or IR light during operation.

## DSBGA MOUNTING

The DSBGA package requires specific mounting techniques which are detailed in TI Application Note AN-1112 (SNVA009). Referring to the section **Surface Mount Assembly Considerations**, it should be noted that the pad style which must be used with the 9-pin package is the NSMD (non-solder mask defined) type.

For best results during assembly, alignment ordinals on the PC board may be used to facilitate placement of the DSBGA device.

## Timing Diagrams




Figure 11. LM3710/LM3711 Reset Time with  $\overline{MR}$  and WDI




Figure 12.  $\overline{LLO}$  Output




Figure 13. PFI Comparator Timing Diagram

### Typical Application Circuits




Figure 14. Monitoring Two Critical Supplies And Dataline




Figure 15. Monitoring Two Supplies plus Manual Reset And Dataline






Figure 16. Monitoring Dual Supplies plus External Fault Input And Dataline



Note:  $\overline{MR}$  input with its 1.225V nominal threshold, may monitor an additional supply voltage. An internal 56 kΩ pull-up resistor is included on this input.

Figure 17. Microprocessor Supervisor with Early Warning Detector

**Figure 18. LM3710 Long Period oscillator**

## REVISION HISTORY

| Changes from Revision D (March 2013) to Revision E         | Page               |
|------------------------------------------------------------|--------------------|
| • Changed layout of National Data Sheet to TI format ..... | <a href="#">12</a> |

## PACKAGING INFORMATION

| Orderable part number               | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-------------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| LM3710XKMM-463/NO.A                 | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 85    | R74B                |
| <a href="#">LM3710XKMM-463/NOPB</a> | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -            | R74B                |
| LM3710XQMM-308/NO.A                 | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 85    | R37B                |
| LM3710XQMM-308/NO.B                 | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 85    | R37B                |
| <a href="#">LM3710XQMM-308/NOPB</a> | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 85    | R37B                |
| LM3710YQMM-232/NO.A                 | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 85    | R77B                |
| LM3710YQMM-232/NO.B                 | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 85    | R77B                |
| <a href="#">LM3710YQMM-232/NOPB</a> | Active        | Production           | VSSOP (DGS)   10 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -            | R77B                |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "-" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device              | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM3710XKMM-463/NOPB | VSSOP        | DGS             | 10   | 1000 | 177.8              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM3710XQMM-308/NOPB | VSSOP        | DGS             | 10   | 1000 | 177.8              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM3710YQMM-232/NOPB | VSSOP        | DGS             | 10   | 1000 | 177.8              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device              | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM3710XKMM-463/NOPB | VSSOP        | DGS             | 10   | 1000 | 208.0       | 191.0      | 35.0        |
| LM3710XQMM-308/NOPB | VSSOP        | DGS             | 10   | 1000 | 208.0       | 191.0      | 35.0        |
| LM3710YQMM-232/NOPB | VSSOP        | DGS             | 10   | 1000 | 208.0       | 191.0      | 35.0        |




# EXAMPLE BOARD LAYOUT



DGS0010A

VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221984/A 05/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DGS0010A

VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221984/A 05/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated