


NOTES:

1. MATERIALS OF CONSTRUCTION:
BODY, & SHELL = BRASS, GOLD PLATED
CONTACT PIN = BRASS, GOLD PLATED
INSULATORS (2) = TEFLON, MIL-P-19468
RETAINER RING = BeCu, NATURAL
GASKET = SILICONE RUBBER, COLOR RED


901-9867-RFX

REVISIONS

DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ.	A	RELEASE TO MFG.	2/2/01	43661	CPM




SCALE 3.000



RECOMMENDED CABLE
STRIPPING DIMENSIONS
SCALE 3.000

CUSTOMER OUTLINE DRAWING
FOR REFERENCE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 0.5 - 6mm ±0.2mm 6 - 30mm ±0.4mm 30 - 120mm ± 0.6mm	MATERIAL	DRAWN C. McGRATH	DATE 1/24/01	TITLE SMA SOLDER PLUG FOR .085 &.086 DIA SEMI-RIGID CABLE	Amphenol Amphenol Corporation Communication and Network Products Division Danbury, CT U.S.A. 06810		
		ENGINEER O. BARTHELMES	DATE 1/24/01				
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE EAR 967698-0 GEN# 901-9868-RFX_ASSY	APPROVED 	DATE 1/24/01	SCALE: 6.0:1 SHEET 2 OF 2			
		CAD FILE I:\SMA\901-9867-RFX					CODE ID 74868