

**FLUKE®**

# Test Tools Catalog

Volume one, 2007



Fluke Ti20  
Thermal Imager



Fluke 975  
AirMeter™



Fluke 1587  
Insulation Multimeter



Fluke 199C  
Color ScopeMeter®

**Find it. Fix it. Fast.**

# Test Tools Catalog Volume 37, 2007

FLUKE®

## Contents

### Fluke tools for:

|                              |   |
|------------------------------|---|
| Commercial Electricians..... | 3 |
| Industrial Electricians..... | 4 |
| HVAC/IAQ Technicians.....    | 5 |

### Online resource centers.....

### Fluke test tool information.....

### Safety and its importance.....

### Service, repair, and calibration.....

### Digital Multimeters

|                                                  |    |
|--------------------------------------------------|----|
| Multimeter Selection Guide.....                  | 10 |
| Faster, Safer Multimeters.....                   | 11 |
| 189 Logging Multimeter.....                      | 12 |
| FlukeView Forms® Software.....                   | 13 |
| 87V Industrial Multimeter.....                   | 14 |
| 179 Digital Multimeter.....                      | 15 |
| Family of True-rms Digital Multimeters.....      | 16 |
| 117 and 115 True-rms Digital Multimeters.....    | 17 |
| 116 and 114 True-rms Digital Multimeters.....    | 18 |
| 77-IV and 73-III Digital Multimeters.....        | 19 |
| 27 Waterproof Multimeter.....                    | 19 |
| 88V Automotive Multimeter.....                   | 20 |
| 8845A/8846A 6.5 Digit Precision Multimeters..... | 21 |

### Electrical Testers

|                                               |    |
|-----------------------------------------------|----|
| T3 and T5 Electrical Testers, VoltAlert™..... | 22 |
| 9040 Rotary Field Indicator.....              | 22 |

### Earth Ground Testers

|                                                                   |    |
|-------------------------------------------------------------------|----|
| 1625 and 1623 Geo Earth Ground Testers.....                       | 23 |
| 1630 Earth Ground Clamp Meter, Handy Geo Earth Ground Tester..... | 24 |

### Power Quality Analyzers

|                                                                               |    |
|-------------------------------------------------------------------------------|----|
| 430 Series Power Quality Analyzers.....                                       | 25 |
| 43B Power Quality Analyzer.....                                               | 26 |
| 1760 Power Quality Recorder, 1650 RPM Power Recorder.....                     | 27 |
| 1740 Series Three-Phase PQ Loggers, VR101S Voltage Event Recorder System..... | 28 |
| 1735 Three-Phase Power Logger, Norma 4/5000 Power Analyzers.....              | 29 |

### Clamp Meters

|                                                                           |    |
|---------------------------------------------------------------------------|----|
| Fluke 345 and LH1050, LH1060 Power Clamp Meters.....                      | 30 |
| Fluke 360 and LH41 Current Clamp Meters, LH2015 True-rms Clamp Meter..... | 31 |
| Better Clamp Meters from Fluke.....                                       | 32 |
| 330 and 320 Series Clamp Meters.....                                      | 33 |
| 902 True-rms HVAC Clamp Meter.....                                        | 34 |

### Insulation Testers and MegOhmMeters

|                                           |    |
|-------------------------------------------|----|
| 1550B and 1520 Megohmmeters.....          | 34 |
| 1587 and 1577 Insulation Multimeters..... | 35 |
| 1507 and 1503 Insulation Testers.....     | 36 |

### Process Calibration Tools

|                                                                |    |
|----------------------------------------------------------------|----|
| Process Tools Selection Guide.....                             | 37 |
| 744, 743B, 741B Documenting Process Calibrators.....           | 38 |
| 726, 725 Precision Multifunction Process Calibrators.....      | 39 |
| 724, 714, 712 Temperature Calibrators.....                     | 40 |
| 718, 717 Pressure Calibrator, 700 Series Pressure Modules..... | 41 |
| 715, 707, 705 Loop Calibrators.....                            | 42 |
| 789, 787 Process Meters.....                                   | 43 |
| 771 Milliamp Process Clamp Meter.....                          | 44 |
| 9102S, 9100S Handheld Drywell Temperature Calibrators.....     | 44 |

### Intrinsically Safe Products

|                                                        |    |
|--------------------------------------------------------|----|
| 707Ex, 718Ex, 725Ex, 700PEx, 574-NI, 68IS, 87V Ex..... | 45 |
|--------------------------------------------------------|----|

### Thermal Imagers

|                                                                                          |       |
|------------------------------------------------------------------------------------------|-------|
| Ti40/Ti50 Series IR FlexCam® Thermal Imagers.....                                        | 46-47 |
| Ti20 Thermal Imager.....                                                                 | 48    |
| Ti30™ Thermal Imager.....                                                                | 49    |
| TiR4, TiR3, TiR2 IR FlexCam™ Thermal Imagers and IR InSight XS, XST Thermal Imagers..... | 50    |

### Thermometers

|                                        |    |
|----------------------------------------|----|
| 570 Series Infrared Thermometers.....  | 51 |
| 54 Series II Contact Thermometers..... | 52 |
| 561 HVACPro Thermometer.....           | 52 |
| 60 Series Infrared Thermometers.....   | 53 |

### HVAC/Indoor Air Quality Tools

|                                                           |    |
|-----------------------------------------------------------|----|
| 975 AirMeter,™ 902 True-rms HVAC Clamp Meter.....         | 54 |
| 971 Temperature Humidity Meter, 983 Particle Counter..... | 55 |

### ScopeMeter® Test Tools

|                                             |    |
|---------------------------------------------|----|
| ScopeMeter Test Tools Selection Guide.....  | 56 |
| 124 Industrial ScopeMeter Test Tools.....   | 57 |
| 190 Series Color ScopeMeter Test Tools..... | 58 |
| Fluke ScopeMeter Accessories.....           | 59 |

### Accessories

|                                                                                     |       |
|-------------------------------------------------------------------------------------|-------|
| Accessory Selection Guide.....                                                      | 60    |
| Accessory Sets and Kits.....                                                        | 61    |
| SureGrip™ Accessories.....                                                          | 62    |
| Accessories for Electronic and Automotive Applications and High Voltage Probes..... | 63    |
| Lights, Software and Specialty Accessories.....                                     | 64-65 |
| Current Clamps.....                                                                 | 66-67 |
| Temperature Accessories.....                                                        | 68-69 |
| Cases, Holsters and Fuses.....                                                      | 70-71 |

### What's new from Fluke.....

### Contact us:

#### United States

General product and sales information: 1-888-44-FLUKE

Fluke Thermal Imagers:  
1-800-760-4620 (U.S. only) all other regions 1-425-446-4620

Service and calibration:

1-800-993-5853

Parts: 1-800-526-4731

#### Canada

General product and sales information: 1-800-36-FLUKE

Service, parts and calibration:

1-800-36-FLUKE

canada@fluke.com

#### Australia

General product and sales information: (2) 8850-3333

Parts: (2) 8850-3333

Service and calibration:

(2) 9771-9300

#### Singapore

General product and sales information: 6738-5655

info.asean@fluke.com

Service, parts and calibration: 6737-2922

service.asean@fluke.com

#### Japan

General product and sales information: +81-3-3434-0180

Service, parts and calibration:

+81-3-3434-0188

Other countries: 1+(425) 446-5500

## Application segment key

To help you better identify the right product for your job, you will find the applicable icons located on the outside edge of each product page.



Residential



Building  
Diagnostics



Electrical



Industrial



HVAC/IAQ



Electronic



Commercial



Process




Automotive

# Fluke test tools to help you get the job done

## Fluke tools for commercial electricians

### Legend

- ◆ Power Distribution Center
- ✕ Heat Exchanger
- △ HVAC Blower
- ◇ Drive Control
- Motor and Motor Control Center
- Electrical



### Fluke 1AC II VoltAlert Voltage Detector



#### Best suited for:

- Non-contact voltage detection on electrical circuits
- Detecting voltage before work begins

See page 22 for details



### Fluke 116 Digital Multimeter



#### Best suited for:

- Measures volts, ohms, capacitance and temperature
- Resistance and continuity
- 600 V ac and dc measurement range

See page 18 for details



### Fluke 62 Mini IR Thermometer



#### Best suited for:

- Surface temperature readings
- Finding heating and ventilation problems
- Non-contact monitoring of electrical motors and panels

See page 53 for details



### Fluke T5 Voltage, Continuity and Current Tester



#### Best suited for:

- Measure loads on a branch circuit at a service level
- Measure the load side voltage of a circuit breaker or fuse
- Map outlets to breakers
- Check individual voltages (either ac or dc)
- Determine resistances up to 1000 ohms
- Check circuit continuity

See page 22 for details



### Fluke 322 Clamp Meter



#### Best suited for:

- Verify the presence of load current, ac/dc voltage and continuity
- Current measurements up to 400 A in tight cable compartments
- Higher resolution for loads below 40 A

See page 33 for details



### Fluke 87V Industrial True-rms Multimeter w/temp



#### Best suited for:


- VSD motor drive installation and troubleshooting
- Accurate frequency and voltage measurements on motor drives and in electrically noisy environments
- Built-in thermometer for temperature measurements
- CAT III 1000 V rated to protect against high voltage transients up to 8 kV

See page 14 for details



# Fluke test tools to help you get the job done

## Fluke tools for industrial electricians



### Legend

- Pumps
- ◆ Drive Control
- ◆ Blowers
- ✕ Motors

### Front line troubleshooting tools

#### Fluke 87V Industrial True-rms Multimeter w/temp



**Best suited for:** VSD motor drive installation and troubleshooting.

##### Features:

- Accurate frequency and voltage measurements on motor drives and in electrically noisy environments
- Built-in thermometer for temperature measurements



See page 13 for details

#### Fluke 1587 Insulation Multimeters



**Best suited for:** Work on motors, generators, cables or switch-gear.

##### Features:

- Measuring insulation test voltages to 1000 V
- Prevents insulation test if voltage > 30 V is detected for added user protection
- Filter for motor drive measurements



See page 35 for details

#### Fluke 337 AC/DC True-rms Clamp Meter



**Best suited for:** Measure inrush current on electric motor startup and electric motor testing and troubleshooting

##### Features:

- Inrush current measurements to measure start up current on electric motors
- Frequency measurements to help track down power quality problems



See page 33 for details

### Preventive and predictive maintenance

#### Fluke 434 Three-Phase PQ Analyzer



**Best suited for:** Troubleshooting and preventing problems in power distribution systems.

##### Features:

- Simultaneously measure voltage and current on all three phases and neutral
- High-resolution color screen simplifies operation
- Tough enough for industrial environments, easy to carry, works for seven hours per battery charge



See page 25 for details

#### Fluke 576 Photographic IR Thermometer



**Best suited for:** Measuring surface temperatures, quickly locating lubrication problems, overloads, short-circuits or misaligned and overheated equipment.

##### Features:

- Last ten temperature readings displayed on bar graph for easy reference
- Customizable log names, alarms and emissivity values for more efficient, less error-prone predictive maintenance routes



See page 51 for details

#### Fluke Ti20 Thermal Imager



**Best suited for:** Displaying a visual image of surface temperatures to easily and safely identify potential problems.

##### For use on:

- Electrical power distribution systems
- Electro-mechanical equipment
- Process instrumentation
- Facility maintenance



See page 48 for details

# Fluke test tools to help you get the job done

## Fluke tools for HVAC/IAQ technicians



### Legend

- ◆ Indoor Air Comfort
- ✗ Superheat and Subcooling
- ▲ Electrical
- ◆ Motors/Pumps/Compressors
- Building Diagnostics
- Filtration and Ventilation
- ▼ Furnace

### Fluke 975 AirMeter™



**Best suited for:**  
Optimizing HVAC ventilation settings for ASHRAE 62 recommendations

- Simultaneously measures, logs and displays temperature, humidity, velocity, CO<sub>2</sub> and CO

See page 54 for details



### Fluke 983 Particle Counter



**Best suited for:**  
Troubleshooting and maintaining indoor air quality

- Measures particle size, temperature, and relative humidity
- Data logging and six-channel particle size display

See page 55 for details



### Fluke 116 Digital Multimeter



**Best suited for:**  
Troubleshooting HVAC equipment and flame sensors

- Thermometer and microamps
- Volts ac/dc, resistance, diode, continuity, and Min/Max/Avg

See page 18 for details



### Fluke 902 True-rms HVAC Clamp Meter



**Best suited for:** HVAC system diagnosis and repair

- Capacitance and true-rms
- DC current to 200  $\mu$ A
- Contact temperature

See page 54 for details



### Fluke 561 HVACPro IR Thermometer



**Best suited for:** Measuring hot, moving, electrical energized objects

- Contact and non-contact measurement
- Compatible with standard type-K thermocouple
- Includes Velcro® pipe probe

See page 52 for details



### Fluke IR Insight XS/XST Thermal Imagers



**Best suited for:** Quick, accurate building diagnostic surveys

- High resolution images and display
- Industry -leading thermal sensitivity
- Simple, one-button operation

See page 50 for details



# Online resource centers

## Test tool applications

### Electrical Resource Center

[www.fluke.com/electrical\\_resource\\_ctr](http://www.fluke.com/electrical_resource_ctr)

Product demos, software downloads, earth ground education, application notes, training and events information.



### HVAC/IAQ Resource Center

[www.fluke.com/IAQ](http://www.fluke.com/IAQ)

FAQs, white papers, case studies and application notes, downloads, and product demos.



### Plant Maintenance Resource Center

[www.fluke.com/plant\\_resource\\_ctr](http://www.fluke.com/plant_resource_ctr)

ROI calculator, PDM program, maintenance techniques, tool profiles, common culprits.



### Thermal Imaging Resource Center

[www.fluke.com/thermal\\_resource](http://www.fluke.com/thermal_resource)

Online product selection guide, product information, application notes, software



### Biomedical Resource Center

[www.fluke.com/biomed\\_resource\\_ctr](http://www.fluke.com/biomed_resource_ctr)

Product news and information, catalog, trade-up program, and tradeshow schedule.

### Electronics Resource Center

[www.fluke.com/electronics\\_resource\\_ctr](http://www.fluke.com/electronics_resource_ctr)

Tips from the field, product demos, application notes, and product showcase.

### Intrinsic Safety Resource Center

[www.fluke.com/ex](http://www.fluke.com/ex)

Standards explanations, industry applications, guidelines, and product information.

### Building Diagnostics Resource Center

[www.fluke.com/buildings](http://www.fluke.com/buildings)

Image gallery, application notes, and expert tips on using thermography to identify structural, thermal, moisture, and air leakage problems in buildings.

### Precision Measurement and Calibration Resource Center

[www.fluke.com/precision\\_resource\\_ctr](http://www.fluke.com/precision_resource_ctr)

New product information, e-news bulletins, total solutions newsletter, industry links, users community, used certified equipment, technical papers and application notes.

### Process Control Resource Center

[www.fluke.com/process\\_resource\\_ctr](http://www.fluke.com/process_resource_ctr)

Process calibration glossary, industry information, ROI calculator, application notes, and product demos.

## Solve more problems with Fluke Tools

Fluke is more than digital multimeters. These days, Fluke offers the ultimate go-everywhere DMM as well as specialized tools for electrical, industrial, HVAC, and electronic applications.

Increasingly, technicians are using their Fluke tools together, in a one-two troubleshooting combination.

Use a thermal imager to find a problem, then use a DMM, clamp meter, or power quality analyzer to fix it.

Use a power logger to check power usage, use an AirMeter to optimize the HVAC system, and then log power again to see the impact of your adjustments.

The online resource centers on this page can help you find the right tools for your applications, learn how to use them, and get to work.

Your site-specific knowledge plus Fluke tools makes for an impressive troubleshooting team.

Plus, the new generation of Fluke tools is smaller, lighter, and easier to use than ever. They meet higher safety standards. They download to reports. And they're as reliable and tough as ever.

By offering a system of tools that work together, Fluke aims to help you solve more problems, faster and better, no matter where you work.

### Utilities Resource Center

[www.fluke.com/utilities\\_resource\\_ctr](http://www.fluke.com/utilities_resource_ctr)

Training and events information, product demos, specialized technical support, application notes, and power quality, thermography and earth ground information for utilities.



# Fluke... more than just tools

FLUKE®

## Test tool information

Since 1949 the Fluke Corporation has been dedicated to the design and manufacturing of innovative test and measurement instruments. Fluke also leads the way in providing programs, training and resources that help you stay at the forefront of your profession.

### FlukePlus Tool Info Online

[www.fluke.com/flukeplus](http://www.fluke.com/flukeplus)

FlukePlus is a website for test tool users who want to learn more. Sign up and get:

- Product tips and "how to" articles
- Previews of the newest Fluke tools
- Special offers and promotions
- Direct connection to Fluke technical support



### Fluke Education Partnership Program

[www.fluke.com/education](http://www.fluke.com/education)

We've teamed up with colleges, trade, technical, vocational schools, and apprenticeship programs to bring the latest application information and tools into the classroom. Currently available in USA, Canada, Brunei, Burma, India, Indonesia, Laos, Malaysia, Philippines, Singapore, Taiwan, Thailand and Vietnam.



### Electrical Measure- ment Safety Program

[www.fluke.com/safety](http://www.fluke.com/safety)

Get a free safety video, a summary of safety standards and helpful articles on safe electrical measurement practices. (Available only in the U.S.)



### Test Tool Users Online Community

[www.fluke.com/community](http://www.fluke.com/community)

See what other test tool users are saying and get your questions answered, fast! The Test Tool Community online bulletin board is free and open to everyone.



### Application Notes

[www.fluke.com/appnotes](http://www.fluke.com/appnotes)

Fluke has a complete library of application notes and white papers on topics ranging from predictive maintenance to maintaining motors and drives to automotive troubleshooting and more.



### Fluke News

[www.fluke.com/flukenews](http://www.fluke.com/flukenews)

Fluke News is published two times a year with new tips, tools and articles in each issue.

#### Fluke Electrical News

For electrical contractors or electricians working in residential, commercial, or industrial environments.



#### Fluke Plant News

For electricians, electrical supervisors, field service technicians, plant technicians and process engineers maintaining industrial equipment in the field or plant.



#### Fluke Electronics News

For electronics or electrical engineers who use DMMs, benchtop meters, and oscilloscopes in prototyping, design and field evaluation situations.



#### Fluke HVAC/IAQ News

All-new articles about tools, measuring practices, and business opportunities for HVAC and Indoor Air Quality (IAQ) professionals.



# Safety and You

## Why is safety important? Why should you care?

Between five and ten times on any given day, arc flash explosions, sufficient to send a victim to a special burn center, take place in the U.S. These incidents and other less serious electrical accidents result in injury—sometimes death—lost work time, medical costs and insurance claims, downtime, the list goes on.

The cost to both the victim, the victim's family and the company involved, are high. Yet many of these accidents can be prevented. The combination of training, good measurement technique, and the use of proper tools can significantly reduce the chance of an accident occurring.

### What are the Standards?

To provide improved protection for users, industry standards organizations have taken steps to clarify the hazards present in electrical supply environments. The American National Standards Institute (ANSI), the Canadian Standards Association (CSA), and the International Electrotechnical Commission (IEC), have created more stringent standards for voltage test equipment used in environments of up to 1000 volts.

ANSI, CSA and IEC define four measurement categories of over-voltage transient impulses. The rule of thumb is that the closer the technician is working to the power source, the greater the danger and the higher the measurement category number. Lower category installations usually have greater impedance, which dampens transients and helps limit the fault current that can feed an arc.

- CAT (Category) IV is associated with the origin of installation. This refers to power lines at the utility connection, but also includes any overhead and underground outside cable runs, since both may be affected by lightning.
- CAT III covers distribution level wiring. This includes 480-volt and 600-volt circuits such as 3-phase bus and feeder circuits, motor control centers, load centers and distribution panels. Permanently installed loads are also classed as CAT III. CAT III includes large loads that can generate their own transients. At this level, the trend to using higher voltage levels in modern buildings has changed the picture and increased the potential hazards.
- CAT II covers the receptacle circuit level and plug-in loads.
- CAT I refers to protected electronic circuits.

Some installed equipment may include multiple categories. A motor drive panel, for example, may be CAT III on the 480-volt power side, and CAT I on the control side.


### Independent testing labs help ensure safety compliance

You want your tools and equipment to help you work safely. But how do you know that a tool designed to meet a safety standard will actually deliver the performance you are paying for?

Unfortunately it's not enough to just look on the box. The IEC (International Electrotechnical Commission) develops and proposes standards, but it is not responsible for enforcing the standards. Wording like "Designed to meet specification..." may not mean a test tool actually performs up to spec. Designer's plans are never a substitute for an actual independent test.



Go to [www.fluke.com/safety](http://www.fluke.com/safety) to view The Fluke Electrical Measurement Safety Program and order your free copy of the Fluke Safety video. This video makes the standards easy to understand and can be used as part of your own internal safety program.



LISTED

Underwriters  
Laboratories (UL)



Canadian Standards  
Association (CSA)



TUV and VDE  
(German standards  
organizations) are  
approval/listing  
agencies



United States  
Department of  
Labor Mine Safety  
and Health  
Administration

That's why independent testing is so important. To be confident, check the product for the symbol and listing number of Underwriters Laboratories (UL), the Canadian Standards Association (CSA), TÜV or another recognized testing organization. Those symbols can only be used if the product successfully completed testing to the agency's standard, which is based on national/international standards. That is the closest you can come to ensuring that the test tool you choose was actually tested for safety.

### What does the CE symbol indicate?

A product is marked CE (Conformité Européenne) to show it conforms to health, safety, environment and consumer protection requirements established by the European Commission. Products from outside the European Union cannot be sold there unless they comply with applicable directives. But manufacturers are permitted to self-certify that they have met the standards, issue their own Declaration of Conformity, and mark the product "CE." The CE mark is not, therefore, a guarantee of independent testing.

### Why are Fluke products different?

Don't be confused by "Listed" vs. "Designed to" in your test tools. IEC sets the standards but does not test or inspect for compliance. So a manufacturer can claim to "design to" a standard with no independent verification. To be UL-Listed, CSA or TÜV-Certified, a manufacturer must employ the listing agency to TEST the product's compliance with the standard. Look for the listing agency's emblem on the meter.

# Service Information

**Think of Fluke first for technical service, repair and calibration**

**Fluke customer support is ready to help**



Calibrating a thermometer.

## Technical service at your fingertips

We know Fluke tool users put their tools through the paces, so we're ready to answer your questions and help keep your tools in top shape. No matter what application, in what industry. And we'll do it through real technical service professionals in Everett, Washington.

**When you need questions answered, call Sales and Application Support at 1-888-44-Fluke or email [fluke-info@fluke.com](mailto:fluke-info@fluke.com)**

The Fluke experts answering your call can help with just about any test tool question. They specialize in:

- Advice on what to buy, from problem analysis to tool compatibility and configuration  
"If I'm working with three phase motors, what's the best tool to use?"
- Help on how to use your tools in any application, from automotive to industrial  
"How come I'm not getting a reading?"  
"How do I transfer my test results?" "How do I measure harmonics?"

**When your Fluke tools need repair or calibration, call Customer Support Services at 1-888-99-Fluke or email [service.status@fluke.com](mailto:service.status@fluke.com). Customers outside the U.S. email [service.international@fluke.com](mailto:service.international@fluke.com) or visit [www.fluke.com/service](http://www.fluke.com/service) to find your nearest location.**

If your tool isn't working correctly, or if you dropped it, ran over it, or dunked it in the pool, call Fluke. If it's not under warranty, we'll give you a cost estimate over the phone. Once you send it in, we'll verify the problem, fix it, test it and put it back in the mail often in less than five working days.

Fluke recommends having your DMMs, Calibrators and ScopeMeter test tools calibrated once a year—especially if you use them often or need accurate measurements to meet regulations requirements. Calibration compares your tool's measurements to the accuracy standard—sort of like setting your watch to match an atomic clock. Some test tools live a pretty rough life. If you calibrate them, you know they're accurate—even after what you put them through.

For more information on servicing your Fluke tools outside of the U.S., see page 2 for contact information.

Application note, literature code 2153519:

## Why calibrate test equipment?

Why would a digital test tool need to be calibrated? It's not as though any analog parts will go out of balance. Well, have any events occurred that would render your instruments less accurate or unsafe? Is accurate measurement essential to your operations? Are you trending data? Read this application note to find out what causes calibration problems and whether you should consider calibrating your test instruments.

Visit [www.fluke.com/why-calibrate](http://www.fluke.com/why-calibrate)



Application note, literature code 2138394:

## Shocking treatment

Because of our commitment to safety, all Fluke equipment is designed to provide as much protection as possible from the inherent dangers of working in the unsettled sea of electricity.

Fluke products are dropped, shocked, short circuited, injected with thousands of volts of electricity and forced to endure extreme temperature, just to get out the door.

To learn more about our product tests, visit [www.fluke.com/shocking](http://www.fluke.com/shocking)



# Pick the right digital multimeter for you

FLUKE®

## Digital Multimeter Selection Guide

|                                            |  |  |  |  |  |  |  |  |
|--------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Models                                     | Highest accuracy with data logging<br>189                                         | Industrial troubleshooting<br>87V                                                 | True-rms and built-in thermometer<br>179                                          | Designed for building maintenance<br>117                                          | Designed for HVAC/R technicians<br>116                                             | Waterproof and chemical resistant<br>27                                             | Two powerful tools in one<br>1587                                                   | 4-20 mA loop diagnostics<br>789                                                     |
| <b>Basic features</b>                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| True-rms readings                          | AC+DC                                                                             | AC                                                                                | AC                                                                                | AC                                                                                | AC                                                                                 |                                                                                     | AC                                                                                  | AC                                                                                  |
| Basic dc accuracy                          | 0.025 %                                                                           | 0.05 %                                                                            | 0.09 %                                                                            | 0.5 %                                                                             | 0.5 %                                                                              | 0.1 %                                                                               | 0.09 %                                                                              | 0.1 %                                                                               |
| Wide bandwidth                             | 100 kHz                                                                           | 20 kHz                                                                            |                                                                                   |                                                                                   |                                                                                    | 30 kHz                                                                              |                                                                                     |                                                                                     |
| Auto/manual ranging                        | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |
| Digits                                     | 4-1/2                                                                             | 4-1/2                                                                             | 3-1/2                                                                             | 3-1/2                                                                             | 3-1/2                                                                              | 3-1/2                                                                               |                                                                                     | 3-1/2                                                                               |
| Counts                                     | 50000                                                                             | 20000                                                                             | 6000                                                                              | 6000                                                                              | 6000                                                                               | 3200                                                                                | 6000                                                                                | 4000                                                                                |
| <b>Measurements</b>                        |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Voltage ac/dc                              | 1000 V                                                                            | 1000 V                                                                            | 1000 V                                                                            | 600 V                                                                             | 600 V                                                                              | 1000 V                                                                              | 1000 V                                                                              | 1000 V                                                                              |
| Current ac/dc                              | 10 A                                                                              | 10 A                                                                              | 10 A                                                                              | 10 A                                                                              | 600 µA                                                                             | 10 A                                                                                | 400 mA                                                                              | 1 A                                                                                 |
| Resistance                                 | 500 MΩ                                                                            | 50 MΩ                                                                             | 50 MΩ                                                                             | 40 MΩ                                                                             | 40 MΩ                                                                              | 32 MΩ                                                                               | 50 MΩ                                                                               | 40 MΩ                                                                               |
| Frequency                                  | 1 MHz                                                                             | 200 kHz                                                                           | 100 kHz                                                                           | 50 kHz                                                                            | 50 kHz                                                                             |                                                                                     | 100 kHz                                                                             | 20 kHz                                                                              |
| Capacitance                                | 50 mF                                                                             | 10 mF                                                                             | 10 mF                                                                             | 10 mF                                                                             | 10 mF                                                                              |                                                                                     | 10 mF                                                                               |                                                                                     |
| Temperature                                | +1350 °C                                                                          | +1090 °C                                                                          | +400 °C                                                                           |                                                                                   | +400 °C                                                                            |                                                                                     | +500 °C                                                                             |                                                                                     |
| dB                                         | 60 dB                                                                             |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Conductance                                | 50 nS                                                                             | 50 nS                                                                             |                                                                                   |                                                                                   |                                                                                    | 32 nS                                                                               |                                                                                     |                                                                                     |
| Duty cycle/pulse width                     | •                                                                                 | •                                                                                 |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Motor drive measurements/low pass filter   |                                                                                   | •                                                                                 |                                                                                   |                                                                                   |                                                                                    |                                                                                     | •                                                                                   |                                                                                     |
| Continuity with beeper                     | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |
| Diode test                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |
| <b>Display</b>                             |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Dual display                               | •                                                                                 |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| Analog bargraph                            | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   |                                                                                     | •                                                                                   |
| Backlight                                  | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| <b>Data storage and exchange</b>           |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Min/Max recording                          |                                                                                   | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |
| Min/Max recording/with time stamp          | •                                                                                 |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     | •                                                                                   |                                                                                     |
| Fast Min/Max                               | 250 µs                                                                            | 250 µs                                                                            |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Display Hold/Auto (Touch) Hold             | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   |                                                                                     | •                                                                                   |
| Relative reference                         | •                                                                                 | •                                                                                 |                                                                                   |                                                                                   |                                                                                    | •                                                                                   |                                                                                     | •                                                                                   |
| PC interface                               | •                                                                                 |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| Data logging                               | •                                                                                 |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | with PC                                                                             |
| Readings memories                          | 100                                                                               |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| <b>Other features</b>                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Automatic selection, LoZ                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Insulation test range                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     | 0.01 MΩ to 2 GΩ                                                                     |                                                                                     |
| VoltAlert, non-contact ac voltage detector |                                                                                   |                                                                                   |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Real time clock                            | •                                                                                 |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Overmolded case, integrated holster        | •                                                                                 |                                                                                   | •                                                                                 |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| Removable holster                          |                                                                                   | •                                                                                 |                                                                                   | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   |                                                                                     |
| ToolPak Magnetic Hangar compatibility      | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  |                                                                                     |                                                                                     | •                                                                                   |
| Closed case calibration                    | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| Separate battery door                      | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |
| Completely sealed/watertight               |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    | •                                                                                   |                                                                                     |                                                                                     |
| Automatic power off                        | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| Low battery indication                     | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |
| Operating temperature range                | -20 °C, +55 °C                                                                    | -20 °C, +55 °C                                                                    | -10 °C, +50 °C                                                                    | -10 °C, +50 °C                                                                    | -10 °C, +50 °C                                                                     | -40 °C, +55 °C                                                                      |                                                                                     | -20 °C, +55 °C                                                                      |
| 4-20 mA                                    |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 24 V loop supply                           |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| <b>Warranty and electrical safety</b>      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Limited lifetime warranty                  | •                                                                                 | •                                                                                 | •                                                                                 |                                                                                   |                                                                                    | •                                                                                   |                                                                                     |                                                                                     |
| Warranty (years)                           |                                                                                   |                                                                                   |                                                                                   | 3                                                                                 | 3                                                                                  |                                                                                     | 3                                                                                   | 3                                                                                   |
| Input alert                                | •                                                                                 | •                                                                                 |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| Dangerous voltage indication               | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| CAT III measurements                       | 1000 V                                                                            | 1000 V                                                                            | 1000 V                                                                            | 600 V                                                                             | 600 V                                                                              | 1000 V                                                                              | 1000 V                                                                              | 1000 V                                                                              |
| CAT IV measurements                        | 600 V                                                                             | 600 V                                                                             | 600 V                                                                             |                                                                                   |                                                                                    | 600 V                                                                               | 600 V                                                                               |                                                                                     |
| See page                                   | 12                                                                                | 14                                                                                | 15                                                                                | 17                                                                                | 18                                                                                 | 19                                                                                  | 35                                                                                  | 43                                                                                  |

More comprehensive information is available at [www.fluke.com/dmm](http://www.fluke.com/dmm)

# Test faster and safer with a new Fluke

FLUKE®

## Move up to more measurement performance and safety

### Move up from your old 87 and benefit from more than a dozen improvements

| Function                           | Original 87       | 87V                                 | Benefit                                                                      |
|------------------------------------|-------------------|-------------------------------------|------------------------------------------------------------------------------|
| Selectable filter for motor drives | No                | Yes                                 | Accurate voltage and frequency measurements on pulse width modulated signals |
| Built-in thermometer               | No                | Yes                                 | No separate thermometer required                                             |
| Capacitance                        | 5 nF to 5 $\mu$ F | 5 nF to 10,000 $\mu$ F              | Measure more capacitors                                                      |
| V dc accuracy and resolution       | 0.1 %, 10 $\mu$ V | 0.05 %, 10 $\mu$ V                  | Precise measurements in a handheld tool                                      |
| Display digits                     | 13.5 mm x 7 mm    | 15.25 mm x 8.5 mm                   | 30 % larger makes it easy to read                                            |
| Backlight                          | Green             | 2-level, bright white               | Easier to read in dark locations                                             |
| Magnetic hanger                    | No                | Optional (included with kit)        | Position meter for easy viewing                                              |
| Peak capture                       | 1 ms              | 250 $\mu$ S                         | Record intermittent problems four times faster                               |
| CAT electrical safety rating       | No                | Yes, 2nd edition ANSI and IEC 61010 | Increased protection from 8 kV spikes that can cause arc flash               |
| Battery door                       | No                | Yes                                 | Change battery quickly without breaking cal seal                             |
| Warranty                           | Expired           | Limited lifetime                    | Lower cost of ownership                                                      |



Get accurate voltage and frequency measurements on adjustable speed motor drives with the 87V.

### Move up from your old 8060 or 8062 and benefit from more than 20 improvements

| Function                          | 8060               | 189                           | Benefit                                                        |
|-----------------------------------|--------------------|-------------------------------|----------------------------------------------------------------|
| Built-in recorder with time stamp | No                 | Yes                           | Record and view intermittent problems without a chart recorder |
| PC interface                      | No                 | Yes, software optional        | Transfer readings to a PC for analysis and documentation       |
| Built-in thermometer              | No                 | Yes, probe optional           | No need to carry a separate thermometer                        |
| Capacitance                       | No                 | 5 nF to 50,000 $\mu$ F        | Measure capacitors with one tool                               |
| V dc and V ac resolution          | 10 $\mu$ V         | 1 $\mu$ V                     | Precise measurements in a handheld tool                        |
| dBv and dBm                       | Yes                | Yes                           | Measure communication circuits                                 |
| Duty cycle and pulse width        | No                 | Yes                           | Measure control circuits                                       |
| In-line current                   | 2 A                | 10 A, 1000 V fuse             | Safely measure five times more current                         |
| Relative offset                   | No                 | Yes                           | Remove test lead resistance<br>See small signal variations     |
| Range selection                   | Manual, 8 switches | Auto/Manual range             | Simpler to use, more durable                                   |
| Peak capture, MIN/MAX             | No                 | 250 $\mu$ S                   | Record intermittent problems                                   |
| Backlight                         | No                 | 2-level, bright white         | Easier to read in dark locations                               |
| Holster                           | No                 | Integrated overmold           | Stands up to accidental drops                                  |
| Magnetic hanger                   | No                 | optional TPAK                 | Position meter for easy viewing                                |
| CAT electrical safety rating      | No                 | Yes, 2nd edition ANSI and IEC | Increased protection from 8 kV spikes that can cause arc flash |
| Battery door                      | No                 | Yes                           | Change battery quickly without breaking cal seal               |
| Warranty                          | Expired            | Limited lifetime              | Lower cost of ownership                                        |



Use the built-in data logging feature of the 189 to record readings and the time they occurred to catch intermittent problems.

### Move up from your old 70 or 20 series and benefit from more than 15 improvements

| Feature                                        | Original 77 | 179                          | Benefit                                                                                |
|------------------------------------------------|-------------|------------------------------|----------------------------------------------------------------------------------------|
| True-rms                                       | No          | Yes                          | Accurate on non-linear signals                                                         |
| Accuracy, basic dc                             | 0.3 %       | 0.09 %                       | Three times more accurate                                                              |
| Temperature                                    | No          | Yes                          | No need for a separate thermometer                                                     |
| Min/Max/Average                                | No          | Yes                          | Capture intermittent problems                                                          |
| Display size                                   | Small       | 20 % larger                  | Large, easy to read                                                                    |
| Display backlight                              | No          | Yes                          | Easy to read in dark locations                                                         |
| Simple to use                                  | Yes         | Yes                          | No retraining required                                                                 |
| Probe holders                                  | Yes         | Improved                     | One-hand operation                                                                     |
| Latest electrical measurement safety standards | Not rated   | 1000 V CAT III, 600 V CAT IV | Designed to withstand 8,000 volt peak transient impulses and protect against arc flash |
| Optional magnetic hanger                       | No          | Yes                          | Position meter in best location                                                        |
| Warranty                                       | Expired     | Limited lifetime             | Lower cost of ownership                                                                |
| Frequency                                      | No          | Yes                          | Built in frequency counter                                                             |
| Capacitance                                    | No          | Yes                          | Measure motor capacitors and components                                                |
| Max. ac voltage                                | 750         | 1000                         | Wider measurement range                                                                |
| Battery door                                   | No          | Yes                          | Change battery quickly without breaking cal seal                                       |



The ultimate multi-purpose meter, the 179 combines precision, safety and reliability to help you get any job done.

# Fluke 189 Logging Multimeter

**Solve complex problems for electronic and industrial applications**



**True-rms**

The Fluke 189 is the most advanced meter with features, precision and accuracy to troubleshoot industrial and electronic equipment in the field or on the bench. The Fluke 189 has a **built-in data logger** to record measurements unattended. Recorded data can be viewed on the 189 or transferred to a PC with optional FlukeView® Forms software.

- Built in data logger (Fluke 189) records reading and time to catch intermittent problems
- True-rms, 100 KHz bandwidth for precise measurement of non linear signals
- 0.025 % dc accuracy and 1 microvolt resolution for bench meter performance in a handheld package
- Measure 20 A for up to 30 seconds, 10 A continuous
- Temperature, capacitance, dB, frequency, pulse width and duty cycle to find more problems with one tool
- Large bright white display with dual parameter readout to view multiple readings at once
- Min/Max with timestamp to record signal fluctuations
- Peak capture to measure transients as short as 250  $\mu$ s
- Isolated IR communication port to send data to a PC (with optional FVF pack)
- Premium test leads and alligator clips (AC72) included
- **New!** Optional USB data cable with FlukeView Forms
- **New!** Optional battery pack (BP189) extends battery life to over 400 hours

## Electrical safety

All inputs are protected to measurement CAT III 1000 V and CAT IV 600 V.



Available in non-logging version as Fluke 187

## Log and document



**Buy Combo Pack and Save**

**NEW! The 189/FVF2 Data Logging Multimeter and Software Combo Pack gives you a practical, affordable approach to predictive maintenance.**

- With built-in data logger, the 189 helps you track down elusive, intermittent problems, monitoring equipment with any of its functions, while you do other jobs
- Overlay data from six meters or six time periods to find cause and effect relationships or for condition monitoring applications
- With break-through accuracy and precision, catch events as brief as 50 ms
- Designed for harsh environments that would ruin most data loggers or multimeters
- Log up to 450 hours of data using the extended battery pack
- Turn data into meaningful graphs and tables using FlukeView Forms software
- TPAK™ Magnetic Hanger allows you to securely hang your meter for monitoring or hands-free use
- Soft carrying case to protect your investment
- USB cable included with kit

## Specifications - 189 and 187 DMMs

| Function    | Range and resolution                                                     | Best accuracy 180 Series |
|-------------|--------------------------------------------------------------------------|--------------------------|
| V dc        | 50.000 mV, 500.00 mV, 3000.0 mV, 5.0000 V, 50.000 V, 500.00 V, 1000.0 V  | $\pm 0.025$ %            |
| V ac        | 50.000 mV, 500.00 mV, 3000.0 mV, 5.0000 V, 50.000 V, 500.00 V, 1000.0 V  | $\pm 0.4$ %              |
| A dc        | 500.00 $\mu$ A, 5.000 $\mu$ A, 50.000 mA, 400.00 mA, 5.0000 A, 10.000 A* | $\pm 0.15$ %             |
| A ac        | 500.00 $\mu$ A, 5.000 $\mu$ A, 50.000 mA, 400.00 mA, 5.0000 A, 10.000 A* | $\pm 0.75$ %             |
| Resistance  | 500.00 $\Omega$ to 500.0 M $\Omega$                                      | $\pm 0.05$ %             |
| Capacitance | 1.000 nF to 50.00 mF                                                     | $\pm 1.00$ %             |
| Frequency   | 500.00 Hz, 5.0000 kHz, 50.000 kHz, 999.99 kHz                            | $\pm 0.005$ %            |
| Temperature | -200 °C to 1350 °C (-328 °F to 2462 °F)                                  | $\pm 1$ % of reading     |
| Duty cycle  | 10 % to 90 %, resolution 0.01 %                                          | —                        |
| Pulse width | 2 ranges, 499.99 ms and 999.9 ms, best resolution 0.01 ms                | 3 %                      |
| dBm, dBv    | -62 to +60, resolution 0.01dB                                            | 0.1 dB                   |

\*10 A continuous, 20 A for up to 30 seconds and not specified.

**Battery life:** 72 hours typical (alkaline), 450 hours typical with Battery Extender (BP189)  
**Size (LxWxD):** 203 mm x 100 mm x 50 mm (8.00 in x 3.94 in x 1.97 in)  
**Weight:** 0.545 kg (19.2 oz)

## Recommended accessories - 189 and 187 DMMs



**TL910**  
Electronic Test Probes  
See page 63



**TL81A**  
Test Lead Kit  
See page 63



**C125**  
Meter Case  
See page 70



**BP189**  
High Capacity Battery Pack  
See page 65



**FVF-SC2**  
FlukeView Forms Software  
See page 65

## Included accessories

Every 180 series meter comes packaged with TL71 Silicone Test Leads, probe holders, two AC72 Alligator Clips, four AA batteries (installed), CD-ROM (users manual and technical notes) and operator's guide.

## Ordering information

Fluke-189/FVF2 Logging Multimeter and Software Combo Pack  
 Fluke-189 Logging Multimeter  
 Fluke-187 Digital Multimeter  
 FVF-SC2 FlukeView Forms Software w/cable

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

# FlukeView® Forms Software

FLUKE®


**Utilize this powerful tool to analyze your measurements**



To take a test drive of the power of FlukeView Forms, download demonstration software for free at [www.fluke.com/flukeviewforms](http://www.fluke.com/flukeviewforms)

Harness the power of the data logging function on your Fluke Digital Multimeter. FlukeView Forms offers an easy-to-use, customizable solution to help you document logged data. Easy-to-use wizards allow you to download readings from your Fluke tool and display individual readings or a series of measurements.

- Graph data to help you detect trends, analyze, predict and prevent problems
- Print, save and share logged data
- Log live readings while connected to a PC, or leave your Fluke 189 in place to capture up to 1,000 readings for download to a PC
- Display readings from up to six different meters on the same graph to show links between multiple processes, events and locations
- Record and display any function the meter measures: volts, ohms, frequency, capacitance, temperature, diode testing and more
- Free demo-reader download allows co-workers or clients to open your report and interact with captured data
- Export data into Microsoft® Excel




You can share reports and add notes to draw attention to and explain anomalies.

Customize reports using your specific data or company logo, spot trends and document interruptions or spikes.



A single graph overlaying two time periods makes analysis easier.



Use the FlukeView designer to turn simple time and event data into fully customized reports.



## Fluke 189, 189/FVF2 Kit and 187 capabilities

|                                                    | 189/FVF2 | 189 | 187 | Benefit                                                                                    |
|----------------------------------------------------|----------|-----|-----|--------------------------------------------------------------------------------------------|
| Fluke 180 Series Multimeter and premium test leads | •        | •   | •   | Fluke's top-of-the-line multimeter with maximum feature set to troubleshoot any situation. |
| PC connectable                                     | •        | •   | •   | Use to download and document test results.                                                 |
| Logging capabilities                               | •        | •   |     | Reduce man-hours by using logging to find problems and intermittent glitches.              |
| FlukeView Forms software                           | •        |     |     | Document and print measurement data in a clear and organized format.                       |
| Overlay and graph data from up to six meters       | •        | •   |     | Find elusive cause/effective relationships.                                                |
| Compatible with FlukeView Forms Demo Reader        | •        | •   | •   | Allow data to be distributed and shared with individuals throughout a company for free.    |

### Compatible with

- FVF-SC2 Fluke 187 and 189 Digital Multimeters, Fluke 1550B MegOhmMeter, Fluke 789 ProcessMeter™
- FVF-SC1 Fluke 53-II and 54-II Thermometers
- FVF-SC3 Fluke 45 Bench Meter

For more information and detailed specifications, go to [www.fluke.com/flukeviewforms](http://www.fluke.com/flukeviewforms)

# Fluke 87V Industrial Multimeter

FLUKE®

## Diagnostic functions for maximum industrial productivity



True-rms

The Fluke 87V has measurement functions, trouble-shooting features, resolution and accuracy to solve more problems on motor drives, in-plant automation, power distribution and electro-mechanical equipment.

### New features for maximum productivity

- Unique function for accurate voltage and frequency measurements on adjustable speed motor drives and electrically noisy equipment (87V and 87V Ex)
- Large digit display with bright two level backlight makes the 87V significantly easier to read
- Measure 20 A for up to 30 sec, 10 A continuously
- Optional magnetic hanger for easy setup and viewing while freeing your hands for other tasks (TPAK)
- Expanded capacitance range to 10,000  $\mu$ F
- Built-in thermometer (87V)

### Electrical safety

All inputs are protected to CAT III 1000 V and CAT IV 600 V. They can withstand impulses in excess of 8,000 V to help protect you from arc blast resulting from surges and spikes.

Available in intrinsically safe version as the **Fluke 87V Ex.**



Also available as 83V average responding multimeter, see below for specifications

Application note, literature code 2155830:

### Multimeter measurements on adjustable speed drives utilizing the Fluke 87V DMM

How do I troubleshoot an adjustable speed drive with a digital multimeter?

Read this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



New

## Features – 87V and 83V DMMs

| Feature                                                                            | 87V Ex | 87V | 83V |
|------------------------------------------------------------------------------------|--------|-----|-----|
| ATEX II 2G EEx ia IIC T4 safety rating for use in Zone 1 and Zone 2                | •      |     |     |
| True-rms ac voltage and current for accurate measurements on non linear signals    | •      | •   |     |
| Selectable filter for accurate voltage and frequency measurements on motor drives  | •      | •   |     |
| 0.05 % dc accuracy                                                                 | •      | •   |     |
| 4-1/2 digit mode for precise measurements                                          | •      | •   |     |
| Built-in thermometer lets you carry one less tool                                  | •      | •   |     |
| Large display digits and two level bright white backlight for increased visibility | •      | •   | •   |
| 10,000 $\mu$ F capacitance range for components and motor caps                     | •      | •   | •   |
| Peak capture to record transients as fast as 250 $\mu$ s                           | •      | •   |     |
| Measure up to 1000 V ac and dc                                                     | •      | •   | •   |
| Measure up to 10 A, 20 A for up to 30 seconds                                      | •      | •   | •   |
| Auto and manual ranging for maximum flexibility                                    | •      | •   | •   |
| Analog bargraph                                                                    | •      | •   | •   |
| Frequency to 200 kHz and % duty cycle                                              | •      | •   | •   |
| Min/Max and average recording to capture variations automatically                  | •      | •   | •   |
| Relative mode to remove test lead resistance from low ohms measurements            | •      | •   | •   |
| Access door for fast battery changes without breaking the calibration seal         | •      | •   | •   |

### Fluke 87V/E2 Industrial Electrician's Combo Kit

Make industrial troubleshooting even more productive with accessories.

- 87V Industrial Multimeter
- **New!** C35 lightweight soft case to provide optimal protection and storage
- TL224 1.5 m silicone leads resist heat
- TP238 removable probes with 4 mm of exposed metal for use on industrial circuits
- AC220 retractable long reach alligator clips
- ToolPak™ meter hanging accessory to hold meter to steel surfaces
- 80BK K-type temperature probe

## Specifications – 87V and 83V DMMs

| Function                  | Range and resolution                                                                                          | Basic accuracy   |         |
|---------------------------|---------------------------------------------------------------------------------------------------------------|------------------|---------|
|                           |                                                                                                               | 87V              | 83V     |
| DC volts                  | 600.0 mV, 6.000 V, 60.00 V, 600.0 V, 1000 V                                                                   | 0.05 %           | 0.1 %   |
| AC volts                  | 600.0 mV, 6.000 V, 60.00 V, 600.0 V, 1000 V                                                                   | 0.7 % (true-rms) | 0.5 %   |
| DC current                | 600.0 $\mu$ A, 6.000 $\mu$ A, 60.00 $\mu$ A, 600.0 mA, 6.000 A, 10.00 A                                       | 0.2 %            | 0.4 %   |
| AC current                | 600.0 $\mu$ A, 6.000 $\mu$ A, 60.00 $\mu$ A, 600.0 mA, 6.000 A, 10.00 A                                       | 1.0 % (true-rms) | 1.2 %   |
| Temperature (excl. probe) | -200 °C to 1090 °C (-328 °F to 1994 °F)                                                                       | 1.0 %            | —       |
| 80BK Temperature Probe    | -40 °C to 260 °C (-40 °F to 500 °F)                                                                           | 2.2 °C or 2 %    | —       |
| Resistance                | 600.0 $\Omega$ , 6.000 k $\Omega$ , 60.00 k $\Omega$ , 600.0 k $\Omega$ , 6.000 M $\Omega$ , 50.00 M $\Omega$ | 0.2 %            | 0.4 %   |
| Capacitance               | 10.00 nF, 100.0 nF, 1.000 $\mu$ F, 10.00 $\mu$ F, 100.0 $\mu$ F, 9.999 $\mu$ F                                | 1.0 %            | 1.0 %   |
| Frequency                 | 199.99 Hz, 1.9999 kHz, 19.999 kHz, 199.99 kHz                                                                 | 0.005 %          | 0.005 % |

**Battery life:** 400 hours typical with backlight off. **Size (LxWxD):** 201 mm x 98 mm x 52 mm (7.9 in x 3.8 in x 2 in). **Weight:** 355 g (12 oz)

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

### Included accessories

Every Fluke 83V and 87V meter comes packaged with TL75 Test Leads, AC72 Alligator Clips, holster, 9 V battery (installed), 80BK Temperature Probe (87V only) CD-ROM (users manual and technical notes) and operator's guide.

### Ordering information

Fluke-87-5 Industrial True-rms Multimeter with Temperature  
Fluke-87-5/E2 Industrial Electrician's Combo Kit  
Fluke-83-5 Industrial Multimeter

# Fluke 179 Digital Multimeter

FLUKE®

**Versatile meters for maintenance and field service**



True-rms

The 179 true-rms Multimeter has the features needed to find most electrical and HVAC problems. Simple to use with significant improvements over the original Fluke 70 Series like true-rms, the 179 has more measurement functions, conformance to the latest safety standards and a much larger display that's easier to view.

## Features include:

- Wide 1000 V measurement range
- True-rms for precise measurement of non linear signals
- Capacitance, resistance, continuity and frequency
- Built-in thermometer (Fluke 179 only)
- Large, easy-to-read display
- Backlight for work in dimly lit areas (Fluke 177 and 179 only)
- Min/Max/Avg to record signal fluctuations
- Free your hands with the optional TPAK magnetic hanger (Fluke TPAK)

## Electrical safety

All inputs are protected to measurement CAT III 1000 V and CAT IV 600 V. This meter can withstand transient impulses in excess of 8000 V to help protect you from arc blasts resulting from surges and spikes.



## 179/EDA2 Electronics Multimeter and Deluxe Accessory Combo Kit

- 179 True-rms Digital Multimeter
- **New!** C35 lightweight soft case to provide optimal protection and storage
- TL910 Electronic Test Probes
- TL224 SureGrip™ Silicone Test Leads resist heat
- AC280 SureGrip™ Heavy Duty Hook Clips
- 80BK Type-K temperature probe
- ToolPak™ meter hanging accessory to hold meter to steel surfaces



## 179/1AC-II Electrician's Multimeter and Voltage Tester Combo Kit

- 179 True-rms Digital Multimeter
- 1AC-II VoltAlert™ Non-Contact Voltage Detector
- **New!** C35 lightweight soft case to provide optimal protection and storage
- AC220 retractable long reach alligator clips
- TP220 sharp 12 mm stainless steel tip provides reliable contact
- TL224 1.5 m silicone leads resist heat
- ToolPak™ meter hanging accessory to hold meter to steel surfaces
- 80BK K-type temperature probe

## Features - 175, 177 and 179 DMMs

| Feature                               | 179    | 177    | 175    |
|---------------------------------------|--------|--------|--------|
| Max voltage                           | 1000   | 1000   | 1000   |
| True-rms                              | •      | •      | •      |
| Temperature                           | •      | •      | •      |
| Basic dc accuracy                     | 0.09 % | 0.09 % | 0.15 % |
| Backlight                             | •      | •      | •      |
| Min/Max/Avg                           | •      | •      | •      |
| ToolPak meter hanging kit with magnet | Opt    | Opt    | Opt    |

## Specifications - 179, 177 and 175 DMMs

| Function                | Range and resolution                                      | Best accuracy                                         |
|-------------------------|-----------------------------------------------------------|-------------------------------------------------------|
| DC voltage              | 600.0 mV, 6.000 V, 60.00 V, 600.0 V, 1000 V               | ± 0.09 % (Models 177 and 179)<br>± 0.15 % (Model 175) |
| AC voltage <sup>1</sup> | 600.0 mV, 6.000 V, 60.00 V, 600.0 V, 1000 V               | ± 1.0 % of reading                                    |
| DC current              | 60.00 mA, 400.0 mA, 6.000 A, 10.00 A <sup>2</sup>         | ± 1.0 % of reading                                    |
| AC current <sup>2</sup> | 60.00 mA, 400.0 mA, 6.000 A, 10.00 A <sup>2</sup>         | ± 1.5 % of reading                                    |
| Resistance              | 600.0 Ω, 6.000 kΩ, 60.00 kΩ, 600.0 kΩ, 6.000 MΩ, 50.00 MΩ | ± 0.9 % of reading                                    |
| Capacitance             | 1000 nF, 10.00 μF, 100.0 μF, 9999 μF                      | ± 1.2 % of reading                                    |
| Frequency <sup>3</sup>  | 99.99 Hz, 999.9 Hz, 9.999 kHz, 99.99 kHz                  | ± 0.1 % of reading                                    |
| Temperature (Model 179) | -40 °C to +400 °C (-40 °F to +752 °F)                     | 1.0 % of reading                                      |

<sup>1</sup>All ac voltage and ac current ranges are specified from 5 % of range to 100 % of range.

<sup>2</sup>10 A continuous, 20 A for up to 30 seconds.

<sup>3</sup>Voltage frequency is specified from 2 Hz to 100 kHz. Current Frequency is specified from 2 Hz to 30 kHz.

**Battery life:** 200 hours typical for alkaline. **Size (HxWxL):** 4.3 cm x 9.0 cm x 18.5 cm (1.7 in x 3.5 in x 7.3 in)

## Recommended accessories - 179, 177 and 175 DMMs



**L210**  
Probe Extender  
with light  
See page 64



**TL220**  
SureGrip Industrial  
Test Lead Set  
See page 61



**CS10**  
Carrying Case  
See page 70



**PV350**  
Pressure-Vacuum  
Module  
See page 65



**i400s**  
AC Current Clamp  
See page 66

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

## Included accessories

Every Fluke 170 Series meter comes packaged with TL75 test leads, 9 V battery (installed) and manual. The Fluke 179 comes with an 80BK Temperature Probe.

## Ordering information

Fluke-179 Digital Multimeter  
Fluke-179/1AC-II Electricians Combo Kit  
Fluke-179/EDA2 Electronics Combo Kit  
Fluke-175 Digital Multimeter  
Fluke-177 Digital Multimeter



# Fluke Family of True-rms Digital Multimeters

FLUKE®

Engineered by Fluke for  
working professionals

| Commercial electricians                                                                                                                                                                                                                                                                                 |                                                                                                      | HVAC/R technicians                                                                                                                                                                                                                                                                     |                                                                                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
|  <p><b>Fluke 112</b></p>                                                                                                                                                                                               |  <p><b>New</b></p>  |  <p><b>Fluke 12, 16</b></p>                                                                                                                                                                           |  <p><b>New</b></p>  |
| <p><b>Fluke 117</b></p> <ul style="list-style-type: none"> <li>• VoltAlert™ non-contact voltage detection</li> <li>• LoZ low impedance input for safer troubleshooting</li> <li>• Resistance, continuity, frequency and capacitance</li> <li>• AC/DC voltage to 600 V, ac/dc current to 10 A</li> </ul> |                                                                                                      | <p><b>Fluke 116</b></p> <ul style="list-style-type: none"> <li>• Temperature to 400 °C</li> <li>• Resistance, continuity, frequency and capacitance</li> <li>• LoZ low impedance input for safer troubleshooting</li> <li>• AC/DC voltage to 600 V, ac/dc current to 600 µA</li> </ul> |                                                                                                        |
| Field service technicians                                                                                                                                                                                                                                                                               |                                                                                                      | Basic electrical                                                                                                                                                                                                                                                                       |                                                                                                        |
|  <p><b>Fluke 110, 111</b></p>                                                                                                                                                                                         |  <p><b>New</b></p> |  <p><b>Fluke 7-600</b></p>                                                                                                                                                                           |  <p><b>New</b></p> |
| <p><b>Fluke 115</b></p> <ul style="list-style-type: none"> <li>• Resistance, continuity, frequency and capacitance</li> <li>• AC/DC voltage to 600 V</li> <li>• AC/DC current to 10 A</li> </ul>                                                                                                        |                                                                                                      | <p><b>Fluke 114</b></p> <ul style="list-style-type: none"> <li>• LoZ low impedance input for safer troubleshooting</li> <li>• Resistance and continuity</li> <li>• AC/DC voltage to 600 V</li> </ul>                                                                                   |                                                                                                        |

| Basic features                             | 114   | 115    | 116     | 117    |
|--------------------------------------------|-------|--------|---------|--------|
| True-rms readings                          | ac    | ac     | ac      | ac     |
| Basic dc accuracy                          | 0.5 % | 0.5 %  | 0.5 %   | 0.5 %  |
| Digits                                     | 3-1/2 | 3-1/2  | 3-1/2   | 3-1/2  |
| Counts                                     | 6000  | 6000   | 6000    | 6000   |
| <b>Measurements</b>                        |       |        |         |        |
| Voltage ac/dc                              | 600 V | 600 V  | 600 V   | 600 V  |
| Current ac/dc                              | —     | 10 A   | 600 µA  | 10 A   |
| Resistance                                 | 40 MΩ | 40 MΩ  | 40 MΩ   | 40 MΩ  |
| Frequency                                  | —     | 50 kHz | 50 kHz  | 50 kHz |
| Capacitance                                | —     | 10 mF  | 10 mF   | 10 mF  |
| Temperature                                | —     | —      | +400 °C | —      |
| <b>Display</b>                             |       |        |         |        |
| Analog bargraph                            | •     | •      | •       | •      |
| Large backlit display                      | •     | •      | •       | •      |
| <b>Data storage and exchange</b>           |       |        |         |        |
| Min/Max recording                          | •     | •      | •       | •      |
| Display hold/auto touch hold               | •     | •      | •       | •      |
| <b>Other features</b>                      |       |        |         |        |
| Automatic selection, LoZ                   | •     | •      | •       | •      |
| VoltAlert, non-contact ac voltage detector | •     | •      | •       | •      |

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

# Fluke 117 and 115 True-rms Digital Multimeters

FLUKE®

Designed for commercial electricians and field service technicians

New



## Fluke 117

The Fluke 117 is the ideal meter for demanding settings like commercial buildings, hospitals and schools. The 117 includes integrated non-contact voltage detection to help get the job done faster.

### The 117 features include:

- **VoltAlert™ Technology** for integrated non-contact voltage detection
- **AutoVolt feature** for automatic ac/dc voltage selection
- **LoZ:** low input impedance prevents false readings due to "ghost voltage"
- Large display and white LED backlight to work in poorly lit areas more effectively
- Compact design for one-handed operation
- Min/Max/Average to record signal fluctuations
- Compatible with optional magnetic hanger (ToolPak™) for hands free operation
- Current measurement 20 A (30 seconds momentary; 10 A continuous)
- Resistance, continuity, frequency and capacitance

## Fluke 115

The new Fluke 115 is the solution for a wide electrical and electronic testing applications.

### The 115 features include:

- Large display and white LED backlight to work in poorly lit areas more effectively
- Compact ergonomic design for one-handed operation
- Min/Max/Average to record signal fluctuations
- Resistance, continuity, frequency and capacitance



New



## Features – 117 and 115 DMMs

| Feature                                                | 117 | 115 |
|--------------------------------------------------------|-----|-----|
| VoltAlert™                                             | •   |     |
| AutoVolt/LoZ                                           | •   |     |
| Analog bargraph                                        | •   | •   |
| Large backlit digital display                          | •   | •   |
| True-rms for accurate measurements on non-linear loads | •   | •   |
| Min/Max recording                                      | •   | •   |
| Display hold                                           | •   | •   |
| 3-1/2 digits                                           | •   | •   |
| 6000 counts                                            | •   | •   |
| CAT III 600 V safety rated                             | •   | •   |

## Specifications – 117 and 115 DMMs

| Function      | Range and resolution | Best accuracy |
|---------------|----------------------|---------------|
| Volts ac/dc   | 600 V                | 0.5 % + 2     |
| Current ac/dc | 10 A                 | 1.0 % + 3     |
| Resistance    | 40 MΩ                | 0.9 % + 2     |
| Capacitance   | 1 nF to 9,999 µF     | 1.9 % + 2     |
| Frequency     | 5 Hz to 50 kHz       | 0.1 % + 2     |
| Diode         | 2 V                  | 0.9 % + 2     |

## Recommended accessories – 117 and 115 DMMs



**ToolPak™**  
Meter Hanger  
See page 71



**TL220**  
SureGrip Industrial  
Test Lead Set  
See page 61



**C50**  
Carrying Case  
See page 70

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

Application note, literature code 1260729:

## Why true-rms?

If you're measuring non-linear loads like variable frequency drives, solid state heater drives, or electronics, you need a true-rms tool to get accurate readings.

Average responding meters will read low, up to 30 or 40 percent low in some cases. This application note explains what true-rms is and when you need it in your test tool.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



New

## 117/322 Electrician's Combo Kit

- 117 True-rms digital multimeter with non-contact voltage detection
- **New!** C115 Deluxe carrying case with shoulder strap
- 322 Compact clamp meter
- TL75 Hard Point Test Lead Set
- ToolPak Magnetic Meter Hanging Strap

## Included accessories

TL75 Test leads, holster, users manual and 9 V battery (installed).

## Ordering information

Fluke-117 Multimeter with Non-Contact Voltage  
Fluke-117/322 Electrician's Combo Kit  
Fluke-115 Multimeter



# Fluke 116 and 114 Digital Multimeters

Designed for HVAC/R technicians and electrical troubleshooting

New



## Fluke 116

The Fluke 116 was specifically designed for the HVAC professional. It has everything needed in an HVAC meter including temperature and microamp measurements to quickly troubleshoot problems with HVAC equipment and flame sensors.

### The 116 features include:

- Built in thermometer for HVAC applications
- Microamps to test flame sensors
- Min/Max/Average to record signal fluctuations
- Large white LED backlight to work in poorly lit areas
- Compact ergonomic design for one-handed operation
- Min/Max/Average to record signal fluctuations
- Compatible with optional magnetic hanger (ToolPak™)
- Resistance, continuity, frequency and capacitance

## Fluke 114

The new Fluke 114 is the troubleshooting tool for "go/no-go" testing. It includes a feature to prevent false readings caused by ghost voltage.

### The 114 features include:

- AutoVolt: Automatic ac/dc voltage selection
- LoZ: Helps prevent false readings due to ghost voltage
- Large white LED backlight to work in poorly lit areas
- Compact ergonomic design for one-handed operation
- Resistance, continuity, frequency and capacitance



New

Application note, literature code 2434064:

## Fossil fuel heating equipment

This application note explains the basic principles of fossil fuel heating systems (gas and oil) and how to troubleshoot them using thermometers, DMMs,

clamp meters, pressure/vacuum modules, and other accessories. The instructions cover the thermostat controls, fan controls, flame verification controls, and cad cell testing.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



## Features - 116 and 114 DMMs

| Feature                                                | 116 | 114 |
|--------------------------------------------------------|-----|-----|
| Temperature measurements                               | •   | •   |
| AutoVolt/LoZ                                           | •   | •   |
| Analog bargraph                                        | •   | •   |
| Large backlit digital display                          | •   | •   |
| True-rms for accurate measurements on non-linear loads | •   | •   |
| Min/Max recording                                      | •   | •   |
| Display hold                                           | •   | •   |
| 3-1/2 digits                                           | •   | •   |
| 6000 counts                                            | •   | •   |
| CAT III 600 V safety rated                             | •   | •   |

## Specifications - 116 and 114 DMMs

| Function               | Range and resolution | Best accuracy |
|------------------------|----------------------|---------------|
| Volts ac/dc            | 600 V                | 0.5 % + 2     |
| Current ac/dc          | 10 A                 | 1.0 % + 3     |
| Temperature (116 only) | +400 °C              | 1.0 % + 18    |
| Resistance             | 50 kΩ                | 0.9 % + 2     |
| Capacitance (116 only) | 1 nF to 9,999 μF     | 1.9 % + 2     |
| Frequency (116 only)   | 5 Hz to 50 kHz       | 0.1 % + 2     |
| Diode (116 only)       | 2 V                  | 0.9 % + 2     |

## Recommended accessories - 116 Digital Multimeter



**80AK**  
DMM Adapter  
See page 69



**80PK-24**  
SureGrip Air Temperature Probe  
See page 68



**80PK-8**  
Pipe Clamp Temperature Probe  
See page 68



**80BK**  
Integrated DMM Temperature Probe  
ships with 116  
See page 68

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

Digital Multimeters



## 116/62 HVAC Combo Kit

- Fluke 116 HVAC Multimeter with Temperature and Microamps
- Fluke 62 Infrared Thermometer
- TL75 Hard Point Test Lead Set
- ToolPak™ Magnetic Meter Hanging Strap
- **New!** C115 Deluxe carrying case with shoulder strap
- **New!** 80PK-11 Pipe Wrap Thermocouple
- Fluke 80AK Thermocouple Adapter
- Fluke 80BK B-Type Integrated Temperature Probe

## Included accessories

TL75 Test Leads, 80BK Integrated Temperature Probe (116 only), holster, users manual and 9 V battery (installed).

## Ordering information

Fluke-116 HVAC Multimeter with Temperature and Microamps  
Fluke-116/62 HVAC Combo Kit  
Fluke-114 Electrical Multimeter

# Fluke 77-IV Digital Multimeter

**Versatile meters for field service  
or bench repair**



The new 77-4 digital multimeter has the features needed to repair most electrical and electronic problems. This meter is simple to use and has significant improvements over Fluke's original 70 Series with more measurement functions, conformance to the latest safety standards, and a much larger display that's easier to view.

## Measures

- Wide 1000 V measurement range
- Average responding ac measurements
- 0.3 % accuracy
- 10 Amps continuous
- Frequency and capacitance
- Resistance and continuity

## Features

- Large display
- Backlight for work in dim areas
- Min / Max to record signal fluctuations
- Integral holster with probe holders
- Free your hands with the optional TPAK magnetic hanger
- Auto and Manual ranging



## Fluke 27 waterproof multimeter

### Completely sealed for extreme conditions

Designed for U.S. military, mining and other extreme applications. A special case with o-rings prevents water from entering the input jacks, switches and fuse door. Meets military specifications for vibration, shock and water resistance.

- Waterproof design with rugged, o-ring sealer case protects rotary switch, input jacks, battery and fuse door
- Operates from -15 °C to +55 °C (5 °F to 131 °F) and 95 % relative humidity



## Features - 77-IV Digital Multimeter

| Feature                            | Old 77    | New 77-IV    | Benefit                          |
|------------------------------------|-----------|--------------|----------------------------------|
| Accuracy                           | 0.3 %     | 0.3 %        | Same great accuracy              |
| True-rms                           | No        | No           | Same familiar readings           |
| Frequency                          | No        | Yes          | Built in frequency counter       |
| Capacitance                        | No        | Yes          | Test components                  |
| Maximum ac voltage                 | 750       | 1000         | Wider measurement range          |
| Min/Max/Average                    | No        | Yes          | Capture transients automatically |
| Display backlight                  | No        | Yes          | Usable in dim areas              |
| Battery door                       | No        | Yes          | Fast battery changes             |
| Probe holders                      | No        | Yes          | One-hand operation               |
| Overvoltage category safety rating | Not rated | 600 V CAT IV | Higher level of protection       |
| Optional magnet hanger             | No        | Yes          | Position meter in best location  |

## Fluke 73-III

The Fluke 73-III product represents one of the best selling multimeter designs of all time. It's classic simplicity combined with attractive feature set make this meter the perfect choice for electronic and automotive applications.

### The 73-III features include:

- Average responding
- Measures both amps and milliamps
- Removable high impact holster
- Manual or autoranging



## Specifications - 77-IV Digital Multimeter

| Function    | Range                 | Best accuracy | Best resolution |
|-------------|-----------------------|---------------|-----------------|
| V dc        | 600.0 mV to 1000 V    | ± (0.3 % + 1) | 0.1 mV          |
| V ac        | 6.000 V to 1000 V     | ± (2.0 % + 2) | 1.0 mV          |
| A dc        | 60.00 mA to 10 A      | ± (1.5 % + 2) | 0.01 mA         |
| A ac        | 60.00 mA to 10 A      | ± (2.5 % + 2) | 0.01 mA         |
| Resistance  | 600.0 Ω to 50 MΩ      | ± (0.5 % + 1) | 0.1 Ω           |
| Capacitance | 1 nF to 9,999 μF      | ± (1.2 % + 2) | 1 nF            |
| Frequency   | 99.99 Hz to 99.99 kHz | ± (0.1 % + 1) | 0.01 Hz         |

## Recommended accessories - 77-IV Digital Multimeter



**i400s**  
AC Current Clamp  
See page 66



**C35**  
Meter Case



**ToolPak™**  
Meter Hanger  
See page 71

## Fluke 77-IV included accessories

TL75 test leads, 9 V battery (installed) and manual.

## Fluke 27 included accessories

TL75 test leads, alligator clips, 9 V battery (installed) and manual.

## Ordering information

Fluke-77-4 Digital Multimeter  
Fluke-73-3 Digital Multimeter  
Fluke-27-YEL Multimeter

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

# Complete automotive diagnostic tools

FLUKE®

Tools designed to help you beat the book



## Fluke 88V Automotive Multimeter

The Fluke 88V Automotive Multimeter is designed to help automotive professionals beat the book. This DMM has more measurement functions, troubleshooting features and accuracy to solve virtually any problems on conventional and hybrid vehicles.

- Automotive test functions include dc and ac voltage, resistance and current
- Min/Max recording for logging the highest and lowest readings over time
- Frequency measurements for magnetic sensors and ac/dc frequency signals
- Duty Cycle for variable duty cycle signals with selectable trigger slope and level
- Pulse width for fuel injector on time measurements
- Conductance testing for secondary ignition coils
- RPM measurements for DIS and conventional ignition systems
- Built-in thermometer

## Fluke 73-III (see pg 19 for details)

- Simple interface for one-handed operation
- Current measurement (A and mA)
- Auto or manual ranging



## Features - 88V and 73 DMMs

| Feature                                                                 | 88V | 73 |
|-------------------------------------------------------------------------|-----|----|
| Digital display with analog bargraph                                    | •   | •  |
| Continuity for detecting opens and shorts                               | •   | •  |
| Diode test for alternator testing                                       | •   | •  |
| Peak Min/Max captures intermittence as fast as 250 microseconds         | •   |    |
| Min/Max average to monitor trends in oxygen sensor values for fuel trim | •   |    |
| Pulse width for fuel injector on time measurements                      | •   |    |
| Milliamp ranges to find low current parasitic drains                    | •   |    |
| Lo-Ohms (.01 Ω) for low resistance sensor and coil measurements         | •   |    |
| Duty cycle for pulse width modulated signals                            | •   |    |
| RPM for ignition systems                                                | •   |    |
| Temperature for coolant and air temperature sensors                     | •   |    |
| Dwell for points and feedback carburetors                               |     |    |
| Limited lifetime warranty                                               | •   | •  |

## Buy accessory kits and save



TLK281

Automotive Test Lead Kit  
See page 61



TLK282

Deluxe Automotive Test Lead Kit  
See page 61



TL28A

Automotive Test Lead Set  
See page 62



TL82

Automotive Pin & Socket Adapter Set  
See page 63

## Recommended automotive accessories - 88V DMM



TP81 or TP82

Insulation Piercing Probes  
See page 63



TP84

Oxygen Sensor Insulation Piercing Probe  
See page 63



TP88

Rigid Backprobe Pin Set  
See page 63



TP40

Automotive Back Probe Pin Set  
See page 63

Application note, literature code 1547394:

## Beat the book

This amazing reference covers test procedures commonly used by experienced automotive technicians. Covers basic troubleshooting techniques and measurements using a DMM and describes tests for the charging system, starting system, fuel and air system, ignition system, and the body electric/engine management/cooling system.



Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



## For the complete diagnostics package and maximum value, pick up the 88V/A combo kit.

- Includes Fluke 88 Series V Automotive Multimeter
- TL224 Heat Resistant Silicone Test Leads
- TP220 Removable Sharp Point Test Probes
- AC285 Large Jaw Alligator Clips
- TPAK Magnetic Hanger
- 80BK Temperature Probe
- RPM80 Inductive Pick-up
- Automotive Backprobe Pins
- Insulation Piercing Probe
- Packaged in a durable carrying case (C800)

## Fluke 88V included accessories

Test leads, 9 V battery (installed), RPM pickup, carrying case and users manual.

## Ordering information

|                  |                                 |
|------------------|---------------------------------|
| Fluke-88-5       | Automotive Multimeter           |
| Fluke-88-5/A KIT | Automotive Multimeter Combo Kit |
| Fluke-73-3       | Digital Multimeter              |

For more information and detailed specifications, go to [www.fluke.com/dmm](http://www.fluke.com/dmm)

Digital Multimeters

# Fluke 8845A and 8846A 6.5 Digit Precision Multimeters

FLUKE®

**Precision and versatility for  
bench or systems applications**

**New**



Fluke 8845A

**New**



Fluke 8846A

True-rms



The Fluke 8845A and 8846A, 6.5 digit precision multimeters have the precision and versatility to handle your most demanding measurements on the bench or in a system.

**Dual display offers versatile graphical capabilities:** The 8845A and 8846A feature a unique graphical display that can reveal signal quality issues like drift, intermittent and stability by viewing the measurement data as a real time TrendPlot™ Histogram or Statistics using the unique analyze mode.

**Wide measurement ranges:** Resistance or current has been extended to cover the widest range possible.

**Perform 4-wire measurements easily with two leads:** Patented split terminal jacks for 2x4 ohms function allow you to perform precise 4-wire measurements with only two leads instead of four. Optional Kelvin leads accessories are available to enable you to establish a 4-wire connection even in tight spaces.

**Systems capabilities:** Both instruments include an RS-232, IEEE-488 and Ethernet interface as standard, with popular DMM emulation modes that make systems integration a simple task.

**Software:** Transfer data points from your meter to your PC with the free copy of FlukeView Forms Basic. To customize your forms, upgrade with FVF-UG.

Application note, literature code 2547797:

## Understanding specifications for precision multimeters

A solid understanding of specifications is critical when you're evaluating the suitability of DMMs for an application, or when you must be confident that your readings accurately reflect reality. This application note discusses some of the thinking behind DMM specifications and spec sheets. It defines the various elements of DMM specs and gives tips on how to apply them.

Want to read more? Go to [www.fluke.com/library](http://www.fluke.com/library) to download this and other application notes, or get info specific to your industry and sign up for Fluke News publications at [www.fluke.com/subscribe](http://www.fluke.com/subscribe).



## Features - 8845A and 8846A

| Feature                               | 8845A                                                                                                                     | 8846A                 |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-----------------------|
| Display                               | Dual VFD Dot Matrix                                                                                                       |                       |
| Resolution                            | 6.5 Digits                                                                                                                |                       |
| Continuity / Diode Test               | Yes                                                                                                                       |                       |
| Analytical Functions                  | Statistics, Histogram, TrendPlot™, Limit Test                                                                             |                       |
| Math Functions                        | Zero, Min/Max/Average, Std Dev; mx + b, dB/dBm                                                                            |                       |
| USB Device Port                       | —                                                                                                                         | USB memory drive port |
| Real Time Clock                       | —                                                                                                                         | Yes                   |
| Interfaces                            | RS-232, IEEE-488.2, Ethernet, USB (with optional adapter)                                                                 |                       |
| Programming Languages/Emulation Modes | SCPI (IEEE-488.2), Agilent 34401A, Fluke 45                                                                               |                       |
| Safety                                | Designed to comply with IEC 61010-2000-1, ANSI / ISA-S82.01-1994, CAN / CSA-C22.2 No.1010.1-92 1000 V CAT I / 600 V CATII |                       |

## Specifications - 8845A and 8846A

| Function*                         | 8845A   |            |               | 8846A              |            |               |
|-----------------------------------|---------|------------|---------------|--------------------|------------|---------------|
|                                   | Range   | Resolution | Accuracy* (%) | Range              | Resolution | Accuracy* (%) |
| Voltage dc                        | 1000 V  | 100 nV     | 0.0035        | 1000 V             | 100 nV     | 0.0024        |
| Voltage ac (freq. 300 Hz)         | 750 V   | 100 nV     | 0.06          | 1000 V             | 100 nV     | 0.06          |
| Resistance (2x4 wire)             | 100 MΩ  | 100 μΩ     | 0.01          | 1 GΩ               | 10 μΩ      | 0.01          |
| Current dc                        | 10 A    | 100 pA     | 0.05          | 10 A               | 100 pA     | 0.05          |
| Current ac (freq. 3 Hz to 10 kHz) | 10 A    | 1 μA       | 0.10          | 10 A               | 10 nA      | 0.10          |
| Freq/period                       | 300 kHz | 1 μHz      | 0.01          | 1 MHz              | 1 μHz      | 0.01          |
| Capacitance                       | —       | —          | —             | 1 nF to 0.1 F      | 1 pF       | 1             |
| Temperature RTD                   | —       | —          | —             | -200 °C to +600 °C | 0.001°     | 0.06°         |

\*Accuracy = ± (% of reading)

Size (HxWxD): 88 mm x 217 mm x 297 mm (3.45 in x 8.54 in x 11.69 in) Weight: 3.6 kg (7.9 lb) One-year warranty

## Recommended accessories - 8845A and 8846A Precision Multimeters



**TL2X4W-PT**  
2x4 Wire Ohms Test Lead  
2 mm probe tip



**TL2X4W-TWE**  
2x4 Wire Ohms  
Tweezer



**884X-512M**  
USB Memory 512M



**FVF-UG**  
FlukeView Forms  
Software Upgrade


For more information and detailed specifications, go to [www.fluke.com/884X](http://www.fluke.com/884X)



Use the built-in TrendPlot paperless chart recorder to graphically identify the extent of drift and intermittent events in analog circuits.



View results in Histogram mode to reveal stability or noise problems in analog circuits.



Handle even the most demanding measurements with high accuracy and 6.5 digit resolution.

## Included accessories

LCI Line Power Cord, TL71 Test Lead Set, Spare Line Power fuse, Programmers Manual/User Manual on CD-ROM, FVF-BASIC FlukeView Forms Software Basic Version.

## Ordering information

Fluke-8845A 6.5 Digit Precision Multimeter, 35 ppm  
Fluke-8846A 6.5 Digit Precision Multimeter, 24 ppm

# Fluke T5 and T3 Electrical Testers

FLUKE®

## Fluke T5 Voltage, Continuity and Current Tester

- Excellent front-line troubleshooting and measurement tool
- Available in 600 V and 1000 V models
- Digital display
- OpenJaw™ current measurement
- Rotary switch selects volts, amps and ohms functions
- Heavy-duty test leads

## Fluke T3 Voltage and Continuity Tester

- LED voltage indicators
- Seven key voltage levels
- Automatically switches to continuity beeper or ac/dc voltage
- Heavy-duty test leads



## Specifications – T5 and T3 Testers

|                                                       | T5-1000                    | T5-600                    | T3                                                       |
|-------------------------------------------------------|----------------------------|---------------------------|----------------------------------------------------------|
| Measure dc voltage                                    | 1000 V                     | 600 V                     | Preset 6 V, 12 V, 24 V, 36 V, 48 V, 110 V and 220 V*     |
| Measure ac voltage                                    | 1000 V                     | 600 V                     | Preset 24 V, 48 V, 120 V, 208 V, 240 V, 277 V and 480 V* |
| Measure ac current (average)                          | 100 A                      | 100 A                     | N/A                                                      |
| Measure continuity                                    | < 25 Ω                     | < 25 Ω                    | < 20,000 Ω                                               |
| Measure resistance                                    | 1000 Ω                     | 1000 Ω                    | N/A                                                      |
| DC polarity indicator                                 | Yes                        | Yes                       | Yes                                                      |
| Detachable probe tips with optional probe tips styles | Yes                        | Yes                       | N/A                                                      |
| Safety rating                                         | 1000 V Overvoltage CAT III | 600 V Overvoltage CAT III | 1000 V Overvoltage CAT III                               |
| Warranty                                              | Two-years                  | Two-years                 | One-year                                                 |

\* Voltage levels will vary depending on country of intended use.

## Fluke 9040 Rotary Field Indicator

The Fluke 9040 is a premium phase rotation tester with a CAT III, 600 V rating. The frequency range is from 15 Hz to 400 Hz for demanding applications. The clear liquid crystal display and the holster make it suitable for rough outdoor applications. This instrument is supplied with three unique, expandable, test probes which fit most sockets.

For more information, visit [www.fluke.com/9040](http://www.fluke.com/9040)



## Fluke 1AC-II/1LAC-II VoltAlert

### The pocket-sized voltage detector

The next generation VoltAlert™ ac non-contact voltage testers from Fluke are easy to use—just touch the tip to a terminal strip, outlet, or supply cord. When the tip glows red and the unit beeps, you know there is voltage present. Electricians, maintenance, service, safety personnel and homeowners can quickly test for energized circuits in the workplace or at home. Certified up to CAT IV 1000 V.

### Two models to choose from:

- **1AC-II** – detects voltage from 90 V ac to 1000 V ac
- **1LAC-II** – detects voltage from 20 V ac to 90 V ac

## Included accessories

The T5-1000 and T5-600 come with detachable probes and instruction sheet. The T3 has fixed test leads and probes.

## Ordering information

|               |                                               |
|---------------|-----------------------------------------------|
| T5-1000       | 1000 V Voltage, Continuity and Current Tester |
| T5-600        | 600 V Voltage, Continuity and Current Tester  |
| T3            | Voltage and Continuity Tester                 |
| T3-1AC Kit    | Voltage and Continuity Tester Kit             |
| T5-H5-1AC Kit | Voltage, Continuity and Current Tester Kit    |
| 1AC-II 5PK    | VoltAlert 5 Pack                              |
| 1AC-II        | Voltage Detector                              |
| 1LAC-II       | Voltage Detector                              |
| 9040          | Rotary Field Indicator                        |

## Buy Electrical Tester Kits and Save



### T3 Tester Kit

- Combo kit includes:
- Fluke T3 Voltage and Continuity Tester
  - Fluke VoltAlert™



### T5-1000 Tester Kit

- Combo kit includes:
- Fluke T5-1000 Voltage Electrical Tester
  - Fluke VoltAlert™
  - Fluke H5 Holster



### VoltAlert™ Multi Pack

Includes five Fluke VoltAlerts. The special kit pricing gets you the fifth VoltAlert™ free. Outfit your entire staff.

## Recommended accessories – Electrical Testers



**H5**  
Electrical Tester Holster  
See page 70



**AC285 (T5)**  
SureGrip™ Alligator Clips  
See page 62



**Meter Cleaner**  
Cleaning Wipes  
See page 71



**T5 Kit**  
Starter Kit  
See page 61



**C520A**  
Leather Tool Case  
See page 70

For more information and detailed specifications, go to [www.fluke.com/tseries](http://www.fluke.com/tseries)

Electrical Testers



# Fluke 1625 and 1623 Geo Earth Ground Testers

FLUKE®

Advanced technology for all your earth ground testing applications



Fluke 1623



Fluke 1625

The new Fluke 1620 Series Earth Ground Testers not only measure ground resistance using the classic 'fall of potential test' but also enable time saving testing using the 'selective' and 'stakeless' methods. 'Selective' testing does not require the electrode under test to be disconnected during the measurement, thus increasing safety. The simple 'stakeless' method quickly checks ground connections using two current transformers (probes) clamped around the ground conductor under test. Offering 'one-button' simplicity, the 1623 is an all-in-one earth ground tester, while the 1625 has extra versatility for more demanding applications.

## Earth ground resistance and soil resistivity should be measured when:

- Designing earth ground systems
- Installing new ground system and electrical equipment
- Periodically testing ground and lightning protection systems
- Installing large electrical equipment such as transformers, switchgears, machines, etc.


The 1623 is perfect for performing predictive maintenance checks of commercial and industrial applications. The 1625 is intended for electrical utility or other high frequency environments.

Brochure, literature code 2633834:

## Earth Ground Resistance: Principles, testing methods and applications

This brochure is a highly informative collection of information about Earth Ground Systems, testing methods and applications.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



## Features – 1625/1623 Earth Ground Testers

| Feature                                                           | 1625         | 1623         |
|-------------------------------------------------------------------|--------------|--------------|
| One-button measurement concept                                    |              | •            |
| 3- and 4-pole earth ground measurement                            | •            | •            |
| 4-Pole soil resistivity testing                                   | •            | •            |
| 2-Pole resistance measurement ac                                  | •            | •            |
| 2-and 4-pole resistance measurement dc                            | •            |              |
| Selective testing, no disconnection of ground conductor (1 clamp) | •            | •            |
| Stakeless testing, quick ground loop testing (2 clamps)           | •            | •            |
| Measuring frequency 128 Hz                                        |              | •            |
| Earth impedance measurement at 55 Hz                              | •            |              |
| Automatic frequency control (AFC) [94 Hz to 128 Hz]               | •            |              |
| Measuring voltage switchable 20/48V                               | •            |              |
| Programmable limits, settings                                     | •            |              |
| Continuity with buzzer                                            | •            |              |
| Dust/water resistance                                             | IP56         | IP56         |
| Safety rating                                                     | CAT II 300 V | CAT II 300 V |


Battery type: 6 x AA alkaline cells

Size (HxWxD): 110 mm x 180 mm x 240 mm (4.33 in x 7.08 in x 9.45 in)

Weight (including batteries): 1623 Geo: 1.1 kg (2.42 lb); 1625 Geo: 1.5 kg (3.31 lb)

Two-year warranty

## Recommended accessories – 1625 and 1623 Earth Ground Testers



## Included accessories

**Fluke 1625 Tester:** 2 test leads, 2 alligator clips, and users manual.

**Fluke 1625 Kit:** Same as above plus stake/reel set 4 pole, selective/stakeless clamp set, and rugged carrying case.

**Fluke 1623 Tester:** 2 test leads, 2 alligator clips, and users manual.

**Fluke 1623 Kit:** Same as above plus stake/reel set 4 pole, selective/stakeless clamp set, and rugged carrying case.

## Ordering information

|                |                                      |
|----------------|--------------------------------------|
| Fluke-1625     | Advanced GEO Earth Ground Tester     |
| Fluke-1625 Kit | Advanced GEO Earth Ground Tester Kit |
| Fluke-1623     | Basic GEO Earth Ground Tester        |
| Fluke-1623 Kit | Basic GEO Earth Ground Tester Kit    |

These products are for unpowered installations measuring grounding connections.

For more information and detailed specifications, go to [www.fluke.com/egt](http://www.fluke.com/egt)

Earth Ground Testers



# Fluke 1630 Earth Ground Clamp Meter

**Measure earth ground loop resistance anywhere. Quickly and easily.**



The Fluke 1630 Earth Ground Clamp is able to measure ground loop resistances—using the Stakeless testing method. This test technique eliminates the dangerous, and time consuming activity of disconnecting parallel grounds, as well as the process of finding suitable locations for auxiliary ground stakes. You can also perform earth ground tests in places you have not considered before: inside buildings, on power pylons or anywhere you don't have access to soil.

With the Stakeless testing method, the Fluke 1630 Earth Ground clamp is placed around the earth ground rod or the connecting cable. No earth ground stakes are used at all. A known voltage is induced by one half of the clamp and the current is measured by the other half. The tester automatically determines the ground loop resistance at this grounding connection. Gone are the days of spending time placing and connecting stakes for each earth ground rod on your system—a major time saver.

- Quick and easy use—no earth ground stakes are necessary
- Large, 35 mm (1.35 in) jaw opening
- Measures ground resistance from 0.025  $\Omega$  to 1500  $\Omega$
- Measures ground leakage current from 0.2 mA to 30 mA
- High and Low alarming
- Automatic self calibration
- Rugged carrying case and resistance check loop included

## What is ground, and what does it do?

The NEC, National Electrical Code, defines a ground as a "conducting connection, whether intentional or accidental between an electrical circuit or equipment and the earth, or to some conducting body that serves in place of the earth."

When talking about grounding it is actually two different subjects, earth grounding and equipment grounding. Earth grounding is an intentional connection from a circuit conductor usually the neutral to a ground electrode placed in the earth. Equipment grounding is to ensure that operating equipment within a structure is properly grounded.

These two grounding systems are required to be separate except for a connection between the two systems to prevent differences in potential from a possible flashover from a lightning strike. The purpose of a ground besides the protection of people, plants and equipment is to provide a safe path for the dissipation of fault currents, lightning strikes, static discharges, EMI and RFI signals and interference.

## Handy GEO Earth Ground Tester Earth ground tester for resistance measurement



The Handy GEO Earth Ground Tester is a rugged, easy-to-use tester for three-pole ground resistance measurements and two-pole ac resistance measurements.

Earth ground resistance is measured by installing earth ground test electrodes and testing with the Handy GEO. Earth ground resistance measurements are used to ensure safe operation and reduce power quality problems. The Handy GEO is extremely lightweight making it ideal to test for lightning protection levels and periodic check-ups during routine maintenance.

Two-pole ac resistance is measured to confirm low resistance between electrical joints:

- Fuse-to-fuse holder (to ensure there is no overheating)
- Bonding of ground earth connections
- Additional bonding
- Cable to terminal connections

AC current can be used to confirm the low resistance path in two directions simultaneously.

The gold standard for measuring ground resistance using classic fall of potential as well as selective and stakeless methods.

## Included accessories

**Fluke 1630 Clamp Meter:** Rugged carrying case with belt, resistance test loop, 9 V battery and users manual.

**Handy GEO Tester:** Rugged rubber holster with carrying belt, battery, and operating instructions.

## Ordering information

|               |                                                                                   |
|---------------|-----------------------------------------------------------------------------------|
| Fluke-1630    | Earth Ground Clamp Meter                                                          |
| Handy GEO     | Earth Ground Tester                                                               |
| Handy GEO Kit | Earth Ground Tester Kit with 25 m and 50 m cable reel and two earth ground stakes |

These products are for unpowered installations measuring grounding connections.

For more information and detailed specifications, go to [www.fluke.com/egt](http://www.fluke.com/egt)

Earth Ground Testers

# Fluke 430 Series Three-Phase Power Quality Analyzers

FLUKE®

**Pinpoint power problems faster, safer and in greater detail**

**New**



Fluke 435



Fluke 434



The Fluke 435 and 434 Three-Phase Power Quality Analyzers help you locate, predict, prevent and troubleshoot problems in three- and single-phase power distribution systems. Troubleshooting is faster with on-screen display of trends and captured events, even while background recording continues. The new IEC standards for flicker, harmonics, and power quality are built right in to take the guess work out of power quality.

**Troubleshoot real-time:**

Analyze the trends using the cursors and zoom tools—even while background recording continues

**AutoTrend:** Every measurement you see is always automatically recorded, without any setup

**Automatic Transient Mode:** Capture 200 kHz waveform data on all phases simultaneously up to 6 kV



**Measure all three phases and neutral:** With included four current probes

**Fully Class-A compliant:** Conduct tests according to the stringent international IEC 61000-4-30 Class-A standard

**System-Monitor:** Up to ten power quality parameters on one screen according to EN50160 power quality standard

**Inrush mode:** For troubleshooting nuisance circuit breaker tripping

**Logger function:** Configure for any test condition with memory for over 400 parameters at user defined intervals



Application note, literature code 2435490:

## Six simple ways to reduce costs with a Fluke 434 Power Quality Analyzer

There are hundreds of power quality measurements you can take on electrical systems and equipment. These instructions focus on four predictive maintenance (PdM)

measurements and two power consumption measurements that can help you uncover hidden costs, protect equipment from damaging conditions, reduce unscheduled downtime, and improve system performance.



## Features - 435 and 434 PQ Analyzers

| Features                                                                                                                                                               | 435                                | 434*                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|----------------------|
| Measures voltage, current, dips, swells, interruptions, harmonics, inter-harmonics, flicker, power, energy, transients, frequency, unbalance, inrush, EN50160 overview | •                                  | •                    |
| Logger function with multi-parameter logging                                                                                                                           | •                                  | optional*            |
| Mains signaling                                                                                                                                                        | •                                  | optional*            |
| Memory size                                                                                                                                                            | 16 MB                              | 8 MB                 |
| Current probes                                                                                                                                                         | 3000 A flexible (4)                | 40 A/400 A clamp (4) |
| Carrying case                                                                                                                                                          | water-tight hard case with rollers | rugged hard case     |
| Software                                                                                                                                                               | Fluke Power Log and FlukeView®     | FlukeView®           |

\*Optional functionality can be added with upgrade kit.

## Recommended accessories - 435 and 434 PQ Analyzers



**I5sPQ3**  
3 pack of 5 A precision current clamps



**i430-flex-4pk**  
4 pack of 3000 A flexible current probes



**C435**  
Water-tight hard case with rollers



**GPS430**  
GPS time synchronization module

For more information and detailed specifications, go to [www.fluke.com/pq](http://www.fluke.com/pq)

## Included accessories

**Fluke 435 Analyzer:** Hard carrying case with rollers, four flexible current probes (i430-flex), five test leads and clips, battery charger, FlukeView software, Power Log software, optical USB cable, color localization set, getting started manual, users manual on CD-ROM.

**Fluke 434 Analyzer:** Hard carrying case, four current probes (i400s), five test leads and clips, battery charger, FlukeView software, optical USB cable, color localization set, getting started manual, users manual on CD-ROM.

## Ordering information

Fluke-435 Three-Phase Power Quality Analyzer  
Fluke-434 Three-Phase Power Quality Analyzer





# Fluke 43B Power Quality Analyzer

## Power quality analysis plus a scope and a meter



The Fluke 43B Power Quality Analyzer performs the measurements you need to maintain power systems, troubleshoot power problems, and diagnose equipment failures. The 43B has 20 storage locations and can store data as well as screens.



- NiMH battery provides extended operating time of 6.5 hours
- Voltage, current and power harmonics up to 51st
- Total harmonic distortion (THD)
- Phase angle of individual harmonics
- FlukeView® software with enhanced analysis and documentation capabilities
- Continuously measure volts and amps cycle-by-cycle for up to 16 days
- Cursors give time and date of sags and swells



## Specifications – 43B Analyzer

| Function                               | Fluke 43B*                   |
|----------------------------------------|------------------------------|
| <b>Volts/Amps/Hz</b>                   |                              |
| Volts rms                              | ± (1 % + 10 counts)          |
| Amps rms                               | ± (1 % + 10 counts)          |
| Frequency (Hz)                         | ± (0.5 % + 2 counts)         |
| Crest Factor (CF)                      | ± (5 % + 1 count)            |
| Sags and swells                        | ± (2 % + 10 counts)          |
| <b>Power</b>                           |                              |
| W, VAR, VA                             | ± (2 % + 6 counts)           |
| PF, Cos (DPF)                          | ± 0.04                       |
| <b>Harmonics and THD</b>               |                              |
| Harmonics                              | ± 3 %                        |
| THD                                    | ± 3 %                        |
| <b>Transient display</b>               |                              |
| Minimum transient detection            | 40 ns                        |
| Inrush current                         | ± 5 % of full scale          |
| <b>Additional capabilities</b>         |                              |
| AutoTrend                              | •                            |
| Real time scope                        | •                            |
| Ohms, diode, continuity, capacitance   | •                            |
| Memory (screens/data)                  | 20 (screens, settings, data) |
| FlukeView software and interface cable | Standard                     |

\*Not including current probe specifications

**Battery life:** Rechargeable NiMH pack (charger included), 6.5 hours typical (continuous)

**Shock and vibration:** Mil 28800E, Type 3, Class III, Style B

**Operating temperature:** 0 °C to 50 °C (32 °F to 122 °F)

**Case:** IP51 (dust, drip waterproof)



**Size (HxWxD):** 232 mm x 115 mm x 50 mm (9.1 in x 4.5 in x 2 in)

**Weight:** 1.1 kg (2.5 lbs)

**Safety:** IEC 1010-1, CAT III 600 V. Tested and approved to UL 3111-1, CSA C.22.2 No. 1010.1-92.

**Warranty:** Three-years on Fluke 43B, one-year on accessories

- Watts, power factor, displacement power factor, VA and VAR
- Voltage and current waveforms
- Calculates three-phase power on balanced loads from a single-phase measurement
- Catch up to 40 voltage transients and waveform distortions



Application note, literature code 2391563:

### The costs of poor power quality

Productivity is the key to survival in today's global competitive environment. Power quality problems can cause processes and equipment to malfunction or shut down.

And the consequences can range from excessive energy costs to complete work stoppage. Obviously, power quality is critical.

To reduce your power bill, you need to record consumption patterns and adjust the system and load timing to reduce one or more of the following:

1. Actual power (kWh) usage
2. Power factor penalties
3. A peak demand charge structure

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



## Recommended accessories – 43B Analyzer



### Included accessories

The Fluke 43B includes a hard case, voltage and current probes, FlukeView® software, power quality instructional CD, USB interface cable, line voltage adapter/battery charger and users manuals.

### Ordering information

Fluke-43B Power Quality Analyzer

For more information and detailed specifications, go to [www.fluke.com/pq](http://www.fluke.com/pq)

Power Quality Analyzers

# Fluke 1760 Power Quality Recorder *Topas*

FLUKE®

## Class-A compliance for the most demanding power quality tests



The Fluke 1760 Three-Phase Power Quality Recorder is the ideal portable instrument for power quality experts. It is fully compliant to IEC 61000-4-30 Class-A, for advanced power quality analysis and consistent compliance testing. Designed for analysis of utility and industrial power distribution systems, in medium- and low-voltage networks, the Fluke 1760 provides the flexibility to customize thresholds, algorithms, and measurement selections. It captures the most comprehensive details on user-selected parameters and allows for later analysis and reporting.

- **Fully Class-A compliant:** Conduct tests according to the stringent international IEC 61000-4-30 Class-A standard
- **GPS time synchronization:** Correlate data with events or datasets from other instruments, with precision
- **Flexible and fully configurable thresholds and scale factors:** Allows user to pinpoint specific issues by defining the detailed criteria for detection and recording of disturbances.
- **Highest safety rating in the industry:** 600 V CAT IV/1000 V CAT III rated for use at the service entrance
- **Uninterrupted power supply (40 minutes):** Never miss important events—even record the beginning and end of interruptions and outages, to help determine the cause
- **10 MHz, 6000 Vpk waveform capture:** Get a detailed picture of even the shortest event
- **2 GB data memory:** Enables detailed, simultaneous recording of numerous power parameters for long periods of time
- **Comprehensive software included:** Provides trend diagrams for root cause analysis, statistical summaries, report writing, and real-time data monitoring in the online mode
- **Plug and play:** Allows quick setup with automatic sensor detection; sensors are instrument powered, eliminating the need for batteries
- **Rugged field design:** Insulated housing and a solid state design with no rotating components, enable reliable testing under nearly any conditions

For more information and detailed specifications, go to [www.fluke.com/pq](http://www.fluke.com/pq)

## Fluke 1650 RPM Power Recorder


### Power recorder

Fewer connections, shorter set up, less mistakes. Patented Full-Disclosure technology captures every measurement, every event, on every cycle, all the time—without thresholds. From simple set-ups to finished reports, the Fluke 1650 is the complete solution to your portable power recording needs. The Power Recorder is all you need to record, analyze, and document:

- Loading and load interaction
- Power consumption and demand
- Sags, swells, harmonics or transient events
- Ground currents
- Phase relationships, including phase imbalance

### Multipoint

For permanent installations, select Multipoint to get the same performance as the portable Power Recorder—simultaneously measuring all power quality parameters, as well as power consumption and harmonics.



For more information and detailed specifications, go to [www.fluke.com/pq](http://www.fluke.com/pq)

Application note, literature code 2555030:

### What does Class A mean to me?

The new IEC 61000-4-30 Class A standard takes the guesswork out of selecting a power quality instrument.

The standard IEC 61000-4-30 Class A defines the measurement methods for each power quality parameter to obtain reliable, repeatable and comparable results. It also defines the accuracy, bandwidth, and minimum set of parameters. Going forward, manufacturers can begin designing to Class A standards, giving technicians a level playing field to choose from and increasing their measurement accuracy, reliability, and efficiency on the job.



### Included accessories

**Fluke 1760 Recorder:** Voltage probes (4), current probes (4), ethernet cable for network connection (1), crosslink ethernet cable for direct PC connection (1), mains cable (1), GPS time sync receiver, PC software on CD-ROM, operators manuals and carrying case.

**Fluke 1650 Recorder:** Five flexible current probes (four 1000 A and one 100 A), PAS software with report writer, ethernet cable and manual.

### Ordering information

|                 |                                                   |
|-----------------|---------------------------------------------------|
| Fluke-1760      | Without fast transient, voltage or current option |
| Fluke-1760TR    | With fast transient option                        |
| 1695-Flexi Pack | Power Recorder                                    |

These power quality recorders are sold exclusively through power quality representatives. To request a demonstration, or to order, call 1-888-257-9897 or email questions to [fpqsupport@fluke.com](mailto:fpqsupport@fluke.com).

Many configurations and accessories are available for these recorders, go to [www.fluke.com/pq](http://www.fluke.com/pq) for more information.



# Fluke 1740 Series Three-Phase PQ Loggers Memobox

**Assess power quality and conduct long-term studies with ease**



Fluke 1744/1743



Fluke 1745

Compact and rugged, the Fluke 1740 Series Three-Phase Power Quality Loggers are everyday instruments for technicians who troubleshoot and analyze power distribution systems. Capable of simultaneously logging up to 500 parameters for up to 85 days and capturing events, the Fluke 1740 Series helps uncover intermittent and hard-to-find power quality issues. The included PQ Log software quickly assesses the quality of power at the service entrance, substation, or at the load, according to the latest EN50160 standard.

- **Plug and play:** Setup in minutes with automatic current probe detection and powering
- **Installs inside the cabinet:** Compact, fully-insulated housing and accessories fit easily in tight spaces, next to live power
- **Determines the root cause:** Included PQ Log software quickly analyzes trends, creates statistical summaries, and generates detailed graphs and tables
- **Monitors power for the long-term:** Data can be downloaded during recording without interruption
- **Measure voltage with premium accuracy:** IEC61000-4-30 Class-A compliant voltage accuracy (0.1 %)
- **Quickly validate quality of power:** Assess power quality according to EN50160 power quality standard, with statistical overview
- **Rugged and reliable:** Designed for everyday field use, with no moving parts and durable, insulated case, with two-year warranty

Application note, literature code 2646555:

## Power quality recording and analysis: Techniques and applications

Hooking up a power quality recorder and taking days' worth of data can give you a rich picture of your power. In this article we'll talk about the various recording techniques



available in power loggers and recorders—understanding the tools and techniques you have available will be key to your strategy. What should you be looking for? And when does recording make sense?

Want to read more? Go to [www.fluke.com/library](http://www.fluke.com/library) to download this and other application notes, or get info specific to your industry and sign up for Fluke News publications at [www.fluke.com/subscribe](http://www.fluke.com/subscribe).

## Features – 1740 Series PQ Loggers

| Features                                                                                               | 1745                                                 | 1744                                                  | 1743 |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------|------|
| Measurement of common power parameters: V, A, W, VA, VAR, PF, energy, flicker, voltage events, and THD | •                                                    | •                                                     | •    |
| Measurement of voltage and current harmonics to the 50th, unbalance, and mains signaling               | •                                                    | •                                                     |      |
| Dust/water resistance                                                                                  | IP50                                                 | IP65 water proof                                      |      |
| Display                                                                                                | LED + LCD                                            | LED                                                   | LED  |
| UPS ride-through                                                                                       | 5 hours                                              | 3 s                                                   | 3 s  |
| Dimensions (HxWxD)                                                                                     | 282 mm x 216 mm x 74 mm<br>(11.5 in x 8.8 in x 3 in) | 170 mm x 125 mm x 55 mm<br>(6.9 in x 5.1 in x 2.2 in) |      |

## Recommended accessories – 1740 Series PQ Loggers



**MBX CLAMP 1 A/10 A + N**  
3-phase+N current clamps  
2 m cable



**MBX 300 POLESET**  
Pole mounting kit for 1743 and 1744



**C435**  
Water-tight hard case with rollers

For more information and detailed specifications, go to [www.fluke.com/pq](http://www.fluke.com/pq)

## Fluke VR101S Voltage Event Recorder System Power tools for power quality



The VR101S is the perfect system for catching sags, swells, transients, outages, and frequency variations on line voltage at receptacles.

The VR101S is a starter system that includes a compact VR101 event recorder, an optical interface cable, and EventView® software that turns your PC into a power quality reporting tool. The VR101S is covered by a one-year warranty.

For more information and detailed specifications, go to [www.fluke.com/vr101](http://www.fluke.com/vr101)

## Included accessories

**Fluke 1740 Series:** 4 Flexible probes 15/150/1500/3000 A with 2 m cable, PQ Log software, RS-232 interface cable and RS-232-USB adapter, 4 black dolphin clips, test leads for voltages and power supply, color localization kit, carrying bag, test certificate with measurement values, printed English manual and multi-language manual CD.

**VR101S:** VR101, optical interface cable, and EventView software on CD.

**VR101:** Instruction sheet.

## Ordering information

|            |                                   |
|------------|-----------------------------------|
| Fluke-1743 | Power Quality<br>Logger – Memobox |
| Fluke-1744 | Power Quality<br>Logger – Memobox |
| Fluke-1745 | Power Quality<br>Logger – Memobox |
| VR101S     | Voltage Event<br>Recorder System  |
| VR101      | Voltage Event<br>Recorder         |

Note: At least one VR101S is required for proper operation.

# Fluke 1735 Three-Phase Power Logger

**Electrical load studies, energy consumption testing, and general power quality logging**



The Fluke 1735 Three-Phase Power Logger is the ideal electrician or technician's tool for conducting energy studies and basic power quality logging. Set up the 1735 in seconds, with the included flexible current probes and color display. The 1735 logs most electrical power parameters, harmonics and captures voltage events.

- Record power and associated parameters for up to 45 days
- Monitor maximum power demand over user-defined averaging periods
- Prove the benefit of efficiency improvements with energy consumption tests
- Measure harmonic distortion caused by electronic loads
- Improve reliability by capturing voltage dips and swells from load switching
- Easily confirm instrument setup with color display of waveforms and trends
- Measure all three phases and neutral with included 4 flexible current probes
- View graphs and generate reports with included Power Log software
- Compact, rugged design with IP65 case, 600 V CAT III and two-year warranty

## Recommended accessories – 1735 Three-Phase Power Logger



**MBX Clamp 1 A/10 A**  
3 precision dual range current clamps (1 A/10 A)




**MBX Clamp 5 A/50 A + N**  
4 precision dual range current clamps (5 A/50 A)



**C435**  
Water-tight hard case with rollers

## Norma 4000 and 5000 High Precision Power Analyzers

The Norma High Precision Power Analyzers deliver precise measurements of single or three-phase current and voltage as well as calculation of power and other derived values. They provides class-leading accuracy for any waveform, frequency or phase shift. Its 144 mm (5.7 in) color display makes it easy to use both in the field and as a table unit in labs and on test benches.



| Configurations     |                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Number of channels | NORMA 4000: 1 phase or 3 phase; NORMA 5000 and 2x3 phases                                                                   |
| Basic accuracy     | 0.05 % to 0.3 % ± rdg depending on options                                                                                  |
| Sample rate        | 1 MHz, 1/3 MHz or 0.1 MHz depending on options                                                                              |
| Ranges             | Up to 100 V and 10 A or 20 A direct inputs, depending on model. With shunts, transducer or clamp accessories – up to 300 A. |
| Mechanical power   | Optional process interface 4 x speed/torque/Pmech                                                                           |
| Interfaces         | RS-232, optional IEEE 488.2/I, Ethernet, USB                                                                                |
| Functions          |                                                                                                                             |
| RMS values         | V/A/P/Q/S and derived values like Fundamental, THD ...                                                                      |
| Oscilloscope       | Simultaneous display of up to three values on sample level                                                                  |
| FFT                | Up to H40 or half of sampling rate                                                                                          |
| Recorder           | Display of three average values over time for trend determination                                                           |
| Vector             | Display of Fundamental of all channels                                                                                      |

For more information and detailed specifications, go to [www.fluke.com/pq](http://www.fluke.com/pq)

Application note, literature code 2584800:

## 30 Day Load Studies with the Fluke 1735 Power Logger

When a building owner wants you to add new loads to an existing service or set of feeders, the first thing you have to determine whether the existing system will support the new loads. If you have a 600 amp service installed in a facility, can you add another 100 amps of load?

To answer this question you have to ask another one: What is the highest load the system carries now? Often, local electrical authorities will need to know these answers before they issue permits.

Want to read more? Go to [www.fluke.com/library](http://www.fluke.com/library) to download this and other application notes, or get info specific to your industry and sign up for Fluke News publications at [www.fluke.com/subscribe](http://www.fluke.com/subscribe)



## Included accessories

**Fluke 1735 Logger:** Four flexible current probes (15 A/150 A/3000 A), Power Log software, voltage leads and clips, color localization set, PC interface cable, international ac adapter (115/230 V, 50/60 Hz), soft carrying case, printed English manual and multi-language manual CD.

**Norma 4000/5000 Analyzers:** Test certificate with calibration values, user manual, power supply cable and are completely customizable with a variety of accessories.

## Ordering information

Fluke-1735 Three-Phase Power Analyzer  
Norma 4000 BU43 High Precision Power Analyzer  
Norma 5000 BU56 High Precision Power Analyzer



# Fluke 345 Power Quality Clamp Meter

**The ideal meter for commissioning and troubleshooting modern electrical loads**



With a bright color display to analyze the harmonic spectrum, a low-pass filter to remove high frequency noise, and a high EMC immunity design, the Fluke 345 is ideal for measurements on switching loads such as variable speed drives, electronic lighting and UPS systems. Additionally, the Hall Effect measurement system makes measurement of dc current possible without the need to break the circuit, and the internal memory enables long-term logging for analysis of trends or intermittent problems.

- **AC/DC current:** Clamp-on measurement of ac peak and dc current up to 2000 A without breaking the circuit
- **Highest safety rating:** 600 V CAT IV/1000 V CAT III rated for use at the service entrance
- **Accurate measurement of parameters:** Even with distorted waveforms present on electronic loads with low-pass filter
- **Data logging:** Identify intermittent faults by logging any power parameters for minutes or months, including harmonics
- **Verify batteries:** Direct measurement of dc ripple (%) for battery and dc systems
- **Troubleshoot harmonics:** Analyze and log harmonics digitally or graphically
- **Inrush current:** Capture and analysis from 3 seconds to 300 seconds
- **Easy-to-use:** Easily confirm instrument setup with large backlit color display of waveforms and trends
- **Three-Phase power:** Built in capability for balanced loads.
- **View graphs and generate reports:** with included Power Log software

Application note, literature code 2722823:

## Basic power quality measurements on the go with the Fluke 345

A great introduction to power quality, this short application note teaches the basics of simple voltage, current, waveform, harmonics, power, inrush, and logging measurements using the Fluke 345. Learn how to read waveforms and how and where to use them, and then learn about harmonics and how they distort voltage and current.

Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library) or sign up for Fluke News to get pertinent information on your industry at [www.fluke.com/subscribe](http://www.fluke.com/subscribe)



## LH1050 and LH1060 Power Clamp Meters

**Ideal combination of a clamp and power meter**



The LH1050/1060 ac/dc meters are essential tools for power measurement and diagnostics on switching loads such as drives and high efficiency lighting. They combine the functionality of a current clamp, power meter and harmonics meter in a single handheld instrument that has been designed to a CAT III 600 V rating. Common applications include:

- Installing and testing of dc power systems
- Measurement of harmonics voltage and current on industrial systems
- Power and energy optimization

### LH1050 and LH1060 features:

- Wide range of measuring tasks possible with V, A, Hz, W, VAR, VA and PF in one easy to use clamp
- True-rms ensures correct, accurate measurement of ac+dc and distorted signals
- Clear presentation of results with bargraph for dual display of V/Hz, A/Hz and PF/W
- Flexible applications with three-phase power capability for balanced loads
- Easy data evaluation with 'Smart Hold' saving up to 7 parameters
- Capture trends with record mode storing Min Max and Average values
- EL backlight visible in varying light levels
- Two-year warranty

### Additional LH1060 features:

- Check startup characteristics with measurement of peak voltage and current values
- Harmonic troubleshooting with measurement of Total Harmonic Distortion (THD), Distortion Factor (DF) and Crest Factor (CF)
- Monitor the effects of loads with dc ripple measurement

### Included accessories

**Fluke 345 Clamp Meter:** Batteries, pair of measuring leads, alligator clips, operating instructions, Power Log software, interface cable pouch, and calibration certificate.

**LH1050/LH1060 Clamp Meters:** Battery, pair of measuring leads, operating instructions, and pouch.

### Recommended accessories

WINLOG S/W WinLOG software for LH 1050/1060, Analyst 2050/2060

### Ordering information

|           |                                 |
|-----------|---------------------------------|
| LH1050    | AC/DC Power Clamp Meter         |
| LH1060    | AC/DC Power Clamp Meter         |
| Fluke-345 | AC/DC Power Quality Clamp Meter |

The LH1050 and LH1060 are not available in Canada.

For more information and detailed specifications, go to [www.fluke.com/clamps](http://www.fluke.com/clamps)

Clamp Meters

# Fluke 360 AC Leakage Current Clamp Meter

**1  $\mu$ A resolution leakage current measurements with a tough, pocket sized clamp**



The unique jaw design of the Fluke 360 eliminates the influence of adjacent current conductors and measures leakage current down to 1  $\mu$ A for monitoring of insulation. The ergonomic design of the Fluke 360 ensures easy measuring. The measuring clamp fits into tight spaces and the wide display angle clearly shows the measurement result. The data hold button keeps the measured value on the display after removing the clamp for the measured conductor.

The light Fluke 360 offers the widest range of current measurement for maintenance professionals and contractors. Use the light and rugged Fluke 360 when it's not possible to power down and break the circuit.

## Current measurement

- Automatic ranging within the manually selected mA or A range
- Ranges 3/30 mA and 30/60 A
- Current resolution 1  $\mu$ A/0.01 mA and 0.01 A/0.1 A
- Frequency range 50 and 60 Hz
- Jaw size: 40 mm (1.55 in) maximum conductor diameter
- Auto power off
- One-year warranty

## LH41 AC/DC Low Current Clamp Meter AC/DC current clamp for low current applications



The compact size of the LH41 makes it ideal for making general measurements on small conductors. With excellent accuracy and resolution of 1 mA, the LH41 offers exceptional performance for automotive and other low current applications.

## Features

- Easy use autoranging ac/dc leakage current measurements from 10 mA to 40 A
- High 1 mA current resolution for quick circuit comparison on sensor and control circuits
- Patented jaw design for high accuracy, low dc current measurement ensures no interference from other circuits
- Push button dc Auto Zero for correct measurement every time
- Battery saving auto power off function
- 'Carry everywhere' pocket size, lightweight design
- Convenient display hold for capturing measurement in inaccessible spots
- CAT III 300 V
- Two-year warranty

## LH2015 AC/DC True-rms Clamp Meter

**High current, large jaw clamp for industrial and utility applications**

The LH2015's large jaw is suitable for current measurements up to 2000 A ac/dc on large conductors or bus bars. The LH2015's measurement accuracy is unaffected by external magnetic fields or off-center conductor positioning due to its advanced jaw design. Its Display-Hold feature freezes the measurement for viewing after measuring and the Max-Hold captures the maximum measured current.



Current clamp measurement can be used when:

- it's not possible to power down equipment and break the circuit.
- checking the current on large loads to avoid overheating of conductors.
- measuring large dc currents in industrial drives.

## Features:

- 2000 ac and dc current measurement
- Accurate true-rms measurement for distorted waveforms
- Large 50 mm (2 in) jaw capacity
- Autoranging and Auto-zero
- Display-Hold and Max-Hold (surge)
- Two-year warranty

## Included accessories

**Fluke 360 Clamp Meter:** Soft carrying pouch and users manual.

**LH41 Clamp Meter:** Battery and operating instructions.

**LH2015 Clamp Meter:** Soft case and users manual.

## Ordering information

|           |                                |
|-----------|--------------------------------|
| Fluke-360 | AC Leakage Current Clamp Meter |
| LH41      | AC and DC Current Clamp Meter  |
| LH2015    | AC/DC True-rms Clamp Meter     |

These products are not available in Canada.

# Get more done with the latest Fluke tools

## Move up to better design and performance with Fluke clamp meters



It's never been more important to be efficient, fast, and accurate at your job. Today, you need a tool that can keep up with the demanding needs of residential, commercial, and industrial electricians. The Fluke 337 Clamp Meter provides you the ability to work quickly and easily in narrow and dark locations, and makes it possible to keep track of your measurements for further analysis.

The Fluke 337 is a significant improvement from the Fluke 30 Series clamps that were built in the mid 1990's. While the 30 Series was a leader in its day, the 337 offers a design that is compact and lightweight, and functionality that allows you to take measurements that are more precise.

Fluke 330 Series clamps are designed more ergonomically with capabilities not found in their predecessors, the Fluke 30, 31, 32, 33 and 36.

### Specialty clamp meters

See page 54 for information on the **NEW!** 902 True-rms HVAC Clamp Meter.

See page 44 for information on the **NEW!** 771 Milliamp Process Clamp Meter.

### Fluke 337 Premium Clamp Meter

- Rugged
- CAT III 600 V
- Inrush
- Compact



| Function                                                                                                                                         | Fluke 30 Series Clamps | Fluke 337           | Benefit                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Three-year warranty                                                                                                                              | Out of warranty        | Three-year warranty | Lower cost of ownership                                                                                                               |
| Small body and jaws fit perfectly in your hand and into tight places                                                                             | —                      | •                   | Fits into tight areas for maximum usability                                                                                           |
| Frequency measurement                                                                                                                            | —                      | •                   | Built-in frequency counter                                                                                                            |
| Meter controls are positioned so current measurements can be done with one hand (index finger on clamp opening lever and thumb on rotary switch) | —                      | •                   | Easier to use, efficient measurements                                                                                                 |
| Large, backlit display is easy-to-see                                                                                                            | —                      | •                   | Use in dark areas                                                                                                                     |
| Inrush current function for measuring starting current for motors, lighting, etc.                                                                | —                      | •                   | Easily measure inrush current on motors, switches, and circuit protectors to determine if equipment can work with high current levels |
| Improved low current measurement accuracy from new microprocessor technology                                                                     | —                      | •                   | More precise measurements                                                                                                             |
| Min/Max capability                                                                                                                               | Max only               | Min/Max             | Easily track your measurements                                                                                                        |

For more information and detailed specifications, go to [www.fluke.com/clamps](http://www.fluke.com/clamps)

# Fluke 337 and 322 Clamp Meters

FLUKE®

**Measure inrush motor starting current the way a circuit breaker sees it**



- Inrush current feature (selected models)
- Small body and jaws fit perfectly in your hand and into tight places
- Controls positioned for one hand operation
- Accurate low current measurements
- Backlight available on most models
- Auto shut-off
- Display hold
- Safety rating: IEC 1010-2-031, CAT III 600 V
- Three-year warranty on 330 Series

## Fluke 322 Clamp Meter

- Precise measurements with 1.8 % basic accuracy
- Resolution up to 0.01 A and 0.1 V
- Measures ac current 40.00 A/400.0 A
- Measures ac and dc volts to 600 V
- Resistance measurement to 400 Ω
- Continuity for quick checking of shorts



## Specifications - 320 and 330 Series

Fluke 320 and 330 Series Clamp Meters offer an impressive array of innovative features with current ranges up to 1000 A. Choose the model that matches the jobs you do.

| (@23 °C ± 5 °C RH 0 to 90 %) |                  | Fluke 321                       | Fluke 322       | Fluke 333                    | Fluke 334      | Fluke 335                | Fluke 336                     | Fluke 337        |
|------------------------------|------------------|---------------------------------|-----------------|------------------------------|----------------|--------------------------|-------------------------------|------------------|
| AC current                   | Range            | to 400.0 A                      | 40.00 A/400.0 A | to 400.0 A                   | to 600.0 A     |                          |                               | to 999.9 A       |
|                              | Accuracy         | 1.8 % + 5 counts (50 to 60 Hz)  |                 | 2 % + 5 counts (50 to 60 Hz) |                |                          | 2 % + 5 counts (10 to 100 Hz) |                  |
|                              | AC response      | Averaging                       |                 | True-rms                     |                |                          |                               |                  |
| Inrush                       | Integration time | —                               | —               | —                            | 100 mS         |                          |                               |                  |
| DC current                   | Range            | —                               | —               | —                            | —              | —                        | 0 to 600.0 A                  | 0 to 999.9 A     |
|                              | Accuracy         | —                               | —               | —                            | —              | —                        | 2 % + 3 counts                |                  |
| AC volts                     | Range            | 400.0 V/600.0 V                 |                 | to 600.0 V                   |                |                          |                               |                  |
|                              | Accuracy         | 1.2 % + 5 counts (50 to 400 Hz) |                 | 1 % + 5 counts (50/60 Hz)    |                |                          | 1 % + 5 counts (20 to 100 Hz) |                  |
|                              | AC response      | Averaging                       |                 | True-rms                     |                |                          |                               |                  |
| DC volts                     | Range            | —                               | 400.0 V/600 V   | to 600.0 V                   |                |                          |                               |                  |
|                              | Accuracy         | —                               | —               | 1 % + 5 counts               |                |                          |                               |                  |
| Ohms                         | Range            | to 400.0 Ω                      |                 | to 600.0 Ω                   | 600.0 Ω/6000 Ω |                          |                               |                  |
|                              | Accuracy         | 1 % + 5 counts                  |                 | 1.5 % + 5 counts             |                |                          |                               |                  |
|                              | Continuity       |                                 |                 | ≤ 30 Ω                       |                |                          |                               |                  |
| Hz                           | Range            | —                               | —               | —                            | —              | —                        | —                             | to 400 Hz        |
|                              | Accuracy         | —                               | —               | —                            | —              | —                        | —                             | 0.5 % + 5 counts |
| MIN/MAX                      |                  | —                               | —               | —                            | —              | —                        | —                             | Yes              |
| Backlight                    |                  | —                               | —               | —                            | Yes            |                          |                               |                  |
| Display hold                 |                  |                                 |                 | Yes                          |                |                          |                               |                  |
| Size                         | H x W x D        | 7.5 in x 2.5 in x 1.4 in        |                 | 9.4 in x 3.1 in x 1.6 in     |                | 9.9 in x 3.1 in x 1.6 in |                               |                  |
|                              | Max wire dia.    | 1 in                            |                 |                              |                | 1.2 in                   |                               |                  |
|                              | Weight           | 8 oz                            |                 |                              |                | 11 oz                    |                               |                  |

## Recommended accessories - 320 and 330 Series



For more information and detailed specifications, go to [www.fluke.com/clamps](http://www.fluke.com/clamps)

Application note, literature code 2041766:

## Making accurate inrush current measurements

New high-efficiency motors require better tools to evaluate and fix the consequences of their high inrush current. The Fluke 335, 336 and 337 Clamp Meters are designed to capture inrush current accurately and, most importantly, synchronously and provide readings that accurately depict what the circuit protector experiences.

This application note covers practices to help you accurately and safely measure and interpret inrush current measurements.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



## Models 333, 334, 335, 336 and 337

**Operating temperature:** -10 °C to 50 °C (-14 °F to 122 °F)

**Altitude:** 2,500 meters

**Battery life:** (2) AA alkaline approximately 150 hours continuous, automatic low battery indicator

**Safety rating:** IEC 1010-2-031, CAT III 600 V

**Temperature de-rating:** Add 0.1 x specified accuracy for each °C above 28 °C or below 18 °C

**Storage temperature:** -40 °C to 60 °C (-40 °F to 140 °F)

## Models 321 and 322

**Operating temperature:** -10 °C to 50 °C (-14 °F to 122 °F)

**Altitude:** 2,000 meters

**Battery life:** (2) AAA carbon zinc approximately 100 hours continuous, automatic low battery indicator

**Safety rating:** IEC 1010-2-031, CAT III 600 V

**Temperature de-rating:** < 18 °C, > 28 °C add 0.1 x specified accuracy /°C

**Storage temperature:** -30 °C to 60 °C (-22 °F to 140 °F)

See page 54 for information on the **NEW! 902 True-rms HVAC Clamp Meter**

## Included accessories

Soft carrying case, test leads, (2) batteries, instruction card and safety information.

## Ordering information

Fluke 321      Fluke 335  
Fluke 322      Fluke 336  
Fluke 333      Fluke 337  
Fluke 334



# Fluke 1550B and 1520 MegOhmMeters

FLUKE®

## Powerful troubleshooting and predictive maintenance tools



The 1550B automatically calculates polarization index and dielectric absorption ratios. The 1550B features:

- Standard test voltages of 250 V, 500 V, 1000 V, 2500 V and 5000 V for a wide range of equipment testing
- Programmable test voltages available in 50-volt steps from 250 V to 1000 V and 100-volt steps from 1000 V to 5000 V
- Automatic calculation of Dielectric Absorption Ratio (DAR) and Polarization Index (PI) with no additional setup
- Easy setup saves time and effort when conducting "timed" and "ramp" test of insulation breakdown
- Improved ramp function (0 V dc to 5000 V dc) for breakdown testing
- Autodischarge of capacitive voltage
- Measures resistances up to one teraohm
- Includes improved FlukeView® Forms Software and Optical Interface cable for easier downloading to a Windows® PC

## Specifications - 1550B MegOhmMeter

The meter's accuracy is specified for one year after calibration at operating temperatures of 0 °C to 35 °C. For operating temperatures outside the range (-20 °C to 0 °C and 35 °C to 50 °C), add  $\pm .25\%$  per °C, except on the 20 % bands add  $\pm 1\%$  per °C.

| Insulation resistance measurement |                                                                    |                           |
|-----------------------------------|--------------------------------------------------------------------|---------------------------|
| Test Voltage (dc)                 | Range                                                              | Accuracy ( $\pm$ reading) |
| 250 V                             | 200 k $\Omega$ to 5 G $\Omega$<br>5 G $\Omega$ to 50 G $\Omega$    | 5 %<br>20 %               |
| 500 V                             | 200 k $\Omega$ to 10 G $\Omega$<br>10 G $\Omega$ to 100 G $\Omega$ | 5 %<br>20 %               |
| 1000 V                            | 200 k $\Omega$ to 20 G $\Omega$<br>20 G $\Omega$ to 200 G $\Omega$ | 5 %<br>20 %               |
| 2500 V                            | 200 k $\Omega$ to 50 G $\Omega$<br>50 G $\Omega$ to 500 G $\Omega$ | 5 %<br>20 %               |
| 5000 V                            | 200 k $\Omega$ to 100 G $\Omega$<br>100 G $\Omega$ to 1 T $\Omega$ | 5 %<br>20 %               |

| Function                | Range                                     | Accuracy ( $\pm$ reading)                   |
|-------------------------|-------------------------------------------|---------------------------------------------|
| Leakage current         | 1 nA to 2 mA                              | $\pm (5\% + 2 \text{ nA})$                  |
| Capacitance measurement | 0.01 $\mu\text{F}$ to 15.00 $\mu\text{F}$ | $\pm (15\% \text{ rdg} + 0.03 \mu\text{F})$ |
| Live circuit indicator  | 30 V to 600 V ac/dc, 50/60 Hz             | $\pm (5\% + 2 \text{ V})$                   |

**Short circuit current:** greater than 1 mA and less than 2 mA

**Bar graph range:** 0 to 1 T $\Omega$

**Insulation test voltage accuracy:** -0 % to +10 % at 1 mA load current

**Induced ac mains current rejection:** 2 mA maximum

**Charging rate for capacitive load:** 5 seconds per  $\mu\text{F}$

**Timer:** 0 to 99 minutes; settable in 1 minute increments; indicated to within 1 second

**Ramp:** 0 % to 100 % of selected test voltage, or until breakdown

**Dimensions (HxWxD):** 330 mm x 242 mm x 170 mm (13 in x 9.5 in x 6.7 in)

**Weight (with battery):** 4 kg (8.8 lb)

**Battery type:** 12 V, lead-acid, rechargeable

**Charger input (ac):** 85 to 250 V ac, 50/60 Hz, 50 VA

**Operating temperature:** -20 °C to 50 °C

(-4 °F to 122 °F)

**Storage temperature:** -20 °C to 65 °C (-4 °F to 149 °F)

**Relative humidity:** 80 % at 31 °C decreasing linearly to 50 % at 50 °C

**Operating altitude:** 0 to 2000 meters

**Enclosure sealing:** IP 40

**Safety conformance:** EN 61010-1, CAT III, 600 V, EN61557, Parts 1 & 2

**Input overload protection:** 600 V ac continuous

**Warranty:** Two-years

**Software:** FlukeView® Forms Basic Software requires a PC running Windows® 95, 98, Me, 2000, NT4.0

## Fluke 1520 MegOhmMeter



A proven workhorse, the 1520 can make up to 5,000 insulation resistance tests, more than any other Fluke insulation tester, without changing batteries. A dual analog/digital display makes it easy to use. A lo-ohms function measures voltage and checks connections. Thanks to superb accuracy, endurance, and handheld size, the 1520 is a long-standing tool of choice for demanding plant and utilities work.

- Large, backlit LCD with analog bar graph and digital display
- Three output voltages for insulation resistance testing: 250 V, 500 V and 1000 V
- Perform up to 5,000 insulation resistance tests without changing batteries
- Insulation resistance testing up to 4000 M $\Omega$ ; switches automatically to voltage measurement when voltage is greater than 30 V ac or 30 V dc
- Auto-discharge of capacitive voltage
- AC/DC voltage measurement up to 600 V
- Lo-Ohms function for testing connections
- Last reading memory display

## Recommended accessories - 1550B MegOhmMeter



**FVF-UG**  
FlukeView Forms  
Software Upgrade  
See page 65



**TL1550EXT**  
25 Foot Extension  
Test Lead Set



**L206**  
Deluxe LED Hat Light  
See page 64

## Recommended accessories - 1520 MegOhmMeter



**TL27**  
Heavy-Duty  
Test Lead Set  
See page 62



**ToolPak™**  
Meter Hanger  
See page 71



**SH100**  
Shoulder harness  
for 1520



**TL223**  
SureGrip™ Electrical  
Test Lead Set  
See page 61



**C43**  
Soft Carrying Case  
See page 70

## Included accessories

**Fluke 1550B MegOhmMeter:** Test leads, 5000 V-rated probes, alligator clips, interface adapter and cable, FlukeView Forms software, line cord, soft carrying case, and users manual.

**Fluke 1520 MegOhmMeter:** TL27 Heavy Duty Test Leads, TP74 Lantern Tip Test Probes, AC285 Large Jaw Alligator Clips, protective holster with hand strap, carrying case with accessory storage, four C-cell alkaline batteries, instruction manual, and instruction manual on CD-ROM.

## Ordering information

Fluke-1520 MegOhmMeter  
Fluke-1550B MegOhmMeter


For more information and detailed specifications, go to [www.fluke.com/1550](http://www.fluke.com/1550)

Insulation Resistance Testing

# Fluke 1587 and 1577 Insulation Multimeters

FLUKE®

## Two powerful tools in one



The Fluke 1587 and 1577 Insulation Multimeters combine a digital 1 kV insulation tester with a full-featured, true-rms digital multimeter in a single compact, handheld unit, which provides maximum versatility for both troubleshooting and preventative maintenance. Whether you work on motors, generators, cables, or switchgear, the Fluke 1587 and 1577 Insulation Multimeters are ideally suited to help you with your tasks.

- Insulation test (1587: 0.01 MΩ to 2 GΩ) (1577: 0.1 MΩ to 600 MΩ)
- Insulation test voltages (1587: 50 V, 100 V, 250 V, 500 V, 1000 V), (1577: 500 V, 1000 V) for many applications
- Live circuit detection prevents insulation test if voltage > 30 V is detected for added user protection
- Auto-discharge of capacitive voltage for added user protection
- Filter for motor drive measurements (1587 only)
- AC/DC voltage, dc millivolts, ac/dc milliamps, resistance (Ω), and continuity
- Capacitance, diode test, temperature, Min/Max, and frequency (Hz) (1587 only)
- Auto power off to save battery power
- Large display with backlight and large digits
- Included accessories: Remote probe, test leads and probes, alligator clips, (K-type thermocouple, 1587 only)
- Accepts optional Fluke TPAK™ magnetic hanging system to free your hands for other work
- Rugged, utility hard case allows you to bring everything you need for the job
- Three-year warranty

## Specifications

|                                                            | 1587 | 1577 |
|------------------------------------------------------------|------|------|
| Insulation test voltages 50 V, 100 V, 250 V, 500 V, 1000 V | •    |      |
| Insulation test voltages 500 V, 1000 V                     |      | •    |
| Insulation test: 0.01 MΩ to 2.0 GΩ                         | •    |      |
| Insulation test: 0.1 MΩ to 600 MΩ                          |      | •    |
| Auto-discharge of capacitive voltage                       | •    | •    |
| Insulation test smoothing reading                          | •    |      |
| Frequency                                                  | •    |      |
| Capacitance                                                | •    |      |
| Diode test                                                 | •    |      |
| Temperature                                                | •    |      |
| Min/Max                                                    | •    |      |
| Low-pass filter (for work on VSDs)                         | •    |      |
| AC/DC Voltage                                              | •    | •    |
| DC Millivolts                                              | •    | •    |
| AC/DC milliamps                                            | •    | •    |
| Resistance (0.1 Ω to 50 MΩ)                                | •    | •    |
| Continuity                                                 | •    | •    |
| Three-year warranty                                        | •    | •    |
| Remote probe, test leads, alligator clips                  | •    | •    |
| K-type thermocouple                                        | •    |      |
| Rugged, utility hard case                                  | •    | •    |
| Auto power off                                             | •    | •    |



## Recommended accessories



**ToolPak™**  
Meter Hanger  
See page 71



**i400s**  
AC Current Clamp  
See page 66



**C2S**  
Meter Case  
See page 70

For more information and detailed specifications, go to [www.fluke.com/1587](http://www.fluke.com/1587)

## Get the most value and productivity from Fluke kits

Establishing a preventive maintenance program is becoming critical to maintaining the uptime of electrical equipment and can significantly reduce both planned and unplanned downtime. Unplanned downtime costs are difficult to calculate, but are often significant. For some industries, it can represent 1 % to 3 % of revenue (potentially 30 % to 40 % of profits) annually.

These kits can help you be proactive and efficient with your maintenance and can save you up to 10 % off the individual price of the tools.

### Fluke 1587/ET Advanced Electrical Troubleshooting Kit includes:



- Fluke 1587 Insulation Multimeter
- Fluke i400 Current Clamp
- Fluke 62 Mini Infrared Thermometer

### Fluke 1587/MDT Advanced Motor and Drive Troubleshooting Kit includes:



- Fluke 1587 Insulation Multimeter
- Fluke i400 Current Clamp
- Fluke 9040 Phase Rotation Indicator

## Included accessories

Remote probe, test leads, alligator clips, K-type thermocouple (1587 only), hard case and user documentation.

## Ordering information

|                |                                              |
|----------------|----------------------------------------------|
| Fluke-1577     | Insulation Multimeter                        |
| Fluke-1587     | Insulation Multimeter                        |
| Fluke-1587/ET  | Advanced Electrical Troubleshooting Kit      |
| Fluke-1587/MDT | Advanced Motor and Drive Troubleshooting Kit |

Insulation Resistance Testing



# Fluke 1507 and 1503 Insulation Testers

## Insulation resistance testing in the palm of your hand



The Fluke 1507 and 1503 Insulation Testers are compact, rugged, reliable, and easy to use. With their multiple test voltages, they are ideal for many troubleshooting, commissioning, and preventive maintenance applications. Additional features, like the remote probe on these tools save both time and money when performing tests.

### Insulation test ranges:

- 1507: 0.01 MΩ to 10 GΩ
- 1503: 0.1 MΩ to 2 GΩ

### Insulation test voltages:

- 1507: 50 V, 100 V, 250 V, 500 V, 1000 V
- 1503: 500 V, 1000 V
- Save both time and money with automatic calculation of Polarization Index and Dielectric Absorption Ratio (1507 only)
- Make repetitive tests simple and easy with the 1507's compare (Pass/Fail) function (only available on the 1507)
- Repetitive or hard-to-reach testing is easy with the remote test probe
- Live circuit detection prevents insulation test if voltage > 30 V is detected for added user protection
- Auto-discharge of capacitive voltage for added user protection
- AC/DC voltage: 0.1 V to 600 V
- Lo-Ohms/Earth bond continuity (200 mA)
- Resistance: 0.01 Ω to 20.00 KΩ
- Save battery power with auto-power off
- Read measurements easily with large, backlit display
- CAT IV 600 V overvoltage category rating for added user protection
- Remote probe, test leads, probes, and alligator clips included with each tester
- Accepts optional Fluke ToolPak™ magnetic hanging system to free your hands for other work
- Four AA alkaline batteries (NEDA 15 A or IEC LR6) for at least 1000 insulation tests
- One-year warranty

Application note, literature code 1579160:

### Insulation resistance testing

Insulation resistance testers can be used to determine the integrity of windings or cables in motors, transformers, switchgear, and electrical installations.



The test method is determined by the type of equipment being tested and the reason for testing. For instance, when testing electrical cabling or switchgear (low-capacitance equipment) the time-dependent capacitive leakage and absorption leakage currents become insignificant and decrease to zero almost instantly. A steady conductive leakage current flow is reached almost instantly (a minute or less) providing perfect conditions for the spot-reading/short time resistance test.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library), or sign up for Fluke News for pertinent information on your industry at [www.fluke.com/subscribe](http://www.fluke.com/subscribe)

## Features – 1507 and 1503 Testers

| Feature                                                    | 1507 | 1503 |
|------------------------------------------------------------|------|------|
| Insulation test voltages 50 V, 100 V, 250 V, 500 V, 1000 V | •    |      |
| Insulation test voltages 500 V and 1000 V                  |      | •    |
| Insulation test: 0.01 MΩ to 10 GΩ                          | •    |      |
| Insulation test: 0.01 MΩ to 2 GΩ                           |      | •    |
| PI/DAR                                                     | •    |      |
| Auto discharge of capacitive voltage                       | •    | •    |
| Remote test probe, test leads, alligator clips             | •    | •    |
| Rugged utility hard case                                   | •    | •    |
| Auto power off                                             | •    | •    |

### Recommended accessories – 1507 and 1503 Testers



**C101**  
Meter Hard Case  
See page 70



**ToolPak™**  
Meter Hanger  
See page 71



**C25**  
Meter Case  
See page 70

### Included accessories

Remote probe, test leads, test probes, alligator clips, holster and user documentation.

### Ordering information

Fluke-1507 Insulation Tester  
Fluke-1503 Insulation Tester

For more information and detailed specifications, go to [www.fluke.com/1507](http://www.fluke.com/1507)

# Pick the right process tool for you

## Process Tools Selection Guide

|                                 |  |  |  |  |  |  |  |  |
|---------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                                 | Loop Calibrator                                                                   | Pressure Calibrator                                                               | Temperature Calibrator                                                            | Precision Multifunction Process Calibrator                                        | Intrinsically Safe Calibrator                                                     | Documenting Process Calibrator                                                      | Process mA Clamp Meter                                                              | ProcessMeter® Test Tool                                                             |
| Model                           | 715                                                                               | 718                                                                               | 724                                                                               | 726                                                                               | 725Ex                                                                             | 744                                                                                 | 771                                                                                 | 789                                                                                 |
| Measure                         |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                     |                                                                                     |                                                                                     |
| V dc                            | 25 V                                                                              |                                                                                   | 30 V                                                                              | 30 V                                                                              | 30 V                                                                              | 300 V                                                                               |                                                                                     | 1000 V                                                                              |
| V ac (true-rms)                 |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   | 300 V                                                                               |                                                                                     | 1000 V                                                                              |
| Resistance                      |                                                                                   |                                                                                   | 3200 Ω                                                                            | 4000 Ω                                                                            | 3200 Ω                                                                            | 11 kΩ                                                                               |                                                                                     | 40 MΩ                                                                               |
| A dc                            | 24 mA                                                                             | 24 mA                                                                             | 24 mA                                                                             | 24 mA                                                                             | 24 mA                                                                             | 110 mA                                                                              | 20.99, 99.9 mA                                                                      | 30 mA, 1 A                                                                          |
| A ac                            |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                     |                                                                                     | •                                                                                   |
| Frequency                       |                                                                                   |                                                                                   |                                                                                   | 15 kHz                                                                            | 10 kHz                                                                            | 50 kHz                                                                              |                                                                                     | 20 kHz                                                                              |
| Pressure                        |                                                                                   | 1 psi, 30 psi, 100 psi and 300 psi                                                |                                                                                   | • <sup>1</sup>                                                                    | • <sup>5</sup>                                                                    | • <sup>1</sup>                                                                      |                                                                                     |                                                                                     |
| Temperature: RTDs               |                                                                                   |                                                                                   | 7 types                                                                           | 8 types                                                                           | 7 types                                                                           | 8 types                                                                             |                                                                                     |                                                                                     |
| Temperature: TCs                |                                                                                   |                                                                                   | 12 types                                                                          | 13 types                                                                          | 12 types                                                                          | 13 types                                                                            |                                                                                     |                                                                                     |
| Source/Simulate                 |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                     |                                                                                     |                                                                                     |
| V dc                            | 20 V                                                                              |                                                                                   | 10 V                                                                              | 20 V                                                                              | 10 V                                                                              | 15 V                                                                                |                                                                                     |                                                                                     |
| Resistance                      |                                                                                   |                                                                                   | 3200 Ω                                                                            | 4000 Ω                                                                            | 3200 Ω                                                                            | 11 kΩ                                                                               |                                                                                     |                                                                                     |
| mA dc/% scale                   | 24 mA                                                                             |                                                                                   |                                                                                   | 24 mA                                                                             | 24 mA                                                                             | 22 mA                                                                               |                                                                                     | 24 mA                                                                               |
| mA source; auto step, auto ramp | •                                                                                 |                                                                                   |                                                                                   | •                                                                                 | •                                                                                 | •                                                                                   |                                                                                     | •                                                                                   |
| Frequency                       |                                                                                   |                                                                                   |                                                                                   | 15 kHz                                                                            | 10 kHz                                                                            | 50 kHz                                                                              |                                                                                     |                                                                                     |
| Temperature: RTDs               |                                                                                   |                                                                                   | 7 types                                                                           | 8 types                                                                           | 7 types                                                                           | 8 types                                                                             |                                                                                     |                                                                                     |
| Temperature: TCs                |                                                                                   |                                                                                   | 12 types                                                                          | 13 types                                                                          | 12 types                                                                          | 13 types                                                                            |                                                                                     |                                                                                     |
| Record                          |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                     |                                                                                     |                                                                                     |
| Min/Max                         |                                                                                   | •                                                                                 |                                                                                   |                                                                                   |                                                                                   | •                                                                                   |                                                                                     | •                                                                                   |
| Hold                            |                                                                                   | •                                                                                 |                                                                                   |                                                                                   |                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   |
| As Found/As Left results        |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                   |                                                                                     |                                                                                     |
| Log data                        |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                   |                                                                                     |                                                                                     |
| Upload data to PC               |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                   |                                                                                     |                                                                                     |
| Remote operation                |                                                                                   |                                                                                   |                                                                                   | •                                                                                 |                                                                                   |                                                                                     |                                                                                     | •                                                                                   |
| Features                        |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                     |                                                                                     |                                                                                     |
| 24 V loop supply                | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | 12 V                                                                              | •                                                                                   |                                                                                     | •                                                                                   |
| Non-contact measurement         |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                     | •                                                                                   |                                                                                     |
| Hart communication              |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                   |                                                                                     |                                                                                     |
| Integrated hand pressure pump   |                                                                                   | •                                                                                 |                                                                                   |                                                                                   |                                                                                   |                                                                                     |                                                                                     |                                                                                     |
| Intrinsically safe (ATEX)       |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 |                                                                                     |                                                                                     |                                                                                     |
| Warranty                        | 3 years                                                                           | 1 year                                                                            | 3 years                                                                           | 3 years                                                                           | 1 year                                                                            | 3 years                                                                             | 1 year                                                                              | 3 years                                                                             |
| NIST traceable certification    | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                   |                                                                                     |                                                                                     |
| Accessories <sup>3</sup>        | A/B                                                                               | C                                                                                 | A/B                                                                               | A/B                                                                               |                                                                                   |                                                                                     |                                                                                     | A/B                                                                                 |
| Pressure enabled <sup>4</sup>   |                                                                                   | •                                                                                 |                                                                                   | •                                                                                 | •                                                                                 | •                                                                                   |                                                                                     |                                                                                     |
| See page                        | 42                                                                                | 41                                                                                | 40                                                                                | 39                                                                                | 45                                                                                | 38                                                                                  | 44                                                                                  | 43                                                                                  |

<sup>1</sup>Fluke 700 Pressure Modules required.

<sup>2</sup>Either the internal sensor or a Fluke 700 Pressure Module may be used.

<sup>3</sup>Accessories: A. Compatible with LockPak B. Compatible with ToolPak C. Accepts hanging straps from ToolPak D. Optional accessories

<sup>4</sup>Fluke Process Calibrators in this guide displaying the Pressure Enabled symbol display readings from the 700 Series Pressure Modules.

<sup>5</sup>Fluke 700PEX Pressure Module required.

# Fluke 741B, 743B and 744 Calibrators

FLUKE®



**For the calibration and troubleshooting of process control instrumentation**



- Calibrate temperature, pressure, voltage, current, resistance and frequency instruments
- Built-in procedures for transmitters, square root transmitters, pressure and temperature switches
- Simultaneously measure and source
- Automatically capture calibration results
- Document procedures and results to meet ISO 9000, EPA, FDA, OSHA, and other government requirements
- Measure/simulate 13 types of thermocouples and eight RTDs
- Store up to 8,000 readings in data logging mode (743B and 744 only)
- Protected against dirt, dust and moisture; unaffected by vibration
- Includes a PC interface (743B and 744 only)
- Operate in English, French, German, Italian and Spanish
- Offer one- and two-year calibration cycles and a three-year warranty (one-year for pressure modules)

## 744: Get HART-ability

The Fluke 744 offers all of the capabilities of the 743B, plus the ability to calibrate, maintain, and troubleshoot HART instrumentation. Integrated HART communication functions permit you to monitor, control, and calibrate HART instrumentation. It handles fast pulsed instruments such as RTD transmitters and PLCs, with pulses as short as 1 ms.

See [www.fluke.com/744upgrade](http://www.fluke.com/744upgrade) for the latest list of HART instruments.

## 741B: A complete documenting calibrator

The 741B is the economical choice for plants that don't use PCs or that require traditional paper forms. It has storage capacity for a day's calibration and measurement data. When you're back at the shop, recall the data on-screen to fill out calibration forms.

## 743B: More memory, plus a PC interface and data logging

The 743B has all the capabilities of the 741B plus a PC interface that lets you load procedures, lists, and instructions created with software—or unload data for printing, archiving, and analysis. With its expanded memory, the 743B can hold a full week of calibrations and procedures.

Application note, literature code 1262439:

## HART® transmitter calibration

The need for calibration of HART smart transmitters is often misunderstood. What do you calibrate and when? Here is a step-by-step procedure showing how to use the Fluke 744 to perform calibration and digital adjustments of Rosemount 3051 and 3144 transmitters and other HART devices.



## Instrumentation management software

The Fluke 743B and 744 are compatible with Fluke 700SW DPC/TRACK software and with software from Beamex, Cornerstone, Emerson, Honeywell, On Time Support, Prime Technologies, Yokogawa, Intools and Meridium.

For more information, visit [www.fluke.com/software](http://www.fluke.com/software)

## Specifications – 741B, 743B and 744

| Function      | Measure                                                      | Sourcing                           |
|---------------|--------------------------------------------------------------|------------------------------------|
| DC voltage    | 0.025 % reading + 0.005 % full scale                         | 0.01 % output + 0.005 % full scale |
| DC current    | 0.01 % reading + 0.015 % full scale                          | 0.01 % output + 0.015 % full scale |
| Resistance    | 0.05 % reading + 50 mΩ                                       | 0.01 % output + 40 mΩ              |
| Frequency     | 0.05 %                                                       | 0.01 %                             |
| Thermocouples | 0.3 °C                                                       | 0.2 °C                             |
| RTDs          | 0.3 °C                                                       | 0.1 °C                             |
| Pressure      | To 0.25 % of full scale, per pressure module specifications. |                                    |

Summary specifications: best case, midrange, one-year.  
**Battery life:** Typically over eight hours  
**Internal battery pack:** NiCd, 7.2 V, 1700 mAh, NiMH 3500 mAh on 744.  
**Battery replacement:** Via snap-shut door without opening calibrator; no tools required  
**Weight:** 1.4 kg (3 lb 1 oz)  
**Size (HxWxD):** 236 mm x 130 mm x 61 mm (9.3 in x 5.1 in x 2.4 in)

## Recommended accessories – 741B, 743B and 744



**C789**  
Meter and Accessory Case  
See page 70



**Fluke-700PTP**  
Pneumatic Test Pump  
See page 69



**Fluke-700Pxx**  
Pressure Modules  
See page 41



**80PK-25**  
SureGrip Piercing Temperature Probe  
See page 68



**TL220**  
SureGrip Industrial Test Lead Set  
See page 61

## Included accessories

TL224 Industrial Test Leads (2 sets), AC220 Test Clips (2 sets), TP220 Test Probes, BP7217 Battery Pack, BC7217 Battery Charger, instruction manual, NIST Traceable calibration certificate and data, serial port cable (743B and 744 only), DPC/TRACK sample version with free PC communication utility software (743B and 744 only).

## Additional 744 accessories

BP7235 NiMH Battery Pack, HART communications cable, HART user's manual and NIST Traceable calibration certificate and data.

## Ordering information

Fluke-741B Documenting Process Calibrator  
 Fluke-743B Documenting Process Calibrator  
 Fluke-744 Documenting Process Calibrator  
 Fluke-700S DPC/Track Software

For more information and detailed specifications, go to [www.fluke.com/740](http://www.fluke.com/740)

Process Calibration Tools

# Fluke 726 and 725 Multi-function Process Calibrators

Step up to unmatched accuracy in process measurement and calibration

New



## Fluke 726 Precision Multifunction Process Calibrator

The Fluke 726 Precision Multifunction Process Calibrator is designed specifically for the Process industry with broad workload coverage, calibration power and unsurpassed accuracy in mind. The 726 measures and sources almost all process parameters and can calibrate almost anything. The 726 will also interpret results without the help of a calculator and store measurement data for later analysis.

- Precise measurement and calibration source performance, accuracies of 0.01 %
- Transmitter error% calculation, interpret calibration results without a calculator
- Memory storage for up to 8 calibration results, return stored calibration data from the field for later analysis
- Frequency totalizer and frequency pulse train source mode for enhanced flowmeter testing
- HART mode inserts 250 ohm resistor in mA measure and source for compatibility with HART instrumentation
- Integrated pressure switch test allows you to capture the set, reset and deadband of a switch
- Custom RTD curves, add calibration constants for certified RTD probes for enhanced temperature measurement
- New voltage input protection design for improved reliability
- Three-year warranty



## Fluke 725 Multifunction Process Calibrator

- Measure volts, mA, RTDs, thermocouples, frequency and ohms to test sensors and transmitters
- Source/simulate volts, mA, thermocouples, RTDs, frequency, ohms and pressure to calibrate transmitters
- Measure/source pressure using any of 29 Fluke 700Pxx Pressure Modules
- Source mA with simultaneous pressure measurement to conduct valve and I/P tests
- Support flow meter testing with frequency and counts per minute (CPM) functions
- Perform fast linearity tests with auto step and auto ramp features



Intrinsically safe version available (see page 45)

## Specifications - 726 and 725 Calibrators

### Measure and source

| Function          | Range or type                                                                                      | Resolution                                           | Accuracy                                            | Notes                                                                        |
|-------------------|----------------------------------------------------------------------------------------------------|------------------------------------------------------|-----------------------------------------------------|------------------------------------------------------------------------------|
| Voltage           | 0 to 100 mV<br>0 to 10 V (source)<br><b>0 to 20 V (source)</b><br>0 to 30 V (measure)              | 0.01 mV<br>0.01 V<br>0.01 V<br>0.01 V                | <b>0.01 %</b> ,<br>0.02 %<br>Rdg + 2 LSD            | Max load, 1 mA                                                               |
| mA                | 0 to 24                                                                                            | 0.001 mA                                             | <b>0.01 %</b> ,<br>0.02 %<br>Rdg + 2 LSD            | Max load, 1000 Ω                                                             |
| mV (TC terminals) | -10.00 mV to +75.00 mV                                                                             | .01 mV                                               | <b>0.01 %</b> , 0.02 %<br>of range + 1 LSD          |                                                                              |
| Ohms              | 15 Ω to 3,200 Ω<br><b>5 Ω to 4,000 Ω</b>                                                           | 0.01 Ω<br>to 0.1 Ω                                   | 0.10 Ω to 1.0 Ω<br><b>0.015 %</b>                   |                                                                              |
| Hz - CPM          | 2.0 to 1,000 CPM<br>1 to 1000 Hz<br>1.0 to 10.0 kHz<br><b>10.0 to 15.0 kHz</b>                     | 0.1 CPM<br>1 Hz<br>0.1 kHz<br><b>0.1 kHz</b>         | ± 0.05 %<br>± 0.05 %<br>± 0.25 %<br><b>± 0.05 %</b> | Source;<br>5 V p-p<br><b>1 V to 20 V p-p</b><br>squarewave,<br>-0.1 V offset |
| Loop supply       | 24 V dc                                                                                            | N/A                                                  | 10 %                                                |                                                                              |
| T/C               | J, K, T, E, L, N, U, XK                                                                            | 0.1 °C, 0.1 °F                                       | to 0.7 °C<br><b>to 0.2 °C</b>                       |                                                                              |
| T/C               | B, R, S, BP                                                                                        | 1 °C, 1 °F                                           | to 1.7 °C<br><b>to 1.2 °C</b>                       |                                                                              |
| RTDs              | <b>Cu (10)</b> , Ni120 (672)<br>Pt 100, 200, 500,<br>1000 (385)<br>Pt 100 (3916),<br>Pt 100 (3926) | <b>0.01 °C</b> ,<br><b>0.01 °F</b><br>0.1 °C, 0.1 °F | <b>to 0.15 °C</b><br>to 0.2 °C                      |                                                                              |

Unique 726 specifications are bolded

### General specifications

**Storage temperature:**  
-20 °C to 71 °C  
**Operating temperature:**  
-10 °C to 55 °C  
**Relative humidity:**  
90 % (10 °C to 30 °C);  
75 % (30 °C to 40 °C);  
45 % (40 °C to 50 °C);  
35 % (50 °C to 55 °C)  
**Shock:** 1 meter drop test  
**Safety:** CSA C22.2  
No. 1010.1:1992  
**EMC:** EN50082-1:1992 and  
EN55022:1994 Class B  
**Size (HxWxD):** 200 mm x  
96 mm x 47 mm (7.9 in x  
3.8 in x 1.9 in)  
**Weight:** 650 g (23 oz)  
**Battery:** Four AA alkaline  
batteries  
**Battery life:** 25 hours  
typical

| Simultaneous function capability                                                   | Channel A | Channel B   |
|------------------------------------------------------------------------------------|-----------|-------------|
| 24.000 mA dc                                                                       | M         | M or S      |
| 24.000 mA dc with 24 V loop supply                                                 | M         |             |
| 100.00 mV dc                                                                       |           | M or S      |
| 30.000 V dc measure                                                                | M         |             |
| 20.000 V dc measure<br>10.000 V dc source<br>20.000 V dc source                    |           | M or S      |
| 15 to 3200 Ohms<br>5 to 4000 Ohms                                                  |           | M or S      |
| Thermocouple J, K, T, E, R, S, B, M, L, U, N, XK, BP                               |           | M or S      |
| RTD Cu 10, Ni120; Pt100 (392); Pt100 (JIS); Pt100, 200, 500, 1000 (385), XK and BP |           | M or S      |
| Pressure (requires Fluke 700PXX Modules)                                           | M         | M used as S |
| Frequency; 10 kHz; (15 KHz 726)                                                    |           | M or S      |

M = Measure, S = Source/Simulate

### Included accessories

TL75 Test Leads, AC72 Test Clips, one pair of stackable test leads, product overview manual (print) and users manual in 14 languages on CD-ROM.

### Ordering information

Fluke-726 Precision Multifunction Process Calibrator  
Fluke-725 Multifunction Process Calibrator  
Fluke-724 Temperature Calibrator (also see page 40)

### Recommended accessories - 726 and 725 Calibrators



**Fluke-700PTP**  
Pneumatic Test Pump  
See page 69



**C125**  
Meter Case  
See page 70



**ToolPak**  
Meter Hanging Kit  
See page 71



**80PK-27**  
SureGrip Industrial Surface Temperature Probe  
See page 68

For more information and detailed specifications, go to [www.fluke.com/726](http://www.fluke.com/726)

# Fluke 712, 714 and 724 Temperature Calibrators

**Accurate and rugged, temperature calibration tools**



The Fluke 710 Series temperature calibrators deliver outstanding performance, durability and reliability. And with a push-button interface, similar to the multifunction Fluke 740 Series Documenting Process Calibrators, the 710s are easy to use. Each calibrator is EMI tolerant, dust- and splash-resistant, and features a removable battery door for quick battery changes.

## Fluke 712 RTD Calibrator

- Compatible with pulsed current transmitters
- Measure temperature from an RTD probe
- Simulate RTD output
- Operates with seven types of RTD
- Measure additional RTDs using Ohms measurement function
- Simulate additional RTDs using Ohms source function
- °F or °C selectable
- 25 % stepping, auto-step and auto-ramp
- Ramp and Step Ramp output functions

## Fluke 714 Thermocouple Calibrator

- Measure temperature from TC probes
- Simulate TC output
- Operable with nine types of thermocouples
- Calibrate linear TC transmitter with mV source function
- Selectable °F or °C
- 25 % stepping, auto-step and auto-ramp
- Available as accessories: Fluke 700TC1 and TC2 Thermocouple Mini-plug Kits
- Ramp and Step Ramp output functions

Data Sheet, literature code 1560369:

## Temperature calibration

See how Fluke can help you calibrate, troubleshoot and verify the most common temperature devices, faster and easier.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



## Fluke 724 Temperature Calibrator

- Source/measure TCs, RTDs, volts and ohms
- Measure mA while supplying loop power
- 25 % and 100 % stepping, auto-step and auto ramp



## Specifications – 712 and 714 Calibrators

| Model     | Function                      | Range                                                         | Resolution                     | Accuracy                    | Notes                                                                          |
|-----------|-------------------------------|---------------------------------------------------------------|--------------------------------|-----------------------------|--------------------------------------------------------------------------------|
| Fluke-712 | Measure/simulate RTD          | -200 °C to 800 °C (Pt 100-385)                                | 0.1 °C, 0.1 °F                 | 0.2 °C, 0.4 °F (Pt 100-385) | Pt; 100 200 500 1000 (385); Pt 100 (392); Pt 100 (392) JIS; Ni 120 (672)       |
|           | Measure/simulate resistance   | 5 Ω to 4000 Ω                                                 | 0.1 Ω                          | 0.025 %                     |                                                                                |
| Fluke-714 | Measure/simulate thermocouple | -200 °C to 1800 °C, depending on type (K, -200 °C to 1370 °C) | 0.1 °C or °F (1 °C or °F; BRS) | 0.5 °C, 0.8 °F (Type K)     | 9 TC types; J K T E R S B per NIST 175 and ITS-90 L U per DIN 43710 and PTS-68 |
|           | Measure/simulate mV           | -10 mV to 75 mV                                               | 0.01 mV                        | 0.015 % +10 µV              |                                                                                |

General specifications for all Fluke 712 through 718 calibrators

Maximum voltage: 30 V Non-operating temperature: -40 °C to 60 °C Operating temperature: -10 °C to 55 °C Relative humidity: 95 % (10 °C to 30 °C); 75 % (30 °C to 40 °C); 45 % (40 °C to 50 °C); 35 % (50 °C to 55 °C)

Operating altitude: 3,000 m max Shock: 1 m drop test Vibration: Random, 2 g, 5-500 Hz

Safety: CSA C22.2 No. 1010.1:1992 EMC: EN50082-1:1992 and EN55022:1994 Class B

Size/weight (HxWxD) (712-717): 187 mm x 87 mm x 32 mm (7.35 in x 3.41 in x 1.25 in) 330 g (12 oz)

Size/weight (HxWxD) (712-717 with holster): 201 mm x 98 mm x 52 mm (7.93 in x 3.86 in x 2.06 in) 600 g (21 oz)

Size/weight (HxWxD) (718): 210 mm x 83 mm x 62 mm (8.25 in x 3.27 in x 2.44 in) 737 g (26 oz)

Size/weight (HxWxD) (718 with holster): 216 mm x 94 mm x 66 mm (8.50 in x 3.72 in x 2.60 in) 992 g (35 oz)

Power: 9 V battery ANSI/NEDA 1604A or IEC 6LR619V alkaline; two batteries in 718

Battery life: 4 to 20 hours, typical, depending on functions used

Warranty: Three-years (one-year on pressure pump in Fluke 718)

## Recommended accessories – 712, 714 and 724 Calibrators



**TL75 (712 and 724)**  
Hard Point  
Test Lead Set  
See page 62

**C550**  
Tool Bag  
See page 70

**TL220 (712 and 724)**  
SureGrip Industrial  
Test Lead Set  
See page 61

**C25 (712 and 714)**  
Large Soft Case  
See page 70

**80PK-24 (714)**  
SureGrip Air  
Temperature Probe  
See page 68

**C101 (724)**  
Meter Hard Case  
See page 70

**80PK-3A (714, 724)**  
Surface Probe  
See page 68

**ToolPak**  
Meter Hanging Kit  
See page 71

For more information and detailed specifications, go to [www.fluke.com/tempcal](http://www.fluke.com/tempcal)

## Included accessories

Each 71X calibrator includes:  
Protective yellow holster with test lead storage, test leads and alligator clips (excluding model 714), single 9 V alkaline battery and instruction sheet (14 languages).

**Fluke 724:** TL75 Test Leads, AC72 Test Clips, one pair of stackable test leads, product overview manual (print) and users manual in 14 languages on CD-ROM.

## Ordering information

Fluke-712 RTD Calibrator  
Fluke-714 Thermocouple Calibrator  
Fluke-724 Temperature Calibrator

# Fluke 718 and 717 Pressure Calibrators

Compact, professional, pressure calibration tools

FLUKE®



New



## Fluke 718 Pressure Calibrators

**New!** 1 psi and 300 psi models in addition to the 30 and 100 psi models previously available

- Compact size, lightweight
- New built-in pressure switch test feature
- Built-in pressure/vacuum hand pump, with vernier and bleed valve
- Pressure and vacuum measurement to 0.05 % of full span, using an internal pressure sensor (dry air only)
- Pressure measurement to 10,000 psi/700 bar using any of 29 Fluke 700Pxx Pressure Modules
- Measure mA with 0.015 % accuracy and 0.001 mA resolution, while providing 24 volt loop power supply
- 1/8 inch NPT female pressure fitting
- Min/Max/Hold functions

**Intrinsically safe 718 version available** (see page 45)

## Fluke 717 Pressure Calibrators

Now with 9 ranges: 1, 30, 100, 300, 500, 1000, 1500, 3000 and 5000 psi

- Measure pressure and vacuum to 0.05 % of full scale with internal 30 or 100 psig sensor
  - 1/8 NPT pressure fitting
  - Compatible with non-corrosive gasses and liquids
- Measure pressure to 10,000 psi/69 mPa using one of 29 Fluke 700Pxx Pressure Modules
- Measure mA with 0.015 % accuracy and 0.001 mA resolution, while providing 24 V loop power
- New built-in pressure switch test feature
- Min/Max/Hold functions



## Specifications - 717 and 718 Calibrators

|                   | Range                                              | Resolution                                          | Comment                                           |
|-------------------|----------------------------------------------------|-----------------------------------------------------|---------------------------------------------------|
| 717-1             | +/- 1 psi, 27.5 in H <sub>2</sub> O, (-7 - +7 kPa) | +0.0001 psi, 0.0001 kPa, 0.0001 in H <sub>2</sub> O | Fluke-718 dry air only and includes on board pump |
| 718-1G            |                                                    |                                                     |                                                   |
| 717-30G           | -12 to + 30 psi, (-83 to 207 kPa)                  | 0.001 psi, 0.001 kPa, 0.001 in H <sub>2</sub> O     | Fluke-718 dry air only and includes on board pump |
| 718-30G           |                                                    |                                                     |                                                   |
| 717-100G          | -12 to + 100 psi, (-83 to 690 kPa)                 | 0.01 psi, 0.01 kPa, 0.01 in H <sub>2</sub> O        | Fluke-718 dry air only and includes on board pump |
| 718-100G          |                                                    |                                                     |                                                   |
| 717-300G          | -12 to +300 psi, (-83 to +2070 kPa)                | 0.01 psi, 0.01 kPa, 0.01 in H <sub>2</sub> O        | Fluke-718 dry air only and includes on board pump |
| 718-300G          |                                                    |                                                     |                                                   |
| 717-500G          | 0-500 psi, 0-3450 kPa                              | 0.01 psi, 0.1 kPa                                   | Compatible with non-corrosive gases and fluids    |
| 717-1000G         | 0-1000 psi, 0-6900 kPa                             | 0.01 psi, 0.1 kPa                                   | Compatible with non-corrosive gases and fluids    |
| 717-1500G         | 0-1500 psi, 0-10342 kPa                            | 0.1 psi, 1 kPa                                      | Compatible with non-corrosive gases and fluids    |
| 717-3000G         | 0-3000 psi, 0-20700 kPa                            | 0.1 psi, 1 kPa                                      | Compatible with non-corrosive gases and fluids    |
| 717-5000G         | 0-5000 psi, 0-34500 kPa                            | 0.1 psi, 1 kPa                                      | Compatible with non-corrosive gases and fluids    |
| Pressure accuracy | 0.05 % of range                                    |                                                     |                                                   |
| mA measurement    | 0-24 mA range                                      | 0.001 mA resolution                                 | Accuracy: ± 0.015 % + 1 count                     |
| Loop power        | 24 V dc                                            |                                                     | Accuracy: ± 10 %                                  |

## Recommended accessories - 717 and 718 Calibrators



**700ILF**  
In-Line Filter  
See page 69



**700LTP**  
Low Pressure  
Test Pump  
See page 69



**TL220**  
SureGrip Industrial  
Test Lead Set  
See page 61



**C25 (717 only)**  
Large Soft Case  
See page 70




**700HTP**  
Hydraulic Test Pump  
See page 69

For more information and detailed specifications, go to [www.fluke.com/pressure](http://www.fluke.com/pressure)

Application note, literature code 2577485:

## Pressure calibration with the Fluke 718

New design protects on-board pump from fluid damage. This application note explains how to drain pressure lines safely before calibration, and how to clean the pressure pump on the new Fluke 718.



Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)



Fluke Process Calibrators in this catalog displaying the Pressure Enabled symbol display readings from the 700 Series Pressure Modules.

## Fluke 700 Series Pressure Modules

- 29 pressure modules
- 8 intrinsically safe pressure modules\*
- Ranges from 1.000 in H<sub>2</sub>O (0.2491 kPa) to 10,000 psi (68.948 MPa)
- Gage, differential, dual (compound), absolute, and vacuum modules
- Rugged cases protect the modules from harsh environments
- Full-accuracy performance from 0 °C to 50 °C
- Pressure readings update twice per second, and may be displayed in up to 11 different units
- One-year warranty

\*for use with 718Ex and 725Ex only (see page 45 for more information)

## Included accessories

**Fluke 718 and 717:** Protective yellow holster, test leads and alligator clips, single 9 V alkaline battery (two 9 V batteries in 718) and instructions.

## Ordering information

Fluke-718 30US Pressure Calibrator  
Fluke-718 100US Pressure Calibrator  
Fluke-718 1G Pressure Calibrator  
Fluke-718 300G Pressure Calibrator  
Fluke-717 30G Pressure Calibrator  
Fluke-717 100G Pressure Calibrator  
Fluke-717 1G Pressure Calibrator  
Fluke-717 300G Pressure Calibrator  
Fluke-717 500G Pressure Calibrator  
Fluke-717 1000G Pressure Calibrator  
Fluke-717 1500G Pressure Calibrator  
Fluke-717 3000G Pressure Calibrator  
Fluke-717 5000G Pressure Calibrator

# Fluke 715, 707 and 705 Loop Calibrators

FLUKE®

## Complete family of volt/mA calibrators



### Fluke 707 and 705

Two powerful models to choose from

- Innovative output adjustment dial on 707 provides 1  $\mu$ A and 100  $\mu$ A resolution and **one-hand operation**
- Large display and simple interface for ease of use
- Simultaneous mA and % readout for quick, easy interpretation of readings
- mA accuracy of 0.015 % on the Fluke 707 and 0.02 % on the 705
- HART™ mode on 707 connects 250 ohm resistor in series with 24 V loop for compatibility with HART communicators
- Push button 25 % steps for fast, easy linearity checks
- "Span Check" for fast confirmation of zero and span
- Selectable slow and fast linear step ramp provide ramping outputs for valve slewing, remote testing and loop functional tests
- 24 V internal loop supply, so you can power and read a transmitter at the same time without carrying a DMM
- 0 mA to 20 mA or 4 mA to 20 mA default start up modes

**Intrinsically safe 707 version available** (see page 45)

Application note, literature code 1989137:

### Troubleshooting process loops

In process systems, problems with the loop can bring things to a screeching halt. In this application note, find out how to use Fluke test tools to identify current loop problems such as noise, ripple and drift.



### Fluke 715 Volt/mA Calibrator

- Source voltage to 200 mV or 20 V
- Measure loop current (0 to 20 mA, 4 to 20 mA) signals with 0.01 % accuracy and 1  $\mu$ A resolution
- Measure voltage output process signals from PLCs, transmitters
- Source or simulate 24 mA loop current
- 24 V loop supply with simultaneous current measurement
- Ramp and Step Ramp output functions



## Specifications – 715, 707 and 705

| Functions                     | Fluke 705 and 707                                                                 | Fluke 715                  |
|-------------------------------|-----------------------------------------------------------------------------------|----------------------------|
| <b>Voltage measurement</b>    |                                                                                   |                            |
| Range                         | 0 to 28 V                                                                         | 0 to 200 mV    0 to 25 V   |
| Resolution                    | 1 mV                                                                              | 10 $\mu$ V    1 mV         |
| Accuracy                      | 705: 0.025 % Rdg + 1 LSD 707, 707Ex: 0.015 % Rdg + 2 LSD                          | 0.01 % Rdg + 2 LSD         |
| <b>Current measurement</b>    |                                                                                   |                            |
| Range                         | 0 to 24 mA                                                                        | 0 to 24 mA                 |
| Resolution                    | 0.001 mA                                                                          | 0.001 mA                   |
| Accuracy                      | 705: 0.02 % Rdg + 2 LSD 707, 707Ex: 0.015 % Rdg + 2 LSD                           | 0.01 % + 2 LSD             |
| <b>Current sourcing</b>       |                                                                                   |                            |
| Range                         | 0 to 20 mA or 4 to 20 mA                                                          | 0 to 20 mA or 4 to 20 mA   |
| Accuracy                      | 705: 0.025 % Rdg + 2 LSD 707, 707Ex: 0.015 % Rdg + 2 LSD                          | 0.01 % Rdg + 2 LSD         |
| Drive capability              | 705: 1000 $\Omega$ @ 24 mA 707: 1200 $\Omega$ @ 24 mA 707Ex: 700 $\Omega$ @ 20 mA | 1000 $\Omega$ @ 24 mA      |
| Loop power while measuring mA | 24 V                                                                              | 24 V                       |
| <b>Voltage sourcing</b>       |                                                                                   |                            |
| Display current and % of span | Yes                                                                               | mA or %                    |
| Auto step, auto ramp          | Yes                                                                               | Yes                        |
| Span Check                    | Yes                                                                               | Yes                        |
| Battery life                  | 18 hours typical, at 12 mA                                                        | 18 hours typical, at 12 mA |

Will over-range to 24 mA

## Recommended accessories – 715, 707, 707Ex and 705 Calibrators



**TL28A**  
Heavy Duty  
Test Lead Set  
See page 62



**TL220**  
SureGrip Industrial  
Test Lead Set  
See page 61



**C25**  
Large Soft Case  
See page 70



**C550**  
Tool Bag  
See page 70



**PV350**  
Pressure Vacuum  
Module  
See page 65

### Included accessories

**Fluke 715:** Protective yellow holster, test leads and alligator clips, single 9 V alkaline battery and instruction sheet (14 languages).

**Fluke 705, 707 and 707Ex:** Protective holster, TL75 Test Leads, AC72 Test Clips and instruction sheet (14 languages).

### Ordering information

Fluke-715 Volt/mA Calibrator  
Fluke-707 Loop Calibrator  
Fluke-707Ex IS Loop Calibrator  
Fluke-705 Loop Calibrator

For more information and detailed specifications, go to [www.fluke.com/loop](http://www.fluke.com/loop)

Process Calibration Tools



HVAC/IAQ



Process

# Fluke 789 and 787 ProcessMeter™ Test Tools

FLUKE®

**Safety rated multimeters with mA source**

**True-rms**



## Fluke 789 ProcessMeter

With the Fluke 789 ProcessMeter, process technicians can do a lot more while carrying a lot less.

### Key Fluke 789 features:

- 24 V loop power supply
- HART mode setting with loop power (adds 250 ohm resistor)
- Double-sized, dual display
- 20 mA drive into 1200 ohms
- Backlight with two brightness settings
- 0 to 100 % mA Span Check buttons to toggle between 4 mA and 20 mA
- Infrared I/O serial port compatible with FlukeView® Forms Software
- Improved battery power with four AA batteries
- Plus all the proven 787 features

## Fluke 787 ProcessMeter

- Simultaneous mA and % of scale readout on mA output
- 25 % Manual Step plus Auto Step and Auto Ramp on mA output
- Min/Max/Average/Hold/Relative modes
- Externally accessible battery for easy changes



(Fluke 789 only)



## Specifications – 789 and 787 ProcessMeter

| Measurement function                                                   | Best accuracy range and resolution                                                                         | (% of reading + LSD)                                                                    |                      |
|------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|----------------------|
| V dc                                                                   | 400.0 mV, 4.000 V, 40.00 V, 400.0 V, 1000 V                                                                | 0.1 % + 1                                                                               |                      |
| V dc (true-rms)                                                        | 400.0 mV, 4.000 V, 40.00 V, 400.0 V, 1000 V                                                                | 0.7 % + 2                                                                               |                      |
| mA dc                                                                  | 30.000 mA                                                                                                  | .05 % + 2                                                                               |                      |
| A dc                                                                   | 1.000 A (0.440 A continuous)                                                                               | 0.2 % + 2                                                                               |                      |
| A ac                                                                   | 1.000 A (0.440 A continuous)                                                                               | 1 % + 2                                                                                 |                      |
| Resistance                                                             | 400.0 Ω, 4.000 k, 40.00 k, 400.0 k, 4.0 M, 40 M                                                            | 0.2 % + 1                                                                               |                      |
| Frequency (0.5 Hz to 20 kHz)                                           | 199.99 Hz, 1999.9 Hz, 19.999 kHz                                                                           | .005 % + 1                                                                              |                      |
| Diode Test                                                             | 789: 2.000 V (shows diode voltage drop) 787: 2.400 V (shows diode voltage drop)                            | 2 % + 1 2 % + 1                                                                         |                      |
| Continuity                                                             | Beeps for resistance < approx. 100 ohms                                                                    |                                                                                         |                      |
| Output function                                                        | Range and resolution                                                                                       | Drive capability                                                                        | Accuracy (% of span) |
| DC current output (Internal battery operation)                         | 0.000 mA to 20.000 mA or 4.000 mA to 20.000 mA (selectable at power-up) Over-range to 24.000 mA            | 789: 24 V compliance or, 1,200 Ohms, @ 20 mA 787: 12 V compliance or, 500 Ohms, @ 20 mA | .05 %                |
| DC current simulate (Ext. 24 Volt loop supply, up to 48 V on 789 only) | 0.000 mA to 20.000 mA or 4.000 mA to 20.000 mA, (selectable at power-up) Over-range to 24.000 mA           | 1000 Ohms, @ 20 mA                                                                      | .05 %                |
| 24 V loop supply                                                       | 789: Minimum 24 V 787: not available                                                                       | 250 Ohms @ 20 mA                                                                        | > 24 V               |
| Current adjustment modes                                               | Manual: Coarse, Fine, 25 % and 100 % step (100 % step 789 only) Automatic: slow ramp, fast ramp, 25 % step |                                                                                         |                      |

Temperature range of 18 °C to 28 °C, for one year after calibration

**Maximum voltage applied between any jack and earth ground:** 1000 V rms **Storage temperature:** -40 °C to 60 °C  
**Operating temperature:** -20 °C to 55 °C **Relative humidity:** 95 % up to 30 °C; 75 % up to 40 °C; 45 % up to 50 °C; 35 % up to 55 °C  
**Safety:** Designed in accordance with EN61010, ANSI/ISA S82.01-1994 and CAN/CSA C22.2 No. 1010.1-92 Over-voltage CAT III  
**Size (HxWxD)/weight (787 with holster):** 52 mm x 98 mm x 201 mm (2.06 in x 3.86 in x 7.93 in)/638 g (1.4 lb)  
**Size (HxWxD)/weight (789):** 50 mm x 100 mm x 203 mm (1.97 in x 3.94 in x 8.00 in)/600 g (1.3 lb)

## Recommended accessories – 787 and 789 ProcessMeter



**TL220**  
SureGrip Industrial  
Test Lead Set  
See page 61



**ToolPak**  
Meter Hanging Kit  
See page 71



**80T-150U**  
Universal  
Temperature Probe  
See page 69



**C125**  
Meter Case  
See page 70



**PV350**  
Pressure Vacuum Module  
See page 65

For more information and detailed specifications, go to [www.fluke.com/processmeters](http://www.fluke.com/processmeters)

Application note, literature code 2041342:

## In-field valve positioner checks

Valve positioners open and close with a 4 to 20 mA signal applied. This application note explains how to adjust these valves so they open and close correctly.

Want to read more? Download this and other application notes

at [www.fluke.com/library](http://www.fluke.com/library)



**True-rms**



## Included accessories

**Fluke-789 ProcessMeter:** TL71 Premium Safety-Designed Test Lead Set plus alligator clips, 4 AA alkaline batteries (installed), product overview and users manual (CD-ROM) in 14 languages.

**Fluke-787 ProcessMeter:** Protective yellow holster with test lead storage, TL75 Safety-Designed Test Lead Set plus alligator clips, one 9 V alkaline battery (installed), product overview and users manual (CD-ROM) in 14 languages.

## Ordering information

Fluke-789 ProcessMeter  
Fluke-787 ProcessMeter



Electrical



HVAC/IAQ



Process

# Fluke 771 Milliamp Process Clamp Meter

**Save time and money troubleshooting process control loops**

**New**



The innovative new Fluke 771 mA Process Clamp Meter is designed to measure, test, and troubleshoot 4–20 mA control signals without breaking the mA loop. Make mA measurements in active control systems without disrupting process control.

## Features:

- Best in class 0.2 % accuracy
- Resolution and sensitivity to 0.01 mA
- Hold function captures and displays changing measurements
- Dual display with both mA measurement and 0 % to 100 % of 4 mA to 20 mA span
- Measurement spotlight illumination hard to see wires in dark enclosures
- Detachable clamp with extension cable for measurements in tight locations
- Includes carrying case that can be used as a belt mounted holster

## Key uses:

- Measure mA signals for PLC and control system analog I/O
- Measure 4 mA to 20 mA output signals from transmitters
- Measure 10 mA to 50 mA signals in older control systems using the 99.9 mA range



| Range                                        | Resolution | Accuracy                    | Features                                     | Notes                                                        |
|----------------------------------------------|------------|-----------------------------|----------------------------------------------|--------------------------------------------------------------|
| -20.99 mA to +20.99 mA                       | 0.01 mA    | 0.2 % or reading + 5 counts | Zero, Hold, backlight, measurement spotlight | Use for measuring and troubleshooting 4 mA to 20 mA signals  |
| -21.0 mA to -99.9 mA<br>+21.0 mA to +99.9 mA | 0.1 mA     | 1 % reading + 5 counts      | Zero, Hold, backlight, measurement spotlight | Use for measuring and troubleshooting 10 mA to 50 mA signals |

For more information and detailed specifications, go to [www.fluke.com/processmeters](http://www.fluke.com/processmeters)

## 9102S and 9100S Handheld Drywell Temperature Calibrators

Fluke Corporation, Hart Scientific Division



### The smallest, lightest and most portable dry-wells in the world

- 9100 model weighs only 2 pounds, 3 ounces (1 kilogram)
- Temperature ranges from -10 °C to 375 °C
- Stability during calibrations to  $\pm 0.05$  °C
- Fast and easy calibrations of RTDs and thermocouples
- Includes RS-232 interface, instrument control software
- Direct interface to the Fluke 744

|                            | 9100S                                                                                   | 9102S                                                         |
|----------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------------|
| Range                      | 35 °C to 375 °C (95 °F to 707 °F)                                                       | -10 °C to 122 °C (14 °F to 252 °F) at 23 °C ambient           |
| Accuracy                   | $\pm 0.5$ °C                                                                            | $\pm 0.25$ °C                                                 |
| Stability                  | $\pm 0.1$ °C at 100 °C $\pm 0.3$ °C at 375 °C                                           | $\pm 0.05$ °C at 0 °C                                         |
| Well-to-well uniformity    | $\pm 0.2$ °C with sensors of similar size at equal depths within wells                  |                                                               |
| Stabilization              | 5 minutes                                                                               | 7 minutes                                                     |
| Well depth                 | 102 mm (4 in); 1.6 mm (1/16 in) hole is 89 mm (3.5 in) deep                             | 102 mm (4 in)                                                 |
| Removable inserts          | N/A                                                                                     | 1/4 in, 3/16 in (Standard) 1/16 in, 1/8 in, 3/8 in (optional) |
| Power                      | 115 V ac ( $\pm 10$ %), 1.5 A or 230 V ac ( $\pm 10$ %, 0.8 A, specify, 50/60 Hz, 175 W | 94 V ac to 234 V ac ( $\pm 10$ %), 50/60 Hz, 60 W; or 12 V dc |
| Size (H x W x D)           | 57 mm x 125 mm x 150 mm (2.25 in x 4.9 in x 5.9 in)                                     | 99 mm x 140 mm x 175 mm (3.9 in x 5.5 in x 6.9 in)            |
| Weight                     | 1 kg (2 lb, 3 oz)                                                                       | 1.8 kg (4 lb)                                                 |
| NIST-traceable calibration | Data at 50 °C, 150 °C, 200 °C, 250 °C, 300 °C and 350 °C                                | Data at -10 °C, 24 °C, 50 °C, 55 °C, 100 °C and 122 °C        |



Detachable clamp used to measure 4 mA to 20 mA signals on transmitters without breaking the loop.

## Fluke 771 included accessories

Carrying case, and instruction manual.

## Ordering information

Fluke-771 Milliamp Process Clamp Meter

## 9102S and 9100S ordering information

|             |                                                   |
|-------------|---------------------------------------------------|
| 9100S-A-156 | Dry-Well, Block A <sup>(1)</sup>                  |
| 9100S-A-256 | Dry-Well, Block A <sup>(2)</sup>                  |
| 9100S-B-156 | Dry-Well, Block B <sup>(1)</sup>                  |
| 9100S-B-256 | Dry-Well, Block B <sup>(2)</sup>                  |
| 9100S-D-156 | Dry-Well, Block D <sup>(1)</sup>                  |
| 9100S-D-256 | Dry-Well, Block D <sup>(2)</sup>                  |
| 9300        | Rugged Carrying Case, 9100                        |
| 9102S-156   | Dry-Well, -10 to 122 (2 Wells) <sup>(1) (3)</sup> |
| 9102S-256   | Dry-Well, -10 to 122 (2 Wells) <sup>(2) (3)</sup> |
| 9320-156    | Battery Pack, 9102 <sup>(1)</sup>                 |
| 9320-256    | Battery Pack, 9102 <sup>(2)</sup>                 |

## 9102S and 9009 inserts

|        |                                         |
|--------|-----------------------------------------|
| 3102-1 | Insert, AL 1/16 in (1.6 mm)             |
| 3102-2 | Insert, AL 1/8 in (3.2 mm)              |
| 3102-3 | Insert, AL 3/16 in (4.8 mm)             |
| 3102-4 | Insert, AL 1/4 in (6.4 mm) (Standard)   |
| 3102-6 | Insert, AL 3/8 in (9.5 mm) (Standard)   |
| 3102-7 | Insert, AL 7/16 in (11.1 mm) (Standard) |
| 3102-8 | Insert, AL 5/32 in (4 mm) (Standard)    |
| 9308   | Hard Carrying Case, 9102/9132           |

<sup>(1)</sup> 156 Blocks are 115 V 50/60 Hz

<sup>(2)</sup> 256 Blocks are 220 V 50/60 Hz

<sup>(3)</sup> Specify two 3102 inserts

# Intrinsically Safe Products

FLUKE®

**Calibrators, thermometers and multimeters designed to intrinsic safety standards**

## What is "Intrinsically Safe"?

Intrinsic safety is a protection method employed in potentially explosive atmospheres. Devices that are certified as "intrinsically safe" are designed to be unable to release sufficient energy, by either thermal or electrical means, to cause ignition of flammable material (gas or dust/particulates).

There are no global intrinsically safe standards or certifications, but there are organizations that influence directives in certain world geographies.



### Factory Mutual

In The United States, Factory Mutual Research, managed by Factory Mutual (FM) Global, is a not-for-profit scientific and testing organization that has tested and certified over 40,000 products in the last 165 years. FM Research has set certification guidelines for equipment used in potentially explosive atmospheres.



### Canadian Standards Association (CSA)

Accreditation body for North American regulations based in Toronto, Canada.



### ATEX

The primary intrinsically safe standard which has been set in the European Union with the Directive 94/9/EC, commonly called ATEX ("Atmosphères Explosibles,") French for explosive atmospheres.

For more information and detailed specifications, turn to the corresponding non-intrinsically safe product pages (Fluke 707, 718, 725, 574, 68) or go to [www.fluke.com/ex](http://www.fluke.com/ex)

| Fluke products                                                                                                                         | ATEX certified                                                                                               | North American Certification                                                                                                                                                  | For additional product detail |
|----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
|  87V Ex: Intrinsically Safe True-rms Multimeter     |  II 2 G EEx ia IIC T4     |                                                                                                                                                                               | See page 14                   |
|  707Ex: Intrinsically Safe mA Calibrator            |  II 2 G EEx ia IIC T4     | <br>APPROVED<br>N.I. Class I, Div 2,<br>Groups A-D T4                                      | See page 42                   |
|  718Ex: Intrinsically Safe Pressure Calibrator      |  II 1 G EEx ia IIC T4     | <br>LR 110400<br>I.S. Class I, Div 1,<br>Groups A-D T4                                     | See page 41                   |
|  725Ex: Intrinsically Safe Multifunction Calibrator |  II 1 G EEx ia IIB 171 °C | <br>LR 110400<br>I.S. Class I, Div 1,<br>Groups B-D, 171 °C                                | See page 39                   |
|  700PEX: Intrinsically Safe Pressure Modules        |  II 1 G EEx ia IIC T4     | <br>221859<br>I.S. Class I, Div 1,<br>Groups A-D T4                                        | See page 41                   |
|  Fluke 574-NI Noninvasive Infrared Thermometer      |                                                                                                              | <br>APPROVED<br>Class I, Division 2,<br>Groups A, B, C, D;<br>Class I, Zone 2 IIC          | See page 51                   |
|  Fluke 68IS Intrinsically Safe Infrared Thermometer |                                                                                                              | <br>APPROVED<br>Class I, Division 1,<br>Groups A, B, C, D<br>Class I, Zone 0 AEx<br>ia IIC | See page 53                   |

For more information and detailed specifications, turn to the corresponding non-intrinsically safe product pages (Fluke 87V, 707, 718, 725, 574, 68) or go to [www.fluke.com/ex](http://www.fluke.com/ex).

Application note, literature code 2096400:

## Making sense of intrinsic safety and intrinsically safe tools

Want to know what industries Intrinsically Safe products are designed for? Want to know why intrinsic safety is so important? Want to make sense of the product ratings and classifications?



Go to [www.fluke.com/ex](http://www.fluke.com/ex)

## Fluke 68IS Intrinsically Safe Infrared Thermometer

- Laser guided sighting system for easy targeting with 1 % accuracy
- 12-point data logging
- Advanced optics to measure smaller targets at greater distances
- Adjustable emissivity for more accurate temperature measurements
- Selectable MAX, MIN, DIF and AVG functions that display values instantly with Hi/Lo Alarm
- Expanded measurement range up to 760 °C (1400 °F)
- RTD probe accessory included for dual contact and non-contact temperature measurements
- Class I, Division 1, Groups A, B, C, D Class I, Zone 0, AEx ia IIC, T4 at 50 °C when used with 9 V alkaline battery



Not available for purchase in Europe.

## Ordering information

|              |                                                                                                      |
|--------------|------------------------------------------------------------------------------------------------------|
| Fluke-87V Ex | IS True-rms Multimeter                                                                               |
| Fluke-707Ex  | IS Loop Calibrator                                                                                   |
| Fluke-718Ex  | IS Pressure Calibrator                                                                               |
| Fluke-725Ex  | IS Multifunction Process Calibrator                                                                  |
| Fluke-700PEX | Pressure Modules (700P01Ex, 700P05Ex, 700P06Ex, 700P09Ex, 700P24Ex, 700P27Ex, 700P29Ex and 700PA4Ex) |
| Fluke-574-NI | Precision Infrared Thermometer w/ Logging SW                                                         |
| Fluke-68IS   | Noninvasive Infrared Thermometer Intrinsically Safe                                                  |

Intrinsically Safe Products



# Ti40 and Ti50 Series IR FlexCam® Thermal Imagers

**The thermal imagers for professionals demanding the best**



Fluke Ti40, Ti45, Ti50, Ti55



Fluke Ti40FT, Ti45FT, Ti50FT, Ti55FT

**New**

## FIND problems faster with Fluke thermal imagers.

Reduce costs and maximize uptime with our complete range of imaging solutions. They combine the largest, sharpest images in the industry with innovative, easy-to-use features. Fluke Ti40 and Ti50 Series reveal more with IR Fusion® Technology—merging infrared and visible light images in one display. Fluke puts powerful technology within your reach.

Application note, literature code 2764017:

## Thermography at Ford's Dearborn Stamping Plant

The Dearborn Stamping Plant has had thermal cameras on site in the past, but has not met the objectives of a successful thermography program. Today, DSP's thermography program is a model for the rest of Ford, and the program came on line in a matter of weeks.

Want to read more? Download this and other application notes at [www.fluke.com/library](http://www.fluke.com/library)




## Features – Ti40 and Ti50 Series Imagers

| Features                                                                                       | Ti40                                | Ti45     | Ti50     | Ti55     |
|------------------------------------------------------------------------------------------------|-------------------------------------|----------|----------|----------|
| 180° articulating flexible lens to view images in every situation                              | •                                   | •        | •        | •        |
| Choice of 3 interchangeable lenses to cover every application                                  | •                                   | •        | •        | •        |
| Large 5" high contrast color LCD for a clear picture independent of lighting conditions        | •                                   | •        | •        | •        |
| Fully radiometric for detailed temperature analysis and tracking                               | •                                   | •        | •        | •        |
| SmartFocus for best image quality and accurate temperature measurements                        | •                                   | •        | •        | •        |
| Windows® CE based menu structure for ease of use                                               | •                                   | •        | •        | •        |
| Personalized instrument set-up for multiple use                                                | •                                   | •        | •        | •        |
| CompactFlash memory cards to store over 1000 IR images plus fully radiometric temperature data | •                                   | •        | •        | •        |
| SmartView reporting and analysis software included                                             | •                                   | •        | •        | •        |
| AutoCapture for making intermittent problems visible                                           | •                                   | •        | •        | •        |
| On-board analysis functions                                                                    | •                                   | •        | •        | •        |
| User defined text annotations for simplified reporting                                         | •                                   | •        | •        | •        |
| Built-in visible light (digital) camera                                                        | FT model                            | FT model | FT model | FT model |
| IR-Fusion blending thermal and visible light images to easily pinpoint suspect components      | FT model<br>Picture-in-picture only | FT model | FT model | FT model |
| IR/Visible Alarm                                                                               |                                     | FT model | FT model | FT model |
| Laser pointer for easy targeting                                                               | FT model                            | FT model | FT model | FT model |
| Flash and torch light for high quality images in dark environments                             | FT model                            | FT model | FT model | FT model |




## IR-Fusion™ Technology

IR-Fusion technology simultaneously captures pixel-for-pixel infrared and visible light images and allows full image optimization with 5 different on-camera as well as software viewing modes. With the integrated laser pointer visible on the images, precise and accurate (faulty) component identification is very easy.



Full IR

Picture-in-Picture



Alpha Blending

IR/Visible Alarm



Full Visible Light



## Complete package

The IR FlexCam thermal imagers are delivered as a complete package.



To find the best thermal imaging solution for your application go to our Thermal Imaging Web Selection Guide at [www.fluke.com/thermal\\_imaging](http://www.fluke.com/thermal_imaging)

# Ti40 and Ti50 Series IR FlexCam® Thermal Imagers

FLUKE®

The thermal imagers for professionals demanding the best

## Specifications – Ti40 and Ti50 Series

|                                                                 | Fluke<br>Ti40                                                                                                                      | Fluke<br>Ti45    | Fluke<br>Ti50    | Fluke<br>Ti55    |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------------------|------------------|------------------|
| Thermal imaging performance                                     |                                                                                                                                    |                  |                  |                  |
| Field of view (FOV)*                                            | 23° horizontal x 17° vertical                                                                                                      |                  |                  |                  |
| Spatial resolution (IFOV)*                                      | 2.60 mrad                                                                                                                          |                  | 1.30 mrad        |                  |
| Min focus distance*                                             | 0.15 m                                                                                                                             |                  |                  |                  |
| Thermal sensitivity (NETD) at 30 °C                             | ≤0.09 °C                                                                                                                           | ≤0.08 °C         | ≤0.07 °C         | ≤0.05 °C         |
| Detector data acquisition/image frequency                       | 30 Hz/30 Hz                                                                                                                        |                  | 60 Hz/60 Hz      |                  |
| Focus                                                           | SmartFocus; single finger continuous focus                                                                                         |                  |                  |                  |
| IR digital zoom                                                 | 2x                                                                                                                                 |                  | 2x               | 2x, 4x, 8x       |
| Detector size                                                   | 160 x 120                                                                                                                          |                  | 320 x 240        |                  |
| Detector type                                                   | Focal Plane Array, Vanadium Oxide (VOx) Uncooled Microbolometer                                                                    |                  |                  |                  |
| Spectral band                                                   | 8 µm to 14 µm                                                                                                                      |                  |                  |                  |
| Visual Imaging performance (Fusion models only)                 |                                                                                                                                    |                  |                  |                  |
| On-camera operating modes                                       |                                                                                                                                    |                  |                  |                  |
| Picture-in-Picture                                              | •                                                                                                                                  | •                | •                | •                |
| Full thermal, full visual light or merged thermal-visual images | Smartview only                                                                                                                     | •                | •                | •                |
| Visible light camera                                            | 1280 x 1024 pixels, full color (1.3 megapixels)                                                                                    |                  |                  |                  |
| Visible light digital zoom                                      |                                                                                                                                    | 2x               | 2x               | 2x, 4x           |
| Visible color alarm above and below                             |                                                                                                                                    | •                | •                | •                |
| Temperature measurement                                         |                                                                                                                                    |                  |                  |                  |
| Calibrated temperature range                                    | -20 °C to 350 °C                                                                                                                   | -20 °C to 600 °C | -20 °C to 350 °C | -20 °C to 600 °C |
| 1200 °C High temperature option                                 |                                                                                                                                    | •                |                  |                  |
| Accuracy                                                        | ± 2 °C or 2 % (whichever is greater)                                                                                               |                  |                  |                  |
| Measurement modes                                               |                                                                                                                                    |                  |                  |                  |
| Centerpoint, center box (area min/max, average)                 | •                                                                                                                                  | •                | •                | •                |
| Moveable spots/boxes                                            |                                                                                                                                    | •                |                  | •                |
| Isotherms, automatic hot and cold point detection               |                                                                                                                                    | •                |                  | •                |
| Emissivity correction                                           | 0.1 to 1.0 (0.01 increments)                                                                                                       |                  |                  |                  |
| Image presentation                                              |                                                                                                                                    |                  |                  |                  |
| Digital display                                                 | 5" large high-resolution backlight LCD                                                                                             |                  |                  |                  |
| Video output                                                    | RS170 EIA/NTSC or CCIR/PAL composite video                                                                                         |                  |                  |                  |
| Palettes                                                        | Grayscale, grayscale inverted, blue red, high contrast, hot metal, ironbow, amber, amber inverted                                  |                  |                  |                  |
| Optional lenses                                                 |                                                                                                                                    |                  |                  |                  |
| 54 mm Telephoto lens                                            | High precision Germanium lens                                                                                                      |                  |                  |                  |
| Field of view (FOV)                                             | 9° horizontal x 6° vertical                                                                                                        |                  |                  |                  |
| Spatial resolution (IFOV)                                       | 0.94 mrad                                                                                                                          |                  | 0.47 mrad        |                  |
| Min focus distance                                              | 0.6 m                                                                                                                              |                  |                  |                  |
| 10.5 mm wide angle lens                                         | High precision Germanium lens                                                                                                      |                  |                  |                  |
| Field of view (FOV)                                             | 42° horizontal x 32° vertical                                                                                                      |                  |                  |                  |
| Spatial resolution (IFOV)                                       | 4.9 mrad                                                                                                                           |                  | 2.45 mrad        |                  |
| Min focus distance                                              | 0.3 m                                                                                                                              |                  |                  |                  |
| Image and data storage                                          |                                                                                                                                    |                  |                  |                  |
| Storage medium                                                  | Compact flash card (512Mb) stores over 1000 IR images                                                                              |                  |                  |                  |
| File formats supported                                          | 14 bit measurement data included.<br>Images: bmp, gif, jpg, png, tiff;<br>Data formats: comma separated (csv), tab separated (txt) |                  |                  |                  |
| Interfaces and software                                         |                                                                                                                                    |                  |                  |                  |
| Interface                                                       | Compact flash card reader included                                                                                                 |                  |                  |                  |
| Included software                                               | SmartView; Full analysis and reporting software                                                                                    |                  |                  |                  |
| Laser (IR-Fusion models only)                                   |                                                                                                                                    |                  |                  |                  |
| Classification                                                  | Class II                                                                                                                           |                  |                  |                  |
| Laser targeting                                                 | Laser dot visible on blended and visual image                                                                                      |                  |                  |                  |
| Controls and adjustments                                        |                                                                                                                                    |                  |                  |                  |
| Set-up controls                                                 | Date/time, °C/°F, language, scale, LCD intensity                                                                                   |                  |                  |                  |
| Image controls                                                  | Level, span, auto adjust (continuous/manual)                                                                                       |                  |                  |                  |
| On-screen indicators                                            | Battery status, emissivity, background temperature and real time clock                                                             |                  |                  |                  |

**Battery life:** 3 hours continuous operation (2 hours on FT models)

**Water and dust resistant:** IP54

**Size (HxWxD):** 162 mm x 262 mm x 101 mm (6.378 in x 10.315 in x 3.9764 in)

**Weight:** 1.85 kg (4.07 lb)

**Two-year warranty**

## Recommended accessories – Ti40 and Ti50 Series Imagers



**103232**  
Anti-glare Hood



**104543**  
Car Charger




**Ti-SBC**  
Battery Charger



**Ti-SBP**  
Rechargeable Battery Pack

## Fluke SmartView™ IR analysis and reporting software for Fluke IR cameras.

Included with each Fluke IR thermal imager, Fluke SmartView software is a modular suite of tools that annotates, views, edits and analyzes IR images. It also generates fully customizable and professional-looking reports in a few easy steps. The IR-Fusion technology is full supported. The software is easy to use for the technician, yet delivers the performance specialized thermographers require for advanced analysis.



## Included accessories

AC adapter (for Ti45 and Ti55 only), video cable, 512 MB compact flash card, compact flash card reader and USB cable, PCMCIA compact flash card adapter, SmartView reporting and analysis software on CD, 2 rechargeable battery packs, battery charger, neck strap, heavy duty carrying case and user manual on CD.

## Ordering information

|                 |                                          |
|-----------------|------------------------------------------|
| Fluke-Ti40-20   | IR FlexCam Thermal Imager                |
| Fluke-Ti40FT-20 | IR FlexCam Thermal Imager with IR-Fusion |
| Fluke-Ti45-20   | IR FlexCam Thermal Imager                |
| Fluke-Ti45FT-20 | IR FlexCam Thermal Imager with IR-Fusion |
| Fluke-Ti50-20   | IR FlexCam Thermal Imager                |
| Fluke-Ti50FT-20 | IR FlexCam Thermal Imager with IR-Fusion |
| Fluke-Ti55-20   | IR FlexCam Thermal Imager                |
| Fluke-Ti55FT-20 | IR FlexCam Thermal Imager with IR-Fusion |

\*For ordering information of optional lenses check the Fluke web.

# Fluke Ti20 Thermal Imager

Everything needed for everyday imaging

New



The Fluke Ti20 Thermal Imager is an unbeatable solution for predictive maintenance and troubleshooting.

- **Complete imaging solution.** The Ti20 Thermal Imager is packaged with all necessary accessories including unlimited-use InsideIR™ companion software and professional training materials.
- **Lowest cost of ownership.** An exceptional value for a high performance imager, the Ti20 also offers affordable instrument service and calibrations.
- **Designed for industrial use.** Rugged Fluke construction; IP54-rated for use in dust and moisture filled environments.
- **Fast and easy inspection routing.** Plan your equipment inspection route, load it once into the imager, and then follow the easy, on-camera instructions each time you perform inspections (simply point, focus and pull the trigger).

## Specifications – Ti20 Thermal Imager

| Detector                                    |                                                                                                              |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Detector type                               | 128 x 96 thermal element focal plane array (FPA) uncooled microbolometer                                     |
| NETD (thermal sensitivity)                  | ≤ 0.2 °C at 30 °C                                                                                            |
| Thermal                                     |                                                                                                              |
| Temperature range                           | -10 °C to 350 °C (14 °F to 662 °F)                                                                           |
| Accuracy                                    | ± 2 °C or 2 % (whichever is greater)                                                                         |
| Optical                                     |                                                                                                              |
| Field of View (FOV)                         | 20° horizontal by 15° vertical                                                                               |
| Optical resolution (D:S)                    | 75:1 or better                                                                                               |
| Target sighting                             | Single laser dot (Meets IEC Class 2 and FDA Class II requirements)                                           |
| Controls and adjustments                    |                                                                                                              |
| Focus                                       | Manual                                                                                                       |
| Minimum focus distance                      | 0.15 m (6 in)                                                                                                |
| Temperature scale                           | °C or °F selectable                                                                                          |
| Palettes                                    | Grayscale, reverse grayscale, rainbow, ironbow                                                               |
| Measurement modes                           | Auto and manual                                                                                              |
| LCD backlight                               | On/off selectable                                                                                            |
| Adjustable emissivity                       | 0.10 to 1.00 in 0.01 increments                                                                              |
| Adjustable reflected background temperature | -50 °C to 460 °C (-58 °F to 860 °F)                                                                          |
| Environmental                               |                                                                                                              |
| Ambient operating temperature               | 0 °C to 50 °C (32 °F to 122 °F)                                                                              |
| Relative humidity                           | 10 % to 95 % non-condensing                                                                                  |
| Storage temperature                         | -25 °C to 70 °C (-13 °F to 158 °F)                                                                           |
| Water and dust resistant                    | IP54                                                                                                         |
| Other                                       |                                                                                                              |
| Display                                     | Large color LCD                                                                                              |
| Storage capacity                            | 50 images stored internally                                                                                  |
| Power                                       | Rechargeable battery pack or six AA batteries                                                                |
| Battery life                                | Three hours continuous use                                                                                   |
| Image frame rate                            | 30 Hz*, 9 Hz                                                                                                 |
| Thermal analysis software                   | InsideIR™ (included) full-featured analysis and reporting software (unlimited use; no per user license fees) |
| Size (HxWxD)                                | 40.64 x 20.32 x 30.48 cm (16 in x 8 in x 12 in)                                                              |
| Weight                                      | 1.2 kg or (2.65 lbs)                                                                                         |
| Warranty                                    | One-year                                                                                                     |

\*Subject to U.S. export license compliance. Applicable outside the U.S. and Canada.

## Recommended accessories – Ti20 Thermal Imager



**Ti20-Visor**  
Sun Visor




**Ti30-TBP**  
Rechargeable Battery Pack



**Ti20-CC**  
Car Charger

For more information and detailed specifications, go to [www.fluke.com/thermal\\_imaging](http://www.fluke.com/thermal_imaging)

## Typical thermal imaging applications



### Electric motors and pumps

Hot spots may be an early indicator of motor winding problems. Elevated temperatures can damage winding insulation, resulting in operational inefficiencies and premature motor failure. An overheated motor may be an indication of an underrated motor in the application, insufficient cooling or electrical power problems.



### Bus bars and fuse boxes

Temperature differences between phases may indicate unbalanced loads, harmonics, component problems, bad connections or bad wiring. These conditions can result in increased energy cost and can damage cables or machines or possibly cause fire. Even small temperature differences between phases should be investigated to determine the root cause.



### Rotating machinery

Ball bearings showing an increased temperature are an indication that either the quality of the lubricant is deteriorating or there is poor alignment between the motor and shaft. These problems can cause the bearings to fail, or a motor or pump to overheat.

## Included accessories

Unlimited-use InsideIR PC software for data storage, analysis and reporting, ac/dc power adapter, USB communication cable, hard carrying case, soft-sided carrying case, wrist strap, two (2) rechargeable battery packs, one (1) AA battery carrier, training materials and getting started guide.

## Ordering information

|                  |                |
|------------------|----------------|
| Fluke-Ti20 US    | Thermal Imager |
|                  | North America  |
| Fluke-Ti20 INT   | Thermal Imager |
|                  | Ampac          |
| Fluke-Ti20 INT 9 | Thermal Imager |
|                  | Ampac 9 Hz     |

# Fluke Ti30™ Thermal Imager

FLUKE®

## Thermal imaging for the industrial technician



The affordable Fluke Ti30™ Thermal Imager is an unbeatable solution for predictive maintenance:

**Complete imaging solution** – The Ti30 Thermal Imager is packaged with all necessary accessories, unlimited-use InsideIR™ companion software, and two days of professional thermography training.\*

**Low cost of ownership** – An exceptional value for a high performance imager, the Ti30 also offers affordable instrument service and calibrations.

**Designed for industrial use** – Over five hours of continuous-use battery life and the capacity to store up to 100 images, allows for a full day of uninterrupted inspections.

**Fast and easy inspection routing** – Plan your equipment inspection route, load it once into the imager, and then follow the easy, on-camera instructions each time you perform inspections.

\*U.S. and Canada only. Training package varies by country. Does not include travel expenses.

### Understanding maintenance routing

Predictive maintenance (PdM) programs rely on periodic inspections of the critical assets comprising a plant or facility. These inspections range from visual inspections to nondestructive testing performed using a variety of technologies. To optimize a PdM program, one must develop a series of routes, determining the equipment to be inspected, the frequency of those inspections, and the sequence or physical course for each.

With the Fluke Ti30™ Thermal Imager, images taken on a planned inspection route can be combined with location names and temperature data and uploaded to the camera for use as a "routing guide." The user is prompted to go to each location on the route to take images during subsequent inspections—improving accuracy. New images can easily be compared to previous scans using InsideIR software (included), helping to identify potential problems before they cause failure.

To learn more about predictive maintenance with the Fluke Ti30™ Thermal Imager, go to [www.fluke.com/thermal\\_imaging](http://www.fluke.com/thermal_imaging)

## Specifications – Ti30™ Thermal Imager

| Detector                                 |                                                                    |
|------------------------------------------|--------------------------------------------------------------------|
| Detector type                            | 120 x160 thermal element uncooled focal plane array microbolometer |
| NETD (Noise equivalent temp. difference) | 200 mK                                                             |
| Thermal                                  |                                                                    |
| Temperature range                        | -10 °C to 250 °C (14 °F to 482 °F)                                 |
| Accuracy                                 | ±2 % or ±2 °C (± 3 % or 3 °C from -10 to 0 °C)                     |
| Optical                                  |                                                                    |
| Optical resolution                       | 90:1                                                               |
| Slit response optical resolution         | 225:1                                                              |
| Minimum diameter measurement spot        | 7 mm (0.27 in) at 61cm (24 in)                                     |
| Field of view (FOV)                      | 17 ° horizontal x 12.8 ° vertical                                  |
| Target sighting                          | Single laser dot (Meets IEC Class 2 & FDA Class II requirements)   |
| Controls and adjustments                 |                                                                    |
| Focus                                    | Focusable, 61cm (24 in) to infinity                                |
| Temperature scale                        | °C or °F selectable                                                |
| Palettes                                 | Gray, ironbow or rainbow                                           |
| Measurement modes                        | Automatic, semi-automatic or manual                                |
| LCD backlight                            | Bright, dim, off-selectable                                        |
| Adjustable emissivity                    | 0.10 to 1.00 by 0.01                                               |
| Reflected background temperature         | -50 °C to 460 °C (-58 °F to 860 °F)                                |
| Environmental                            |                                                                    |
| Ambient operating temperature            | -10 °C to 50 °C (14 °F to 122 °F)                                  |
| Relative humidity                        | 10 to 90 % non-condensing                                          |
| Storage temperature                      | -25 °C to 70 °C (-13 °F to 158 °F) [without batteries]             |
| Other                                    |                                                                    |
| Storage capacity                         | 100 images                                                         |
| Power                                    | Rechargeable battery pack or 6AAs (not included)                   |
| Battery life                             | Minimum 5 hours continuous use                                     |
| Image frame rate                         | 20 Hz*, 9 Hz                                                       |
| Thermal analysis software                | InsideIR (included)                                                |
| PC software operating systems            | Microsoft® Windows® 2000® or XP®                                   |
| Weight (includes batteries)              | 1 kg (2.2 lb)                                                      |
| Warranty                                 | 1 year (U.S. only)                                                 |

\*Subject to U.S. export license compliance. Applicable outside the U.S. and Canada.



Store infrared images in InsideIR software

### Included accessories

Unlimited-use InsideIR PC software for data storage, analysis and reporting, docking station with universal power adapter and USB connection, hardshell carrying case, USB field cable, rechargeable battery pack, sun visor, interactive CD, training presentation CD, carrying pouch, wrist strap, and quick reference card.

### Optional

NIST Calibration Certificate

### Ordering information

|                 |                                                   |
|-----------------|---------------------------------------------------|
| Fluke-Ti30 US   | Thermal Imager/<br>North America                  |
| Fluke-Ti30 EL   | Thermal Imager/<br>Latin America                  |
| Fluke-Ti30 EL/9 | Thermal Imager/<br>Latin America,<br>9 Hz Version |

To request a demonstration, call 1-800-44-Fluke (1+425-446-5500 outside the U.S.) or visit [www.fluke.com/demo](http://www.fluke.com/demo)

For more information and detailed specifications, go to [www.fluke.com/thermal\\_imaging](http://www.fluke.com/thermal_imaging)

# FlexCam™ TiR4, TiR3, and TiR2 IR Thermal Imagers

FLUKE®

**The expert's choice for building diagnostics**



Fluke TiR2, TiR3, TiR4



Fluke TiR2/FT, TiR3/FT, TiR4/FT

The new Fluke TiR2, TiR3 and TiR4 thermal imagers are for professionals demanding the best and most thorough solutions in building diagnostics applications. The Fluke TiR-Series provides the industry's largest LCD to view on-camera images, augmented with the innovative IR-Fusion™ technology to better pinpoint building problems. IR-Fusion is the overlay of IR and visible images, allowing one to clearly identify critical points within the thermal image.

- Industry leading thermal sensitivity ( $\leq 0.050^\circ\text{C}$  NETD on TiR4) ( $0.07^\circ\text{C}$  NETD on TiR2 and TiR3) provides solid resolution, and ultra high-quality images.
- IR-Fusion technology automatically merges visual and thermal images pinpointing trouble areas quicker by automatically relating thermal images with the real world. (included with Flk-TiR/FT series, optional with Flk-TiR series)

- The  $180^\circ$  articulating lens is great for viewing around obstructions.
- The 5" high resolution, high contrast display is the biggest display in the industry.
- $320 \times 240$  focal plane array and 20 mm high quality Germanium lens with continuous single finger focus provide exceptional image resolution (Model TiR2 available with  $160 \times 120$  only).
- SmartView™ professional report writing software generates fast, easy customizable reports including rich image analysis.
- The intuitive operation with on-camera Windows CE interface makes it easy to use.



## IR-Fusion™ Technology

*Infrared and visible light images fused together on one display.*

IR-Fusion Technology captures a visible light image in addition to the infrared image and takes the mystery out of IR image analysis. It helps to better identify and report suspect areas and enable the repair to be done right the first time.

- **Full IR** – for analyzing very high resolution IR imaging. Detect the smallest temperature variations to track down the origin of problems and fully document the extent of remediation. Full IR images are automatically linked to full visible light images.

- **Picture-in-Picture** – for creating an IR "window" surrounded by a visible light frame to easily identify thermal anomalies, while maintaining a frame of reference with surroundings.
- **Alpha blending** – for combining visible and infrared images together in any ratio to create a single image with enhanced detail that will help in precisely locating problems.
- **IR/visible alarm** – for displaying only temperatures that fall above, below, or in between a specified range as IR image, leaving the rest of the scene as a fully visible light image.
- **Full visible light** – a bright, detailed pixel-for-pixel reference image of subject areas for documentation and reporting.

## IR InSight XS & XST Thermal Imagers

The New Fluke IR InSight XS & XST portable infrared imagers combine outstanding image quality and thermal sensitivity. They are optimized for low contrast thermal applications encountered in building sciences applications and show problems that other infrared cameras cannot. These easy to use cameras include SmartView™ software to customize and prepare professional infrared survey reports.

- $160 \times 120$  focal plane array
- $0.07^\circ\text{C}$  (Industry leading thermal sensitivity ( $\leq$  NETD))
- Simple robust one-button operation
- 3.5-inch, 30 bit color, high resolution, high-contrast display
- SmartView professional report writing software



## TiR2, TiR3 and TiR4 Included accessories

AC adapter (for TiR2 and TiR4 only), video cable, 512 MB compact flash card, compact flash card reader and USB cable, PCMCIA compact flash card adapter, SmartView reporting and analysis software on CD, 2 rechargeable battery packs, battery charger, neck strap, heavy duty carrying case and user manual on CD.

## InSight XS and XST Included accessories

Serial/USB download adapter kit/cable, SmartView reporting software on CD, 2 rechargeable battery packs, battery charger, neck strap, heavy-duty carrying case, user manual on CD.


## Ordering information

|                |                                             |
|----------------|---------------------------------------------|
| Flk-TiR2-20    | IR Flexcam BD Thermal Imager                |
| Flk-TiR2/FT-20 | IR Flexcam BD Thermal Imager with IR-Fusion |
| Flk-TiR3-20    | IR Flexcam BD Thermal Imager                |
| Flk-TiR3/FT-20 | IR Flexcam BD Thermal Imager with IR-Fusion |
| Flk-TiR4-20    | IR Flexcam BD Thermal Imager                |
| Flk-TiR4/FT-20 | IR Flexcam BD Thermal Imager with IR-Fusion |
| Flk-INSXT-20   | IR InSight, 20MM, XST                       |
| Flk-INSXS-20   | IR InSight, 20MM, XS                        |

# Fluke 570 Series Infrared Thermometers

FLUKE®

## The predictive maintenance professional's precision diagnostic tool



CE

The Fluke 572, 574 and 576 non-contact thermometers are ideal professional diagnostic tools for maintenance professionals requiring the most accurate temperature readings at all distances. Predictive maintenance professionals requiring analysis and documentation use the 574 or 576 models, with 100-point data logging and digital photographs (576 only) with the included software for graphing and analysis for follow-up reporting and documentation.

- Backlit display for poorly lit areas
- Displays last ten temperature readings on bar graph for easy reference
- Enhanced optics (distance to spot ratio up to 60:1) allow measurements of smaller objects from farther away
- Coaxial three-dot laser sighting system highlights the true diameter of measurement spots at all distances
- Adjustable emissivity setting (all models) and 30 pre-set common material values (574, 576) for more accurate measurements
- 100-data point logging for documentation (574, 576)
- Customizable log names, alarms, and emissivity values for personalized measurements (574, 576)
- Software to log, graph, and analyze temperature data via RS-232 (574) connection or USB connection (576, includes photo viewing feature)
- Instantly captures photographs of measurement locations along with temperature and date-time information for improved documentation and maintenance follow-up (576)
- Close-focus option available for specialized applications
- Durable hard plastic storage case



CE

## Specifications - 572, 574 and 576 IRTs

| Models                                                   | Fluke-572                                                                                                                  | Fluke-574                                                                 | Fluke-574-NI                  | Fluke-576                                              |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------|
| Temperature range                                        | -30 °C to 900 °C (-25 °F to 1600 °F)                                                                                       |                                                                           |                               |                                                        |
| D:S (Distance to Spot size)                              | 60:1 [50:1 with close focus option (close focus not available with NI model)]                                              |                                                                           |                               |                                                        |
| Laser sighting                                           | 3-dot, coaxial, extra-bright                                                                                               |                                                                           |                               |                                                        |
| Emissivity                                               | Adjustable                                                                                                                 |                                                                           |                               | Adjustable, plus table of 30 preset values             |
| Accuracy                                                 | ± 0.75 % of reading or (± 0.75 °C (± 1.5 °F) whichever is greater (assumes ambient operating temperature of 23 °C [73 °F]) |                                                                           |                               |                                                        |
| Response time                                            | 250 mSec                                                                                                                   |                                                                           |                               |                                                        |
| Display hold (7 seconds)                                 | Yes                                                                                                                        |                                                                           |                               |                                                        |
| LCD backlight                                            | Yes                                                                                                                        |                                                                           |                               |                                                        |
| MAX, MIN temperatures                                    | Yes                                                                                                                        |                                                                           |                               |                                                        |
| DIF, AVG temperatures                                    | No                                                                                                                         | Yes                                                                       | Yes                           | Yes                                                    |
| Recall last reading                                      | Yes                                                                                                                        |                                                                           |                               |                                                        |
| Audible/visible HI alarm                                 | Yes                                                                                                                        |                                                                           |                               |                                                        |
| Audible/visible LO alarm                                 | No                                                                                                                         | Yes                                                                       | Yes                           | Yes                                                    |
| Bar graph display                                        | Yes                                                                                                                        |                                                                           |                               |                                                        |
| 100 points data logging                                  | No                                                                                                                         | Yes                                                                       | Yes                           | Yes                                                    |
| Data graphing software (Windows 2000, XP, NT compatible) | No                                                                                                                         | Yes                                                                       | Yes                           | Yes                                                    |
| Photo viewing software (Windows 2000, XP, NT compatible) | No                                                                                                                         | No                                                                        | No                            | Yes                                                    |
| 26 images (640 x 480 pixel)                              | No                                                                                                                         | No                                                                        | No                            | Yes                                                    |
| 100 images (320 x 240 pixel)                             | No                                                                                                                         | No                                                                        | No                            | Yes                                                    |
| Image file format (.jpg)                                 | No                                                                                                                         | No                                                                        | No                            | Yes                                                    |
| Protective hard case                                     | Yes                                                                                                                        |                                                                           |                               |                                                        |
| Weight                                                   | 472 g (1 lb, 1 oz)                                                                                                         | 480 g (1 lb, 1 oz)                                                        | 480 g (1 lb, 1 oz)            | 580 g (1 lb, 1 oz)                                     |
| Dimensions                                               | 16.7 cm x 5 cm x 19.8 cm (6.58 in x 1.97 in x 7.80 in)                                                                     |                                                                           |                               | 16.7 cm x 5 cm x 23.8 cm (6.58 in x 1.97 in x 9.37 in) |
| Power                                                    | 2 AA batteries                                                                                                             | 2 AA batteries/<br>AC adapter                                             | 2 AA batteries/<br>AC adapter | 2 AA batteries/<br>USB                                 |
| Warranty                                                 | Two-years, conditional                                                                                                     |                                                                           |                               |                                                        |
| Additional options/accessories                           | Nylon holster, NIST<br>Traceable Calibration<br>Certificate                                                                | Nylon holster,<br>NIST Traceable Calibration Certificate,<br>Analog cable |                               |                                                        |

For more information and detailed specifications, go to [www.fluke.com/thermometers](http://www.fluke.com/thermometers)

### 574-NI Nonincendive Thermometer

When safety is a concern and data logging and downloading are required, the Fluke 574 Nonincendive (NI) model thermometer is the product to choose. It has the same great features as the standard 574 model thermometers with the extra confidence of a Factory Mutual approval for use in hazardous environments.

Class I, Division 2, Groups A, B, C, D: Class I, Zone 2 IIC; T4 Ta=50 °C when used with 1.5 V alkaline batteries.



### Fluke 576 Photographic Non-contact Thermometer

The Fluke 576 thermometer measures temperature while digitally photographing the measured area and its surroundings. The 576 allows you to:

- Ensure consistency of repeated measurements by using prior photos as a reference.
- Position the laser sighting to assure the measurement area is the same.
- Create customized company reports with the software, data and photos, using standard Windows programs.

### Included accessories

2 AA batteries, operator's guide (on CD), durable hard case, thermocouple K probe (574, 576), power supply (574), RS-232 data cable (574), USB 1.1 cable (576), data graphing, storage and analysis software on CD (574, 576)

### Ordering information

|              |                                                                       |
|--------------|-----------------------------------------------------------------------|
| Fluke-572    | Precision Infrared Thermometer                                        |
| Fluke-572-CF | Precision Infrared Thermometer with Close Focus Option                |
| Fluke-574    | Precision Infrared Thermometer w/Logging SW                           |
| Fluke-574-NI | Precision Infrared Thermometer w/Logging SW Nonincendive              |
| Fluke-574-CF | Precision Infrared Thermometer w/Logging SW Close Focus               |
| Fluke-576    | Precision, Photographic Infrared Thermometer w/Logging SW             |
| Fluke-576-CF | Precision, Photographic Infrared Thermometer w/Logging SW Close Focus |

# Fluke 54 Series II Thermometer

FLUKE®

## Lab accuracy in a field thermometer



The Fluke 51, 52, 53 and 54 Series II Thermometers offer high accuracy with fast response times to quickly capture your measurement and show trends. Choose from four models to get the functionality, thermocouple support and data logging you need.

### All models offer:

- Laboratory accuracy:  $\pm (0.05\% + 0.3\text{ }^{\circ}\text{C})$
- Large backlit dual display presents all the information you need at a glance
- MIN, MAX, and AVG—with time references—captures major events
- Electronic Offset function maximizes overall accuracy by allowing you to compensate for thermocouple errors
- Supports a wide range of thermocouple types
- Temperatures displayed in  $^{\circ}\text{C}$ ,  $^{\circ}\text{F}$ , or Kelvin (K)
- Splash and dust resistant case
- Sleep mode to increase battery life (typical 1000-hour life)
- Battery door allows easy battery replacement without breaking the calibration seal

### Powerful data logging capabilities

The Fluke 53 and 54 Series II can log up to 500 points of data to internal memory.

- User-adjustable recording intervals
- Real-time clock captures the exact time of day of events
- Recall function allows logged data to be easily reviewed on the meter display
- For further analysis and graphing, data can be exported to optional FlukeView® PC software using the thermometer's IR communication port



## Fluke 561 HVACPro

### Two-in-one infrared and contact thermometer for HVAC/R professionals

The Fluke 561 HVACPro combines the temperature measurement functions that professionals need for most HVAC jobs, all in one tool. It measures both IR and contact temperature, replacing several hundred dollars worth of equipment.

- IR thermometer for measurements up close or at a distance, without a ladder
- Contact thermometry capability, compatible with all standard mini-connector K-type thermocouples, preserves your investment in thermocouples
- Velcro® pipe probe for superheat and sub-cooling and other contact and ambient measurements
- MIN, MAX and DIF functions help you quickly identify problems
- Scan large areas or small objects quickly and efficiently



## Specifications – 51, 52, 53 and 54 Series II

| Feature                                                           | 51                                                                                                                                                                              | 52            | 53            | 54            |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------|---------------|
| Thermocouple types                                                | K,J,T,E                                                                                                                                                                         | K,J,T,E       | K,J,T,E,N,R,S | K,J,T,E,N,R,S |
| Number of inputs                                                  | Single                                                                                                                                                                          | Dual          | Single        | Dual          |
| Time stamp                                                        | Relative time                                                                                                                                                                   | Relative time | Time of day   | Time of day   |
| Temperature measurement accuracy (for temperatures above -100 °C) | Type J,K,T,E,N: $\pm [0.05\% + 0.3\text{ }^{\circ}\text{C} (0.5\text{ }^{\circ}\text{F})]$ Type R,S: $\pm [0.05\% + 0.4\text{ }^{\circ}\text{C} (0.7\text{ }^{\circ}\text{F})]$ |               |               |               |
| Measurement range (depending on thermocouple type)                | -250 °C (-418 °F) to 1767 °C (3212 °F)                                                                                                                                          |               |               |               |
| Display resolution                                                | 0.1 °C /°F/K < 100° 1° °C/°F/K $\geq 1000^{\circ}$                                                                                                                              |               |               |               |
| Operating temperature                                             | -10 °C to 50 °C (14 °F to 122 °F)                                                                                                                                               |               |               |               |
| Storage temperature                                               | -40 °C to 60 °C (-40 °F to 140 °F)                                                                                                                                              |               |               |               |
| Humidity                                                          | 0 % to 90 %; 0 °C to 35 °C (32 °F to 95 °F), 0 % to 70 %; 0 °C to 50 °C (32 °F to 122 °F)                                                                                       |               |               |               |
| Weight                                                            | 400 g (14 oz)                                                                                                                                                                   |               |               |               |
| Size (HxWxD)                                                      | 17.3 cm x 8.6 cm x 3.8 cm (6.8 in x 3.4 in x 1.5 in)                                                                                                                            |               |               |               |
| Battery                                                           | 3 AA batteries; typical 1000-hour life                                                                                                                                          |               |               |               |

## Included accessories

### Fluke 50 Series II includes:

80PK-1 Bead Thermocouple(s), batteries, overview manual and instructional guide on CD-ROM.

### Fluke 561HVACPro includes:

Infrared thermometer with contact thermometer capabilities, thermocouple K-type Velcro® pipe probe, hand-carrying case and user manual with HVAC measurement guide.

## Ordering information

- Fluke-51-2 Digital Thermometer, Single Input
- Fluke-52-2 Digital Thermometer, Dual Input
- Fluke-53-2 Datalogging Thermometer, Single Input
- Fluke-54-2 Datalogging Thermometer, Dual Input
- Fluke-561 HVACPro Thermometer

## Recommended accessories – 51, 52, 53 and 54 Series II Thermometers



**TPak**  
ToolPak Meter  
Hanging Kit  
See page 71



**80PK-8**  
Pipe Clamp  
Temperature Probe  
See page 68



**80PK-22**  
SureGrip™ Immersion  
Temperature Probe  
See page 68



**80PK-25**  
SureGrip™ Piercing  
Temperature Probe  
See page 68



**FVF-SC1**  
FlukeView Forms  
Software  
See page 65

For more information and detailed specifications, go to [www.fluke.com/thermometers](http://www.fluke.com/thermometers)

Thermometers



# Fluke 68 Infrared Thermometer

FLUKE®

**Measuring temperature in hard-to-reach, hot, rotating or dangerous situations**



Reach for a rugged Fluke IR thermometer. You get easy and safe temperature readings in less than a second.

These handheld portable tools enable professionals to research heating and ventilation problems, monitor the status of electrical motors and electrical panels and diagnose car malfunctions with ease.

## Fluke 63, 66 and 68 pistol grip infrared thermometers

The new Fluke 63, 66 and 68 pistol grip thermometers offer an easy to use solution for temperature measurement in hard-to-reach, hot, rotating or dangerous situations.

- Wide temperature range and quick response time
- Superb optics for measuring temperature of surfaces from a distance
- Laser sighting
- Adjustable emissivity (66/68 only) for more accurate temperature measurement

**Intrinsically safe Fluke 68 version available** (see page 45)

## Specifications – 561, 61, 62, 63, 66, 68

|                               | 561                                                                           | 61                                                      | 62                                                       | 63                                                                                        | 66                                                                                    | 68                                      |
|-------------------------------|-------------------------------------------------------------------------------|---------------------------------------------------------|----------------------------------------------------------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----------------------------------------|
| Temperature range             | -40 °C to 550 °C<br>(-40 °F to 1022 °F)                                       | -18 °C to 275 °C<br>(0 °F to 525 °F)                    | -30 °C to 500 °C<br>(-20 °F to 932 °F)                   | -32 °C to 535 °C<br>(-25 °F to 995 °F)                                                    | -32 °C to 600 °C<br>(-25 °F to 1100 °F)                                               | -32 °C to 760 °C<br>(-25 °F to 1400 °F) |
| Emissivity                    | Adjustable with three settings:<br>Low (0.3),<br>Medium (0.7),<br>High (0.95) | Fixed at 0.95                                           |                                                          |                                                                                           | Digitally adjustable<br>(from 0.1 to 1.0 by 0.01)                                     |                                         |
| Optical resolution (D:S)      | 12:1                                                                          | 8:1                                                     | 10:1 at 80 %<br>energy                                   | 12:1                                                                                      | 30:1                                                                                  | 50:1                                    |
| Laser sighting (class II)     | Single point laser                                                            | Offset single point laser                               |                                                          |                                                                                           |                                                                                       |                                         |
| Response time                 | 500 mSec (95 %<br>of reading)                                                 | < 500 mSec                                              | < 500 mSec                                               | ≤ 0.5 second (95 % of reading)                                                            |                                                                                       |                                         |
| Minimum usable spot size      | 25 mm (1 in)                                                                  |                                                         |                                                          |                                                                                           | 24 mm (0.9 in)                                                                        | 18 mm (0.7 in)                          |
| Resolution                    | 0.1 °C (0.1 °F)<br>of reading                                                 | 0.2 °C (0.5 °F)                                         |                                                          |                                                                                           | 0.1 °C (0.1 °F)                                                                       |                                         |
| Repeatability                 | ± 0.5 % of<br>reading or ± 1 °C<br>(± 2 °F), which-<br>ever is greater        | ± 2 °C or<br>± 2 %, whichever<br>is greater             | ± 0.5 % or ≤ ± 1 °C (± 2 °F), whichever is greater       |                                                                                           |                                                                                       |                                         |
| Ambient operating temperature | 0 °C to 50 °C (32 °F to 120 °F)                                               |                                                         |                                                          |                                                                                           |                                                                                       |                                         |
| Relative humidity             | 10 to 90 % RH non-condensing,<br>at < 30 °C (86 °F)                           | 10 to 90 % RH non-condensing, at<br>< 50 °C (120 °F)    | 10 to 90 % RH non-condensing, at < 30 °C (86 °F) ambient |                                                                                           |                                                                                       |                                         |
| Storage temperature           | -20 °C to 65 °C<br>(-25 °F to 150 °F)                                         | -20 °C to 60 °C<br>(-4 °F to 140 °F)<br>without battery | -20 °C to 65 °C<br>(-4 °F to 150 °F)<br>without battery  | -20 °C to 60 °C (-13 °F to 158 °F) without battery                                        |                                                                                       |                                         |
| Dimensions                    | 17.8 cm x 16.5<br>cm x 5.1 cm (7 in<br>x 6.5 in x 2 in)                       | 190 mm x 51 mm<br>x 41 mm (7.5 in x<br>2 in x 1.6 in)   | 152 mm x 101 mm<br>x 38 mm (6 in x<br>4 in x 1.5 in)     | 200 mm x 160 mm x 55 mm (8 in x 6 in x 2 in)                                              |                                                                                       |                                         |
| Weight                        | 330 g (11.6 oz)                                                               | 341 g (0.75 lb)                                         | 200 g (7 oz)                                             | 320 g (11 oz)                                                                             |                                                                                       |                                         |
| Power                         | 2 AA batteries<br>(alkaline or NiCd)                                          | 9 V alkaline or customer supplied NiCd battery          |                                                          |                                                                                           |                                                                                       |                                         |
| Battery life (alkaline)       | 12 hours                                                                      |                                                         |                                                          | 10 hours with<br>laser and back-<br>light on, 40 hours<br>with laser and<br>backlight off | 20 hours with laser and backlight<br>on 50 % 40 hours with laser and<br>backlight off |                                         |
| Typical distance to target    | Up to 2 m (6 ft)                                                              | 1 m (3 ft)                                              | Up to 2 m (6 ft)                                         | Up to 2 m (6 ft)                                                                          | Up to 5 m (15 ft)                                                                     | Up to 8 m (25 ft)                       |
| Warranty                      | Two-year limited                                                              | One-year                                                | Two-year limited                                         | Two-year limited                                                                          | Two-year limited                                                                      | Two-year limited                        |

## Recommended accessories – 60 Series Thermometers



**80PR-60**  
Temperature Probe  
(66/68 only)  
See page 69



**H6**  
Meter Case  
(63/66/68 only)  
See page 70



**LVD1**  
Volt Light  
(all models)  
See page 64



**C510**  
Meter Case  
(61 only)  
See page 70



**C90**  
Meter Case  
(61 only)  
See page 70

For more information and detailed specifications, go to [www.fluke.com/thermometers](http://www.fluke.com/thermometers)

## New! Fluke 62 Mini Infrared Thermometer

- Temperature measurement range up to 500 °C (932 °F)
- 10:1 optics
- Accurate to within ± 1.5 % of reading or ± 1.5 °C
- MAX temperature display
- Laser sighting
- Backlit display



## Fluke 61 Infrared Thermometers

- Easy to use one button operation
- Easy targeting with bright laser
- Shock-absorbing molding increases ruggedness



## Included accessories

**Fluke 61 includes:** instruction sheet and 9 V battery.

**Fluke 62 includes:** storage pouch and instruction sheet.

**Fluke 63, 66, 68 includes:** carrying case, hand strap, instruction manual and 9 V battery.

## Ordering information

Fluke-61 Infrared Thermometer  
Fluke-62 Mini Infrared Thermometer

Fluke-63 Infrared Thermometer  
Fluke-66 Infrared Thermometer  
Fluke-68 Infrared Thermometer  
Fluke-68IS Intrinsically Safe Infrared Thermometer



# Fluke 975 AirMeter™

**Five powerful tools in one, with simple one-touch air velocity**



The Fluke 975 test tool combines five powerful air quality tools into one. Identify and diagnose indoor air quality issues quickly and easily with one rugged, handheld device. The Fluke 975 measures and simultaneously displays temperature, humidity, CO<sub>2</sub> and CO. At the press of a button, it quickly measures air flow and percentage of outside air.

- Simultaneously measures, logs, and displays temperature, humidity, CO<sub>2</sub>, and CO on a bright, backlit LCD display
- One-touch air flow and velocity with available probe\*
- Wet bulb and dew point temperature
- % of outside air calculation
- CO<sub>2</sub> and CO field calibration feature
- Automatically compensates for barometric pressure changes
- Min/Max/Average on all measured and calculated readings
- Audible and visual threshold alarms
- Extensive discrete or continuous data logging capacity, downloadable to PC via USB interface

\*Included with Fluke 975V, optional with Fluke 975

|                   | Range                                          | Display Resolution | Accuracy                                                                                                                       |
|-------------------|------------------------------------------------|--------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Temperature       | -20 °C to 50 °C<br>(-5 °F to 122 °F)           | 0.1 °C (0.1 °F)    | ± 0.9 °C/± 1.62 °F from 40 °C to 60 °C ± 0.5 °C/± 1.00 °F from 5 °C to 40 °C ± 1.1 °C/± 1.98 °F from -20 °C to 5 °C            |
| Relative humidity | 10 % to 90 % RH non-condensing                 | 1 %                | ± 2 % RH (10 % RH to 90 % RH)                                                                                                  |
| Air velocity      | 50.0 fpm to 3000 fpm<br>0.25 m/sec to 15 m/sec | 1 fpm (0.005m/sec) | ±4 % or 4 fpm* ±4 % or 0.02 m/sec* whichever is greater *Accuracy specification only valid for velocity readings above 50 fpm. |
| CO <sub>2</sub>   | 0 to 5000 ppm                                  | 1 ppm              | Warm up time 1 min (5 minutes for full specification)<br>2.75 % + 75 ppm                                                       |
| CO                | 0 to 500 ppm                                   | 1 ppm              | ± 5 % or ± 3 ppm, whichever is greater, @ 20 °C and 50 % RH                                                                    |

## Also available:

**Fluke-975CK AirMeter Calibration Kit** includes the gases and tools necessary to keep your Fluke 975 AirMeter calibrated.



**Fluke-975AP AirMeter Velocity Probe** for use with Fluke 975 AirMeter.



## Fluke 902 True-rms HVAC Clamp Meter

**Get more done**

Heating, ventilation, air conditioning (HVAC) technicians require a service tool that can consistently keep up with their demands. The Fluke 902 expands the existing line of quality Fluke clamp meters by delivering the features necessary to diagnose and repair HVAC systems. Combined with True-rms technology and a CAT III 600 V rating, the Fluke 902 helps technicians do their jobs safely and accurately.

- Designed for HVAC applications with capacitance, dc current (µA), and temperature measurements
- Small body and jaws fit perfectly in your hand and into tight places
- Handy 'Display Hold' button keeps measurements on the display
- Meter controls are positioned so current measurements can be done with one hand (index finger on clamp opening lever and thumb on rotary switch)

**New**



|                       | Range                                                                      | Accuracy                                                                                    |
|-----------------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Voltage dc            | 0 - 600 V                                                                  | 1 % ± 5 counts                                                                              |
| Voltage ac (True-rms) | 0 - 600 V                                                                  | 1 % ± 5 counts (50/60 Hz)                                                                   |
| Current ac (True-rms) | 0 - 600 A                                                                  | 2.0 % ± 5 counts (50/60 Hz)                                                                 |
| Current dc            | 0 - 200 µA                                                                 | 1.0 % ± 5 counts                                                                            |
| Resistance            | 0 - 9999 Ω                                                                 | 1.5 % ± 5 counts                                                                            |
| Continuity            | <= 30 Ω                                                                    | -                                                                                           |
| Temperature Range     | -10 °C to 400 °C (-14 °F to 752 °F)<br>-40 °C to -10 °C (-40 °F to -14 °F) | +/-1.0 % + 0.8 °C (+/-1.0 % + 1.5 °F) typical +/-5.0 % + 1.5 °C (+/-5.0 % + 3.3 °F) typical |
| Capacitance           | 1-1000 µF                                                                  | 1.9 % ± 2 counts                                                                            |

## Included accessories

**Fluke 975 includes:** AA alkaline batteries (3), Users manual (with safety information), calibration cap, hard carrying case, FlukeView® Forms software, power adapter, international power plugs, air velocity probe (Fluke 975V only).

**Fluke 902 includes:** AA alkaline batteries (2), Users manual (with safety information), soft carrying case, T175 Test Leads (1 pair), 80BK Integrated Temperature Probe (1).

## Ordering information

Fluke-975 AirMeter™  
Fluke-975V AirMeter™ with Velocity  
Fluke-902 HVAC Clamp Meter

# Indoor Air Quality Tools

Easy-to-use tools to help you maintain good IAQ



## Fluke 971 Temperature Humidity Meter

Temperature and humidity are two important factors in maintaining optimal comfort levels and good indoor air quality. Quickly and conveniently take accurate humidity and temperature readings with the Fluke 971. The Fluke 971 is invaluable for facility maintenance and utility technicians, HVAC-service contractors, and specialists who assess indoor air quality (IAQ). Lightweight and easy to hold, the Fluke 971 is the perfect tool for monitoring problem areas. With a rugged holster and twist-open protective sensor cover, the Fluke 971 is built to perform and made to last.

### Features:

- Backlit dual display of humidity and temperature
- Measures dew point and wet bulb temperatures
- 99 record storage capacity
- Ergonomic design with belt clip and protective holster
- Quick-response capacitance sensor with twist-open protective cover
- Compact and lightweight at 188 g (6.6 oz)
- Temperature range from -20 °C to 60 °C (-4 °F to 140 °F)
- Relative humidity from 5 % to 95 %
- Min/Max/Avg Data hold
- Low battery indicator

## Fluke 983 Particle Counter

The Fluke 983 Particle Counter measures and displays six channels of particle size distribution. The Fluke 983 holds 5000 logged samples including date, time, counts, sample volume, temperature and relative humidity. Data is easily downloaded using the included windows compatible utility software. The Fluke 983 is invaluable for IAQ investigations, allowing you to determine size distribution of airborne particles or track down a particle source.

### Features:

- Compact and easy to operate
- Graphic liquid crystal display with backlight
- Simple connection to computer or printer
- Selectable sample time, count data and programmable delay
- Set sample size to cubic feet or liters, set temperature measurements to °C or °F
- Data displayed in totalize or concentration modes
- Automatic turn-off when battery voltage drops below safe operating level
- Meets JISB9921:1997 and CE standards
- Battery or ac operation with internal rechargeable battery
- Protective holster
- Rugged, hard shell carrying case



### Also available:

#### Fluke 983TPK Thermal Printer Kits

Print the results of a single sample or an entire data logging session with the new Fluke 983 Thermal Printer Kit accessory. Available in 220 V and 120 V models and includes two rolls of thermal printer paper, battery pack, power adapter and serial adapter.


## CO-220 Carbon Monoxide Meter

- Standalone CO meter that does not require a digital multimeter
- Large backlit LCD displays CO levels from 0 to 1000 ppm
- Beeper triggers with increasing frequency as CO levels rise
- MAX hold function stores and displays the maximum CO level
- Automatic sensor zeroing and self-test upon startup



## CO-210 Carbon Monoxide Probe

- Use as an accessory to a digital multimeter with DC millivolt inputs
- Displays CO level readings from 0 to 999 ppm, with a resolution of 1 ppm and accuracy of  $\pm 5\%$
- Also used as a standalone device with an LED indicator and beeper that triggers with increasing frequency as CO levels rise



## CO-205 Aspirator Kit

The CO-205 flue gas sampling accessory kit includes:

- Stainless steel sampling tube
- Aspirator to draw flue sample
- Replaceable particulate filter
- Nose cap for connection to the Fluke CO-210/CO-220

### Included accessories

**Fluke 971 includes:** operation manual, four AAA alkaline batteries.

**Fluke 983 includes:** Certificate of Calibration (NIST), Windows compatible software download utility, DB9 to RS-232 adapter and cable, isokinetic probe, high purity tubing, 1/8 in. hose barb adapter, power supply, operation manual, zero count filter, protective holster and hard molded plastic case.

### Ordering information

|                  |                            |
|------------------|----------------------------|
| Fluke-971        | Temperature Humidity Meter |
| Fluke-983        | Particle Counter           |
| Fluke-983TPK 220 | Thermal Printer Kit, 220 V |
| Fluke-983TPK 120 | Thermal Printer Kit, 120 V |
| Fluke-CO-205     | Aspirator Kit              |
| Fluke-CO-210     | Carbon Monoxide Probe      |
| Fluke-CO-220     | Carbon Monoxide Meter      |

For more information and detailed specifications, go to [www.fluke.com/IAQ](http://www.fluke.com/IAQ)

# Fluke ScopeMeter® Test Tools

FLUKE®

**Handheld oscilloscopes for professionals  
with challenging troubleshooting situations**



The ScopeMeter 192, 196 and 199 high-performance oscilloscopes have bandwidth of 60, 100 and 200 MHz and sample rates up to 2.5 GS/s. The C models add a high-resolution color display that has a fast update rate, waveform pass/fail testing and a digital persistence mode—making the analysis of complex and dynamic signals that much easier.

For industrial, electronic or electro mechanical applications, the 123 and 124 Industrial ScopeMeters feature 20 MHz bandwidth, Connect-and-View™ software for quick measurements and a dual DMM and paperless recorder to get virtually any job done.

## Specifications – ScopeMeter® Test Tools

|                                               | Fluke 199C                                                     | Fluke 196C | Fluke 199B              | Fluke 196B | Fluke 192B | Fluke 124                  | Fluke 123   |
|-----------------------------------------------|----------------------------------------------------------------|------------|-------------------------|------------|------------|----------------------------|-------------|
| Bandwidth                                     | 200 MHz                                                        | 100 MHz    | 200 MHz                 | 100 MHz    | 60 MHz     | 40 MHz                     | 20 MHz      |
| Max real time sample rate                     | 2.5 GS/s                                                       | 1.0 GS/s   | 2.5 GS/s                | 1.0 GS/s   | 0.5 GS/s   | 25 MS/s                    | 25 MS/s     |
| Max record length (per input)                 | 3000 Points                                                    |            |                         |            |            | 512 Points (min/max pairs) |             |
| Number of Inputs                              | 2 Scope and 1 DMM (Isolated)                                   |            |                         |            |            | 2 Scope Or DMM             |             |
| Input sensitivity                             | 2 mV/div. to 100 V/div.                                        |            | 5 mV/div. to 100 V/div. |            |            | 5 mV/div. to 500 V/div.    |             |
| Independently isolated floating inputs        | •                                                              |            |                         |            |            |                            |             |
| Display and display modes                     |                                                                |            |                         |            |            |                            |             |
| Display                                       | Color                                                          |            | Monochrome              |            |            | Monochrome                 |             |
| Persistence                                   | Digital with variable decay                                    |            | On/Off                  |            |            | —                          |             |
| Envelope mode                                 | •                                                              |            |                         |            |            | •                          |             |
| Waveform compare                              | •                                                              |            |                         |            |            |                            |             |
| FFT                                           | •                                                              |            |                         |            |            |                            |             |
| Pass/fail testing                             | •                                                              |            |                         |            |            |                            |             |
| Triggering                                    |                                                                |            |                         |            |            |                            |             |
| Connect-and-View™ trigger                     | •                                                              |            |                         |            |            | •                          |             |
| Edge, single, free run                        | •                                                              |            |                         |            |            | •                          |             |
| Video                                         | •                                                              |            |                         |            |            | •                          |             |
| Video lines                                   | •                                                              |            |                         |            |            | •                          |             |
| Pulse width                                   | •                                                              |            |                         |            |            |                            |             |
| External                                      | •                                                              |            |                         |            |            | With ITP 120 Option        |             |
| Advanced functions                            |                                                                |            |                         |            |            |                            |             |
| Cursors                                       | •                                                              |            |                         |            |            | •                          |             |
| Zoom                                          | •                                                              |            |                         |            |            |                            |             |
| Dual input Trendplot™                         | •                                                              |            |                         |            |            |                            |             |
| ScopeRecord™ mode                             | •                                                              |            |                         |            |            |                            |             |
| Automatic capture and replay last 100 screens | •                                                              |            |                         |            |            |                            |             |
| Waveform mathematics                          | •                                                              |            |                         |            |            |                            |             |
| Save setups and screens                       | 10                                                             |            |                         |            |            | 20                         | 10          |
| True-rms multimeter                           | 5000 Counts Volts, Amps, Ohms, Continuity, Diode, Temp         |            |                         |            |            |                            |             |
| Safety, power and warranty                    |                                                                |            |                         |            |            |                            |             |
| Safety (EN61010-1)                            | CAT II 1000 V/CAT III 600 V                                    |            |                         |            |            | CAT III 600 V <sup>1</sup> |             |
| Battery                                       | 4-hour Ni-MH                                                   |            |                         |            |            | 7-hour NiMH                | 7-hour NiMH |
| Line power                                    | Adapter/battery charger included                               |            |                         |            |            |                            |             |
| PC printer interface                          | Yes, using optional optically isolated cable                   |            |                         |            |            |                            |             |
| Warranty                                      | Three-year on main instrument/one-year on standard accessories |            |                         |            |            |                            |             |

<sup>1</sup>Max input voltage CAT II 1000 V with VPS40, 40 MHz 10:1 voltage probe.

## Recommended accessories – ScopeMeter Test Tools

| Model   | Description                               | 192, 196, 199 | 123, 124 |
|---------|-------------------------------------------|---------------|----------|
| SCC 120 | Software, cable and carrying case package |               | •        |
| SCC 190 | Software, cable and carrying case package | •             |          |
| C125    | Compact soft case                         |               | •        |
| C195    | Universal soft carrying case              | •             |          |
| PAC91   | Optical to parallel printer adapter cable | •             | •        |

**Connect  
and  
View™**

For more information and detailed specifications, go to [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter)

ScopeMeter Test Tools

# Fluke 124 and 123 Industrial ScopeMeter® Test Tools

FLUKE®

**Three-in-one simplicity for fast answers wherever you work**




The compact ScopeMeter 123 and 124 are the rugged solution for industrial troubleshooting and installation applications. These are truly integrated test tools, with oscilloscope, multimeter and "paperless" recorder in one affordable, easy-to-use instrument. Find fast answers to problems in machinery, instrumentation, control and power systems.

- A dual input 40 MHz or 20 MHz digital oscilloscope
- Two 5,000-count true-rms digital multimeters
- Cursor measurements (Fluke 124 only)
- A dual input TrendPlot recorder
- Connect-and-View trigger simplicity for hands-off operation
- Shielded test leads for oscilloscope, resistance, continuity and capacitance measurements
- Full bandwidth, heavy duty 10:1 probe (Included standard with Fluke 124)
- Up to seven hours battery operation with standard battery
- CAT III 600 V safety certified
- Optically isolated RS-232 interface
- Rugged, compact case



## A three-in-one tool


The ScopeMeter 123 and 124 combine a 40 MHz or 20 MHz dual input digital storage oscilloscope, two true-rms digital multimeters and a dual input TrendPlot™ recorder all in a compact, battery powered instrument. Leave all other test tools behind because the ScopeMeter 123 and 124 Test Tools are the only one you'll need.



Dual-input measurement shows both meter reading and waveform at the same time (124, incl. cursors)

## Connect-and-View™ triggering for an instant, stable display

Scope users know how difficult triggering can be. Incorrect settings show unstable and sometimes incorrect results. Fluke's unique Connect-and-View recognizes signal patterns, and automatically sets up correct triggering. It provides a stable, reliable and repeatable display of virtually any signal including motordrive and control signals—without touching a button. Signal changes are instantly recognized and settings adjusted for once again a stable display.



Connect-and-View captures even the most complex motor drive signals

## One test lead measures all

High-frequency waveform, meter, capacitance and resistance measurements and continuity checks are all covered by the shielded test leads. No time wasted finding or swapping leads. The included accessories allow hook-up at test objects of every dimension.

## Battery powered mobility

Up to seven hours of battery operation frees you from mains outlets for true on-the-move working. The handheld format and the weight of just 1.2 kg, make the instrument easy to carry and to fit comfortably in your hand. The rugged, drip proof case assures long life and reliable operation in the harshest industrial environments.

## Use TrendPlot™, dual channel recorder, to help find intermittents, fast

The toughest faults to find are those that happen only once in a while—intermittents. They can be caused by bad connections, dust, dirt, corrosion or

Application note, literature code 2126072:

## Verifying CAN bus signals with a Fluke ScopeMeter 120 Series

Verifying the physical layer signals of two-wire differential serial bus system. Read a detailed application note on [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter)



Check the starting capacitor of a motor with the ScopeMeter 124

simply broken wiring or connectors. Other factors, like line outages and sags, or the starting and stopping of a motor can also cause a machine to stop. You may not be around to see it—your Fluke ScopeMeter will. In this "paperless recorder" mode, you can plot the min, max, peak and average values over time, up to 16 days. The two inputs can plot any combination of volts, amps, temperature, frequency and phase, with time and date stamp-to help lead you to the cause of those faults quickly.

## Safety certified


The 123 and 124 ScopeMeter Test Tools and the included shielded test leads are safety certified for measurements on CAT III 600 V industrial power systems. Via the optically isolated OC4USB interface, the 123 and 124 can be safely connected to a printer for direct print-out or to a PC for later analysis and documentation using FlukeView software. And using the VPS40 probe, measurement up to CAT II 1000 V are fully supported.

## Ordering information

|                |                                           |
|----------------|-------------------------------------------|
| FLUKE-124/003  | Industrial ScopeMeter 40 MHz              |
| FLUKE-124/003S | Industrial ScopeMeter 40 MHz with SCC Kit |
| FLUKE-123/003  | Industrial ScopeMeter 20 MHz              |
| FLUKE-123/003S | Industrial ScopeMeter 20 MHz with SCC Kit |

For more information and detailed specifications, go to [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter)

ScopeMeter Test Tools



# Fluke 192, 196 and 199 ScopeMeter® Test Tools

**Speed, performance and analysis power.  
See more, fix more with color.**



Whether you are performing routine maintenance and calibration, or troubleshooting the hardest to solve problems like intermittent failures or sources of unwanted noise—the Fluke ScopeMeter 192, 196 and 199 include all the tools needed to get the job done. With 200 MHz bandwidth, up to 2.5 GSa/s real-time sampling rate, 27500 points memory for high resolution waveform ScopeRecord™, measurement TrendPlot™ and FFT analysis, analyzing signal details, finding random glitches and sources of unwanted noise or interference become routine tasks.

- Dual-input—200, 100 or 60 MHz bandwidth
- Up to 2.5 GSa/s real-time sampling and 3 k points memory per input
- Automatic and advanced triggering functions—Connect&View, pulse width, dual slope and n-cycle for synchronizing on specific waveform details

- Fast Fourier Transform (FFT) for frequency domain, spectrum display of signal harmonics or fidelity. (C models)
- Digital persistence for analyzing complex dynamic waveforms like on an analog scope (C models)
- Automatic capture and replay of 100 screens
- 27,500 points per input record length using ScopeRecord mode
- TrendPlot paperless chart recorder for trend analysis up to 22 days
- Waveform reference for visual comparisons and automatic pass/fail testing (C models) of waveforms
- Five hours rechargeable Ni-MH battery pack




## See what's really happening

With a maximum real-time sampling rate of 2.5 GSa/s per input, you can see what really happens, with 400 ps resolution. Both inputs have their own digitizer, so you can simultaneously acquire two waveforms and analyze them with the highest resolution and detail. If an anomaly flashes by on the screen, just press the Replay button to see it again.

## Frequency Spectrum Analysis

All C models now include Frequency Spectrum Analysis functionality based on Fast Fourier Transformation (FFT) analysis as a standard feature. This makes it possible for you to identify the individual frequency components contained in a signal. The spectrum analysis function is also handy to reveal the effects of vibration, signal interference or crosstalk. An automatic window function assures optimal windowing, although you may manually select your preferred time window.



## Automatic capture and replay of 100 screens

Scope users know how frustrating it is to see a one-time anomaly flash by—never to be seen again. Not with the ScopeMeter 190 Series. Now you can look back in time with a touch of the replay button. In normal use, the instrument continuously memorizes the last 100 screens. Each time a new screen is acquired, the oldest is discarded. At any moment you can “freeze” the last 100 screens and scroll through picture-by-picture or replay as a “live” animation. Cursors can be used for further analysis.



## Deep memory for high-resolution ScopeRecord™ and Trendplot™

The ScopeRecord memory stores 27,500 points per input, for high-resolution recording of waveform events up to 48 hours, and captures fast intermittents and glitches as short as 50 ns. This continuous roll mode also stores events like motion profiles, UPS, power supply and motor start-ups.

In Trendplot or “paperless recorder” mode, you can plot the minimum, maximum peak and average measurement (DMM or Automatic Scope) values over time—up to 22 days. The two inputs can plot any combination of volts, amps, temperature, frequency


Application note, literature code 2043253:

## All DSO isolated channels are not the same

Displaying information from multiple information sources—“channels” at once is critical to troubleshooting and maintaining today's complex equipment and most modern power control systems' circuitry require different reference measurements. Now one tool will do it all.



Go to [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter) for more information.



and phase with time and date stamp to help lead you to the cause of those faults quickly.

## Waveform Pass/Fail testing

Waveform reference allows an acquired trace to be stored and designated reference trace for visual comparisons, or it can be used as the reference for automatic Pass/Fail testing (C models only). Up to 100 individually matching (Pass) or non-matching (Fail) waveforms can be stored in the replay memory (C models only), allowing you to monitor your system's behavior over a long period of time, without the need for you to attend!

## Ordering information

|                 |                                       |
|-----------------|---------------------------------------|
| Fluke-192B/003  | ScopeMeter 60 MHz B/W                 |
| Fluke-192B/003S | ScopeMeter 60 MHz B/W with SCC kit    |
| Fluke-196B/003  | ScopeMeter 100 MHz B/W                |
| Fluke-196B/003S | ScopeMeter 100 MHz B/W with SCC kit   |
| Fluke-199B/003  | ScopeMeter 200 MHz B/W                |
| Fluke-199B/003S | ScopeMeter 200 MHz B/W with SCC kit   |
| Fluke-196C/003  | ScopeMeter 100 MHz color              |
| Fluke-196C/003S | ScopeMeter 100 MHz color with SCC kit |
| Fluke-199C/003  | ScopeMeter 200 MHz color              |
| Fluke-199C/003S | ScopeMeter 200 MHz color with SCC kit |

For more information and detailed specifications, go to [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter)

# Fluke ScopeMeter® Test Tool accessories

FLUKE®

Measurements made easier

Data Sheet, literature code  
1629076:

## ScopeMeter accessories

Fluke accessories can enhance or expand the measurement capabilities of your ScopeMeter.

Go to [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter) for your copy of the ScopeMeter accessories data sheet.



## Cable and adapters

### PAC91

- Printer Adapter Cable 0.25 m
- Safety designed optical to parallel printer adapter cable
- See instrument manual for compatible printers



### PM9091

- 50 Ohm Coaxial BNC cable set, 3 x 1.5 m
- Three colored BNC male connectors (red, gray and black) for easy identification



### OC4USB

- Optically-isolated serial to USB adapter



### PM9092

- 50 Ohm Coaxial BNC cable set, 3 x 0.5 m
- Three colored BNC male connectors (red, gray and black) for easy identification



### PM9081

- Dual Banana Plug 4 mm male to female BNC Adapter
- The set consists of two adapters



### PM9093

- Male BNC to dual female BNC T-piece
- Set consists of two adapters



### PM9082

- Dual Banana Jack 4 mm female to male BNC Adapter
- The set consists of two adapters easy identification



### BB120

- Two shielded Banana-to-BNC Adapters
- Adapting Probes and BNC adapters to 123 and 124 ScopeMeter Test Tools



## Trigger and differential probes

### DP120 Differential Probe

- 1.5 m with shrouded banana probe tips (red and black)
- CAT III 600 V/CAT II 1000 V rated



### ITP120 Optically Isolated Trigger Probes

- 1.2 m, for ScopeMeter 123
- Included hookclip with ground lead
- Max. signal voltage and voltage to ground: CAT II 600 V rms



## Software, carrying cases and kits

### SCC120 Software Cable Case for 123, 124

### SCC190 Software Cable Case for 192, 196, 199

Accessories package, including:

- FlukeView® ScopeMeter® Software for Windows® English, French and German language
- OC4USB Optically Isolated RS-232 Adapter/Cable
- Hard Carrying Case C120 or C190



### C120 Hard Carrying Case for 123, 124

### C190 Hard Carrying Case for 192, 196, 199

- Storage compartments for test leads, probes, instruction manual, power adapter and other small accessories

### C195 Soft Carrying Case Universal

- Durable soft case. Adjustable storage compartments suitable for all ScopeMeter models. Storage compartments for test leads, probes, instruction manual, power adapter and other accessories



### C125 Compact Soft Case for 123, 124

- Zippered carrying case (black) for 123, 124
- Pouch is designed to carry test leads and probes
- Convenient belt loop accommodates tool belt



For more information and detailed specifications, go to [www.fluke.com/scopemeter](http://www.fluke.com/scopemeter)

# Fluke accessory selection guide

FLUKE®

Find the right accessories to make your meter work for you

|                       |                          | 10/11/12/12B | 110/111/112 | 114/115/116/117 | 21/23/26/75/77/79 | 27 | 70/73 III | 175/177 | 179 | 83/85/87 III/83V | 87/89 IV | 87V | 187/189 | 45 | 39/41B | 43B | 90 Series | 120 Series | 190 Series | 50S/50D | 51/52/53/54 II | 61/65 | 63/66/68 | 321/322 | 333/334/335/336/337 | 705/707 | 712/713 | 714 | 715 | 716/717 | 718 | 725/726 | 741/743 | 744 | 787/789 | T3/T5 | 1587 | 1577 |   |
|-----------------------|--------------------------|--------------|-------------|-----------------|-------------------|----|-----------|---------|-----|------------------|----------|-----|---------|----|--------|-----|-----------|------------|------------|---------|----------------|-------|----------|---------|---------------------|---------|---------|-----|-----|---------|-----|---------|---------|-----|---------|-------|------|------|---|
| Current               | i200                     |              |             |                 |                   |    | 73        |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     | 3       |       |      |      |   |
|                       | i200s                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | i400                     |              |             |                 |                   |    | 73        |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     | 3       |       |      |      |   |
|                       | i400s                    | 4            | 4           | 4               | 4                 | 4  | 4         | 4       | 4   | 4                | 4        | 4   | 4       | 4  | 4      | 4   |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     | 3       | 4     | 4    |      |   |
|                       | 80i-600A                 |              |             |                 |                   |    | 73        |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | i1000s                   | 4            | 4           | 4               | 4                 | 4  | 4         | 4       | 4   | 4                | 4        | 4   | 4       | 4  | 4      | 4   |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       | 4    | 4    |   |
|                       | i2000 flex               |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | i3000 flex               |              |             |                 | 4                 |    |           |         |     |                  |          |     |         |    |        | 4   |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      | 4    | 4 |
|                       | i3000s                   |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | i410                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     | 5         | 5          | 5          | 5       |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| i1010                 |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        | 5   | 5         | 5          | 5          |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| i30/i30s              |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| Temperature           | 80AK                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | 80BK                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | All 80PK Probes          | 1            | 1           | 2               | 1                 | 1  | 1         | 1       | 2   | 1                | 2        | 2   | 2       | 1  |        | 1   | 1         | 1          | 1          |         |                |       |          |         |                     |         |         |     |     | 1       |     |         |         |     |         |       | 2    |      |   |
|                       | 80PJ-1/80PJ-9            |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      | 2    |   |
|                       | 80PT-25                  |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      | 2    |   |
|                       | 80TK                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | 80T-150U                 |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      | 2    |   |
|                       | 80PJ-EXT                 |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | 80PK-EXT                 | 1            | 1           | 2               | 1                 | 1  | 1         | 1       | 2   | 1                | 2        | 2   | 2       | 1  |        | 1   | 1         | 1          | 1          |         |                |       |          |         |                     |         |         |     |     | 1       |     |         |         |     |         |       | 2    |      |   |
|                       | 80PT-EXT                 |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      | 2 |
| 80CK-M                | 1                        | 1            | 2           | 1               | 1                 | 1  | 1         | 2       | 1   | 2                | 2        | 2   | 1       |    | 1      | 1   | 1         | 1          |            |         |                |       |          |         |                     |         |         |     | 1   |         |     |         |         |     |         |       | 2    |      |   |
| 80CJM                 |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      | 2    |   |
| 80PR-60               |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                | 66/68 |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      | 2    |   |
| Cases                 | C50                      |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                | 65    |          |         |                     |         |         |     |     |         |     |         |         |     |         | 787   |      |      |   |
|                       | C520                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C550/C1600               |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C12A                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C23                      |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                | 61    |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C25                      |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                | 61    |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C33                      |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C43                      |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C90                      |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C125                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| C789                  |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| C20                   |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| C101                  |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| Holsters              | C10                      | **           |             | **              |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | C70Y                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | H80M                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | H3                       |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | H5                       |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | H6                       |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | ToolPak Meter Hanger     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| Test Leads            | Standard Test Lead Input | U            | U           | U               | U                 | U  | U         | U       | U   | U                | U        | U   | U       | U  | U      | U   | U         | U          | U          | U       | U              | U     | U        | U       | U                   | U       | U       | U   | U   | U       | U   | U       | U       | U   | U       | U     | U    | U    |   |
|                       | TL220                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | TL223                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | TL225                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | TL238                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | TL80A                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | TL81A                    |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | TL71                     |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| TL76                  |                          |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| Specialty             | FlukeView Forms Software |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | PV350 (pressure)         |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | FOM (fiber optic)        |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
|                       | CO-210                   |              |             |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |
| 80K-6, 80K-15, 80K-40 | dc                       | dc           | dc          |                 |                   |    |           |         |     |                  |          |     |         |    |        |     |           |            |            |         |                |       |          |         |                     |         |         |     |     |         |     |         |         |     |         |       |      |      |   |

(1) Requires 80TK (2) Requires 80AK (3) Limited low level ac capability - see page 40 (4) Requires PM9081/001 Adapter (5) Requires PM9082/001 adapter

U A universal accessory. Works with most brands of meters. For detailed Current Clamp specifications see pages 58 and 59. \*included with the 12B and 16 \*\* 53, 54 only

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

# Fluke accessory sets and kits

FLUKE®

**Combines our most popular accessories into a convenient money saving package**



## **New! TL225 SureGrip™ Stray Voltage Adapter Test Lead Kit**

- **Stray Voltage Adapter**
- **TL224** Suregrip Silicone Test Leads
- **TP220** Suregrip Test Probes
- **C75** Soft Accessory Case



## **TLK281 Automotive Test Lead Kit**

- **TP81** Insulation Piercing Probes
- **TL224** Suregrip Silicone Test Leads
- **TP220** Suregrip Test Probes
- **AC220** Suregrip Plunger Style Alligator Clips
- **AC285** Suregrip Alligator Clips
- **Handy Fluke carrying case**
- **TP81** rated to 60 V dc; all others rated to CAT III 1000 V, CAT IV 600 V



## **TLK282 Deluxe Automotive Test Lead Kit**

- **TP81** Insulation Piercing Probes
- **Set of five TP40 Automotive Back Probe Pins**
- **TL224** Suregrip Silicone Test Leads
- **TP220** Suregrip Test Probes
- **AC220** Suregrip Plunger Style Alligator Clips
- **AC285** Suregrip Alligator Clips
- **C280** Suregrip Hook Clips
- **Handy Fluke carrying case**
- **TP81** and **TP40** rated to 60 V dc; all others rated to CAT III 1000 V, CAT IV 600 V



## **TLK-220 SureGrip™ Accessory Kit with Meter Carry Case**

- **AC220** Plunger Style Alligator Clips
- **AC285** Large Jaw Alligator Clips
- **TP220** Sharp Test Probes
- **TL224** Right to Straight Test Leads
- **Zippered vinyl carry case with moveable divider**
- **Holds large DMMs**

## **TLK-225 SureGrip™ Master Accessory Kit**

- **AC220** Plunger Style Alligator Clips
- **AC280** Plunger Style Hook Clips
- **AC283** Plunger Style Pincer Clips
- **AC285** Large Jaw Alligator Clips
- **TP220** Sharp Test Probes
- **TL224** Right to Straight Test Leads
- **6-pocket storage pouch, keeps the entire set together**



## **T5 Tester Starter Kit**

Getting started kit for electricians who already own a Fluke T5 Tester.

- **TP220** Test Probes
- **AC285** Large Jaw Alligator Clips
- **C33** Zippered Soft Case



## **TL238 SureGrip™ Test Lead Set for high energy environments**

- **Insulated tip probes help lessen risk of arc flash explosion**
- **Probe extenders keep hands away from live current**
- **Includes one pair each, insulated test tip probes, probe extenders and TL224 test leads**
- **Probes and leads CAT III 1000 V, CAT IV 600 V, 10 A, extenders CAT III 1000 V 10 A**



## **TL220 Industrial Test Lead Set**

- **Starter kit for industrial applications**
- **TP220 has round, stainless steel tip**
- **Includes 1 pair: AC220, TP220, TL222**
- **CAT III 1000 V, CAT IV 600 V, 10 A**



## **TL223 Electrical Test Lead Set**

- **Starter kit for electrical applications**
- **TP1 has flat blades for wall sockets**
- **Includes 1 pair: AC220, TP1, TL224**
- **CAT III 1000 V, CAT IV 600 V, 10 A**

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)



Residential



Industrial



Commercial



Electrical



HVAC/IAQ



Process



Electronic

# Fluke SureGrip™ accessories

FLUKE®

**A complete set of probes, leads and clips**

## Modular test leads and test probes (use test probes with test leads)

### TL221 SureGrip™ Silicone Test Lead Extension Kit

- Superior strain relief
- Includes two adapters to extend leads 1.5 m
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

### TL222 SureGrip™ Silicone Insulated Test Leads

- Recommended for use with AC220, AC280, AC283 test clips
- Superior strain relief
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

### TL224 SureGrip™ Silicone Insulated Test Leads

- 1.5 m silicone-insulated wire resists heat and cold
- Superior strain relief
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

### TL27 Heavy Duty Test Leads

- Rugged EPDM insulation
- 1.5 m long with shrouded, straight connectors and excellent strain reliefs on each end
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

### TP1, TP2, TP4 and TP38 Slim Reach™ Test Probes

- Slender probe bodies for probing closely spaced or recessed points
- TP1 has a flat blade
- TP2 has 2 mm diameter tip
- TP4 has 4 mm diameter tip
- TP38 has stainless steel insulated probe to help lessen the risk of arc flash explosion
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

### TP220 SureGrip™ Industrial Test Probes

- Sharp, 1/2 in. stainless steel tip provides reliable contact
- Flexible finger barrier improves grip
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

## Push-on clips

### AC72 Alligator Clips

- Slide-on style for test probes
- Jaws open to 8 mm
- For use with TL71 and TL75 test lead and probe sets
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

## Modular clips (for use with test leads)

### AC220 SureGrip™ Alligator Clips

- Insulated, nickel plated jaws grip objects up to 3/8 in.
- Blunt tip grabs round screw heads
- CAT III 1000 V, CAT IV 600 V, 10 A

### AC280 SureGrip™ Hook Clips

- Profile narrows to .22 in. at tip
- Hook opening .20 in. at front, .08 in. at base
- CAT III 1000 V, CAT IV 600 V, 3 A

### AC283 SureGrip™ Pincer Clips

- 4.5 in. flexible, insulated shaft
- Nickel plated pincers open to .20 in.
- CAT III 1000 V, CAT IV 600 V, 1 A

### AC285 SureGrip™ Alligator Clips

- Multi-purpose tooth pattern grips anything from fine gauge wire to a 3/4 in. nut
- Nickel-plated steel jaws
- CAT III 1000 V, CAT IV 600 V, 10 A

### AC89 Heavy Duty Insulation Piercing Clip

- Plunger style, safety grip operation with insulated jaws
- Small pin pierces 30 to 14 AWG insulated wire
- CAT III 1000 V, 5 A, CAT IV 600 V, 5 A

### AC87 Heavy Duty Bus Bar Clip Set

- One pair (red, black) of flat, right angle design for connecting to bus bars
- Adjustable collar provides two ranges of jaw openings up to 30 mm
- CAT III 1000 V, 5 A rating



SureGrip accessories provide a reliable grip in slippery hands. Rubber-overmolded surfaces and finger-hugging curves give the user a comfortable, steady hold on the accessory so they can focus on making an accurate measurement.

## Test lead and probe in one

### TL71 Premium DMM Test Lead Set

- Flexible silicone insulated leads are heat and cold resistant
- Distinctive comfort grip probes
- Recommended for  $\mu$ V measurements
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A

### TL28A Automotive Test Lead Set

- Large, solid copper alligator clips with 0.5 in. opening
- Flexible silicone insulated lead are heat and cold resistant
- CAT I 30 V, 10 A


### TL76 2 mm/4 mm Test Lead Set

- 2 mm threaded probes with removable 4 mm banana-style spring contacts
- Flexible 1.5 m silicone leads
- CAT III 1000 V, CAT IV 600 V, 10 A

### TL75 Hard Point Test Lead Set

- Extremely hard alloy tips resist wear
- Distinctive comfort grip probes
- CAT III 1000 V, 10 A, CAT IV 600 V, 10 A
- 1.5 m PVC leads

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)



# Fluke test leads, probes and clips

FLUKE®

Test leads for all your measurement needs

## For electronic applications



### TL80A Basic Electronic Test Lead Set

- 6 piece set with zippered case
- Probes, alligator clips and tip extenders for electronic applications
- CAT II 300 V



### TL910 Electronic Test Probes with Replacement Tips

- Small profile provides accessibility
- Comes with 5 sets of replaceable tips
- Replacement tips: TP912
- CAT III 1000 V, 3 A



### TL81A Deluxe Electronic Test Lead Set

- 22 piece set with quadfold pouch
- Includes mini alligator clips, hooks and pincers for virtually every electronic need
- Slide-on IC probe tip adapter and test lead couplers
- Both modular test leads and lead-probe combinations
- CAT II 300 V



### TP80 Electronic Test Probes

- Tapered tip ideal for probing electronic components or boards
- Removable guard for IC probing
- CAT III 1000 V, 10 A



### TP920 Test Probe Adapter Kit

- IC test tip adapters, extended tips, medium alligator clips fit over TL71 and TL75 test lead sets
- IC test tip Adapter, 3 A
- Extended probe tip, 3 A
- Med. alligator clip, 5 A
- CAT II 300 V



### TL40 Retractable Probe Assembly

- Retractable, insulated sharp probe tip
- CAT II 300 V, 2 A



### TL26A Telecom Test Lead Set

- 5-way multipoint test clips for telecommunications applications
- Flexible silicone insulated leads are heat and cold resistant
- CAT I 30 V, 8 A

## For automotive applications




### New! TP81, TP82 and TP84

New piercing probes for Automotive applications. Control the depth as you pierce insulation.

- Stainless steel probe pierces insulation on 14, 16 and 18 gauge wire
- Design provides complete insulation while working on fuel injectors or sensors
- TP81 for use with modular test leads (Fluke TL224)
- TP82 slips over probe tips (Fluke TL71)
- TP84 is 12 inches long to reach farther into engine compartments.
- Rated to 60 V dc

### New! TP83 Rigid Backprobe Pin Set

- 2 inch long pins pass between the weather pack seal and wire
- Use with Fluke TL71 or TL75 test lead sets
- Rated to 60 V dc



### New! TP40 Automotive Back Probe Pin Set

- Set of five 1.5 inch pins Rated to 60 V dc
- Provide an easy connection past weather pack seals to connector conductors
- Use with Fluke TL71 or TL75 test lead sets



### New! TL82 Automotive Pin & Socket Adapter Set

- Collection of male and female adapters allows you to make firm connection to pin and socket connectors
- Adapters with flexible tips come in the following sizes: 22, 20, 16 and 12
- Rated to 60 V dc

## High-voltage probes

### 80K-6, 80K-15, 80K-40 High Voltage Probes

- Allows a digital multimeter to measure up to 6,000 volts peak, 15,000 volts peak and 40,000 volts peak respectively
- 1000:1 division ratio output when connected to 10 M $\Omega$  multimeter
- Ground clip included
- Intended for low energy applications that are referenced to ground
- 80K-15 (not available in Europe)

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

Accessories



Residential



Industrial



Commercial



Electrical



HVAC/IAQ



Process



Electronic

# Fluke illuminates the task at hand

FLUKE®

Get all the light you need and keep your hands free

Shed light on the point of contact

## LVD1 Volt Light

Non-contact ac voltage detector and LED flashlight combined in one convenient, compact design. Exclusive dual-sensitivity.

- Detects voltages from 40 V ac to 300 V ac
- Voltage detector glows blue at 50 Hz to 60 Hz or 2.5 cm to 38 cm (1 in to 5 in) away from source
- Ultra-bright white LED with 100,000 hour bulb life
- AAA battery included



## L211 Probe Light Kit

- **L200** probe light
- **TL71** premium DMM test lead set
- **C75** zippered case



## L205 Mini Hat Light

Rugged, high-intensity Xenon worklight

- Attaches to a baseball cap
- Includes a hat clip
- Includes two AAA batteries
- Waterproof



## L200 Probe Light

- Small, rugged light easily attaches to any Fluke test probe
- Bright white LED never burns out
- 120-hours of battery life
- Two 3 V watch batteries included



## L215 SureGrip™ Kit with Probe Light and Probe Extenders

- **L200** probe light
- **TP220** SureGrip test probes
- **TL224** SureGrip test leads
- **TP280** test probe extenders
- Soft foldable pouch, keeps the entire set together



## L207 High-Intensity Light with Limited Edition Fluke Cap

- Includes L205 Mini Xenon worklight
- Black baseball-style cap with Fluke logo
- Light is waterproof
- Includes two AAA batteries



## L206 Deluxe LED Hat Light (hard hat not included)

Attach it to a hard hat, a baseball cap, or even a panel door for all the light you need

- Three super bright white LEDs—never burn out
- Special hard-hat attachment included
- 40-hour battery life
- Includes three AAA batteries



## L210 Probe Light and Probe Extenders

- 8 in. probe extenders fit modular test probes
- Probe and extender length complies with NFPA recommendations
- Bright white LED illuminates contact area
- Probe light fits on extender or test probe

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

Accessories



Residential



Industrial



Commercial



Electrical



HVAC/IAQ



Process



Electronic

# Fluke specialty accessories and software

FLUKE®

Extend the utility of your multimeter

## Logging software



### FlukeView® Forms

Harness the power of the data logging function on your Fluke Digital Multimeter, Thermometer or ProcessMeter. Log live readings while connected to a PC, or leave your Fluke 189, 789 or 54-II in place to capture up to 1,000 readings for download to a PC. FlukeView® Forms easy-to-use wizards allow you to download readings from your Fluke tool and store and display individual readings or a series of measurements. Spot trends and document interruptions or spikes. Use standard forms or the FlukeView® Designer feature to customize reports using your specific data or company logo. Free demo-reader download allows co-workers or clients to open your report and interact with captured data.

#### Choose the model that's right for you:

- FVF-SC1: Includes software and cable used with 53-II and 54-II Thermometers and 87IV and 89IV DMMs
- FVF-SC2: Includes software and cable used with 180 Series DMMs and 789 ProcessMeters
- FVF-SC3: Includes software and cable used with 45 Bench Meters

Go to [www.fluke.com/flukeviewforms](http://www.fluke.com/flukeviewforms) to download the demo.

### New! FlukeView® Forms Basic

An abridged version of FlukeView Forms. Analyze and share data with the provided standard forms. Available for use with 180 Series DMMs and 789 ProcessMeters, only. Upgrade to the full FlukeView Forms with FVF-UG.

## Make extended logging easier



### New! BP189 High Capacity Battery Pack for Fluke 180 Series Multimeters

- Expands battery life up to 450 hours
- Accepts four C batteries
- Allows you to use your Fluke 189 to continually log data for up to two weeks

## Stray voltage



### New! SV225/10PAK

- Pack of 10 stray voltage adapters
- Adapter makes sure meter has low input impedance that eliminates stray voltage

## Pressure and vacuum



### PV350 Pressure Vacuum Module

- Digital pressure and vacuum measurements in a single module
- Measures HVAC/R, hydraulic and pneumatic pressures to 350 psig/2413 kPa (usable to 500 psig)
- Measures to 76 cm Hg (29.9 in Hg) vacuum (not intended for measuring microns of vacuum)
- Compatible with most popular digital multimeters

## Fiber optics



### FOM Fiber Optic Meter

The Fluke Fiber Optic Meter (FOM) helps you test and maintain fiber optic cable without having to buy a whole new meter. Plug the FOM directly into any DMM with a mV dc function and a 10 mΩ input impedance, and quickly and accurately verify fiber optic cable system loss. Light sources and patch cords sold separately.



### FOS 850 and FOS 850/1300 Fiber Optic Light Sources

A variety of LED light sources allow you to test different cables.



### H900 Test Lead Holder

- Heavy duty construction with mounting holes
- Holder has 10 slots for wires up to 8 mm in diameter
- Over-all dimensions: 27.9 cm L x 8.9 cm W x 3.2 cm H
- One-year warranty

# Fluke current clamps


For use with DMMs, scopeMeters and power quality analyzers

## AC current clamp specifications

|                                 | i200                          | i200s                       | i400                           | i400s                                                               | 80i-600A                                                                           | i1000s                                                                                  | i2000 flex                                              | i3000s flex                                                                       |
|---------------------------------|-------------------------------|-----------------------------|--------------------------------|---------------------------------------------------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------|-----------------------------------------------------------------------------------|
| AC current range                | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 0.5 A to 400 A                                                      | 1 A to 600 A                                                                       | 0.2 A to 1000 A                                                                         | 2 A to 2000 A ac rms                                    | 1 A to 3000 A                                                                     |
| Accuracy                        | ≤ 3 % +0.5 A48 to 65 Hz       | ≤ 1 % +0.5 A 48 Hz to 65 Hz | 2 % + 0.06 A 45 Hz to 400 Hz   | .5 A to 40 A, 2 % + .015 A, 5 A to 400 A, 2 % + .04 A, 45 to 400 Hz | 2 % 50 Hz to 1 kHz 10 A to 100 A: 2 % +0.5 A 100 A to 1000 A: 1 % +1 A 48 to 65 Hz | 0.2 to 10 A: 3 % +0.1 A 10 A to 100 A: 2 % +0.5 A 100 A to 1000 A: 1 % +1 A 48 to 65 Hz | ± 1 % of range 45 to 65 Hz Ranges: 20 A, 200 A, 2000 A* | 1 to 30 A: 2 % + 0.1 A 1 to 300 A: 2 % + 0.5 A 1 to 3000 A: 2 % + 2 A 48 to 65 Hz |
| Bandwidth (-3 dB)               | 40 Hz to 40 kHz               | 40 Hz to 40 kHz             | 5 kHz to 20 kHz                | 5 Hz to 10 kHz                                                      | 10 Hz to 50 kHz                                                                    | 5 Hz to 100 kHz                                                                         | 10 Hz to 20 kHz                                         | 10 Hz to 100 kHz                                                                  |
| Maximum conductor diameter      | 20 mm (0.8 in)                | 20 mm (0.8 in)              | 32 mm (1.25 in)                | 32 mm (1.25 in)                                                     | 50 mm (1.98 in)                                                                    | 54 mm (2.13 in)                                                                         | 177 mm (7 in)                                           | 64 x 100 mm (2.52 x 3.94 in)                                                      |
| Maximum conductor size          | 300 MCM                       | 300 MCM                     | 750 MCM                        | 750 MCM                                                             | 2-500 MCM or 1-1000 MCM                                                            | 2-500 MCM or 1-1000 MCM                                                                 | 60 mm (2.4 in) circumference                            | 610 mm or 915 mm                                                                  |
| Output levels                   | 1 mA/A                        | 10 mV/A 100 mV/A            | 1 mA/A                         | 10 mV/A 1 mV/A                                                      | 1 mA/A 10 mV/A                                                                     | 1 mV/A 10 mV/A 100 mV/A                                                                 | 100 mV/A 10 mV/A 1 mV/A                                 | 10 mV/A 1 mV/A 0.1 mV/A                                                           |
| Output cable                    | 1.5 m shrouded banana plugs   | 2 m to BNC termination      | 1.5 m shrouded banana plugs    | 2.5 m to BNC termination                                            | 1.2 m shrouded banana plugs                                                        | 1.6 m to BNC termination                                                                | 2 m with double shrouded banana plugs                   | 2.1 m to BNC termination                                                          |
| Warranty                        | One-year                      | One-year                    | One-year                       | One-year                                                            | One-year                                                                           | One-year                                                                                | One-year                                                | One-year                                                                          |
| Safety rating                   | CAT III 600 V                 | CAT III 600 V               | CAT III 1000 V CAT IV 600 V    | CAT III 1000 V CAT IV 600 V                                         | CAT III 600 V                                                                      | CAT III 600 V                                                                           | CAT III 600 V                                           | CAT III 600 V                                                                     |
| Meter compatibility             | AC range                      |                             |                                |                                                                     |                                                                                    |                                                                                         |                                                         |                                                                                   |
| 10/11/12/12B/16/18              |                               | 1 A to 200 A                |                                | 1 A to 400 A                                                        |                                                                                    | 0.1 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 110/111/112                     |                               | 3 A to 200 A                |                                | 30 A to 400 A                                                       |                                                                                    | 3 A to 1000 A*                                                                          | 30 A to 2000 A                                          | 30 A to 3000 A                                                                    |
| 114/115/116/117                 | 60 A to 200 A (115, 117 only) | 1 A to 200 A ac             | 60 A to 400 A (115, 117 only)  | 0.6 A to 400 A ac*                                                  | 60 A to 600 A                                                                      | 0.2 A to 1000 A ac*                                                                     | 4 A to 2000 A ac                                        | 1 A to 3000 A ac                                                                  |
| 21/23/73/75/77 Series III       | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.1 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 26/79 Series III                | 1 A to 40 A                   | 1 A to 200 A                | 1 A to 40 A and 200 A to 400 A | 1 A to 400 A                                                        | 1 A to 40 A and 200 A to 600 A                                                     | 0.2 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 2 A to 3000 A                                                                     |
| 27                              | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.1 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 70 Series III                   |                               | 1 A to 200 A                |                                | 1 A to 400 A                                                        |                                                                                    | 0.1 A to 1000 s*                                                                        | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 175/177/179                     | 3 A to 200 A                  | 1 A to 200 A                | 3 A to 400 A                   | 3 A to 400 A*                                                       | 3 A to 600 A                                                                       | 0.3 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 3 A to 3000 A                                                                     |
| 1577/1587 Insulation Meter      | 3 A to 200 A                  | 1 A to 200 A                | 3 A to 400 A                   | 3 A to 400 A*                                                       | 3 A to 600 A                                                                       | 0.3 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 3 A to 3000 A                                                                     |
| 83-III, 83-V, 88V               | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.1 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 85/87 Series III 87 Series V    | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.2 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 2 A to 3000 A                                                                     |
| 87/89 Series IV 187/189         | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.1 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 8060A/8062A DMMs                | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.2 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 2 A to 3000 A                                                                     |
| 860 Series Graphical Multimeter | 1 A to 200 A                  | 1 A to 200 A                | 1 A to 400 A                   | 1 A to 400 A                                                        | 1 A to 600 A                                                                       | 0.3 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 3 A to 3000 A                                                                     |
| 43B Power Meter                 |                               | 1 A to 200 A <sup>1</sup>   |                                | 0.35 A to 400 A                                                     |                                                                                    | 0.1 A to 1000 A <sup>1</sup>                                                            | 4 A to 2000 A <sup>1</sup>                              | 1 A to 3000 A <sup>1</sup>                                                        |
| 433/434 Power Quality           |                               | 1 A to 200 A                |                                | 1 A to 400 A                                                        |                                                                                    | 0.3 A to 1000 A                                                                         | 5 A to 2000 A                                           | 1.2 A to 3000 A                                                                   |
| 9X ScopeMeter                   |                               | 1 A to 200 A                |                                | 1 A to 400 A                                                        |                                                                                    | 0.1 A to 1000 A                                                                         | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 123/124 ScopeMeter              |                               | 1 A to 200 A                |                                | 1 A to 400 A                                                        |                                                                                    | 0.25 A to 1000 A                                                                        | 4.5 A to 2000 A                                         | 2.5 A to 3000 A                                                                   |
| 190 Series ScopeMeter           |                               | 1 A to 200 A                |                                | 1 A to 400 A                                                        |                                                                                    | 0.1 A to 1000 A                                                                         | 4 A to 2000 A                                           | 1 A to 3000 A                                                                     |
| 45 DMM                          | 1.5 A to 100 A                | 1 A to 200 A                | 1.5 A to 100 A                 | 1 A to 400 A                                                        | 1.5 A to 100 A and 500 A to 600 A                                                  | 0.15 A to 1000 A*                                                                       | 4 A to 2000 A                                           | 1.5 A to 3000 A                                                                   |
| 74X Series Process Calibrators  |                               | 1.1 A to 200 A              |                                | 1.1 A to 400 A                                                      |                                                                                    | 1.1 A to 1000 A*                                                                        | 11 A to 2000 A                                          | 11 A to 3000 A                                                                    |
| 787/789 ProcessMeter            | 50 A to 200 A                 | 1 A to 200 A                | 50 A to 400 A                  | 1 A to 400 A                                                        | 50 A to 440 A                                                                      | 0.2 A to 1000 A*                                                                        | 4 A to 2000 A                                           | 2 A to 3000 A                                                                     |

<sup>1</sup> Current and watt readings will be multiples of 10 higher or lower than actual.  
\* Requires PM9081/001 or BP880 Adapters

## AC only models



i200s



i400s



80i-600A



i1000s



i2000 flex



i3000s flex

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

## Accessories

# Fluke current clamps

**For use with DMMs, ScopeMeters  
and Power Quality Analyzers**

## AC/DC current clamp specifications

|                            | 80i-110s                                                                                   | i410                                      | i1010                                   | i30                                      | i30s                         |
|----------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------|-----------------------------------------|------------------------------------------|------------------------------|
| DC range                   | 0.1 A to 100 A                                                                             | 1 to 400 A                                | 1 to 1000 A                             | 4 mA to 20 A                             | 4 mA to 20 A                 |
| AC range                   | 0.1 A to 70 A                                                                              | 1 A to 400 A                              | 1 A to 600 A                            | 4 mA to 20 A rms                         | 4 mA to 20 A rms             |
| Accuracy                   | 0.1 A to 10 A; dc to 1 kHz: $\pm 3\%$ + 50 mA; up to 100 A add 15 %; up to 20 kHz add 12 % | 3.5 % + 0.5 A for dc or ac (45 to 400 Hz) | 2 % + 0.5 A for dc or ac (45 to 400 Hz) | $\pm 1\% \pm 2$ mA                       | $\pm 1\% \pm 2$ mA           |
| Bandwidth (-3 dB)          | 100 kHz                                                                                    | 3 kHz                                     | 10 kHz                                  | dc to 20 kHz (-0.5 dB)                   | dc to 100 kHz (-0.5 dB)      |
| Zero error adjustment      | Yes                                                                                        | Yes                                       | Yes                                     | Yes                                      | Yes                          |
| Maximum conductor diameter | 11.8 mm (0.46 in)                                                                          | 30 mm (1.18 in)                           | 30 mm (1.18 in)                         | 19 mm (0.75 in)                          | 19 mm (0.75 in)              |
| Maximum conductor size     | 1 AWG                                                                                      | 750 MCM or 2-500 MCM                      | 750 MCM or 2-500 MCM                    | 250 MCM                                  | 250 MCM                      |
| Output levels              | 10 mV/A, 100 mV/A                                                                          | 1 mV/A                                    | 1 mV/A                                  | 100 mV/A                                 | 100 mV/A                     |
| Output cable               | 1.6 meter with BNC termination                                                             | 1.2 meter with shrouded banana plugs      | 1.2 meter with shrouded banana plugs    | 1.5 meter with shrouded dual banana plug | 2 meter with BNC termination |
| Battery life               | 40 hours                                                                                   | 60 hours                                  | 60 hours                                | 30 hours                                 | 30 hours                     |
| Warranty                   | One-year                                                                                   | One-year                                  | One-year                                | One-year                                 | One-year                     |
| Safety                     | CAT II 600 V; CAT III 300 V                                                                | CAT III 600 V                             | CAT III 600 V                           | CAT III 300 V                            | CAT III 300 V                |

\* Requires PM9081/001 Adapter

\*\* Requires PM9082/001 Adapter

## Power quality ac combo packs for 4-phase current measurements

**Buy  
Combo Pack  
and Save**




i430flex 4-pack



i5sPQ3

## AC/DC models



80i-110s



i410



i1010

## i30s and i30 Hall Effect AC/DC Current Clamps

- Use with multimeters or recorders for non-intrusive current measurements

**New**



i30s



i30

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)


# Fluke temperature accessories

FLUKE®

## Hot probes with cool designs

### SureGrip™ temperature accessories

The innovative SureGrip™ design from Fluke is now available in select temperature probes. The soft rubber handle combined with a new ergonomic shape is so comfortable to hold that you'll forget about the probe and focus on the measurement. All SureGrip probes have an improved, more flexible strain relief for a long life.



Soft rubber handle provides a secure grip

Cleans up with soap and water



### The right tool for the job


Make better temperature measurements with a probe designed for your application. The 80PK-8 pipe clamp probe (shown) is specifically designed for measuring pipe temperatures, calculating superheat and sub-cooling for refrigeration troubleshooting. Other special purpose probes shown are designed for making quick surface, fluid and air temperature measurements. The piercing probe makes it possible to make temperature measurements below the surface of a soft object. To enable your Fluke DMM or 50 Series II thermometer to make its' best possible measurements, chose the correct probe from the selection guide below.

|                    | Bead                                                                                | Bead                                                                                | HVAC                                                                                | Immersion                                                                           | Surface                                                                             | Air                                                                                 | Piercing                                                                             | General purpose                                                                       | Industrial surface                                                                    | Pipe clamp                                                                            |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                    |  |  |  |  |  |  |  |  |  |  |
|                    | 80BK                                                                                | 80PK-1<br>80PJ-1                                                                    | 80PK-11                                                                             | 80PK-22                                                                             | 80PK-3A                                                                             | 80PK-24                                                                             | 80PK-25<br>80PT-25                                                                   | 80PK-26                                                                               | 80PK-27                                                                               | 80PK-8                                                                                |
| Lowest temp        | -40 °C (-40 °F)                                                                     |                                                                                     | -30 °C (-22 °F)                                                                     | -40 °C (-40 °F)                                                                     | 0 °C (32 °F)                                                                        | -40 °C (-40 °F)                                                                     | K Type: -40 °C (-40 °F)<br>T Type: -196 °C (-321 °F)                                 | -40 °C (-40 °F)                                                                       | -127 °C (-196 °F)                                                                     | -29 °C (-20 °F)                                                                       |
| Highest temp       | 260 °C (500 °F)                                                                     |                                                                                     | 105 °C (221 °F)                                                                     | 1090 °C (1994 °F)                                                                   | 260 °C (500 °F)                                                                     | 816 °C (1500 °F)                                                                    | 350 °C (662 °F)                                                                      | 816 °C (1500 °F)                                                                      | 600 °C (1112 °F)                                                                      | 149 °C (300 °F)                                                                       |
| Probe material     | K type wire with teflon insulation                                                  |                                                                                     | Velcro                                                                              | Inconel 600                                                                         | K type sensor with teflon body                                                      | Inconel                                                                             | 316 Stainless Steel                                                                  | 304 Stainless Steel                                                                   |                                                                                       | K type sensor with pvc body                                                           |
| Probe length       | 1 m Lead Wire                                                                       |                                                                                     | 19 m Velcro cuff                                                                    | 21.27 cm (8.375 in)                                                                 | 9.525 cm (3.75 in)                                                                  | 21.59 cm (8.5 in)                                                                   | 10.16 cm (4 in)                                                                      | 21.57 cm (8.5 in)                                                                     | 20.32 cm (8 in)                                                                       | for pipes from 6.4 mm (.25 in) to 34.9 mm (1.375 in)                                  |
| Cable length       | 1 m (39 in)                                                                         |                                                                                     |                                                                                     |                                                                                     | 1.3 m (4 ft)                                                                        | 1 m (39 in)                                                                         |                                                                                      |                                                                                       |                                                                                       |                                                                                       |
| Connection         | Standard Banana Jack                                                                | Molded Thermocouple Plug                                                            |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |                                                                                       |                                                                                       |
| SureGrip handle    | No                                                                                  | No                                                                                  | No                                                                                  | Yes                                                                                 | No                                                                                  | Yes                                                                                 | Yes                                                                                  | Yes                                                                                   | Yes                                                                                   | No                                                                                    |
| Key feature        | Ideal for initial troubleshooting. Can be secured in place with a magnet.           |                                                                                     | Velcro probe allows hands free temperature measurement.                             | For use in liquids or in gels.                                                      | Exposed junction for direct contact with flat or slightly convex surfaces.          | Perforated baffle for air and non-caustic gas measurements                          | Probe material safe for use in foods. Sharp tip pierces solid surfaces..             | Use for general purpose air or surface measurements                                   | Low conductivity stainless steel minimizes thermal shunt-ing. Extra rugged.           | Clamps securely to pipe. Measurements are repeat-able to 0.56 °C (1 °F).              |
| Thermocouple types | K                                                                                   | K, J                                                                                | K                                                                                   | K                                                                                   |                                                                                     |                                                                                     | K, T                                                                                 | K                                                                                     |                                                                                       |                                                                                       |
| Typical use        |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |                                                                                       |                                                                                       |
| General purpose    | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                    | •                                                                                     | •                                                                                     | •                                                                                     |
| HVAC               |                                                                                     | •                                                                                   | •                                                                                   |                                                                                     | •                                                                                   | •                                                                                   |                                                                                      | •                                                                                     |                                                                                       | •                                                                                     |
| Food service       |                                                                                     |                                                                                     |                                                                                     | •                                                                                   |                                                                                     |                                                                                     | •                                                                                    |                                                                                       |                                                                                       |                                                                                       |
| Industrial         | •                                                                                   | •                                                                                   | •                                                                                   |                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       | •                                                                                     | •                                                                                     |
| Residential        | •                                                                                   | •                                                                                   |                                                                                     |                                                                                     | •                                                                                   | •                                                                                   | •                                                                                    |                                                                                       |                                                                                       |                                                                                       |
| Commercial         | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                   | •                                                                                    | •                                                                                     | •                                                                                     | •                                                                                     |

Use an 80AK adapter with meters with temperature function such as the 16, 78, 83V, 87V, 88V, 179, 187 and 189  
The 80TK enables your meter to read temperature using mV (see the Accessory selection guide on page 60 for meters)  
For the Fluke Thermometer, 51, 52, 53, and 54 III, no adapter is necessary for thermocouple types K, J, T and E

For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

Accessories



# Fluke Temperature accessories

FLUKE®

Turn your digital multimeter into a thermometer

## Other temperature accessories

### 80TK Thermocouple Module

- Converts K-Type thermocouple signals into mV output
- Connects to DMM via standard banana plugs
- Switch selectable °C or °F
- Range: -50 °C to 1000 °C (-58 °F to 1832 °F)
- Includes 80PK-1 probe



### 80T-150U Universal Solid State Temperature Probe

- For measurement of air, surface and non-corrosive materials
- Measurement range: -50 °C to 150 °C (-58 °F to 302 °F)
- Output: 1 mV/°C or 1 mV/°F (switch selectable)
- Connects to DMM via standard banana plugs




### 80AK DMM Adapter

- Adapts K-type thermocouple mini-connector to dual banana plug inputs
- Compatible with all Fluke DMMs with temperature measurement functions
- Measurement range and accuracy is not affected by the 80AK adapter



### 80BK Integrated DMM Temperature Probe

- Compatible with all Fluke DMMs with temperature measurement functions
- K-Type thermocouple with standard banana jack
- Convenient one-piece construction
- Measurement range: -40 °C to 260 °C (-40 °F to 500 °F)



### 80CK-M and 80CJ-M Type K and J Male Mini-Connectors

- Isothermal screw terminal for K or J wire
- Suitable for up to 20 gauge thermocouple wire
- Color coded to industry standards (K-yellow, J-black)
- Two per package



### 80PJ-EXT, 80PK-EXT, 80PT-EXT Thermocouple Wire Extension Kits


- For extending and repairing J, K or T-type thermocouple wires.
- Kit includes 3 m (approx. 9 ft.) of thermocouple wire and 1 pair of male/female mini-connectors
- Maximum continuous exposure temperature: 260 °C (500 °F)
- 80PK-EXT is compatible with K-type thermometers; 80PJ-EXT is designed for J-Type thermometers, and 80PT-EXT is designed for T-type thermometers



## Thermocouple Plug Kits


### 700TC1

- A kit of 10 mini-plug connectors. One each of the following: Type J (black), Type K (yellow), Type T (blue), Type E (purple), Type R/S (green), Type B or Cu (white), Type L (J-DIN) (blue), Type U (T-DIN) (brown), Type C (red), Type N (orange)



### 700TC2

- A kit of 7 mini-plug connectors. Type J (black), two Type K (yellow), two Type E (purple), one Type T (blue), one Type R/S (green), one



## New!

### 80PR-60 RTD Temperature Probe

- Resistance temperature detector probe designed to add contact measurements to your Fluke 66 and 68 Non-Contact Infrared Thermometers
- Measurement range: -40 °C to 260 °C (-40 °F to 500 °F)
- 3.5 mm phono type jack is only appropriate for Fluke 66 and 68 Thermometers



## Process tools accessories

### BP7217

- NiCd rechargeable battery; nominal 7.2 volt, 1700 mA hr
- Use in 867B meters or 700 and 740 Series Calibrators



### BP7235

- NiMH rechargeable battery; nominal 7.2 Volt, 3500 mA hr
- Use in 700 and 740 Series Calibrators



### 700LTP Low Pressure Test Pump

The Fluke 700LTP is designed to generate either vacuum to -12 psi/-0.85 bar or pressures to 30 psi/2000 mbar. The Fluke 700 LTP is primarily intended for low pressure applications.



### 700ILF In-line Filter

The Fluke 700ILF can be used to isolate the calibrator from incidental contact with fluids. Particularly useful with the 718 calibrator to help keep moisture or oils from contaminating the on-board pump.



### 700PTP Pneumatic Test Pump

The 700PTP is a handheld pressure pump designed to generate either vacuum to -11.6 psi/-0.8 bar or pressure to 600 psi/25 bar.



### 700HTP Hydraulic Test Pump

The 700HTP is designed to generate pressures up to 10,000 psi/700 bar. Use the Fluke-700PRV adjustable relief valves to limit pressures to 1360 psi and 5450 psi.



### 700HTH Hydraulic Test Hose

The 700HTH is a 10,000 psi, 700 bar test hose that connects to a calibration unit under test from a Fluke 700HTP hydraulic test pump.



### 700PMP Pressure Pump

The 700PMP is a hand-operated pressure pump to provide pressures up to 150 psi/1000 kPa. Output fitting is 1/8 FNPT.



### Fluke 700-IV Current Shunt

Conversion factor: 10 mV = 1 mA  
Accuracy (% of input, 1 year): 0.025 %  
Input current: 0 to 55 mA  
Input resistance: 250 Ω nominal  
Output resistance: 10 Ω nominal  
Accuracy specification applies from +18 °C and 28 °C to 50 °C  
Maximum input voltage: 30 V dc



For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

# Fluke cases and holsters

A premium meter deserves a premium case

|                           | Premium cases                                                                     |                                                                                   | Soft cases                                                                                                                          |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     | Hard cases                                                                          |                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                           |  |  |                                                    |  |  |  |  |  |  |  |  |
|                           | C520A                                                                             | C510                                                                              | C25                                                                                                                                 | C50                                                                               | C90                                                                               | C12A                                                                              | C125                                                                              | C43                                                                                | C789                                                                                | C20                                                                                 | C101                                                                                |
|                           | Genuine top grade leather cowhide.                                                |                                                                                   | Zippered carrying cases protect your meter; most cases come with belt loops so your meter is stored conveniently on your tool belt. |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     | Tough polypropylene cases hold and protect meters and accessories.                  |                                                                                     |
| Dimensions                | 22.5 cm x 7.0 cm x 4.8 cm<br>(10 in x 3.125 in x 2.125 in)                        | 20.3 cm x 11.3 cm x 5.1 cm<br>(9 in x 5 in x 2.25 in)                             | 19.2 cm x 11 cm x 5.6 cm<br>(8.5 in x 4.9 in x 2.5 in)                                                                              | 16.9 cm x 8.5 cm x 3.4 cm<br>(7.5 in x 3.75 in x 1.5 in)                          | 19.2 cm x 7.9 cm x 5.6 cm<br>(8 in x 3.5 in x 2.5 in)                             | 15.1 cm x 11.3 cm x 3.4 cm<br>(6.7 in x 5 in x 1.5 in)                            | 23.7 cm x 13.5 cm x 5.6 cm<br>(10.5 in x 6 in x 2.5 in)                           | 30.4 cm x 19.7 cm x 6.7 cm<br>(13.5 in x 8.75 in x 3 in)                           | 27.0 cm x 22.5 cm x 6.7 cm<br>(12 in x 10 in x 3 in)                                | 22.5 cm x 13.5 cm x 9.0 cm<br>(10 in x 6 in x 4 in)                                 | 30.5 cm x 36 cm x 10.5 cm<br>(12 in x 14.2 in x 4.1 in)                             |
| <b>DMMs</b>               |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 10/11/12/12B              |                                                                                   | •                                                                                 |                                                                                                                                     |                                                                                   |                                                                                   | •                                                                                 |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 110/111/112               |                                                                                   | •                                                                                 |                                                                                                                                     | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 16                        |                                                                                   | •                                                                                 |                                                                                                                                     | •                                                                                 | •                                                                                 | •                                                                                 | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 21/23/26/75/77/79         |                                                                                   | •                                                                                 | •                                                                                                                                   |                                                                                   | •                                                                                 |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 27                        |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     | •                                                                                   | •                                                                                   |
| 70/73 III                 |                                                                                   | •                                                                                 | •                                                                                                                                   |                                                                                   | •                                                                                 |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 175/177                   |                                                                                   | •                                                                                 | •                                                                                                                                   |                                                                                   | •                                                                                 |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 179                       |                                                                                   | •                                                                                 | •                                                                                                                                   |                                                                                   | •                                                                                 |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 83/85/87 Series III       |                                                                                   | •                                                                                 | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  |                                                                                     |                                                                                     | •                                                                                   |
| 87/89 IV                  |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| 83/87 Series V            |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| 187/189                   |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  |                                                                                     | •                                                                                   | •                                                                                   |
| 867B                      |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    | •                                                                                   |                                                                                     |                                                                                     |
| <b>Clamp meters</b>       |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 321/322                   |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| <b>Insulation testers</b> |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 1503/1507<br>1577/1587    |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| <b>Thermometers</b>       |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 50S/50D                   |                                                                                   | •                                                                                 | •                                                                                                                                   | •                                                                                 | •                                                                                 |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 51/52/53/54 Series II     |                                                                                   | •                                                                                 | •                                                                                                                                   | •                                                                                 | •                                                                                 |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 61                        |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 65                        |                                                                                   | •                                                                                 |                                                                                                                                     | •                                                                                 | •                                                                                 |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| <b>Electrical testers</b> |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| T3/T5                     | •                                                                                 |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 7-600/7-300               |                                                                                   |                                                                                   |                                                                                                                                     | •                                                                                 |                                                                                   | •                                                                                 |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| <b>ScopeMeters</b>        |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 123/124                   |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  | •                                                                                   |                                                                                     | •                                                                                   |
| <b>Power quality</b>      |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 39/41B                    |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                  | •                                                                                   |                                                                                     |                                                                                     |
| <b>Process tools</b>      |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |                                                                                     |
| 70S/70T                   |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 712/713                   |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   | •                                                                                 |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 714/715/716/717           |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     | •                                                                                   |
| 725                       |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 |                                                                                    |                                                                                     | •                                                                                   | •                                                                                   |
| 741/743/744               |                                                                                   |                                                                                   |                                                                                                                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                  | •                                                                                   |                                                                                     |                                                                                     |
| 787                       | •                                                                                 | •                                                                                 | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  | •                                                                                   |                                                                                     | •                                                                                   |
| 789                       |                                                                                   |                                                                                   | •                                                                                                                                   |                                                                                   |                                                                                   |                                                                                   | •                                                                                 | •                                                                                  | •                                                                                   | •                                                                                   | •                                                                                   |

## C1600 Meter and Accessories Gear Box

This rugged, molded plastic case will carry Fluke digital multimeters, process calibrators and most Fluke accessories used for these meters.

- Deep interior large enough to hold and protect your gear
- Rubber gasket in lid seals out dust and keeps contents dry
- Lift out tray keeps everything organized



## C550 Tool Bag

- Steel reinforced frame
- Rugged ballistic cloth with heavy duty hardware
- Large zippered storage compartment with 25 pockets
- Weather resistant
- Carry all your tools to the job



## C75 Accessory Case

- Zippered carrying case with two inside pockets
- Carry test lead sets or probes



## H6 Infrared Thermometer Holster

- Durable nylon construction protects your thermometer while keeping it within reach
- For Fluke 63, 66 and 68 Infrared Thermometers



## H5 Electrical Tester Holster

- Rugged fabric holster includes flap for lead storage and built-in belt loop
- Fits Fluke T3 and T5 testers



## H3 Clamp Meter Holster

- Rugged fabric holster includes flap for lead storage and built-in belt loop
- For Fluke 320 and 330 Series Clamp Meters



For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

# Fluke holsters and fuses

Take care of your test tools—  
inside and out

## Protective meter holsters



### C10 Meter Holster

- Snap on yellow holster absorbs shocks and protects meter from rough handling
- Fits Fluke 10 Series DMMs



### C70Y Meter Holster

- Snap on yellow holster absorbs shocks and protects meter from rough handling
- Flex-Stand™ allows meter to hang, lean or stand for convenience and best viewing
- For Fluke 70 and 73 Meters



### H80M Protective Holster with magnetic strap

- Snap on holster absorbs shocks and protects meter from rough handling
- Magnetic strap solution makes it easy to hang your meter for hands free work
- For Fluke 80 Series DMMs, 710 Series and 787 calibration tools

## ToolPak™ Magnetic Meter Hanging Solution

- Free both hands to make measurements
- Hang your meter from metallic surfaces like panels and pipes
- Kit includes universal hanger clips (two), hook and loop straps (two lengths), adapter and strong magnet
- Attaches to back of many Fluke meters, including 110, 170, 180 Series, 87V and 83V DMMs, 724, 725 and 789 Process Calibrators, 70 Series III DMMs, 1503, 1507, 1577 and 1587 Insulation Multimeters and 50 Series II Digital Thermometers



## Fuse selection guide

Replacement fuses for Fluke DMMs are available from your distributor in 440 mA, 500 mA, 630 mA, 1 A, 2 A, 3 A, 11 A, and 15 A values. To order direct from Fluke call 1-888-99-FLUKE (U.S.) or contact your distributor.

| Model                                                                                                                                                    | Fuse requirements                                                                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| 21/23/75/77-II                                                                                                                                           | P/N 871173; 630 mA 250V fuse<br>P/N 892583; 15 A 600 V fuse                                     |
| 21-III/75-III 73-III                                                                                                                                     | P/N 871173; 630 mA 250 V fuse<br>P/N 803293 11 A 1000 V fuse                                    |
| 76/29/79-II<br>83/85/87/88 (S/N < 65650001)                                                                                                              | P/N 871207; 1 A 600 V fuse<br>P/N 892583; 15 A 600 V fuse                                       |
| 25/27 (S/N < 7247001)                                                                                                                                    | P/N 871173; 630 mA 250 V fuse<br>P/N 871202; 3A 600 V fuse<br>P/N 892583; 15A 600 V fuse        |
| 27 (S/N > 7247001)                                                                                                                                       | P/N 943121; 440 mA 1000 V fuse<br>P/N 803293; 11A 1000 V fuse                                   |
| 45 (S/N < 7211001)                                                                                                                                       | P/N 871181; 500 mA 250 V fuse<br>P/N 892583; 15 A 600 V fuse                                    |
| 45 (S/N > 7211001)                                                                                                                                       | P/N 871181; 500 mA 250 V fuse<br>P/N 943121; 440 mA 1000 V fuse<br>P/N 803293; 11 A 1000 V fuse |
| 73 and 73-II                                                                                                                                             | P/N 892583; 15 A 600 V fuse                                                                     |
| 863/865/867/867B<br>83/85/87 (S/N > 65650001)<br>87-IV/89-IV/187/189/<br>83-III/85-III/87-III/87E-III/83V/87V<br>23-III/77-III/26-III/79-III/175/177/179 | P/N 943121; 440 mA 1000 V fuse<br>P/N 803293; 11 A 1000 V fuse                                  |
| 111/112                                                                                                                                                  | P/N 803293; 11 A 1000 V fuse                                                                    |
| 712/713/714/715/716/717/718                                                                                                                              | P/N 686527; 125 mA 250 V fuse                                                                   |
| 724/725                                                                                                                                                  | P/N 2002234 (qty. 1); 50 mA 250 V fuse                                                          |
| 1577/1587                                                                                                                                                | P/N 943121; 440 mA 1000 V fuse                                                                  |
| 1503/1507                                                                                                                                                | P/N 2279339; 315 mA, 1000 V fuse                                                                |

## New! MeterCleaner Wipes

- Industrial strength cleaning formula removes surface dirt, oil and grease
- Safe on rubber
- Safe to the environment
- Comes in two sizes: 6-pack (MC6) and 50-pack (MC50)



## Verification tools

### IntelliTone 200 Kit

- IntelliTone digital processing eliminates noise and false signals
- New SmartTone™ analog toning precisely isolates individual wire pairs
- Locates cables safely and effectively on active networks
- Verifies twisted-pair installation with visual end-to-end continuity test
- Identifies, diagnoses, and troubleshoots datacom/telecom services



## Test the integrity of UTP, Coax, phone and security cabling using known standards.



### MicroScanner Pro

- The essential cable verification tester
- Measures length and distance to fault via true TDR (Time Domain Reflectometry)
- Pinpoints opens, shorts, reversed, crossed and split pairs
- Tests UTP, STP and coax cables
- Flashes hub and switch port lights
- Identifies active networking hubs and detects speed/duplex settings
- Analog tone generator with four song selections

### MicroMapper

- The fast, comprehensive LAN wiremap checker
- Tests twisted-pair cables for opens, shorts, crossed pairs, split pairs, or any miswires
- Verifies correct pin outs, wiremap



For more information and detailed specifications, go to [www.fluke.com/accessories](http://www.fluke.com/accessories)

# What's New from Fluke

**The new products to help keep you up and running**



## Fluke Ti20 Thermal Imager

The Fluke Ti20 Thermal Imager is an unbeatable solution for predictive maintenance and troubleshooting.

- Includes unlimited-use InsideIR™ companion software and professional training materials.
- Designed for industrial use. IP54-rated for use in dust and moisture filled environments.
- Follow easy, on-camera instructions each time you perform inspections (simply point, focus and pull the trigger) for fast and easy inspection routing.

**For more information, see page 48.**



## Fluke 117 Electrician's Digital Multimeter

The Fluke 117 is one of four new compact digital multimeters. Choose from models specifically designed for Commercial Electricians, HVAC/R Technicians and Field Service Technicians. Engineered by you, designed by Fluke.

- VoltAlert™ Technology for integrated non-contact voltage detection.
- AutoVolt feature for automatic ac/dc voltage selection.
- LoZ: low input impedance prevents false readings due to "ghost voltage".

**For more information, see page 17.**



## Fluke 975 AirMeter™

The Fluke 975 AirMeter test tool raises indoor air monitoring to the next level by combining five powerful tools in one, rugged and easy-to-use handheld device.

The Fluke 975 measures:

- Temperature
- Relative Humidity
- Air Velocity
- CO<sub>2</sub>
- CO

**For more information see page 54.**

Your authorized Fluke distributor



## Fluke 8845A and 8846A 6.5 Digit Precision Multimeters

- 6.5 digit resolution
- Graphical display
- Basic V dc accuracy of up to 0.0024 %
- 100 uA to 10 A Current
- 10 ohm to 1 Gohm resistance
- 2x4 Wire ohms measurement technique
- Frequency, period, capacitance and RTD temperature measurements
- Analytical modes; TrendPlot™ Histogram and Statistics
- USB device port, for memory storage devices
- RS-232, IEEE-488 and LAN interfaces

**For more information, see page 21.**

**Fluke. Keeping your world up and running.™**

### Fluke Corporation

PO Box 9090,  
Everett, WA USA 98206

Fluke Europe B.V.  
PO Box 1186, 5602 BD  
Eindhoven, The Netherlands

For more information call:  
In the U.S.A. (800) 443-5853 or  
Fax (425) 446-5116  
In Europe/M-East/Africa  
(31 40) 2 675 200 or  
Fax (31 40) 2 675 222  
In Canada (800) 36-FLUKE or  
Fax (905) 890-6866  
From other countries  
+1 (425) 446-5500 or  
Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2006 Fluke Corporation.  
All rights reserved. Specifications  
subject to change without notice.  
LEM is a trademark of LEM Holding S.A.  
Corporation. Microsoft is a registered  
trademark of Microsoft Corporation.  
Printed in U.S.A. 11/2006  
1274458 C-US-N Rev 0  
**Volume 37**