


**Part Number: 91820-3318**

P'FLEX H'R HI-TEMP NO PEGS AU 18 CKT



Series image - Reference only

<b>Status:</b>	<b>OBSOLETE</b>
<b>Replacement:</b>	<a href="#">908143618</a>
<b>Series:</b>	<a href="#">91820</a>
<b>Category:</b>	Ribbon Cable / Wire Trap Connectors

**Product Environmental Compliance**

EU RoHS: ELV and RoHS Compliant



China RoHS:

REACH SVHC: Contains SVHC: No

Low-Halogen Status: Not Low-Halogen

**Part Detail****General**

<b>Status</b>	<b>Obsolete</b>
Category	Ribbon Cable / Wire Trap Connectors
Series	<a href="#">91820</a>
Component Type	PCB Header
Glow-Wire Compliant	No
Product Name	Picoflex®

**Physical**

Circuits (Loaded)	18
Circuits (maximum)	18
Color - Resin	Black
Durability (mating cycles max)	100
Entry Angle	Vertical
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	High Temperature Thermoplastic
Number of Rows	1
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.60mm
Packaging Type	Tube
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Plating min - Mating	0.762µm
Plating min - Termination	0.102µm
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Open Ends
Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Surface Mount
Wire Insulation Diameter	N/A
Wire Size AWG	N/A
Wire/Cable Type	Ribbon Cable

**Electrical****(Please review the Product Specification for specific details.)**

Current - Maximum per Contact	2.4A
Voltage - Maximum	250V AC/DC

**Solder Process Data**

Duration at Max. Process Temperature (seconds)	40
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	3
Process Temperature max. C	260

**Material Info****Application Tooling**

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

---

**Previously Available Application Tooling**

[Check our list of old tooling that used to be available for this part](#)