





LOC	DIST	REVISIONS					
E	B	P	LTR	DESCRIPTION	DATE	DWN	APVD
			BA2	ECR-13-015529	04OCT2013	KR	TN




RECOMMENDED LAND PATTERN FOR
INDUCTANCE VALUES 100 μ H OR HIGHER




RoHS Compliant

RECOMMENDED LAND PATTERN FOR
INDUCTANCE VALUES 1.5 μ H - 82 μ H




1 INDUCTANCE CODE

2 FOR FURTHER INFORMATION SEE DATA SHEET FOR
3632 SERIES-SHIELDED SMD POWER INDUCTORS



SCHEMATIC DIAGRAM



2008

RELEASED FOR PUBLICATION

THIS DRAWING IS UNPUBLISHED.

ALL RIGHTS RESERVED.

BY -

2008


©

DIMENSIONS:

mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±0.2
1 PLC	±0.1
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±5°



DWN 03-Sep-08

SUBHASH.M

CHK 03-Sep-08

PRAKASH.S

APVD 03-Sep-08

STEPHEN.P

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

MATERIAL

-

FINISH

-

TE Connectivity

NAME

SHIELDED SMD POWER INDUCTOR
SERIES 3632B

SIZE

A 4

CAGE CODE

00779

DRAWING NO

C- 1625813

RESTRICTED TO

-

Customer Drawing

SCALE 2:1

SHEET 1 OF 1

REV BA2