

T-51-10-08

FUJITSU**4-CHANNEL 8-BIT
A/D CONVERTER****MB4052**July 1988
Edition 4.0**4-CHANNEL 8-BIT A/D CONVERTER SUBSYSTEM**

The Fujitsu MB 4052 is an analog-to-digital converter (ADC) for general purpose which features four channels of analog inputs and 8-bit data length of digital output.

Analog input signal is converted to serial 8-bit digital data by the successive-approximation technique which provides high-speed conversion, i.e. many analog data can be converted within a short time.





All digital I/O signals including control inputs are TTL level compatible so as to provide wide application such as in microprocessor-controlled system and so on.

- Single Power Supply;
DIP: +3.5V to +6.0V or +8.0V to +18V (with Internal Regulator)
FPT: +3.5V to +6.0V or +8.0V to +13.2V (with Internal Regulator)
- Multiplex 4-Channel Analog Inputs
- Analog Input Voltage Ranges:
0 to $1/2V_{CC1}$ (Standard mode: RS = 1)
0 to $1/8V_{CC1}$ (Contracted mode: RS = 0)
0 to $2V_{CC1}$ (Expanded mode: through built-in Divider)
- Analog Input Bias Current: 250nA Max.
- Resolution: 8 bits
- Linearity: 0.19% Max.
- Successive-Approximation Conversion: 100 μ s/ch Max. at $f_{CLK} = 100$ kHz
- Ratio-Metric Conversion by Reference Voltage V_{CC1}
- Serial Data Output (Open-Collector)
- TTL/CMOS Compatible Digital I/O
- Package: DIP-16C-C02
DIP-16P-M04
FPT-16P-M03

ABSOLUTE MAXIMUM RATINGS (All Voltages referenced to A.G/D.G)

Rating	Symbol	Value	Unit
Power Supply Voltage	V_{CC1}	+7	V
	V_{CC2}	+20	V
Digital Input Voltage	V_{ID}	-0.5 to +20	V
Digital Output Voltage (Off-State)	V_{OH}	+20	V
Analog Input Voltage	V_{IA}	$V_{CC1} + 0.5$	V
Storage Temperature	Ceramic	T_{STG}	$^{\circ}$ C
	Plastic		
		-55 to +150	
		-40 to +125	


NOTE: Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. Functional operation should be restricted to the conditions as detailed in the operational sections of this data sheet. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

CERAMIC PACKAGE
DIP-16C-C02PLASTIC PACKAGE
DIP-16P-M04PLASTIC PACKAGE
FPT-16P-M03**PIN ASSIGNMENT**

This device contains circuitry to protect the inputs against damage due to high static voltages or electric fields. However, it is advised that normal precautions be taken to avoid application of any voltage higher than maximum rated voltages to this high impedance circuit.

T-51-10-08

FUJITSU
MB4052



RECOMMENDED OPERATING CONDITIONS

(T_A = -30°C to +85°C)

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Power Supply Voltage	V _{CC1}	3.5	5.0	6.0	V
	V _{CC2}	DIP	8.0	12.0	V
		FPT	8.0	12.0	V
Digital Output Low Current	I _{OL}	—	—	8	mA
Operating Temperature	T _A	-30	—	+85	°C

T-51-10-08

FUJITSU
MB4052

PIN DESCRIPTIONS

INPUT FOR VOLTAGE RANGE EXPANSION (EX 2), PIN 2

This input pin is provided to expand the voltage range of analog input signal.

This input pin is connected to the internal one-to-four voltage divider which reduces an analog signal level to one fourth of input level.

OUTPUT FOR VOLTAGE RANGE EXPANSION (EX 1), PIN 3

This output pin is provided to expand the allowable analog input level in co-operation with the above EX 2 pin.

A reduced signal which is divided in the internal divider is output on this pin.

This output pin can be connected to any of standard analog inputs A_0 , A_1 , A_2 or A_3 so that the EX 2 pin can function as one of 4-channel inputs.

ANALOG INPUTS (A_0 TO A_3), PINS 4, 5, 6 AND 7

These input pins are provided to receive four channels of analog inputs.

One of these four channels is selected by a combination of C_0 and C_1 inputs.

CHANNEL SELECT (C_1 AND C_0), PINS 9 AND 10

These control inputs are used to designate one of four analog inputs as shown in Table 1.

Table 1 CHANNEL SELECTION

C_1	C_0	Channel
0	0	A_0
0	1	A_1
1	0	A_2
1	1	A_3

CHIP SELECT ($\overline{CS}$), PIN 11

This control input pin is used to start analog-to-digital conversion.

When $\overline{CS}$ goes low, the A/D conversion start and the DATA OUT output is enabled.

When an A/D conversion is completed or termination of conversion is required, $\overline{CS}$ is made high.

A/D CONVERSION CLOCK (ADC CLK), PIN 12

This clock signal is input to the internal successive approximation register and used as timing signal for A/D conversion.

The conversion speed of this device is determined by this clock rate.

Ten clock cycles are required for a complete 8-bit conversion.

A precise cycle time is not always required for this clock signal.

DATA OUTPUT (DATA OUT), PIN 13

This output pin is provided to output the A/D conversion results as digital signals.

The converted digital data are serially output in the order of start-bit, MSB (Most Significant Bit), 2SB (Second Significant Bit), . . . , 7SB, LSB (Least Significant Bit) and stop-bit in synchronization with the ADC CLK clock signal.

RANGE SELECT (RS), PIN 14

This control input is provided to select an analog input voltage range as shown in Table 2.

This input must not be changed during an A/D conversion.

Table 2 RANGE SELECTION

RS	Voltage Range
0	0 to $1/8 V_{CC1}$
1	0 to $1/2 V_{CC1}$

ANALOG GROUND (A.G) AND DIGITAL GROUND (D.G), PINS 1 AND 8

These are terminals for ground.

The analog circuitry and digital circuitry have separate ground terminals, respectively.

POWER SUPPLIES (V_{CC2} AND V_{CC1}), PINS 15 AND 16

When the device operates within a voltage range of 3.5V to 6.0V, the power source is connected to V_{CC1} which is shorted to V_{CC2} .

When the device operates within a voltage range of 8V to 18V in case of DIP Packages and 8V to 13.2V in case of Flat Package, the power source is connected to V_{CC2} .

In this high voltage operation mode, the V_{CC1} pin is used as an output pin which supplies +5V stabilized voltage and 10mA load current and the supplied voltage is regulated in the internal voltage regulator.

V_{CC1} is used as the reference voltage of A/D conversion regardless any two types voltage.

T-51-10-08

FUJITSU

FUJITSU

MB4052

ANALOG CIRCUIT CHARACTERISTICS FOR PLASTIC DIP PACKAGE

(V_{CC1} = 3.5V to 6.0V, T_A = -30°C to +85°C)

Parameter		Symbol	Condition	Value			Unit
				Min.	Typ.	Max.	
Resolution			—	—	—	8	Bit
Linearity Error			V _{CC1} = 5V	—	—	±0.5	LSB
Differential Linearity Error				—	—	±0.9	LSB
Zero Transition Voltage	Contracted Range	V _{ZC}	V _{CC1} = 5V, T _A = 25°C	0	6	16	mV
	Standard Range	V _{ZS}		7	17	27	mV
	Expanded Range	V _{ZE}		22	62	102	mV
Full Scale Transition Voltage	Contracted range	V _{FC}		600	625	650	mV
	Standard Range	V _{FS}		2.475	2.500	2.525	V
	Expanded Range	V _{FE}		9.600	10.000	10.400	V
Comparator Input Current		I _{IC}	V _{CC1} = 5V	—	-100	-250	nA
Divider Input Resistance for Expanded Range		R _{INE}	—	5	10	15	kΩ
Regulator	Output Voltage	V _{OR}	8V ≤ V _{CC2} ≤ 18V	4.5	5.0	5.5	V
	Line Regulation			—	4.0	—	mV/V
	Load Regulation		V _{CC2} = 12V, 0mA ≤ I _{out} ≤ -10mA	—	0.5	—	mV/mA
	Output Voltage Temperature		V _{CC2} = 12V	—	50	—	ppm/°C
Conversion Cycle Time		t _{CYC}	f _{CLK} = 100kHz	—	—	100	μs/ch

A minus sign (-) prefixed to a current value indicates that the current flows from the IC to the external circuit.

T-51-10-08

FUJITSU

MB4052

ANALOG CIRCUIT CHARACTERISTICS FOR CERAMIC DIP PACKAGE

(V_{CC1} = 3.5V to 6.0V, T_A = -30°C to +85°C)

Parameter		Symbol	Condition	Value			Unit
				Min.	Typ.	Max.	
Resolution			—	—	—	8	Bit
Linearity Error			V _{CC1} = 5V	—	—	±0.4	LSB
Differential Linearity Error				—	—	±0.8	LSB
Zero Transition Voltage	Contracted Range	V _{ZC}	V _{CC1} = 5V, T _A = 25°C	0	6	16	mV
	Standard Range	V _{ZS}		7	17	27	mV
	Expanded Range	V _{ZE}		22	62	102	mV
Full Scale Transition Voltage	Contracted range	V _{FC}		610	625	640	mV
	Standard Range	V _{FS}		2.480	2.500	2.520	V
	Expanded Range	V _{FE}		9.760	10.000	10.240	V
Comparator Input Current		I _{IC}	V _{CC1} = 5V	—	-100	-250	nA
Divider Input Resistance for Expanded Range		R _{INE}	—	5	10	15	kΩ
Regulator	Output Voltage	V _{OR}	8V ≤ V _{CC2} ≤ 18V	4.5	5.0	5.5	V
	Line Regulation			—	4.0	—	mV/V
	Load Regulation		V _{CC2} = 12V, 0mA ≤ I _{out} ≤ -10mA	—	0.5	—	mV/mA
	Output Voltage Temperature		V _{CC2} = 12V	—	50	—	ppm/°C
Conversion Cycle Time		t _{CYC}	f _{CLK} = 100kHz	—	—	100	μs/ch

7

A minus sign (-) prefixed to a current value indicates that the current flows from the IC to the external circuit.

FUJITSU
MB4052

ANALOG CIRCUIT CHARACTERISTICS FOR PLASTIC FLAT PACKAGE

(V_{CC1} = 3.5V to 6.0V, T_A = -30°C to +85°C)

Parameter		Symbol	Condition	Value			Unit
				Min.	Typ.	Max.	
Resolution			—	—	—	8	Bit
Linearity Error			V _{CC1} = 5V	—	—	±0.5	LSB
Differential Linearity Error				—	—	±0.9	LSB
Zero Transition Voltage	Contracted Range	V _{ZC}	V _{CC1} = 5V, T _A = 25°C	0	6	16	mV
	Standard Range	V _{ZS}		7	17	27	mV
	Expanded Range	V _{ZE}		22	62	102	mV
Full Scale Transition Voltage	Contracted range	V _{FC}		600	625	650	mV
	Standard Range	V _{FS}		2.475	2.500	2.525	V
	Expanded Range	V _{FE}		9.600	10.000	10.400	V
Comparator Input Current		I _{IC}	V _{CC1} = 5V	—	-100	-250	nA
Divider Input Resistance for Expanded Range		R _{INE}	—	5	10	15	kΩ
Regulator	Output Voltage	V _{OR}	8V ≤ V _{CC2} ≤ 18V	4.5	5.0	5.5	V
	Line Regulation			—	4.0	—	mV/V
	Load Regulation		V _{CC2} = 12V, 0mA ≤ I _{out} ≤ -10mA	—	0.5	—	mV/mA
	Output Voltage Temperature		V _{CC2} = 12V	—	50	—	ppm/°C
Conversion Cycle Time		t _{CYC}	f _{CLK} = 100kHz	—	—	100	μs/ch

A minus sign (-) prefixed to a current value indicates that the current flows from the IC to the external circuit.

T-51-10-08

FUJITSU
MB4052

DIGITAL CIRCUIT DC CHARACTERISTICS

(V_{CC1} = 3.5V to 6.0V, T_A = -30°C to +85°C)

Parameter	Symbol	Condition	Value			Unit
			Min.	Typ.	Max.	
Input Clamp Voltage	V _{IC}	V _{CC1} = 3.5V, I _{IL} = -18mA	—	—	-1.5	V
High Level Input Current	I _{OH}	V _{CC1} = 3.5V, V _{IH} = 2.0V, V _{IL} = 0.8V, V _{OH} = 20V	—	—	100	μA
Low Level Output Voltage	V _{OL1}	V _{CC1} = 3.5V, V _{IH} = 2.0V, V _{IL} = 0.8V, I _{OL} = 4mA	—	—	0.4	V
	V _{OL2}	V _{CC1} = 3.5V, V _{IH} = 2.0V, V _{IL} = 0.8V, I _{OL} = 8mA	—	—	0.5	V
High Level Input Current	I _{IH1}	V _{CC1} = 6.0V, V _{IH} = 2.7V	—	—	20	μA
	I _{IH2}	V _{CC1} = 6.0V, V _{IH} = 20V	—	—	100	μA
Low Level Input Current	I _{IL}	V _{CC1} = 6.0V, V _{IL} = 0.4V	—	-50	-150	μA
Power Supply Current for V _{CC1}	I _{CC1}	V _{CC1} = 6.0V	—	15*	30	mA
Power Supply Current for V _{CC2}	I _{CC2}	V _{CC1} = Open, V _{CC2} = 20V for DIP Package V _{CC2} = 13.2V for FLAT Package	—	15	25	mA

*Note: This typical value is measured at V_{CC1} = 5.0V and T_A = 25°C.

A minus sign (-) prefixed to a current value indicates that the current flows from the IC to the external circuit.

The values are measured at V_{CC1} = V_{CC2} except the I_{CC2} parameter of .

DIGITAL CIRCUIT AC CHARACTERISTICS

(V_{CC1} = 3.5V to 6.0V, T_A = -30°C to +85°C)

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
ADC CLK Cycle Time	t _{CY}	10	—	—	μs
ADC CLK H Level Pulse Width	t _{WAC+}	2.5	—	—	μs
ADC CLK L Level Pulse Width	t _{WAC-}	2.5	—	—	μs
CS H Level Pulse Width	t _{WCS+}	1.5	—	—	μs
CS Set-up Time	t _{SCS}	1	—	—	μs
CS Hold Tin.	t _{HCS}	1	—	—	μs
Channel Set-up Time	t _{SCH}	0	—	—	μs
Channel Hold Time	t _{HCH}	1	—	—	μs
Propagation Delay Time	t _{PLH}	—	800	2,000	ns
	t _{PHL}	—	800	2,000	ns

FUJITSU
MB4052

T-51-10-08

Fig. 2 - AC CHARACTERISTICS WAVEFORM






Fig. 3 - TIMING DIAGRAM





Note: RS should be held to one ranged "1" or "0" until data conversion is completed.

T-51-10-08


FUJITSU
MB4052



TYPICAL WAVEFORMS OF PROPAGATION DELAY




TYPICAL CONVERSION WAVEFORM



FUJITSU
MB4052

T-51-10-08


Fig. 5 - EXAMPLE OF EXPAND RANGE MODE CONNECTION




T-51-10-08

FUJITSU
MB4052

PACKAGE DIMENSIONS



7



FUJITSU
MB4052

T-51-10-08

PACKAGE DIMENSIONS (continued)

