



Rad-Hard 60 V, 30 A, N-channel Power MOSFET



SMD.5



Features

V_{DS}	I_D	$R_{DS(on)}$ typ.	Q_g
60 V	30 A	36 mΩ	43 nC

- Fast switching
- 100 % avalanche tested
- Hermetic package
- 50 krad TID
- SEE radiation hardened

Description

The STRH40N6 is a N-channel Power MOSFET able to operate under severe environment conditions and radiation exposure. It provides high reliability performance and immunity to the total ionizing dose (TID) and single event effects (SEE).

Qualified as per ESCC detail specification No. 5205/024 and available in SMD.5 hermetic package it is specifically recommended for space and harsh environment applications and suitable for in-Satellite power conversion, motor control and power switch circuits.

In case of discrepancies between this datasheet and the relevant agency specification, the latter takes precedence.

Product status link

[STRH40N6](#)

Device summary

Product summary					
Part numbers	Quality level	ESCC Part number	Package	Lead finish	Radiation level
STRH40N6S1	Engineering model	5205/024	SMD.5	Gold	-
STRH40N6SG	ESCC flight			Solder-dip	50 krad
STRH40N6ST					

Note: See [Table 8](#) for ordering information.

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
$V_{DS}^{(1)}$	Drain-source voltage ($V_{GS} = 0$)	60	V
$V_{GS}^{(2)}$	Gate-source voltage	± 20	V
I_D	Drain current (continuous)	30	A
	Drain current (continuous) at $T_{amb} = 100\text{ °C}$	19	A
$I_{DM}^{(3)}$	Drain current (pulsed)	120	A
P_{TOT}	Total dissipation at $T_C = 25\text{ °C}$	75	W
P_{TOT}	Total dissipation at $T_a = 25\text{ °C}$	2.5	W
$dv/dt^{(4)}$	Peak diode recovery voltage slope	2.5	V/ns
T_{op}	Operating temperature range	-55 to 150	°C
T_j	Max. operating junction temperature range	150	°C

1. This rating is guaranteed at $T_j \geq 25\text{ °C}$ (see [Figure 9](#)).
2. This value is guaranteed over the full range of temperature.
3. Pulse width limited by safe operating area.
4. $I_{SD} \leq 40\text{ A}$, $di/dt \leq 1060\text{ A}/\mu\text{s}$, $V_{DD} = 80\%V_{(BR)DSS}$

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	1.67	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	50	°C/W

2 Avalanche data

Table 3. Avalanche data

Symbol	Parameter	Value	Unit
I_{AR}	Avalanche current, repetitive or not-repetitive (pulse width limited by T_J max.)	15	A
E_{AS}	Single pulse avalanche energy (starting $T_J = 25\text{ }^{\circ}\text{C}$, $I_D = 20\text{ A}$, $V_{DD} = 40\text{ V}$)	354	mJ
E_{AS}	Single pulse avalanche energy (starting $T_J = 110\text{ }^{\circ}\text{C}$, $I_D = 20\text{ A}$, $V_{DD} = 40\text{ V}$)	105	
E_{AR}	Repetitive avalanche ($V_{DD} = 50\text{ V}$, $I_{AR} = 17.5\text{ A}$, $f = 10\text{ KHz}$, $T_J = 25\text{ }^{\circ}\text{C}$, duty cycle = 50 %)	20	mJ
	Repetitive avalanche ($V_{DD} = 40\text{ V}$, $I_{AR} = 15\text{ A}$, $f = 100\text{ KHz}$, $T_J = 25\text{ }^{\circ}\text{C}$, duty cycle = 10 %)	1.3	
	Repetitive avalanche ($V_{DD} = 40\text{ V}$, $I_{AR} = 15\text{ A}$, $f = 100\text{ KHz}$, $T_J = 110\text{ }^{\circ}\text{C}$, duty cycle = 10 %)	0.4	

1. Maximum rating value.

3 Electrical characteristics

Table 4. Electrical characteristics ($T_{amb} = 25\text{ °C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Max.	Unit
I_{DSS}	Zero gate voltage drain current ($V_{GS} = 0$)	$BV_{DSS} = 48\text{ V}$		10	μA
		$BV_{DSS} = 48\text{ V}, T_C = 125\text{ °C}$		100	μA
I_{GSS}	Gate body leakage current, ($V_{DS} = 0$)	$V_{GS} = 20\text{ V}$		100	nA
		$V_{GS} = -20\text{ V}$	-100		
		$V_{GS} = -20\text{ V}, T_C = 125\text{ °C}$		200	
		$V_{GS} = 20\text{ V}, T_C = 125\text{ °C}$	-200		
$V_{(BR)DSS}^{(1)}$	Drain-to-source breakdown voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	60		V
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 1\text{ mA}$	2	4.5	V
		$V_{DS} = V_{GS}, I_D = 1\text{ mA}, T_C = 125\text{ °C}$	1.5	3.7	
		$V_{DS} = V_{GS}, I_D = 1\text{ mA}, T_C = -55\text{ °C}$	2.1	5.5	
$R_{DS(on)}$	Static drain-source on resistance	$V_{GS} = 12\text{ V}, I_D = 15\text{ A}$		0.045	Ω
		$V_{GS} = 12\text{ V}, I_D = 15\text{ A}, T_a = 125\text{ °C}$		0.076	
C_{iss}	Input capacitance	$V_{DS} = 25\text{ V}, f = 1\text{ MHz}, V_{GS} = 0\text{ V}$	1312	1968	pF
$C_{oss}^{(2)}$	Output capacitance		281	421	pF
C_{rss}	Reverse transfer capacitance		111	167	pF
Q_g	Total gate charge	$V_{DD} = 30\text{ V}, I_D = 40\text{ A}, V_{GS} = 12\text{ V}$	35	52	nC
Q_{gs}	Gate-to-source charge		9	13	nC
Q_{gd}	Gate-to-drain ("Miller") charge		12	18	nC
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 30\text{ V}, I_D = 20\text{ A}, R_G = 4.7\text{ }\Omega, V_{GS} = 12\text{ V}$	13	21	ns
t_r	Rise time		26	92	
$t_{d(off)}$	Turn-off delay time		18	48	
t_f	Fall time		7	16	
$V_{SD}^{(3)}$	Diode forward voltage	$I_{SD} = 30\text{ A}, V_{GS} = 0\text{ V}$		1.5	V
		$I_{SD} = 30\text{ A}, V_{GS} = 0\text{ V}, T_a = 125\text{ °C}$		1.275	
$t_{rr}^{(2)}$	Reverse recovery time	$I_{SD} = 40\text{ A}, di/dt = 100\text{ A}/\mu\text{s}, V_{DD} = 48\text{ V}, T_j = 25\text{ °C}$	288	432	

1. This rating is guaranteed at $T_j \geq 25\text{ °C}$ (see Figure 9. Normalized $V_{(BR)DSS}$ vs temperature).

2. Not tested in production, guaranteed by process.

3. Pulsed: pulse duration = 300 μs , duty cycle $\leq 1.5\%$

4 Radiation characteristics

This products is guaranteed in radiation as per ESCC 5205/024 and ESCC 22900 specification at 50 krad. Each lot tested in radiation is accepted according to the characteristics as per [Table 5](#).

4.1 Total dose radiation (TID) testing

The bias with $V_{GS} = +15\text{ V}$ and $V_{DS} = 0\text{ V}$ is applied during irradiation exposure.

The parameters listed in [Table 5](#) are measured:

- Before irradiation
- After irradiation
- After 24 hrs at room temperature
- after 168 hrs at 100 °C anneal

Table 5. Post-irradiation electrical characteristics ($T_{amb} = 25\text{ °C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Max.	Unit
I_{DSS}	Zero gate voltage drain current ($V_{GS} = 0$)	$V_{DS} = 48\text{ V}$		10	μA
I_{GSS}	Gate body leakage current, ($V_{DS} = 0$)	$V_{GS} = 20\text{ V}$		100	nA
		$V_{GS} = -20\text{ V}$	-100		
$V_{(BR)DSS}$	Drain-to-source breakdown voltage	$V_{GS} = 0\text{ V}$, $I_D = 1\text{ mA}$	48		V
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}$, $I_D = 1\text{ mA}$	2	4.5	V
$R_{DS(on)}$	Static drain-source on resistance	$V_{GS} = 12\text{ V}$, $I_D = 15\text{ A}$		0.045	Ω
V_{SD}	Diode forward voltage	$I_{SD} = 30\text{ A}$, $V_{GS} = 0\text{ V}$		1.5	V

1. Pulsed: pulse duration = 300 μs , duty cycle $\leq 1.5\%$

4.2 Single event effect RBSOA

The STRH40N6 is extremely resistant to heavy ions exposure as per MIL-STD-750E, test method 1080, bias circuit of Figure 2.

SEB and SEGR tests are performed with a fluence of $3e+5$ ions/cm² with the following acceptance criteria:

- SEB test: drain voltage checked, trigger level is set to $V_{DS} = -5$ V. Stop condition: as soon as a SEB occurs or if the fluence reaches $3e+5$ ions/cm².
- SEGR test: the gate current is monitored every 200 ms. A gate stress is performed before and after irradiation. Stop condition: as soon as the gate current reaches 100 nA (during irradiation or during PIGS test) or if the fluence reaches $3e+5$ ions/cm².

Table 6. Single event effect (SEE), reverse biased safe operating area (RBSOA)

Ion	Let (Mev/(mg/cm ²))	Energy (MeV)	Range (μm)
Kr	32	768	94
Br	38	300	38
I	61	330	31

Figure 1. Single event effect, RBSOA





Figure 2. Single event effect, bias circuit



AM09224v1

5 Electrical characteristics (curves)

Figure 3. Safe operating area




Figure 4. Thermal impedance




Figure 5. Output characteristics




Figure 6. Transfer characteristics












Figure 7. Gate charge vs gate-source voltage

Figure 8. Capacitance variations

Figure 9. Normalized $V_{(BR)DSS}$ vs temperature

Figure 10. Static drain-source on-resistance

Figure 11. Normalized gate threshold voltage vs temperature

Figure 12. Normalized on-resistance vs temperature


Figure 13. Source drain-diode forward characteristics



6 Test circuits

Figure 14. Switching times test circuit for resistive load



Note: Max driver V_{GS} slope = 1 V/ns (no DUT)

Figure 15. Source drain diode waveform





Figure 16. Unclamped inductive load test circuit (single pulse and repetitive)




7 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

7.1 SMD.5 package information

Figure 17. SMD.5 package outline



7386434_REV7

Table 7. SMD.5 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	2.84		3.30
A1	0.25	0.38	0.51
b	7.13	7.26	7.39
b1	5.58	5.72	5.84
b2	2.28	2.41	2.54
b3	2.92	3.05	3.18
D	10.03	10.16	10.28
D1	0.76		
E	7.39	7.52	7.64
e		1.91	

Note: The lid is not connected to any pin.

8 Order codes

Table 8. Ordering information

Part number	Agency specification	Quality level	Radiation level	Package	Weight	Lead finish	Marking ⁽¹⁾	Packing
STRH40N6S1	-	Engineering model	-	SMD.5	1 g	Gold	STRH40N6S1	Strip pack
STRH40N6SG	5205/024/01	ESCC	50 krad				Solder-dip	
STRH40N6ST	5205/024/02	flight				520502402F		

1. Specific marking only. The full marking includes in addition: For the Engineering Models: ST logo, date code; country of origin (FR). For ESCC flight parts: ST logo, date code, country of origin (FR), ESA logo, serial number of the part within the assembly lot.

Contact ST sales office for information about specific conditions for products in die form.

9 Other information

9.1 Traceability information

Date code information is described in the table below.

Table 9. Date codes

Model	Date code ⁽¹⁾
EM	3yywwN
Flight	yywwN

1. yy = year, ww = week number, N = lot index in the week.

9.2 Documentation

Table 10. Documentation provided for each type of product

Quality level	Radiation level	Documentation
Engineering model	-	Certificate of conformance
Flight	50 krad	Certificate of conformance ESCC qualification maintenance lot reference Radiation data at 25 / 50 krad at 0.1 rad / s.

Revision history

Table 11. Document revision history

Date	Revision	Changes
03-Jan-2011	1	First release.
25-Aug-2011	2	Updated order codes in <i>Table 1: Device summary</i> and <i>Table 14: Ordering information</i> . Minor text changes.
09-Nov-2011	3	Updated dynamic values on <i>Table 7: Pre-irradiation switching times</i> . Document status changed from preliminary data to datasheet.
28-Mar-2012	4	Updated title in cover page.
03-Oct-2012	5	<i>Figure 4: Safe operating area</i> has been modified.
01-Jul-2013	6	Updated order codes in <i>Table 1: Device summary</i> , <i>Table 12: Single event effect (SEE)</i> , <i>safe operating area (SOA)</i> , <i>Figure 2: Single event effect, SOA</i> and <i>Table 14: Ordering information</i> . Added <i>Section 7.1: Other information</i> . Minor text changes.
09-Sep-2013	7	Updated <i>features</i> in cover page.
14-May-2014	8	Updated <i>Table 5: Pre-irradiation on/off states</i> .
19-May-2014	9	Updated <i>Table 9: Post-irradiation on/off states @ T_J = 25 °C, (Co60 γ rays 50 K Rad(Si))</i> .
04-Mar-2016	10	Updated: <i>Features</i> , <i>Table 5</i> , <i>Table 8</i> , <i>Table 9</i> , <i>Table 10</i> , <i>Table 11</i> and <i>Table 15</i> . Updated <i>Section 6: Package information</i> . Minor text changes.
15-Jun-2021	11	Updated <i>SMD.5 package information</i> . Minor text changes.
07-Jul-2021	12	Updated ESCC detail specification No. from 5205/021 to 5205/024.
04-Oct-2021	13	Updated <i>Table 8</i> and <i>Table 10</i> .
08-Feb-2024	14	Updated <i>Table 4</i> .
11-Sep-2024	15	Updated Table 4 , and Table 5 .

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved