



- NOTES
- MARK MANUFACTURER'S NAME, CATALOG LISTING, FED. MFG. CODE AND DATE CODE
  - 2X ELECTRICAL LEADS TO LAMPS: 20 GAGE PER MIL-W-81044/6
  - 2X FILTERS: RED MS250101-13A
  - 2X LAMPS: MS25237-327 (28 VOLTS)
  - MAXIMUM POWER CONSUMPTION PER LAMP TO BE 4.5 WATTS
  - TEE HANDLE: MATTE PLASTIC PER MIL-STD-395, PAINTED RED, COLOR NUMBER 31136 PER FED-STD-595
  - HANDLE MUST NOT APPEAR LIT UNDER AMBIENT LIGHT CONDITIONS AND MUST APPEAR LIT WHEN ENERGIZED UNDER AMBIENT LIGHT CONDITIONS
  - TORQUE FASTENER 4 TO 6 IN-LB MAXIMUM AFTER INSTALLATION
  - CONTACTS SEALED PER MIL-PRF-8805 SYMBOL 3 (WATERTIGHT)

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
CHARACTERISTICS		ELECTRICAL DATA	
OPERATING FORCE — — — 7-10 LBS		CONTACT ARRANGEMENT	
OVERTRAVEL — — — .075 MIN		6X S P D T	
TOTAL TRAVEL — — — .9 TYP		28 VDC	
FUNCTIONAL LAMP LIFE — 25 OPERATIONS MIN		LOAD (AMPS)	SEA LEVEL 50,000 FT
		CONTACT	SILVER SILVER
		RESISTIVE	7 4
		INDUCTIVE	4 2.5
		MOTOR	— —

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
MICRO SWITCH a Honeywell Division		SWITCH - ENCLOSED	
FED. MFG. CODE 01929		CATALOG LISTING PH-130	

THIRD ANGLE PROJECTION			
SCALE FULL			
DO NOT SCALE PRINT			
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			
ONE PLACE	(.0)	±.030	
TWO PLACES	(.00)	±.015	
THREE PLACES	(.000)	±.005	
ANGLES		± 4°	
WEIGHT .55 LB MAX			

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[PH-130](#)