

TO BE SOLD  
ONLY WITH  
INSTALLATION  
INSTRUCTIONS



**424C**  
**LISTED**

90 °C [194 °F] Max  
(Vinyl and Nylon)  
105 °C [222 °F] Max  
(Polyvinylidene Fluoride)



**LR 7189**  
**CERTIFIED**

90 °C [194 °F] Max  
(Vinyl)  
105 °C [222 °F] Max  
(Nylon)

WIRE RANGE (AWG)	WIRE TYPE	SPLICE TYPE	SPLICE RATING
22-16	SOLID OR STRANDED	VINYL BUTT AND PARALLEL	600 V MAX (1000 V FIXTURE OR SIGN)
18-14	SOLID OR STRANDED	POLYVINYLIDENE FLUORIDE BUTT	
16-14	SOLID OR STRANDED	VINYL BUTT AND PARALLEL	
12-10	12-10 STRANDED AND 12 SOLID	VINYL OR NYLON BUTT AND VINYL PARALLEL	

**NOTE:** 22-16 splices are stamped 22-18 in accordance with MIL-T-7928.

©2004 Tyco Electronics Corporation, Harrisburg, PA  
All International Rights Reserved  
AMP and Tyco are trademarks. \*Trademark  
Other products, logos, and company names used are the  
property of their respective owners.

TOOLING ASSISTANCE CENTER 1-800-722-1111  
FAX/PRODUCT INFO 1-800-522-6752  
For Regional Customer Service, visit our website at  
[www.tycoelectronics.com](http://www.tycoelectronics.com)

**1 of 1**

Revised per EC 0990-1692-04