

Product Catalog

For Web Assistance: (800) 323-0198

Product Index

- Hookup Wire
- Braided Stranded Copper Wire
- Multiconductor
- Tubing

Coaxial Cable

Check the Items You'd Like to Add to Your Quote or Order

Military Specification Hookup Wire POLYTETRAFLUOROETHYLENE (PTFE) INSULATION *MIL-W-16878/4 (PREVIOUSLY TYPE 'E')

Standard Putups: 100 ft. 1000 ft. See color chart 8 in Technical Section. Consult factory for availability of other colors and color combinations.	DESCRIPTION	FEATURES & APPLICATIONS
	- Conductors: Silver-plated copper with 40 microinches minimum coating thickness per ASTM B-298. Also available on special order are constructions with nickel-plated copper, silver-plated or nickel-plated, high-strength high-conductivity copper alloy. - Insulation: Extruded PTFE, nominal wall .010 (0.25mm). Bondable treated or sodium-etched coating can be supplied upon request. - Color Coding: Insulation color coding to MIL-STD-104 is available in solid colors and stripes.	This wire insulated with PTFE is rated at 600 volts rms, with the corresponding DC potential at 1,500 volts. Suitable for high-frequency use at elevated temperatures in high-reliability programs where electrical and thermal stability are important
	CHARACTERISTICS	APPROVALS
	- Temperature Range: -55C to +200C with silver-plated conductors. -55C to +260C with nickel-plated conductors. - Insul. Flaw Test (Spark Test): 4,600 Volts rms @ 3.0 kHz. - Min. Insul. Resist.: Meets specification requirements. - Heat Resistance: +290C for 96 hours. - Voltage Rating: 600 Volts rms.	Passes VW-1 Vertical Flame Test. OHSA Acceptable. MIL-W-16878/4 (previously Type 'E').

	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm		Nom. O.D. in. mm		Military Number
	13201	32	Solid	.008	0.20	.028	0.71	M16878/4BAA
	13207	32	7/40	.009	0.23	.029	0.74	M16878/4BAB
	13219	32	19/44	.010	0.25	.030	0.76	N/A
	13001	30	Solid	.010	0.25	.030	0.76	M16878/4BBA
	13007	30	7/38	.012	0.30	.032	0.81	M16878/4BBB
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm		Nom. O.D. in. mm		Military Number
	13019	30	19/42	.012	0.30	.030	0.76	N/A
	12801	28	Solid	.013	0.33	.033	0.64	M16878/4BCA
	12807	28	7/36	.015	0.38	.035	0.89	M16878/4BCB*
	12819	28	19/40	.015	0.38	.035	0.89	N/A
	12601	26	Solid	.016	0.41	.036	0.91	M16878/4BDA
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm		Nom. O.D. in. mm		Military Number
	12607	26	7/34	.019	0.48	.039	0.99	M16878/4BDB
	12619	26	19/38	.019	0.48	.039	0.99	M16878/4BDE*
	12401	24	Solid	.020	0.51	.040	1.02	M16878/4BEA
	12407	24	7/32	.024	0.61	.044	1.12	M16878/4BEB
	12419	24	19/36	.024	0.61	.044	1.12	M16878/4BEE*
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm		Nom. O.D. in. mm		Military Number
	12201	22	Solid	.025	0.64	.045	1.14	M16878/4BFA
	12207	22	7/30	.030	0.76	.050	1.27	M16878/4BFB
	12219	22	19/34	.030	0.76	.050	1.27	M16878/4BFE*
	12001	20	Solid	.032	0.81	.052	1.32	M16878/4BGA
	12007	20	7/28	.038	0.97	.058	1.47	M16878/4BGB
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm		Nom. O.D. in. mm		Military Number
	12019	20	19/32	.038	0.97	.058	1.47	M16878/4BGE*
	11801	18	Solid	.040	1.02	.060	1.52	M16878/4BHA
	11807	18	7/26	.048	1.22	.068	1.73	M16878/4BHB
	11819	18	19/30	.047	1.19	.068	1.73	M16878/4BHE*

	11619	16	19/29	.053 1.35	.076 1.98	M16878/4BJE*
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
	11419	14	19/27	.067 1.70	.093 2.36	M16878/4BKE*
	11219	12	19/25	.084 2.13	.111 2.62	M16878/4BLE*
	11037	10	37/26	.110 2.79	.138 3.51	M16878/4BMG*

CF-Consult factory. N/A-Not available as M16878. *Also available in latest revision of MIL-W-22759/11. Manufactured to latest available revision without surface marking. Other AWG's and strandings available upone request (see NEMA HP-3).

If you wish to add the products to your quote or complete your quote check one of these buttons

[Contact](#)

Copyright 1997-2001, Dearborn Wire and Cable, Inc.