



NICKEL CADMIUM BATTERIES: INDIVIDUAL DATA SHEET

P-120SCJS 4/5SC size (KR23/34) Type: R


Dimensions (with tube) (mm)



Typical Charge Characteristics



Typical Discharge Characteristics



Specifications

		mm	inch	
Diameter		23.0 +0/-1.0	0.89 +0/-0.02	
Height		34.0 +0/-1.5	1.34 +0/-0.06	
Approximate Weight		Grams	Ounces	
		37g	1.31	
Nominal Voltage			1.2V	
Discharge Capacity*		Average**	1300mAh	
		Rated (Min.)	1200mAh	
Approx. Internal impedance at 1000Hz at charged state			6mΩ	
Charge		Standard	120mA (0.1It) x 16 hrs.	
		Rapid***	1200mA (1It) x 1.5 hrs.	
Ambient Temperature	Charge	Standard	°C	°F
			0°C to 45°C	32°F to 113°F
		Rapid	10°C to 40°C	50°F to 104°F
	Discharge		-20°C to 65°C	-4°F to 149°F
	Storage	< 2 years	-20°C to 35°C	-4°F to 95°F
		< 6 months	-20°C to 45°C	-4°F to 113°F
		< 1 month	-20°C to 55°C	-4°F to 131°F
		< 1 week	-20°C to 65°C	-4°F to 149°F

* 0.2It discharge capacity after charging at 0.1It for 16 hours.

** For reference only.

*** Refer to "Charge Methods for Ni-Cd Batteries"

Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge / discharge specs, warning label contents and unit design.

Note: [It] was previously expressed as [C]. [It] is an IEC standard expression for the amount of charge or discharge current and is expressed as:

$$It(A) = Cn(Ah)/1h.$$

• [It] is the reference test current in amperes

• [Cn] is the rated capacity of the cell or battery in Ampere-hours.

n = the time base [hours] for which the rated capacity is declared

