



LFS Series

Paddle Flow Switches



- Stainless steel SS304 paddle
- 3/4"PF or 1"PT mounting plug thread
- IP65 Aluminium alloy housing or DIN 43650 connection
- Use for flow detection in pipes from 1" bore to 3" bore
- Maximum operating pressure 20 bar

Technical Specification

Housing material	Aluminium Alloy	Paddle material	304grade SS
Temperature range	-30 to +150°C	Maximum pressure	20 bar
Set point tolerance	±25%	Pressure drop	0.2 bar
Repeatability	±5%	Connection in housing or by DIN 43650	

Electrical Specification

Contact Form		SPDT
Switching Power Max	VA	40
Switching Voltage AC/DC Max	V	230
Switching Current Max	A	1.0

All ratings are for resistive load only.

Standard Parts	Mounting thread	Connection
LFS-01	1"NPT	Terminate in housing
LFS-02	3/4"BSP	Terminate in housing
LFS-03	1"NPT	DIN 43650
LFS-04	3/4"BSP	DIN 43650

The LFS range of flow switches are paddle devices that are mounted vertically through a socket or upstand process connection.


Electrical connections are made within the housing, which has a screw on sealed lid and cable gland.

A choice of paddle sizes is supplied with each switch and selection can be made with reference to the chart opposite.

Pipe Dia	1"		1.25"		1.50"		2"		2.5"		3"	
Switch	Op	Rel	Op	Rel	Op	Rel	Op	Rel	Op	Rel	Op	Rel
Paddle length												
1"	19	15.2	32.2	24.7	45.5	34.1	64.4	56.8				
1.25"			24.7	17.1	34.1	26.5	56.8	45.5	87.1	75.8		
1.50"					53	37.9	87.1	60.6	121.2	94.7		
2"							68.2	45.5	90.9	64.4	125	102.3
2.5"									75.8	49.3	102.3	121.2
3"											83.3	60.6

NB: Flow rates in litres per minute

Mechanical Dimensions



Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE
Telephone +44 (0) 1202 897969

Email: sales@cynergy3.com

ISO9001 CERTIFIED

www.cynergy3.com