

2SK2124

Silicon N-Channel Power F-MOS FET

■ Features

- Avalanche energy capacity guaranteed: $EAS > 130\text{mJ}$
- $V_{GS} = \pm 30\text{V}$ guaranteed
- High-speed switching: $t_f = 60\text{ns}$
- No secondary breakdown

■ Applications

- Contactless relay
- Diving circuit for a solenoid
- Driving circuit for a motor
- Control equipment
- Switching power supply


■ Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Drain to Source breakdown voltage	V_{DS}	450	V
Gate to Source voltage	V_{GS}	± 30	V
Drain current	DC	I_D	A
	Pulse	I_{DP}	A
Avalanche energy capacity	EAS^*	130	mJ
Allowable power dissipation	$T_C = 25^\circ\text{C}$	P_D	50
	$T_a = 25^\circ\text{C}$		2
Channel temperature	T_{ch}	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to $+150$	$^\circ\text{C}$









* $L = 4.1\text{mH}$, $I_L = 8\text{A}$, $V_{DD} = 50\text{V}$, 1 pulse

■ Electrical Characteristics ($T_C = 25^\circ\text{C}$)

Parameter	Symbol	Conditions	min	typ	max	Unit
Drain to Source cut-off current	I_{DSS}	$V_{DS} = 360\text{V}$, $V_{GS} = 0$			0.1	mA
Gate to Source leakage current	I_{GSS}	$V_{GS} = \pm 30\text{V}$, $V_{DS} = 0$			± 1	μA
Drain to Source breakdown voltage	V_{DSS}	$I_D = 1\text{mA}$, $V_{GS} = 0$	450			V
Gate threshold voltage	V_{th}	$V_{DS} = 25\text{V}$, $I_D = 1\text{mA}$	2		5	V
Drain to Source ON-resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 4\text{A}$		0.56	0.75	Ω
Forward transfer admittance	$ Y_{fs} $	$V_{DS} = 25\text{V}$, $I_D = 4\text{A}$	3	5		S
Diode forward voltage	V_{DSF}	$I_{DR} = 8\text{A}$, $V_{GS} = 0$			-1.7	V
Input capacitance (Common Source)	C_{iss}	$V_{DS} = 20\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$		1300		pF
Output capacitance (Common Source)	C_{oss}			160		pF
Reverse transfer capacitance (Common Source)	C_{rss}			70		pF
Turn-on time (delay time)	$t_{d(on)}$	$V_{GS} = 10\text{V}$, $I_D = 4\text{A}$ $V_{DD} = 150\text{V}$, $R_L = 37.5\Omega$		25		ns
Rise time	t_r			45		ns
Fall time	t_f			50		ns
Turn-off time (delay time)	$t_{d(off)}$			150		ns
Thermal resistance between channel and case	$R_{th(ch-c)}$				2.5	$^\circ\text{C/W}$



Area of safe operation (ASO)

 $P_D - T_a$ EAS — T_j  $I_D - V_{DS}$  $I_D - V_{GS}$  $V_{th} - T_C$  $R_{DS(on)} - I_D$  $R_{DS(on)} - I_D$  $|Y_{fs}| - I_D$ 