



950MHz FET-Input Buffer with 75Ω Output

General Description

The MAX4005 is a $\pm 5\text{V}$, single-ended unity-gain buffer with a high-impedance JFET input, intended to drive a 75Ω load. A 75Ω thin-film output resistor is included on-board to minimize reflections when driving a 75Ω load through a transmission line of arbitrary length. Gain in this configuration is 0.5.

Features

- ♦ 950MHz Bandwidth
- ♦ 350ps Rise/Fall Times
- ♦ 0.11%/0.03° Differential Gain/Phase Error
- ♦ 1000V/ μs Slew Rate
- ♦ 10pA Input Bias Current
- ♦ 75Ω Output Impedance

MAX4005


Applications

Video Buffer / Line Driver
 Isolation Between High-Impedance Node
 and Low-Impedance Instrument
 Remote Signal Sensing
 Impedance Transformation
 Fanout Multiplier for 75Ω Distribution Systems


Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
MAX4005CSA	0°C to +70°C	8 SO

Typical Operating Circuit



Pin Configuration



950MHz FET-Input Buffer with 75Ω Output

ABSOLUTE MAXIMUM RATINGS

Input Voltage.....	±2.5V	Ground Voltage.....	0.0V
V _{CC} Supply Voltage.....	+5.5V	Continuous Power Dissipation (T _A = +70°C).....	471mW
Output-Stage Supply	+5.5V	Operating Temperature Range.....	0°C to +70°C
V _{EE} Supply Voltage.....	-5.5V	Lead Temperature (soldering, 10sec).....	+300°C
Peaking Pad Voltage.....	0.0V		

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS






(V_{CC} = 4.75V to 5.25V, V_{EE} = -4.75V to -5.25V, T_A = +25°C, stated performance characterized for T_A = 0°C to +70°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
+5V V _{CC} Current	I _{VCC1}	V _{IN} = 0V, R _L = 75Ω	9	14	19	mA
+5V Output Stage Quiescent Current	I _{VCC2}	V _{IN} = 0V, R _L = 75Ω	9	11	14	mA
-5V V _{EE} Current	I _{VEE}	V _{IN} = 0V, R _L = 75Ω	17	24	31	mA
Output Offset Voltage		R _L = 75Ω, gain = 0.5	-3		3	mV
Output Resistance	R _{OUT}		74.0	75.0	76.5	Ω
Input Current	I _B	V _{IN} = 0V	-1	0.01	1	nA
Gain		R _L = 75Ω	0.49	0.50	0.51	
Linearity		R _L = 75Ω, measured over input dynamic range		0.50	1	%
Input Dynamic Range		R _L = 75Ω, gain = 0.5	-1.3		1.6	V
+5V V _{CC} Power-Supply Rejection Ratio		V _{IN} = 0V, R _L = 75Ω	40	55		dB
+5V Output Stage Power-Supply Rejection Ratio		V _{IN} = 0V, R _L = 75Ω	50	75		dB
-5V V _{EE} Power-Supply Rejection Ratio		V _{IN} = 0V, R _L = 75Ω	40	60		dB
TYPICAL OPERATING PERFORMANCE (V _{CC} = 5.0V, V _{EE} = -5.0V, R _L = 75Ω, T _A = +25°C, unless otherwise noted.)						
Bandwidth	BW	-3dB		950		MHz
		-6dB		2000		
Input Capacitance	C _{IN}			2.2		pF
Settling Time to 0.1%	t _{SET}	V _{IN} = 0.25V step, V _{OUT} = 0.125V step		2		ns
Rise/Fall Times	t _{RISE} /t _{FALL}	V _{IN} = 0.25V step with < 30ps rise time		350		ps
Gain Flatness	GF	At 30MHz		±0.01		dB
Gain Flatness ±0.1dB	GF1			60		MHz
Gain Flatness ±0.2dB	GF2			80		MHz
Slew Rate	SR	V _{IN} = 2.5V step with 200ps rise time		1000		V/μs
Overdrive Recovery Time	t _{OD}	V _{IN} = 2.5V step		5		ns
2nd Harmonic Distortion	2HD	At 50MHz		-50		dBc
3rd Harmonic Distortion	3HD	At 50MHz		< -60		dBc
3rd-Order Intercept	TOI	At 100MHz		28		dBm
Differential Gain Error	DG	At 3.58MHz		0.11		%
Differential Phase Error	DP	At 3.58MHz		0.03		degrees

950MHz FET-Input Buffer with 75Ω Output

Typical Operating Characteristics

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



950MHz FET-Input Buffer with 75Ω Output

Pin Description

PIN	NAME	FUNCTION
1, 8	VEE	-5V Negative Supplies
2	IN	High-Impedance Input
3	GND	Ground
4	VCC	+5V Positive Supply
5	VCCO	Output Stage +5V Positive Supply
6	OUT	Output ($Z_{OUT} = 75\Omega$)
7	PEAK	Normally no connection. Capacitor to ground will peak frequency response.

Applications Information

Power Supply

The MAX4005 allows for two separate +5V supplies for the output stage and the rest of the MAX4005 circuit. The supplies are bonded out separately to give the option of using a different +5V supply. The output stage is a Class A type, with the output transistor fed by a current source in the emitter, so its current will vary with output signal. For best bandwidth and pulse response, solder bypass chip capacitors directly from the supply pins on the four corners of the package to a ground plane.

Input Impedance

The MAX4005 has a JFET input with an input capacitance of only 2pF. As a result, the leakage current is typically less than 10pA. This exceptionally high input impedance is important in applications that require isolation between a high source impedance and a low-impedance transmission cable. An attenuator may be used in front of the MAX4005 to increase the dynamic range and reduce input capacitance.

Output Impedance

A 75Ω precision thin-film output resistor is included on-board to provide more precise reverse termination than standard discrete resistors. This minimizes reflections caused by impedance mismatching when driving transmission cable. The MAX4005 can also drive a 50Ω load with only a slight loss in amplitude (gain drops from 0.5 to 0.4). The typical operating performance specifications shown in the *Electrical Characteristics* have been verified with a 50Ω load, as well as a 75Ω load.

Frequency Response Peaking

To peak the response to compensate for losses when driving long transmission lines, connect a chip capacitor of about 10pF to 50pF between the PEAK pin and ground. This peaking occurs in the 200MHz to 500MHz range. The PEAK pin will normally be left open for flat-test response.

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

4 Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 (408) 737-7600