

THIRD ANGLE PROJECTION

NOTES

- A. MATERIAL AND FINISH
1. HOUSING, LEVER, LOCK PLUG AND TRIGGER: DIE CAST ZINC, SEE ASSEMBLY PART NUMBER TABLE.
 2. SPRING: 302 STAINLESS STEEL, PASSIVATED
 3. TORSION SPRING: 302 STAINLESS STEEL, NATURAL.
 4. SPIRAL PIN: SAE 51420, NATURAL
 5. LOCKWASHER: SPRING STEEL, ZINC ALLOY PLATE BRIGHT PLUS SEALER.
 6. SCREWS AND HEX NUT: LOW CARBON STEEL, ZINC ALLOY PLATE BRIGHT PLUS SEALER.
 7. BRACKET: 1010 STEEL, ZINC ALLOY PLATE BRIGHT PLUS SEALER.
 8. KEYS: BRASS, NICKEL PLATED.
- B. MOUNTING SCREW ASSEMBLY CONSISTS OF: M5 SCREW WITH LOCKWASHER, USE LONGER SCREWS (NOT SUPPLIED) FOR THICKER DOORS.
- C. LOCKPLUG INSTALLATION:
1. POSITION LOCKPLUG AND ORIENT RETAINING WAFFER (LAST WAFFER LOCATED AT THE BOTTOM OF LOCK) AT THE LOCK POSITION AND INSERT INTO THE TRIGGER.
 2. BE SURE THE LOCKPLUG IS FULLY SEATED AGAINST THE TRIGGER, THEN REMOVE KEY.

