

DATA SHEET

Our products make your products perform!

DeoxIT® **DN5 Spray** Contact Cleaner & Rejuvenator

Part No.: DN5S-6N

Container Size: 163 g

Product Description:

Unique contact cleaner, rejuvenator, conductivity enhancer and lubricant; dissolves oxidation and corrosion on metal surfaces, fills in microscopic gaps and reseals surface for better contact to enhance flow of electricity. Improves connector performance/reliability.

Temperature range: -34 to +200°C.



Features/Benefits:

Spray - Quick Dry, Non Drip and Safe on Plastics.

DeoxIT® D100L concentrate has approximately 20% chemical cleaning action.

Excellent cleaning/deoxidizing, good protection, no ozone depletion.

Improves conductivity and reduces intermittent connections.

Reduces arcing, RFI, wear and abrasion.

Cleaner Audio - Clearer Video - Reliable Data.

Formulation:

5% DeoxIT® D100L

70-74% 1,1,1,3,3-PENTAFLUOROPROPANE (460-73-1)

1-5% isopropyl alcohol (67-63-1)

20% hydrocarbon propellant (75-28-5, 74-98-6)



DeoxIT® - Product Selection Guide

	DOUNE!		DeoxIT® GOLD GxL	DeoxIT® GOLD Gx2		DeoxIT® FaderLube
New Surfaces		V	~	V	V	~
* In Service / Used	/					~
Gold surfaces		V	V	~		
Oxidation / corrosion visible	V					
Conductive plastics						~
** Outdoor / Severe environments	V					V
Deoxidizing / cleaning properties	20%	0.1%	0.1%	0.0%	0.0%	0.0%
Metal / Plastic surfaces	Yes	Yes	Yes	Yes	Yes	
Plastics compatibility	Excellent	Excellent	Exceller	nt Excelle	nt Exceller	nt Excellent
Temperature range (°C)	-34/200	-45/240	-45/310	-45/500	-34/210	-26/150
Stationary & moving surfaces	Yes	Yes	Yes	Yes	Yes	Yes
Seals & protects base metals	Good	Excellent	Exceller	nt Excelle	nt Good	No

- ✓ All products are Nonflammable and RoHs Compliant
- In Service: Clean with DeoxIT®. For added protection, follow with DeoxIT® GOLD (indoors), DeoxIT® SHIELD (outdoors) or DeoxIT® Grease (additional barrier).
- ** Severe environments: Pre-clean with DeoxIT®. Follow with DeoxIT® SHIELD or DeoxIT® Grease.

DeoxIT® - Spray Selection Guide

Product Series	FP	QD	NF	РС	VOC
Standard - 5% solution	~			~	75
D5S-6, D5MS-15, G5S-6, G5MS-15,					
S5S-6, S5MS-15, F5S-6, F5MS-15					
N Series - 5% solution		~	V	~	20
DN5S-6N, DN5MS-15, GN5S-6N,					
GN5MS-15, SN5S-6, SN5MS-15					
X Series - 5% solution		~	V	~	20
GX5S-6N					
100 Series - 100% solution			~	~	0
D100S-2, G100S-2, F100S-2					

FP = Flushing properties QD = Quick dry / non drip NF = Nonflammable PC = Plastics compatibility VOC = VOC (%)

Other Applicators:

D5S-6	5%	spray	142 g	flammable
D5MS-15	5%	mini-spray	14 g	flammable
DN5MS-15	5%	spray	14 g	nonflammable
D100S-2	100%	spray	57g	nonflammable
D100P	100%	pen	6 mL	nonflammable
K-D1W	100%	wipes	individual	nonflammable
D100L-2DB	100%	brush	7.4 mL	nonflammable
D100L-25C	100%	needle dispenser	25 mL	nonflammable
D100L (bulk)	100%	bottle/drum	assort.	nonflammable
D5L (bulk)	5%	bottle/drum	assort.	flammable

DeoxIT® Essential Reference:

DeoxIT® - Brings old systems back to life!

DeoxIT® GOLD - Maintains new system performance!

DeoxIT® SHIELD - Maintains new system performance for severe environments!

Shipping Information:

Hazardous: Y - ORMD VOC (%): >25%

Other Information:

YES RoHS Compliant:

DN5S-6N http://store.caig.com/app/site/media/sitemedia.nl/id.908/.f MSDS Link: DeoxIT® Product Sheet: http://store.caig.com/app/site/media/sitemedia.nl/id.775/.f

MentorCard Link: http://www.deoxit.com/pdf/MentorCards av.pdf WHY DeoxIT® is Different: http://www.deoxit.com/pdf/why_deoxit.pdf

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither CAIG Laboratories, Inc., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. All service performed on internal parts and equipment should be provided by qualified technicians.

Contact Information:



North America

CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064 USA Tel: (858) 486-8388

Fax: (858) 486-8398

Website

www.caig.com www.deoxit.com

General email

info@caig.com

Technical email

tech@caig.com