



REV	DESCRIPTION	DATE	DESIGNED
△			

NOTE

- Unless otherwise specified, tolerances are ± 0.3 .
- The deviation at the top of post shall be ± 0.15 .
- Post side with holding construction for housing.
- Tolerance of hole pitch on PCB are not cumulative.

B5P9S-VH-() (LF) (SN)	5	31.68	35.56	33.08
B4P7S-VH-() (LF) (SN)	4	23.76	27.66	25.16
B3P5S-VH-() (LF) (SN)	3	15.84	19.74	17.24
B2P3S-VH-() (LF) (SN)	2	7.92	11.82	9.32
Part No.	Cir-cuits	A	B	C

Part No.	Color
B()P()S-VH (LF) (SN)	Natural
B()P()S-VH-BK (LF) (SN)	Black
B()P()S-VH-BL (LF) (SN)	Blue
B()P()S-VH-R (LF) (SN)	Red
B()P()S-VH-Y (LF) (SN)	Yellow
B()P()S-VH-M (LF) (SN)	Green

2	WAFER	66 NYLON		UL94V-0
1	POST	BRASS	COPPER-UNDERPLATED TIN-PLATED	
No.	PART NAME	MATERIAL	SURFACE FINISH	REMARKS
SIZE	UNIT	SCALE	PROJECTION	DATE
A3	METRIC	3:1	☉	APR.12.2005
APPROVED	CHECKED	DESIGNED	DRAWN	SERIES NAME
S.K		T.S	M.O	VH CONNECTOR
PART No.				B()P()S-VH-() (LF) (SN)
DRAWING No.				KRD-35752 RD

JST J.S.T.MFG.CO.,LTD.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

EC4109-2