

Product: <u>1618A</u> ☑

CATV Video, RG11, 14 AWG BCCS, Quad Shield, Waterblocked



Product Description

Series 11, 14 AWG solid .064" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® IV quad shield (Foil + 60% Braid + Foil + 40% Braid), polyethylene jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material Nominal Diameter No. of Coax 14 Solid BCCS - Bare Copper Covered Steel 0.064 in 1 Conductor Count: 1 Insulation Material Nominal Diameter

| PE - Polyethylene (Foam) | 0.28 in |
|--------------------------|---------|
| Insulation Table Notes: | |

Insulation Table Notes: Gas Injected

Outer Shield

| Type | Layer | Material | Material Trade Name | Coverage [%] |
|-------|----------|-------------------------------|---------------------|--------------|
| Tape | 1 | Tri-Laminate (Alum+Poly+Alum) | Duofoil® | 100% |
| Braid | 2 | Aluminum | | 60% |
| Tape | 3 | Tri-Laminate (Alum+Poly+Alum) | Duofoil® | 100% |
| Braid | 4 | Aluminum | | 40% |
| Outer | Shield 7 | Table Notes: | CoreGuard® | |

Outer Jacket

| Material | Nominal Diameter |
|-------------------|------------------|
| PE - Polyethylene | 0.407 in |

Electrical Characteristics

Conductor DCR

| N | Nominal Conductor DCR | Nominal Outer Shield DCR | Outer Conductor DCR |
|---|-----------------------|--------------------------|---------------------|
| 1 | 11 Ohm/1000ft | 3 Ohm/1000ft | 3 Ohm/1000ft |

Capacitance

Nom. Capacitance Conductor to Shield 16.2 pF/ft

Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance
75 Ohm

Return Loss

| Frequency [MHz] | Min. Structural Return Loss (SRL) |
|-----------------|-----------------------------------|
| 5 - 1000 MHz | 20 dB |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.2 ns/ft | 83% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) |
|-----------------|-----------------------------------|
| 5 MHz | 0.38 dB/100ft |
| 55 MHz | 0.96 dB/100ft |
| 211 MHz | 1.9 dB/100ft |
| 270 MHz | 2.13 dB/100ft |
| 300 MHz | 2.25 dB/100ft |
| 350 MHz | 2.42 dB/100ft |
| 400 MHz | 2.6 dB/100ft |
| 450 MHz | 2.75 dB/100ft |
| 550 MHz | 3.04 dB/100ft |
| 750 MHz | 3.65 dB/100ft |
| 870 MHz | 4.06 dB/100ft |
| 1000 MHz | 4.35 dB/100ft |

Voltage

Non-UL Voltage Rating 300 V RMS

Temperature Range

| Operating Temperature Range: | -55°C To +80°C | |
|------------------------------|----------------|--|

Mechanical Characteristics

| Bulk Cable Weight: | 52 lbs/1000ft |
|--------------------------------------|---------------|
| Maximum Recommended Pulling Tension: | 308 lbs |
| Minimum Minor Axis Bend Radius: | 4.25 in |

Standards

| RG Type: | 11 |
|--------------|----|
| Series Type: | 11 |

Applicable Environmental and Other Programs

| Environmental Space: | Outdoor - Water Exposure |
|--|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Burial: | Yes |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Plenum/Non-Plenum

| Plenum (Y/N): | No | |
|---------------|----|--|

Related Part Numbers

| Va | ria | nts |
|----|-----|-----|

| Item # | Color | Put-Up Type | Length | UPC |
|---------------|--------|-------------|----------|--------------|
| 1618A 0101000 | Black | Reel | 1,000 ft | 612825119296 |
| 1618A 0031000 | Orange | Reel | 1,000 ft | 612825119289 |

History

| Update and Revision: | Revision Number: 0.388 Revision Date: 02-03-2025 |
|----------------------|--|

© 2025 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.