

MN86074

Image Processing LSI

■ Overview

The MN86074 boosts image quality by applying various image processing techniques to the analog signal from an image sensor. Features include correction of laser printer dot spreading at the pixel level, processing to enhance the compression ratio, reproduction of halftone images with 64-gradation, two-dimensional MTF correction using moire suppression, and infinite shading for all pixels using a division technique. These combine to yield top image reproduction quality.

■ Features

- Image processing that yields top image quality
 - Infinite shading for all pixels using a division technique
 - Error dispersion processing that reproduces halftone images with 64-gradation
 - User-programmable gamma curve
 - Two dimensional MTF correction
 - High-quality reduction with a user-specified scaling factor
 - Preserves halftone gradation
 - Preserves fine black lines for text
 - High-speed processing requiring only 2 ms per line for an A3 page at 200 dpi
 - Built-in analog processing circuits: offset correction circuit, gain correction circuit, and 8-bit analog-to-digital converter
 - Drive signal generator for CCDs, CISs, and other image sensors
- Gain control: Analog control using an external operational amplifier and the built-in field effect transistor (FET)
 - An external resistor determines the follow-up range. (The standard range is from +6 dB to -12 dB.)
 - Built-in circuits: Gain control circuit + FET
 - A/D converter: Half flash converter
 - Number of bits: 8
 - Conversion speed: 0.1 to 1.5 MHz
 - Shading correction
 - Infinite shading for all pixels using a division technique
 - Distortion correction levels relative to A/D converter's dynamic range
 - 0 – 75% 6-bit precision
 - 75 – 87.5% 5-bit precision
 - 87.5 – 93.8% 4-bit precision
 - MTF correction:
 - Laplacian transforms (processing for text images)
 - Reference to five pixels
 - Halftone processing
 - Error dispersion processing: Reproduction of 64-gradation using 6-bit processing
 - Gamma correction:
 - User-definable by loading a conversion curve
 - Conversion levels: 6 bits to 6
 - Binary coded:
 - Fixed slice
 - Slice level: User-specified 5-bit value
 - Reduction in primary scanning direction:
 - Decimation with image clock or line enable
 - Reduction ratio in primary scanning direction:
 - Binary coded 0.78% to 100%
 - Halftone processing: 50 to 100% (in 0.78% increments)
 - Reduction correction in primary scanning direction
 - Black pixel preservation (for reduction in primary scanning direction)

■ Brief Specifications


- Image processing speed: 0.1 to 1.5 million pixels per second
- Pixels per line: max. 8192 pixels-blanking pixels
 - 1-line interval: max. 8192 pixels
- Offset correction: negative feedback to preamplifier
 - The chip controls the feedback voltage using A/D conversion data from black pixel runs.
 - Built-in circuits: Feedback voltage control circuit + source follower circuit

- Line density correction in secondary scanning direction
 - Three-line OR processing (for line density conversion in secondary scanning direction from 7.7 line/mm to 3.85)
- Clock inputs
 - Image clock $\times 16$
 - Image clock $\times 8$
- Sensor interfaces
 - CCD sensor
 - Generates the following drive signals: FSH (ϕ SH), FCK1, 2 (ϕ 1, 2), FR (ϕ R), FSP (ϕ SP)
 - Contacting image sensor
 - Generates the following drive signals: FSH (SI), FSP (CLK).
 - FSP (CLK): 75% or 87.5%.
- Memory interfaces
 - Line lengths up to 2048 pixels 64-Kbit SRAM $\times 1$
 - Line lengths of 2049 to 4096 pixels
 - 64-Kbit SRAM $\times 2$
 - or 256-Kbit SRAM $\times 1$
 - Line lengths of 4097 to 8192 pixels
 - 256-Kbit SRAM $\times 1$
- Image bus interface
 - Serial mode with request ($\overline{\text{VREQ}}$) input and enable ($\overline{\text{VSEN}}$), clock ($\overline{\text{VSCK}}$), and data ($\overline{\text{VSDA}}$) outputs
- Scanning modes
 - Free scanning
 - Cycle scanning
- System interface
 - Interface to 8-bit microprocessors (Intel format)
- Image data I/O function
 - Image data output after shading correction (8 bits)
 - Image data output after multivalued smoothing (6 bits)
 - Image data input sent from external A/D converter (8 bits)
- Output ports
 - 8 pins (pins double as image data I/O pins)
- Mechanism drive interface
 - User-defined timing pulse output
- Power supply
 - Digital circuits, DV_{DD} : 5.0 V
 - Analog circuits, AV_{DD} : 5.0 V
 - A/D converter reference voltages
 - V_{REFH} : 5.0 to 3.0V
 - V_{REFL} : 2.0 to 0.0V

■ Applications

- Facsimile equipment


■ Pin Assignment




(TOP VIEW)

QFH084-P-1212


■ Pin Function Chart




■ Application Circuit Example #1: Line lengths up to 2048 pixels



■ Application Circuit Example #2: Line lengths of 2049 to 4096 pixels




■ Application Circuit Example #3: Line lengths of 4097 to 8192 pixels



■ Package Dimensions (Unit: mm)

QFH084-P-1212



Request for your special attention and precautions in using the technical information and semiconductors described in this material

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this material is limited to showing representative characteristics and applied circuit examples of the products. It does not constitute the warranting of industrial property, the granting of relative rights, or the granting of any license.
- (3) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this material are subject to change without notice for reasons of modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, redundant design is recommended, so that such equipment may not violate relevant laws or regulations because of the function of our products.
- (6) When using products for which dry packing is required, observe the conditions (including shelf life and after-unpacking standby time) agreed upon when specification sheets are individually exchanged.
- (7) No part of this material may be reprinted or reproduced by any means without written permission from our company.

Please read the following notes before using the datasheets

- A. These materials are intended as a reference to assist customers with the selection of Panasonic semiconductor products best suited to their applications.
Due to modification or other reasons, any information contained in this material, such as available product types, technical data, and so on, is subject to change without notice.
Customers are advised to contact our semiconductor sales office and obtain the latest information before starting precise technical research and/or purchasing activities.
- B. Panasonic is endeavoring to continually improve the quality and reliability of these materials but there is always the possibility that further rectifications will be required in the future. Therefore, Panasonic will not assume any liability for any damages arising from any errors etc. that may appear in this material.
- C. These materials are solely intended for a customer's individual use.
Therefore, without the prior written approval of Panasonic, any other use such as reproducing, selling, or distributing this material to a third party, via the Internet or in any other way, is prohibited.