



- Ⓡ Height: 7.4mm Max
- Ⓡ Footprint: 19.8mm x 19.6mm Max
- Ⓡ Current Rating: up to 73A
- Ⓡ Inductance Range: .405μH to 6.2μH
- Ⓡ Moisture Sensitivity Level: 1
- Ⓡ Storage Temperature: -40°C to +130°C

Electrical Specifications @ 25°C — Operating Temperature -40°C to +130°C⁸


Part Number ^{5,7}	Inductance @ Irated (μH ±15%)	Irated ¹ (A _{DC})	DCR (mΩ)		Inductance @ 0 A _{DC} (μH ±15%)	Saturation Current ²		Heating ³ Current (A)
			TYP	MAX		25°C	100°C	
2-TURN (LOW - LOSS) SERIES								
PL10100	0.45	73	.38	.48	0.45	95	80	73
PL10101	0.63	54	.38	.48	0.65	63	53	73
PL10102	0.85	39	.38	.48	0.91	46	37	73
PL10103	1.05	30	.38	.48	1.10	35	30	73
PL10104	1.25	25	.38	.48	1.30	29	26	73
PL10105	1.45	21	.38	.48	1.50	24	22	73
2-TURN SERIES								
PL10106	0.45	52	.78	.98	0.45	95	80	52
PL10107	0.63	52	.78	.98	0.65	63	53	52
PL10108	0.85	39	.78	.98	0.91	46	37	52
PL10109	1.05	30	.78	.98	1.10	35	30	52
PL10110	1.25	25	.78	.98	1.30	29	26	52
PL10111	1.45	21	.78	.98	1.50	24	22	52
3-TURN SERIES								
PL10112	0.95	42	1.15	1.43	1.0	68	54	42
PL10113	1.40	36	1.15	1.43	1.5	43	35	42
PL10114	1.90	25	1.15	1.43	2.0	29	25	42
PL10115	2.40	20	1.15	1.43	2.5	23	21	42
PL10116	2.80	15	1.15	1.43	3.0	18	16	42
PL10117	3.40	12	1.15	1.43	3.5	15	13	42
4-TURN SERIES								
PL10118	1.60	37	1.44	1.80	1.60	55	43	37
PL10119	2.40	30	1.44	1.80	2.42	35	27	37
PL10120	3.30	17	1.44	1.80	3.60	20	18	37
PL10121	4.00	14	1.44	1.80	4.40	16	15	37
PL10122	4.90	11	1.44	1.80	5.34	13	12	37
PL10123	5.80	9	1.44	1.80	6.20	11	10	37

NOTES:

- The rated current as listed is either 85% of the saturation current or the heating current, depending on which value is lower.
- The saturation current is the current which causes the inductance to drop by 15% at the stated ambient temperatures (25°C and 100°C). This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effects) to the component.
- The heating current is the DC current which causes the temperature of the part to increase by approximately 45°C. This current is determined by mounting the component on a PCB with .25" wide, 2 oz. equivalent copper traces, and applying the current to the device for 30 minutes with no forced air cooling.
- In high volt*time applications, additional heating in the component can occur due to core losses in the inductor which may necessitate derating the current in order to limit the temperature rise of the component. In order to determine the approximate total losses (or temperature rise) for a given application, the total copper and core losses should be taken into account. For approximate value of core losses, in a given application, use the core loss graph on page 24.
- Optional Tape & Reel packaging can be ordered by adding a "T" suffix to the part number (i.e. PL10118 becomes PL10118T). Pulse complies to industry standard tape and reel specification EIA481.
- Meets solderability test per IPC/EIA J-STD-002B using flux type ORLO.
- The temperature of the component (ambient plus temperature rise) must be within the stated operating temperature range.

Mechanical


PL101XX




Suggested Pad Layouts and Schematics

PL101XX


PL10100 - PL10111
 .405 to 1.50 μ H
 21 to 73 Adc



PL10112 - PL10117
 1.00 to 3.40 μ H
 12 to 42 Adc








PL10118 - PL10123
 1.60 to 6.20 μ H
 9 to 37 Adc



Inductance vs. Current Characteristics (25°C)


PL101XX



Total Power Dissipation = Copper Loss (W) + Core Loss (W)

Copper Loss (W) = $Current(rms)^2 \cdot DCR(m\Omega) / 1000$
Core Loss (W) = per table

Transceiver Tin/Lead Recommended Reflow Profile (Based on J-STD-020D)



T _{SMIN} (°C)	T _{SMAX} (°C)	T _L (°C)	T _P (°C MAX)	t _s (s)	t _L (s)	t _p (s MAX)	Ramp-up rate (T _L to T _P)	Ramp-down rate (T _P to T _L)	Time 25°C to peak temperat (s MAX)
100	150	183	225	60-120	60-150	20	3°C/s MAX	6°C/s MAX	360

Notes:

1. All temperatures measured on the package leads.
2. Maximum times of reflow cycle: 2.

For More Information

PulseR North America
 Headquarters
 Two Pearl Buck Court
 Bristol, PA 19007
 U.S.A.

For Global Sales Representatives and Locations Visit:
<http://www.pulseruggedized.com>

Tel: +1.215. 781. 6400
 Fax: +1.215. 781. 6403

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2018. PulseR, LLC. All rights reserved.