



PRODUCT OVERVIEW

The HPR4XXC Series uses advanced circuit design and packaging technology to realize superior reliability and performance. A 70kHz push-pull oscillator is used in the input stage. The HPR4XXC Series has a wide frequency response and low oscillation problems when used with high frequency isolation amplifiers. Reduced parts count and high efficiency add to the reliability of the HPR4XXC Series.

degradation of reliable operation. In addition, the high efficiency of the HPR4XXC Series means the series is able to offer greater than 10 W/inch³ of output power density. Operation down to no load will not impact the reliability of the series, although this product has a >1mA minimum load for specifications purposes.

The HPR4XXC Series provides high isolation in a very small package. The use of surface mounted devices and manufacturing technologies makes it possible to offer premium performance and low cost.

FEATURES

- High Isolation Voltage: 3000 VPK Test
- Single-In-Line Package (SIP)
- Internal Input and Output
- Low Cost
- Non-Conductive Case

- High Output Power Density: 10 Watts/Inch³
- Extended Temperature Range: -25°C to +85°C
- High Efficiency to 79%
- RoHS Compliant

As of September 2014, ONLY the following part numbers will be available: HPR400C; HPR403C; HPR404C; HPR417C

PRODUCT SELECTION CHART

	Model		Nominal Input Voltage	Rated Output Voltage	Rated Output Current	Input Current			Reflected Ripple Current	Efficiency	Recommended Alternatives	
						No Load	Rated Load					
							Typ.	Max.				
			V _{DC}	V _{DC}	mA	mA		mAp-p	%			
DESIG		HPR400C	5	5	150	20	216	235	10	69	NMV0505SAC / MEV1S0505SC	
	OBSOLETE	*	HPR402C	5	15	50	20	212	235	5	71	NMV0515SAC / MEV1S0515SC
		HPR403C	5	±5	±75	20	218	245	5	68	NMV0505SC / MEV1D0505SC	
		HPR404C	5	±12	±30	20	212	235	5	68	NMV0512SC / MEV1D0512SC	
OBSOLETE	*	HPR405C	5	±15	±25	20	220	220	5	75	NMV0515SC / MEV1D0515SC	
OBSOLETE	*	HPR407C	12	12	62	10	81	90	5	77	NMV1212SAC / MEV1S1212SC	
OBSOLETE	*	HPR410C	12	±12	±30	10	81	90	5	74	NMV1212SC / MEV1D1212SC	
OBSOLETE	*	HPR411C	12	±15	±25	10	81	90	5	77	NMV1215SC / MEV1D1215SC	
OBSOLETE	*	HPR414C	15	15	50	8	72	80	5	69	NMV1515SAC / MEV1S1515SC	
ECO		HPR417C	15	±15	±25	8	63	66	5	79	NMV1515SC / MEV1D1515SC	
	OBSOLETE	*	HPR418C	24	5	150	8	48	53	15	65	MEV1S2405SC
	OBSOLETE	*	HPR422C	24	±12	±30	8	45	50	15	67	MEV1D2412SC
	OBSOLETE	*	HPR423C	24	±15	±25	8	45	50	15	69	MEV1D2415SC
OBSOLETE		HPR401C	5	12	62	20	212	235	5	70	NMV0512SAC / MEV1S0512SC	
		HPR406C	12	5	150	10	90	100	5	69	NMV1205SAC / MEV1S1205SC	
		HPR408C	12	15	50	10	81	90	5	77	NMV1215SAC / MEV1S1215SC	
		HPR409C	12	±5	±75	10	88	98	5	71	NMV1205SC / MEV1D1205SC	
		HPR412C	15	5	150	8	72	80	5	69	NMV1505SAC/ MEV1S1505SC	
		HPR413C	15	12	62	8	72	80	5	69	NMV1512SAC / MEV1S1512SC	
		HPR415C	15	±5	±75	8	72	80	5	69	NMV1505SC / MEV1D1505SC	
		HPR416C	15	±12	±30	8	63	70	5	76	NMV1512SC / MEV1D1512SC	
		HPR419C	24	12	62	8	48	53	15	65	MEV1S2412SC	
		HPR420C	24	15	50	8	45	50	15	69	MEV1S2415SC	
		HPR421C	24	±5	±75	8	45	50	15	69	MEV1D2405SC	

★ LAST TIME BUY: AUGUST 31, 2014. CLICK HERE FOR OBSOLESCENCE NOTICE OF FEBRUARY 2014.



SPECIFICATIONS, ALL MODELS

Specifications are at $T_A = +25^\circ\text{C}$ nominal input voltage unless otherwise specified.

	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
OUTPUT	INPUT					
	Voltage Range		4.5	5	5.5	VDC
			10.8	12	13.2	VDC
			13.5	15	16.5	VDC
			21.6	24	26.4	VDC
	OUTPUT					
	Rated Power				750	mW
	Voltage Setpoint Accuracy	Rated Load, Nominal V_{IN}			± 5	%
	Ripple & Noise	BW = DC to 10MHz		150	200	mVp-p
		BW = 10Hz to 2MHz		30	40	mVrms
GENERAL	Voltage (Over Input Voltage Range)	1mA to Rated Current, $V_{OUT} = 5V$	4.75		7	VDC
		1mA to Rated Current, $V_{OUT} = 12V$	11.40		15	VDC
		1mA to Rated Current, $V_{OUT} = 15V$	14.25		18	VDC
	Temperature Coefficient			.01	.05	%/ $^\circ\text{C}$
	REGULATION					
	Load Regulation (All other modes)	Rated Load to 1mA Load		3		%
	GENERAL					
	ISOLATION					
	Rated Voltage		1000			VDC
	Test Voltage	60 Hz, 60 Seconds	3000			Vpk
	Resistance		10			$G\Omega$
	Capacitance			25	100	pF
	Leakage Current	$V_{ISO} = 240VAC, 60Hz$		2	7	μArms
	Switching Frequency			170		kHz
	Frequency Change	Over Line and Load		24		%
	Package Weight				3	g
	MTTF per MIL-HDBK-217, Rev. F*	Circuit Stress Method				
	Ground Benign	$T_A = +25^\circ\text{C}$	7.9			MHr
	TEMPERATURE					
	Specification		-25	+25	+85	$^\circ\text{C}$
	Operation		-40		+100	$^\circ\text{C}$
	Storage		-40		+110	$^\circ\text{C}$

SOLDERING INFORMATION


The HPR4XXC devices are intended for wave soldering or manual soldering.

They are not intended to be subject to surface mount processes under any circumstances.


The normal wave soldering process can be used with these devices where the device is subjected to a maximum wave temperature of 260°C for a period of no more than 10 seconds. Within this time and temperature range, the integrity of the device's plastic body will not be compromised and internal temperatures within the converter will not exceed 175°C . Care should be taken to control manual soldering limits identical to that of wave soldering.

TYPICAL PERFORMANCE CURVES

Specifications are at $T_A = +25^\circ\text{C}$ nominal input voltage and nominal load.




SAFE OPERATING AREA



NOTES:

- 1.) When operated within the SAFE OPERATING AREA as defined by the above curves, the output voltage of HPR4XXC devices is guaranteed to be within 95% of its steady-state value within 100 milliseconds after the input voltage has reached 95% of its steady-state value.
- 2.) For dual output models, total load capacitance is the sum of the capacitances on the plus and minus outputs.

MECHANICAL



PIN CONNECTIONS	
1.	+VIN
2.	-VIN
5.	-VOUT
6.	COM*
7.	+VOUT

*Common pin not present on single output models.

Notes:

All dimensions are in inches (millimeters).
 GRID: 0.100 inches (2.54 millimeters)
 PIN PLACEMENT TOLERANCE: ± 0.015"
 MATERIAL: Lead material is phosphor bronze; lead finish is 100-300 microinches of matte tin over a barrier layer of 5-40 microinches of nickel.

ABSOLUTE MAXIMUM RATINGS

Internal Power Dissipation.....450mW
 ShortCircuitDurationMomentary
 Lead Temperature (soldering, 10 seconds max ...+300°C*)

*NOTE: Refer to Reflow Profile for SMD Models.

ORDERING INFORMATION

Device Family _____ **HPR** **4XX** **C**
 HPR Indicates DC/DC Converter
 Model Number _____
 Selected from Table of Electrical Characteristics
 RoHS Compliant Version _____



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Murata:](#)

[HPR400](#) [HPR401](#) [HPR402](#) [HPR406](#) [HPR407](#) [HPR408](#) [HPR412](#) [HPR413](#) [HPR414](#) [HPR418](#) [HPR419](#) [HPR420](#)
[HPR403](#) [HPR404](#) [HPR405](#) [HPR409](#) [HPR410](#) [HPR411](#) [HPR415](#) [HPR416](#) [HPR417](#) [HPR421](#) [HPR422](#) [HPR423](#)