

TECHNICAL CHARACTERISTICS

SPECIFICATION

>Contact Rating:

25mA, 24VDC
100mA, 50VDC

>Contact Resistance:

50mOHM max.
100mOHM max.

>Insulation Resistance: min. 100MOHM at 500VDC

500VAC for 1 minute

>Dielectric Strength:

1000g max.

>Operating Force:

1000g max.

>Mechanical Life:

min. 5000 cycles

>Electrical Life:

2000 cycles / 25mA, 24VDC

>Flat Actuator with top tape sealed

MATERIAL

>Cover: PPS UL 94V-0, color Black

>Base: PPS UL 94V-0, color Black

>Actuator: PA 46 UL HB, color White

>Tape: Polyimide Film

>Contact: Gold Plated

>Terminal: Gold Plated

SOLDERING INFORMATION

>Terminal in SMD version

>Reflow soldering according to JEDEC J-STD 020 Hot Air 3 cycles max.

>Keep in "off" position during soldering

>For cleaning or washing only with top tape sealed

>VPH Heating Process only with top tape sealed

WASHABLE DEFINITION

Please do not submerge washable products into water or cleaning agents or put them in locations exposed to water or liquids completely.

When cleaning by hand (brushing), please do not use excessive force on our switch to avoid malfunction afterwards, because you could deform function relevant areas or you could damage sealing functions.

Do not clean washable series immediately after soldering. The cleaning agent may be absorbed into the switch through respiration while the switch cools.

ENVIRONMENTAL

>Storage condition: -40°C ~ +85°C

>Operation condition: -40°C ~ +85°C

>Compliance: Lead Free, ROHS, Reach

PACKAGING INFORMATION

>Tape & Reel packaging

>On delivery in "off" position

Pole 1 please refer separateness specification.

Scale - 2:1

DIMENSION


No. Of Pole	2	3	4	5	6
Dim. A (mm)	5.52	8.06	10.60	13.14	15.68
No. Of Pole	7	8	9	10	12
Dim. A (mm)	18.22	20.76	23.30	25.84	30.92

REV	FILE	DATE	BY	EDV NO	Dimension	Position	SIZE
				4181211608xx.dft			A4
e	Pole 1 seperate specification	14-02-25	DaF	Checked			
d	Washable Definition	14-02-24	DaF				
c	dimension 8,4+/-0,2	14-01-31	DaF				
b	warning text	11-10-26	WJ				
a	Actuator: HB was 94V-0	11-08-26	WJ				
				WE eiCan CAD	Würth Elektronik eiCan		
					Scale 2:1		
						Position	
							SIZE
							A4
					Drawing.- No.	4181211608xx	
							System :Solid Edge V20

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.



Pole 1 please refer separateness specification.

