



Specifications for BNC Connectors

BNC style connectors are miniature, light-weight, weatherproof interconnecting devices characterized by their two-stud, quick disconnect bayonet lock coupling arrangement. Their design functions satisfactorily from DC to 11 GHz in static applications, or from DC to 4GHz in applications involving vibration. The connectors typically yield a low VSWR (reflected signal) to 4GHz. Primary applications include radio telecommunications, broadcast equipment, medical equipment, computer, Precision Video, High definition studio broadcast, video switching and test instrumentation where frequent coupling and de-coupling are necessary. Bomar’s BNCs are available in an extensive variety of configurations and cable sizes and are impedance matched to either 50 ohm or 75 ohm.

MATERIALS		
Connector Parts	Material	Equivalent Standard
Connector Body and Parts	Brass	ISOCuZn38Pb2 Body Part
Male Contact Pin	Brass	QQ-B-626
Commercial Grade	Zinc Alloy/Brass	-----
Outer Contact	Brass	QQ-B-750
Socket Contact	Beryllium Copper	QQ-C-530 / MIL-H-7199
-----	Phosphor Copper	CuBe2
Crimp Ferrule	Annealed Copper	QQ-C-576
Insulators, Standard Versions	Teflon	L-P403 / BS4271
-----	Delrin	Grade B
Rubber Gaskets	Silicone Rubber	ASTM-E1418PSI
Plating	Nickel (Silver Optional)	MIL-G-45204

ELECTRICAL

Requirement	Performance		Test † Specification
Impedance	50W	75W	
Frequency Range	0-4GHz	0-1 GHz	-----
VSWR	1.30 Max.		MIL-C-39012
RF Insertion Loss	0.2 db Min. at 3 GHz		MIL-C-39012
RF Leakage	-55 db Min. at 3 GHz		MIL-C-39012
Test Voltage (At Sea Level)	1500V rms		MIL-STD-202
Working Voltage (At Sea Level)	500V rms		MIL-STD-202
Insulation Resistance	5000 Meg ohms Min.		MIL-STD-202
Contact Resistance	3 Milli ohms Max.		MIL-C-39012

MECHANICAL & ENVIRONMENTAL

Requirement	Performance	Test † Specification
Durability	500 Insertions & Extractions Min.	MIL-C-39012
Shock	50 G	MIL-STD-202
Vibration	20 G from 80-2000 Hz	MIL-STD-202
Cable Retention (Cable Types)	60 lbs. Minimum Pull Test	MIL-C-39012
Coupling Nut	60 lbs. Maximum	MIL-C-39012
Temperature Range	Teflon: -55 to +199 C	-----
	Delrin: -40 to +85 C	-----
Moisture Resistance	Continuous Test	MIL-STD-202
Salt Spray	48 Hours	MIL-STD-202

†Products are made to conform to the Mil standard but are for commercial applications and are not QPL.

3 Piece Crimp

BNC three piece crimp connectors feature semi-captive contacts that “click” into place assuring perfect installation. Each crimp pin has a vent hole for optional soldering. Soldering is recommended for all stranded conductors 26 AWG or smaller.

Part Number (Male)	RoHS	(LD), **	Fig. No.	RG/U Cable
310A205A	✓	.200 In.	Fig. 1	6, 21 AWG Center Conductor
310A205A18	✓	.200 In.	Fig. 1	6 CATV, 18 AWG Center Conductor
310A205F	✓	.124 In.	Fig. 1	58A/U, 58C/U Stranded, 141, Thin PVC
310A205FS	✓	.124 In.	Fig. 1	58/U Solid Conductor
310A205FV	✓	.125 In.	Fig. 2	58/U Thin-Net Plenum
310A205FV2	✓	.125 In.	Fig. 2	Mini 59, RGB Cable (23 AWG)
310A205FV3	✓	.125 In.	Fig. 2	Mini 59, RGB Cable (26 AWG)
310A204G	✓	.150 In.	Fig. 1	59, 62, 210
310A205G20	✓	.150 In.	Fig. 1	RG59 20 AWG Center Cond.
310A205G23	✓	.150 In.	Fig. 1	Belden 8241
310A205MV	✓	.125 In.	Fig. 3	174, 178, 196, Mini RGB Cable 50 W
310B205MV	✓	.125 In.	Fig. 3	174, 178, 196, Mini RGB Cable 75 W
310A205N	✓	.090 In.	Fig. 3	179, 187
310A205P	✓	.125 In.	Fig. 1	223
310B205Q	✓	.205 In.	Fig. 1	Belden 8281 True 75 Ohms
310A204T	✓	.150 In.	Fig. 2	59, 62, Plenum
310A208W2	✓	.103 In.	Fig.1	Mini 59, RGB Cable (26 AWG)
✓ RoHS compliant ** crimp shank				



Fig.1



Fig.2



Fig.3



Fig.4



Fig.5

Twist-On and 2 Piece Crimp

BNC Twist-On connectors are field installable and require no tooling other than a stripping tool for the cable preparation. The center conductor is inserted into Bomar’s unique Posi-Con™ contact, as the connector is twisted onto the cable’s outer jacket.

BNC 2 Piece crimp connectors make use of a fully captivated pin. Just insert the center conductor into the connector body, slide the ferrule over the braid, and apply a single hex-crimp to the ferrule. These connectors are easy to install and reliable and are recommended only for the lower data transmission speeds.

Part Number	RoHS	Gender	Fig. No.	RG/U Cable
310A405A	✓	Male	Fig. 8	6, Thick net
310A405F	✓	Male	Fig. 8	58A/U Solid Cond, 141, Thin PVC
310A405F1	✓	Male	Fig. 8	58/U Solid Cond, -.172"-.178"
310A405F2	✓	Male	Fig. 8	58/U Thin Plenum -.158"-.162"
310A405F3	✓	Male	Fig. 8	Thin Plenum .150"
310A405G	✓	Male	Fig. 8	59, 62, 210 PVC
310A405T	✓	Male	Fig. 8	59, 62, 210 Plenum
320A405F	✓	Female	Fig. 8A	58 Solid (PVC)
320A405G	✓	Female	Fig. 8A	59, 62, 210 (PVC)
310X205F	✓	Male	Fig. 6	RG58 (PVC)
310X205G	✓	Male	Fig. 6	RG59, 62 (PVC)
320X205F	✓	Female	Fig. 7	RG58 (PVC)
320X205G	✓	Female	Fig. 7	RG59, 62 (PVC)
✓ RoHS compliant				



Fig.8A



Fig.8



Fig.6



Fig.7

Standard Clamp

BNC standard clamp style is a simplified version of the original military clamp style. It is required that the contact be soldered to the center conductor of the cable.

Part Number	RoHS	Gender	Fig. No.	RG/U Cable
310A105A	✓	Male	9	6
310A105D	✓	Male	9	11A
310A105F	✓	Male	9	58, 58A, 58C, 141
310A105G	✓	Male	9	59, 62, 210
310A105M	✓	Male	9	174, 188, 316
320A105F*	✓	Female	10	58, 58A, 58C, 141
320A105G*	✓	Female	10	59, 62, 214



Figure 9



Figure 10

✓

 RoHS compliant

Specialty Broadcast Plugs

[Click here for complete Broadcast Catalog](#)

Broadcast grade BNC connectors are perfectly matched to 75 ohm impedance’s. The superior plugs are for studio wiring and other broadcast uses. Solid precision machined brass, not die-cast, hold up under the toughest conditions. Here, we are showing the eight most popular but there are many more versions matched to the popular cable manufacturer’s part number.



Part Number	RoHS	Gender	Belden Cable
SBC1505A	✓	Male	1505A
SBC1694A	8281	Male	1694A
SBC1695A	✓	Male	1695A
SBC7731A	✓	Male	7731A
SBC8218	✓	Male	8218
SBC8241	✓	Male	8241
SBC8281	✓		




Figure 13




Figure 14



Figure 15




Figure 16




Fig. 17




Fig. 18



Part Number		Description	Fig No.	Hole ID
321A245A		R/M Crimp, RG6	13	.500
321A245F		R/M Crimp, RG58 , Thin-net PVC	13	.500
321A245FV		R/M Crimp, Thin-Net Plenum	14	.500
321A245G		R/M Crimp, RG59, 62, 210	13	.500
321A245M		R/M Crimp, RG174, 188, 196, 316	14	.500
321B245M*		R/M Crimp, RG174, 188, 196, 316	14	.500
321B245N*		R/M Crimp, RG179, 187	15	.500
326A515		F/M Solder (Grounded)	16	.375
326R515		F/M Solder (Isolated) White Bushing	17	.375
326R515RD		F/M Solder (Isolated) Red Bushing	17	.375
326R515GN		F/M Solder (Isolated) Green Bushing	17	.375
326R515BL				




Fig. 26





Fig. 27B



These BNC jacks are manufactured to the highest standards to assure stability in maintaining impedance matching at 50 ohm and 75 ohm applications. The 50 ohm versions have been approved by most of the U.S. manufacturers of LAN cards, and the 75 ohm is in wide use in High Definition Video applications which require the use of a True 75 ohm connector. Contacts are phosphor bronze and will remain resilient even after hundreds of insertions.

Black Valox (75W) Lo-Profile W/ Posts (TPX) 50W .515 Gold 31
N/A

Part Number		Body Material	Description	Imp.	Height F.M.S.	Contact Plating	Fig. No.
364M095		Nickel/Zinc	4 Post Low Profile, Metal	50W	.453	Gold	38
364M0975		Nickel /Zinc	4 Post Low Profile, Metal	75W	.453	Gold	38
364A595		White Valox	Standard Profile W/ Posts	50W	.610	Gold	28
364A595T		White Valox	Standard Profile W/ Posts (TPX)	50W	.610	Gold	28
364A595NP*		White Valox	Standard Profile WO Posts	50W	.610	Gold	35
364A595NPT*		White Valox	Standard Profile WO Posts (TPX)	50W	.610	Gold	35
364A595B		Black Valox	Standard Profile W/ Posts	50W	.610	Gold	30
364A595BT		Black Valox	Standard Profile W/ Posts (TPX)	50W	.610	Gold	30
364A595BNP*		Black Valox	Standard Profile WO Posts	50W	.610	Gold	35
364A595BNPT*		Black Valox	Standard Profile WO Posts (TPX)	50W	.610	Gold	35
364A595BL		White Valox	Lo Profile W/ Posts	50W	.515	Gold	29
364A595BLT		White Valox	Lo Profile W/ Posts (TPX)	50W	.515	Gold	29
364A595BLNP*		White Valox	Lo-Profile W/O Posts	50W	.515	Gold	34
364A595BLB		Black Valox	Lo-Profile W/ Posts	50W	.515	Gold	31
364A595BLBT							

364A595BLBNP*	✔	Black Valox	Lo-Profile W/O Posts	50W	.515	Gold	34
364M595	✔	Nickel /Zinc	Standard Profile W/ Posts	50W	.620	Gold	32
364M595T	✔	Nickel /Zinc	Standard Profile W/ Posts (TPX)	50W	.620	Gold	32
364M595M	✔	Nickel /Zinc	Super Lo-Profile W/ Clips	50W	.340	Gold	35A
364M595MT	✔	Nickel /Zinc	Super Lo-Profile W/ Clips (TPX)	50W	.340	Gold	35A
364M595L	✔	Nickel / Zinc	Lo-Profile W/ Posts	50W	.529	Gold	33
364M595LT	✔	Nickel / Zinc	Lo-Profile W/ Posts (TPX)	50W	.529	Gold	33
364A595NP	✔	White Valox	Standard Profile WO Posts	50W	.610	Gold	35
364A595NPT	✔	White Valox	Standard Profile WO Posts (TPX)	50W	.610	Gold	35
364A595BNP*	✔	Black Valox	Standard Profile WO Posts	50W	.610	Gold	35
364A595BLNP*	✔	White Valox	Lo-Profile W/O Posts	50W	.515	Gold	-
364A595BLBNP*	✔	Black Valox	Lo-Profile W/O Posts	50W	.515	Gold	34
364A795	✔	White Valox	Standard Profile W/ Posts (TPX)	75W	.610	Gold	28
364A795T	✔	White Valox	Standard Profile W/ Posts	75W	.610	Gold	28
364A795B	✔	Black Valox	Standard Profile W/ Posts	75W	.610	Gold	30
364A795BT	✔	Black Valox	Standard Profile W/ Posts (TPX)	75W	.610	Gold	30
364A795BL	✔	White Valox	Lo-Profile W/ Posts	75W	.515	Gold	29
364A795BLT	✔	White Valox	Lo-Profile W/ Posts (TPX)	75W	.515	Gold	29
364A795BLB	✔	Black Valox	Lo-Profile W/ Posts	75W	.515	Gold	31
364A795BLBT	✔	Black Valox	Lo-Profile W/ Posts (TPX)	75W	.515	Gold	31
364M795	✔	Metal	Standard Profile W/ Posts	75W	.620	Gold	32
364M795T	✔	Metal	Standard Profile W/ Posts (TPX)	75W	.620	Gold	32
364M795L	✔	Metal	Lo-Profile W/ Posts	75W	.529	Gold	33
364M795LT	✔	Metal	Lo-Profile W/ Posts (TPX)	75W	.529	Gold	33
364F595BL	✔	White Valox	9400pF 500V Decoupled	50W	.515	Gold	36
364F595BLB	✔	Black Valox	9400 pF 500V Decoupled	50W	.515	Gold	37
364H595BL	✔	White Valox	9400 pF 1500V Decoupled	50W	.515	Gold	36
364H595BLB	✔	Black Valox	9400 pF 1500V Decoupled	50W	.515	Gold	37
364NT	✔	Zinc/Brass	Jam Nut (364 Series)	N/A	----	----	36N
364LW	✔	Zinc/ Steel	Lock Washer (364Series)	N/A	----	----	37N
364 KNT	✔	Brass/Nickel	Knurled Nut (364 Series)	N/A	----	----	38N



Fig. 28



Fig. 29



Fig. 30



Fig. 31



Fig. 32



Fig. 33



Fig. 34



Fig. 35



Fig. 36 (top) Fig. 37

✔ RoHS compliant reflow or wave solder ✔ RoHS compliant wave solder only

(TPX) insulator for re-flow solder

Board Clips Are Available In Place of Posts. Add Suffix “C”




Spear-point clips lock snugly into the board.

Hardware

	Fig. 36N	Fig. 37N

Note:
Mounting hardware is optional and must be ordered separately. Hardware is not sold without the connectors.



* Denotes that items are not popular and may require a special minimum order quantity.



V-Bite ® PC Edge Mount

The **V-Bite ®** is an industry award winning design PCB connector with all the advantages a designer could want. It edge mounts to the board which offers the lowest profile and utilizes very little PCB real estate. It lends itself to surface mount and through-hole soldering techniques. There are versions for IR and convection reflow soldering. Because the connector locks into place both above and below the PCB it disperses rotational torque relief to the board and not the solder points. The **V-Bite ®** design offers the lowest VSWR ratings due to the straight through-put contact design. No right angles for reflection. Available in 50 and 75 ohm, threaded and non-threaded. Other options for PCB thickness available. Other interfaces available. (See “F”, BNC Twin and TNC sections.)

Part Number	RoHS	Description	Imp	Contact	Fig. No.
361V504ER	✓	BNC Jack W/ Teflon For Reflow Solder	50W	Phos./Gold	39A
361V504ET	✓	BNC Threaded Jack W/ Teflon For Reflow Solder	50W	Phos./Gold	39
361V509E	✓	BNC Jack W/ Polyethylene Insulator	50W	Phos./Tin	39A
361V509ET	✓	BNC Threaded Jack W/ Polyethylene Insulator	50W	Phos./Tin	39
361V704ER	✓	BNC Jack W/ Teflon For Reflow Solder	75W	Phos./Gold	39A
361V704ET	✓	BNC Threaded Jack W/ Teflon For Reflow Solder	75W	Phos./Gold	39
361V704EFT	✓	BNC Threaded Jack W/ Teflon Insulator/Flange	75W	Phos./Gold	39B
361V709E	✓	BNC Jack W/ Polyethylene Insulator	75W	Phos./Gold	39A
361V709ET	✓	BNC Threaded Jack W/ Polyethylene Insulator	75W	Phos./Gold	39
361KNT	✓	Knurled Nut (361 Series)	NA	---	---
3M61V704	✓	Mini- BNC Jack W/ Teflon for Reflow Solder	75W	Phos./Gold	39C
✓ RoHS compliant reflow or wave solder ✓ RoHS compliant wave solder only					



Low Profile .270 High FMS

Anti Rotational

VSWR 1.15:1

Patented V-Bite® Snaps Into PCB

Surface Mount Center Contact

Pick & Place Version Available



Fig. 39



Fig. 39B




Fig. 39C

Reduced Size PCB Right Angle Mount


The Super Low™ Profile BNC PC jack reduces the amount of board space needed to mount a PC jack. Board clips hold the unit in place for soldering. The smallest, lowest profile right angle BNC jack available.

The Lo-Deco™ features a four post design that offers greater stability after wave soldering. Also featured is a gold plated contact and nickel plated cast zinc body. Smooth, sleek and aesthetically pleasing design is tumbled to remove casting lines.

Part Number	RoHS	Description	Imp.	Contact	Fig. No.
364M595M	✓	BNC Super Low Profile Jack	50W	Phos./Gold	35A
364M595MT	✓	BNC Super Low Profile Jack	50W	Phos./Gold	35A
364M795M	✓	BNC Super Low Profile Jack	75W	Phos./Gold	35A
364M795MT	✓	BNC Super Low Profile Jack	75W	Phos./Gold	35A
364M095	✓	BNC Lo-Deco Jack	50W	Phos./Gold	38
364M0975	✓	BNC Lo-Deco Jack	75W	Phos./Gold	38
✓ RoHS compliant reflow or wave solder ✓ RoHS compliant wave solder only					



Fig 35A



PC Layout for Super Low Profile







Fig. 38

Dual PC Jacks (Threaded)

Right Angle or Vertical Stacked: When board space becomes a serious issue and you still need the robust, full size, BNC connectors, a dual stacked right angle or vertical version will do the trick. Assembly insertion time is cut in half as well. The Dual 364 series is available in both Valox isolated and all metal construction.

(shown with closed back option FS)




		Right Angle			
Part Number	RoHS	Description	Imp.	Contact	Fig.No.
364A2595	✓	Dual Right Angle, White Valox	50W	Phos./Gold	38A
364A2595T	✓	Dual Right Angle, White Valox (TPX)	50W	Phos./Gold	38A
364A2795	✓	Dual Right Angle, White Valox	75W	Phos./Gold	38A
364A2795T	✓	Dual Right Angle, White Valox (TPX)	75W	Phos./Gold	38A
364A2595B	✓	Dual Right Angle, Black Valox	50W	Phos./Gold	38A
364A2795B	✓	Dual Right Angle, Black Valox	75W	Phos./Gold	38A
364M2595	✓	Dual Right Angle, Metal	50W	Phos./Gold	38B
364M2595T	✓	Dual Right Angle, Metal (TPX)	50W	Phos./Gold	38B
364M2795	✓	Dual Right Angle, Metal	75W	Phos./Gold	38B
364M2795T	✓	Dual Right Angle, Metal (TPX)	75W	Phos./Gold	38B
3M64M2795	✓	Dual Right Angle, Metal Mini-BNC	75W	Phos-Gold	38C
364KNT	✓	Knurled Nut for Dual BNC	N/A	Brass/Nickel	38D
		Vertical			
Part Number	RoHS	Description	Imp.	Contact	Fig.No.
364S2595	✓	Dual Vertical, White Valox	50W	Phos./Gold	40D
364S2795	✓	Dual Vertical, White Valox	75W	Phos./Gold	40D
364S2595B	✓	Dual Vertical, Black Valox	50W	Phos./Gold	40D
364S2795B	✓	Dual Vertical, Black Valox	75W	Phos./Gold	40D
364S2595M	✓	Dual Vertical, Metal	50W	Phos./Gold	----
364S2795M	✓	Dual Vertical, Metal	75W	Phos./Gold	----
		Tool			
Part Number	RoHS	Description	Imp.	Contact	Fig.No.
BD36400	-	Hex Shafted Tool for Knurled Nut	N/A	Steel/Nickel	38E
✓	RoHS compliant reflow or wave solder ✓ RoHS compliant wave solder only				
Note:Hardware is optional and must be ordered separately					

Multi-Port PC Jacks (Non-Threaded)

Side By Side: These right angle units are available in dual or quad configurations. These units are not threaded for panel installation using a jam nut. Up one fourth the installation time.

Part Number		Description	Imp.	Contact	Fig. No.
365A2595		Dual Right Angle, Side By Side White Valox	50W	Phos./Gold	38B
365A2795		Dual Right Angle, Side By Side White Valox	75W	Phos./Gold	38B
365A2595B		Dual Right Angle, Side By Side Black Valox	50W	Phos./Gold	38B
365A2795B		Dual Right Angle, Side By Side Black Valox	75W	Phos./Gold	38B
365A4595		Quad Right Angle, Side By Side White Valox	50W	Phos./Gold	38C
365A4795		Quad Right Angle, Side By Side White Valox	75W	Phos./Gold.	38C
365A4595B		Quad Right Angle, Side By Side Black Valox	50W	Phos./Gold	38C
365A4795B		Quad Right Angle, Side By Side Black Valox	75W	Phos./Gold	38C
 RoHS compliant reflow or wave solder  RoHS compliant wave solder only					



LED Indicator PC Jacks

This unthreaded BNC PCB series is available with amber and green LEDs¹ that are embedded into the Valox body alongside of each BNC port. They can be used to indicate various situations, or conditions of communications through the connector. Single and dual, and quad side by side styles are available.

Part Number		Description	Imp	Contact	Fig. No.
365AL595		BNC Single Port, White	50W	Phos./Gold	38E
365AL595B		BNC Single Port, Black	50W	Phos./Gold	---
365AL2595		BNC Dual Port, White	50W	Phos./Gold	---
365AL2595B		BNC Dual Port, Black	50W	Phos./Gold	---
365AL4595		BNC Quad Port, White	50W	Phos./Gold	38
365AL4595B		BNC Quad Port, Black	50W	Phos./Gold	38

 RoHS compliant reflow or wave solder
 RoHS compliant wave solder only



Fig 38E








Fig. 38

PCB and Panel Layouts for 365 Series



Panel Cut Out Quad

LED BNC






Fig. 35




Fig. 36



Fig. 37




Fig. 48




Fig. 46




Fig. 41




Fig. 49




Fig. 45




Fig. 47

Specialty LAN Adapters

Double Down™ adapters are designed to allow parallel cables entering a patch panel, or a BNC LAN terminal port to be guided at a right angle to the input jack. Two versions accomplish this: one is a right angle with side-by-side jacks for areas with little rear clearance, and the other is a straight version for installations where width between panel jacks is limited. Crimp types are for permanent installations. Goalie, and Goalie Brute allow parallel cable 90° entry which require a minimum of rotational cable space.



*Minimum quantity Requirements May Apply - Contact Sales

Terminators

BNC terminators are available in standard 1% tolerance versions and in the economy 5% tolerance styles. The standard types have removable color coded caps for easy identification. The economy type are color coded as well but caps are not removable.

Part Number		Description	Fig. No.
310X054A		50 W with Red Cap	50
310C054		50 W with Grounding Chain	51
310X074		75 W with Blue Cap	50
HBC310X075		75 W Precision .1% Tolerance	52
310X094		93 W with Yellow Cap	50
HBC310X075		75 W Precision .1% Tolerance	53
EJ175		50 W Economy	52A
EJ177		75 W Economy	52A
EJ179		93 W Economy	52A
 RoHS compliant			



Fig. 50



Fig. 51



Fig. 52



Fig. 52A



Coax Crimp Tools

Professional grade hex-crimp tools for coaxial connectors are available in ratchet and non-ratcheting types, both provide dependable service. Ratchet tools feature replaceable dies. Included is a convenient release mechanism to unlatch the ratchet in the event of an improper crimp. Each too also crimps the contact pin to the conductor.

Part Number	Description
BD10100	Hex Crimp Ratchet for "F" Types, RG59, RG6
BDHD100	Hex Crimp Ratchet for Belden 8281
BDHD200	Hex Crimp Ratchet for BNC/TNC RG58,59,62 and MV
BDHD100	Hex Crimp Ratchet for Mini-RG59
BD11012	Hex Crimp Ratchet for "N" Crimp RG11, RG213, RG214
BDHD100	Hex Crimp Ratchet for BNC/TNC RG6, RG59