

USB female insert - VS-04-BUA-BUB-F/IP67 - 1653838

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://download.phoenixcontact.com>)



USB socket insert, 4-pos., socket USB type A on socket USB type B, for the Freenet system in the panel mounting frame, IP20 terminal outlet, 19" patch panel and service interface, pluggable from both directions



Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 970161
Custom tariff number	85366990
Country of origin	GERMANY

Technical data

Mechanical characteristics

Number of positions	4
Connection profile	USB
Insertion/withdrawal cycles	≥ 1000
Connection method	Socket, type B
Ambient temperature (operation)	-15 °C ... 65 °C

Material data

Inflammability class according to UL 94	V0
Housing material	PC
Contact carrier material	Thermoplastic
Contact material	Copper alloy
Contact surface material	Gold over nickel
Degree of protection	IP20

Electrical characteristics

USB female insert - VS-04-BUA-BUB-F/IP67 - 1653838

Technical data

Electrical characteristics

Rated voltage (III/3)	30 V
Rated current	1 A
Insulation resistance	$\geq 1 \text{ G}\Omega$
Transmission characteristics (category)	USB 2.0

Classifications

ETIM

ETIM 2.0	EC000830
ETIM 3.0	EC001855
ETIM 4.0	EC001855
ETIM 5.0	EC000438

UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27279218
eCl@ss 7.0	27440205
eCl@ss 8.0	27440205

Approvals

Approvals

Approvals

GOST

Ex Approvals

USB female insert - VS-04-BUA-BUB-F/IP67 - 1653838

Approvals

Approvals submitted

Approval details



Accessories

Accessories


Panel mounting frames - VS-A-F-IP67 - 1653744



Panel mounting frame, IP67, for Freenet system, for round panel cutout, with grommet, without mounting screws, color: gray


Drawings

Schematic diagram



Pin assignment socket USB, type A

Schematic diagram



Pin assignment socket USB, type B