


NYLON FULLY INSULATED CLOSE END CONNECTORS



Specifications

- **Maximum Electrical Rating:** 300 Volts
- **Maximum Temperature:** +105°C
- **Terminal Material:** Copper
- **Plating:** Tin
- **Insulated Material:** Nylon



Ordering Information:


Wire Range AWG / mm ²	NTE Part Number	Dimensions inch(mm)				
		B	L	F	D	d
22 – 18 AWG 0.5 – 1.5mm ²	76-NFICEC22	.197 (5.0)	.709 (18.0)	.315 (8.0)	.256 (6.5)	.094 (2.4)
16 – 14 AWG 1.5–2.5mm ²	76-NFICEC16	.217 (5.5)	.827 (21.0)	.354 (9.0)	.315 (9.0)	.118 (3.0)
12 – 10 AWG 4–6mm ²	76-NFICEC12	.276 (7.0)	.985 (25.0)	.394 (10.0)	.413 (10.5)	.157 (4.0)
8 AWG 8mm ²	76-NFICEC8	.354 (9.0)	1.102 (28.0)	.433 (11.0)	.492 (12.5)	.189 (4.8)

TWIST-ON WIRE CONNECTORS WITH SPRING INSERT



Specifications

- **Maximum Electrical Rating:** 300 Volts / 600 Volts
- **Maximum Temperature:** +105°C
- **Insulated Material:** PVC




Ordering Information:

Wire Range AWG / mm ²	NTE Part Number	Dimensions inch(mm)			Insulation Color
		d	D	L	
22 – 14 AWG	76-WN22	.264 (6.7)	.339 (8.6)	.598 (15.2)	Grey
22 – 14 AWG	76-WN16	.390 (9.9)	.472 (12.0)	.866 (22.0)	Orange
22 – 10 AWG	76-WN12	.433 (11.0)	.551 (14.0)	.965 (24.5)	Yellow

STRIPPING QUICK SPLICE

Specifications

- **Maximum Electrical Rating:** 600 Volts
- **Maximum Temperature:** +105°C
- **Terminal Material:** Brass
- **Plating:** Tin
- **Insulated Material:** Polypropylene



Ordering Information:

Wire Range AWG / mm ²	NTE Part Number	Dimensions inch(mm)			Insulation Color
		B	H	L	
22 – 18 AWG 0.5 – 1.5mm ²	76-QS22	.787 (20.0)	.315 (8.0)	.984 (25.0)	Red
16 – 14 AWG 1.5–2.5mm ²	76-QS16	.787 (20.0)	.315 (8.0)	.984 (25.0)	Blue
12 – 10 AWG 4–6mm ²	76-QS12	.787 (20.0)	.433 (11.0)	1.378 (35.0)	Yellow