



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

SCSI/Fibre Channel - 3-ft. SCSI Cable HD50M to Centronic 50M Double Shielded

MODEL NUMBER: **S356-003**



Highlights

- Premium double-shielded cable
- 25 twisted-pair conductors

System Requirements

- Any external SCSI II device or controller card requiring Cen50 or HD50 interface

Package Includes

- 3-ft. SCSI Cable HD50M to Centronic 50M Double Shielded

Description

Multi-platform SCSI II (fast SCSI) external peripheral cable HD50M to C50M. This 3ft cable is designed to connect two SCSI II devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- Low-capacitance impedance matched 28 AWG stranded tinned copper insulated in polypropylene
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

General Info	
Product Group	COMPUTER & STORAGE CABLES
INPUT	
Cable Length (ft.)	3
UPC ASSIGNMENT	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Carton UPC#	037332014023
CONNECTIONS	
Connector A	HD50 (MALE)
Connector B	CENTRONICS 50 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.