



SAW Components

SAW Duplexer

W-CDMA Band 5 / CDMA 800

Series/type:	B7654
Ordering code:	B39881B7654P810
Date:	December 28, 2011
Version:	2.0



SAW Components

B7654

SAW Duplexer


836.5 / 881.5 MHz

Data sheet




Application

- Low-loss SAW duplexer for mobile telephone W-CDMA Band 5 / CDMA 800 systems
- Low insertion attenuation
- Low amplitude ripple
- Single-ended to balanced transformation in Antenna-Rx path
- Impedance transformation 50 Ω to 100 Ω in Antenna-Rx path




Features

- Package size 3.0 x 2.5 x 1.14 mm³
- RoHS compatible
- Approximate weight 0.032 g
- Package for **Surface Mount Technology (SMT)**
- Ni, Au-plated terminals
- Balanced Rx port, unbalanced Tx port
- **Electrostatic Sensitive Device (ESD)**
- Fully matched by integrated matching network
- **Moisture Sensitive Level 3**



Pin configuration

- 1 Tx input, unbalanced
- 3, 4 Rx output, balanced
- 6 Antenna
- 2, 5, 7, 8, 9 To be grounded





SAW Components

B7654

SAW Duplexer

836.5 / 881.5 MHz

Data sheet



Characteristics

Temperature range for specification: $T = -30^{\circ}\text{C}$ to $+85^{\circ}\text{C}$
 Tx terminating impedance: $Z_{Tx} = 50\ \Omega$
 Antenna terminating impedance: $Z_{Ant} = 50\ \Omega$
 Rx terminating impedance: $Z_{Rx} = 100\ \Omega$ (balanced)

Characteristics Tx-Antenna				min.	typ. @ 25 °C	max.	
Center frequency		f_c		—	836.5	—	MHz
Maximum insertion attenuation		α					
	824.0 ... 849.0 MHz			—	1.7	2.2	dB
Amplitude ripple (p-p)		$\Delta\alpha$					
	824.0 ... 849.0 MHz			—	0.8	1.3	dB
Tx port VSWR							
	824.0 ... 849.0 MHz			—	1.8	2.1	
Antenna port VSWR							
	824.0 ... 849.0 MHz			—	1.8	2.1	
Attenuation		α					
10.0	... 420.0	MHz		30	45	—	dB
420.0	... 494.0	MHz		38	55	—	dB
494.0	... 701.0	MHz		30	42	—	dB
701.0	... 728.0	MHz		35	42	—	dB
728.0	... 764.0	MHz		36	42	—	dB
764.0	... 804.0	MHz		30	42	—	dB
860.0	... 869.0	MHz		5	11	—	dB
869.0	... 894.0	MHz		44	55	—	dB
1565.42	... 1573.374	MHz		35	45	—	dB
1573.374	... 1577.466	MHz		40	45	—	dB
1577.466	... 1585.42	MHz		35	45	—	dB
1597.5515	... 1605.88	MHz		40	44	—	dB
1648.0	... 1698.0	MHz		30	42	—	dB
1884.0	... 1919.0	MHz		30	39	—	dB
1930.0	... 1990.0	MHz		34	38	—	dB
2110.0	... 2170.0	MHz		33	37	—	dB
2400.0	... 2500.0	MHz		25	35	—	dB
2500.0	... 2547.0	MHz		20	33	—	dB
3286.0	... 3406.0	MHz		15	24	—	dB
4255.0	... 4600.0	MHz		15	26	—	dB
4934.0	... 5350.0	MHz		8	17	—	dB
5725.0	... 6000.0	MHz		6	14	—	dB



SAW Components

B7654

SAW Duplexer

836.5 / 881.5 MHz

Data sheet



Characteristics

Temperature range for specification:	T = -30 °C to +85 °C
Tx terminating impedance:	Z _{Tx} = 50 Ω
Antenna terminating impedance:	Z _{Ant} = 50 Ω
Rx terminating impedance:	Z _{Rx} = 100 Ω (balanced)

Characteristics Antenna-Rx	min.	typ. @ 25 °C	max.	
Center frequency f_c	—	881.5	—	MHz
Maximum insertion attenuation α 869.0 ... 894.0 MHz	—	2.2	2.7	dB
Amplitude ripple (p-p) $\Delta\alpha$ 869.0 ... 894.0 MHz	—	0.9	1.4	dB
Antenna port VSWR 869.0 ... 894.0 MHz	—	1.7	2.0	
Rx port VSWR 869.0 ... 894.0 MHz	—	2.0	2.3	
CMRR ($ S_{32}-S_{42} / S_{32}+S_{42} $) 869.0 ... 894.0 MHz	21 ¹⁾	26	—	dB
Attenuation α				
10.0 ... 447.0MHz	45	55	—	dB
447.0 ... 824.0MHz	40	55	—	dB
824.0 ... 849.0MHz	45	55	—	dB
849.0 ... 854.0MHz	23	31	—	dB
909.0 ... 970.0MHz	13	17	—	dB
970.0 ... 1320.0 MHz	40	46	—	dB
1360.0 ... 2180.0MHz	45	60	—	dB
2180.0 ... 4500.0MHz	35	41	—	dB
4500.0 ... 6000.0MHz	30	37	—	dB

¹⁾ A combination of 10 ° phase balance and 1 dB amplitude balance corresponds to 19.6 dB CMRR

**SAW Components****B7654****SAW Duplexer****836.5 / 881.5 MHz****Data sheet****Characteristics**

Temperature range for specification: $T = -30\text{ °C to }+85\text{ °C}$
Tx terminating impedance: $Z_{Tx} = 50\ \Omega$
Antenna terminating impedance: $Z_{Ant} = 50\ \Omega$
Rx terminating impedance: $Z_{Rx} = 100\ \Omega$ (balanced)

Characteristics Tx-Rx	min.	typ. @ 25 °C	max.	
Differential mode isolation α				
824.0 ... 849.0 MHz	52	56	—	dB
869.0 ... 894.0 MHz	50	57	—	dB
Common mode isolation α				
824.0 ... 849.0 MHz	45	49	—	dB



SAW Components

B7654

SAW Duplexer

836.5 / 881.5 MHz

Data sheet



Characteristics

Temperature range for specification:	T = -30 °C to +85 °C
Tx terminating impedance:	Z _{Tx} = 50 Ω
Antenna terminating impedance:	Z _{Ant} = 50 Ω
Rx terminating impedance:	Z _{Rx} = 100 Ω (balanced)

Intermodulation Characteristics SV-LTE coexistence CDMA Cell - LTE Band 13 ¹⁾	min.	typ. @ 25 °C	max.	
Case 1 - IM3 in CDMA Cell Rx band²⁾ $f_{TX5} = 824.0 \dots 832.0 \text{ MHz}$ $P_{TX5}^{3)} = 24 \text{ dBm}$ $f_{jam} = 779.0 \dots 787.0 \text{ MHz}$ $P_{jam} = 9 \text{ dBm}$ $f_{RX5} = 869.0 \dots 877.0 \text{ MHz}$ P_{RX5}	—	-103	—	dBm
Case 2 - IM3 in B13 Rx band²⁾ $f_{TX5} = 824.0 \dots 828.0 \text{ MHz}$ $P_{TX5}^{3)} = 24 \text{ dBm}$ $f_{jam} = 785.0 \dots 787.0 \text{ MHz}$ $P_{jam} = 9 \text{ dBm}$ $f_{RX13} = 746.0 \dots 750.0 \text{ MHz}$ P_{RX13}	—	-112	—	dBm

¹⁾ In combination with TDK-EPC LTE Band13 duplexer B7928

²⁾ See picture 1 on page 7.

³⁾ Power level at Ant of picture 1 on page 7.



SAW Components	B7654
SAW Duplexer	836.5 / 881.5 MHz


Data sheet



Maximum ratings

Storage temperature range	T_{stg}	-40/+85	°C	
DC voltage	V_{DC}	5	V	
ESD voltage	V_{ESD}	100 ¹⁾	V	
Input power at				machine model, 1 pulse
824.0 ... 849.0 MHz	P_{in}	29	dBm	source and load impedance 50 Ω
elsewhere	P_{in}	10	dBm	} continuous wave
				55 °C, 5000h

¹⁾ According to JESD22-A115A (machine model), 1 negative and 1 positive pulse.



Picture 1: Signal definition for SV-LTE coexistence intermodulation specification using TDK-EPC CDMA cell duplexer B7654 in combination with LTE Band 13 duplexer B7928.



SAW Components

B7654


SAW Duplexer

836.5 / 881.5 MHz


Data sheet



Frequency response Tx-Antenna



Frequency response Tx-Antenna (wideband)



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components

B7654


SAW Duplexer

836.5 / 881.5 MHz


Data sheet



Frequency response Antenna-Rx



Frequency response Antenna-Rx (wideband)



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components

B7654


SAW Duplexer

836.5 / 881.5 MHz


Data sheet



Frequency response Tx-Rx



Frequency response Tx-Rx (wideband)



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components

B7654

SAW Duplexer

836.5 / 881.5 MHz

Data sheet









Return loss

S_{11} Tx-port

S_{22} Antenna-port

S_{33} Rx-portReferences



Please read *cautions and warnings* and *important notes* at the end of this document.

**SAW Components****B7654****SAW Duplexer****836.5 / 881.5 MHz****Data sheet**

Type	B7654
Ordering code	B39881B7654P810
Marking and package	C61157-A3-A87
Packaging	F61074-V8211-Z000
Date codes	L_1126
S-parameters	B7654_NB.s4p, B7654_WB.s4p See file header for pin/port assignment.
Soldering profile	S_6001
RoHS compatible	Defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

Published by EPCOS AG

Systems, Acoustics, Waves Business Group

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2011. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EPCOS:

[B39881B7654P810](#)