



CTA/CTB24

24Amp - 400/600/800/1200V - TRIAC

Applications

- Phase Control
- Static Switching
- Light Dimming
- Motor Speed Control
- Kitchen Equipment
- Power Tools
- Solenoid Valve Controls:
 - Dishwashers
 - Washing Machines

- > **Suitable for General Purpose AC Switching**
- > **Alternistor/No Snubber Versions for Inductive Loads**
- > **Logic Level Available for use with Microcontrollers and Low Level Devices**
- > **IGT Range 35-50 mA (Q1)**
- > **V_{DRM}/V_{RMM} 400, 600, 800, 1200V**

Absolute Maximum Ratings

	CONDITIONS	SYMBOL	RATING
RMS On-State Current (full sine wave)	T _c = 100°C T _c = 75°C	T0-220AB T0-220AB Iso	I _{T(RMS)} 24A
Non Repetitive Surge Peak On-State Current (Full Cycle, T _j Initial = 25°C)	F = 50 Hz F = 60 Hz	I _{TSM}	250A 260A
I ² t Value for fusing	tp = 10 ms	I ² t	340A ² s
Critical rate of rise of on-state current I _G = 2 x I _{GT} , tr < 100 ns, T _j = 125°C	F = 120 Hz	di/dt	50A/μs
Peak Gate Current @ T _j = 125°C	tp = 20 μs	I _{GM}	4A
Average Gate Power Dissipation @ T _j = 125°C		P _{G(AV)}	1W
Storage Temperature Range		T _{stg}	-40 to +150°C
Operating Junction Temperature Range		T _j	-40 to +125°C
Isolation Voltage (CTA Series only)		V _{ISO}	2500 V _{RMS}




Electrical Characteristics

ALTERNISTOR/NO SNUBBER AND LOGIC LEVEL (3 Quadrants)

		CW	BW
I _{GT} MAX @ V _D = 12 V, R _L = 30Ω NOTE 1	QI-II-III	35mA	50mA
V _{GT} MAX @ V _D = 12 V, R _L = 30Ω	QI-II-III	1.3V	1.3V
V _{GD} MIN @ V _D = V _{DRM} , R _L = 3.3kΩ T _j = 125°C	QI-II-III	0.2V	0.2V
I _H MAX @ I _T = 500 mA NOTE 2		50mA	75mA
I _L MAX @ I _G = 1.2 I _{GT}	QI-III	50mA	70mA
I _L MAX @ I _G = 1.2 I _{GT}	Q-II	80mA	100mA
dv/dt MIN @ V _D = 67%V _{DRM} (gate open) NOTE 2 T _j = 125°C		500V/μs	1000V/μs
(di/dt) _c MIN without Snubber NOTE 2 T _j = 125°C		13A/ms	22A/ms

STANDARD (4 Quadrants)

		B
I _{GT} MAX @ V _D = 12 V, R _L = 30Ω NOTE 1	QI-II-III	50mA
I _{GT} MAX @ V _D = 12 V, R _L = 30Ω NOTE 1	QIV	100mA
V _{GT} MAX @ V _D = 12 V, R _L = 30Ω	Q-All	1.3V
V _{GD} MIN @ V _D = V _{DRM} , R _L = 3.3kΩ T _j = 125°C	Q-All	0.2V
I _H MAX @ I _T = 500 mA NOTE 2		80mA
I _L MAX @ I _G = 1.2 I _{GT}	QI-III-IV	70mA
I _L MAX @ I _G = 1.2 I _{GT}	Q-II	160mA
dv/dt MIN @ V _D = 67%V _{DRM} (gate open) NOTE 2 T _j = 125°C		500V/μs
(dv/dt) _c MIN @ (di/dt) _c = 13.3 A/ms NOTE 2 T _j = 125°C		10V/μs



GENERAL NOTES


1. Minimum IGT is guaranteed at 5% of IGT max.
2. For both polarities of A2 referenced to A1
3. All parameters at 25 degrees C unless otherwise specified.

Static Characteristics

V_T MAX @ $I_{TM} = 35$ A, $t_p = 380\mu s$ NOTE 2	$T_j = 25^\circ C$	1.55V
V_{TO} MAX @ Threshold Voltage NOTE 2	$T_j = 125^\circ C$	0.85V
R_d MAX @ Dynamic Resistance NOTE 2	$T_j = 125^\circ C$	16m Ω
I_{ORM} MAX @ $V_{ORM} = V_{RRM}$	$T_j = 25^\circ C$	5 μ A
I_{RRM} MAX @ $V_{ORM} = V_{RRM}$	$T_j = 125^\circ C$	3mA

Thermal Resistances

	SYMBOL	RATING
Junction to Case (AC)	TO-220AB	$R_{th(j-c)}$ 0.8°C/W
Junction to Case (AC)	TO-220AB Isolated	$R_{th(j-c)}$ 1.7°C/W
Junction to Ambient	TO-220AB	$R_{th(j-a)}$ 60°C/W
Junction to Ambient	TO-220AB Isolated	$R_{th(j-a)}$ 60°C/W



Weight: 2.3g (0.08 oz)

Dimensions

REF.	Millimeters		Inches	Typ.	Max.
	Min.	Typ.			
A	15.24		0.6		0.62
B		3.23		0.127	
C	12.78		0.503		0.543
D	9.96		0.392		0.408
E	0.69		0.027		0.037
F	1.22		0.048		0.052
G	4.62		0.182		0.19
H	0.46		0.018		0.024
I	2.49		0.098		0.112
J	2.39		0.094		0.106
K	6.48		0.255		0.271
L	3.78		0.149		0.153
M	15.49	16	0.61	0.63	0.65
N	2.59		0.102		0.114
O	0.99		0.039		0.061
P	0.99		0.039		0.061
Q		2.67		0.105	

Part Number Selection

Part Number	Voltage [Vpk]	I_{GT} [mA]	Type	Package
CTA/CTB24-xxxB	400, 600, 800, 1200	50mA	Standard	TO-220AB
CTA/CTB24-xxxBW	400, 600, 800, 1200	50mA	Alternistor/No Snubber	TO-220AB
CTA/CTB24-xxxCW	400, 600, 800, 1200	35mA	Alternistor/No Snubber	TO-220AB

Part Number Designation





Fig. 1: Power dissipation versus RMS on-state current (full cycle).




Fig. 2: RMS on-state current versus case temperature (full cycle)




Fig. 3: On-state current versus on-state voltage (instantaneous values)




Fig. 4: Non-repetitive surge peak on-state current versus number of cycles.

ISO9001 Certified

Approvals

UL - Pending

USA

Sales Support (877) 502-5500

Tech Support (877) 702-7700

Fax (619) 710-8540

Email: sales@crydom.com

Crydom Corp

2320 Paseo de las Americas, Suite 201

San Diego, CA 92154

EUROPE - UK

Telephone +44 (0) 1202 365070

Fax +44 (0) 1202 365090

Email: intsales@crydom.com

Crydom International Ltd.

7 Cobham Road

Ferndown Industrial Estate

Wimborne, Dorset BH21 7PE

Germany

Telephone +49 (0) 180 3000 506

ASIA - Thailand

Telephone +66 (0)2 665 2517

Fax +66 (0)2 665 2588

Crydom Asia

18/8 Fico Place 12th Floor

Soi Sukhumvit 21 (Asoke)

Klongtoey Nua, Wattana

Bangkok, Thailand 10110