




- NOTES:
1. FOR USE WITH BOEING BMS13-65 OF & ADAMS RUSSELL FC14Z CABLE.
 2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
 3. FOR CRIMPING USE DIE KTH-2211.
 4. INTERFACE PER MIL-STD-348, FIG. 304-1.
 5. CENTER CONTACT (1-547-47MA9) SUPPLIED UNASSEMBLED.
 6. MARK PACKAGE: KINGS 1205-47-9 YRWK (DATE CODE)

7. MATERIALS:
- INSULATOR-TEFLON, ASTM-D-1710
 - OUTER CONTACT-BER. COP., ASTM-B196
 - K-GRIP SLEEVE-COMMERCIAL BRONZE, ASTM-B135
 - GASKET-SILICONE RUBBER, A-A-59588
 - C-RING-PHOS. BRONZE, ASTM-B103
 - ALL OTHER METAL PARTS-BRASS, ASTM-B16
8. FINISHES:
- CENTER CONTACTS: .000050 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290(RoHS)
 - OUTER CONTACT: .000200 MIN SILVER PER ASTM B700 OVER .000020 MIN. COPPER PER ASTM B734(RoHS)
 - ALL OTHER METAL PARTS: .000050 MIN NICKEL PLATE PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734(RoHS)
9. ELECTRICAL CHARACTERISTICS:
- NOMINAL IMPEDANCE-50 OHMS
 - FREQUENCY RANGE-DC TO 11 GHZ
 - WORKING VOLTAGE-1000 VRMS

10. WEIGHT:38.9 GRAMS(0.086 POUNDS)

REVISIONS	
ISSUE	CHANGES
0	ER 33871 KH 04/13/92
1	ER 37604 A KH 03/25/98
2	ER 38095 E TML 09/29/00
3	CN 38787 E DCT 3/6/3
E	ER 34269 COL 09/02/11

1205-47-9

SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

WAS: E-17393

USED ON

CAGE CODE:91836

PLUG, N

DRAWN	KH	DATE	04/13/92
DESIGN	JT	DATE	04/14/92
APPR.		DATE	

WINKINGS BY WINCHESTER ELECTRONICS	
Winchester Electronics 82 Bernas Industrial Road North Wallingford, CT 06492	B
SIZE	

1205-47-9