



ODC™ Plug & Socket Cable Assemblies

The ODC connectors, together with the support optical cable, are becoming the standard interface specified in 3G, 4G and WiMax Base Station remote radios and Fiber-to-the-Antenna applications. The ODC cable assembly is based on the N Type RF Coax connector. The product, however, is not limited to the above applications. The ODC cable assemblies have passed tests like salt mist, vibration and shock and meet protection class IP68. They are well suited for Industrial and Aerospace and Defense applications.

ODC™ Plug & Socket Cable Assemblies

KEY FEATURES

- 2 and 4 Channel
- Multimode - 2 & 4 Ch;
Singlemode - 2 Ch
- Compact design with 2 x or 4
x 1.25mm ferrules
- Built-in socket available with
square or hexagonal flange
- Water proof, dust proof and
corrosion resistant
- Screw lock mechanism
- Scoop proof
- One hand, blind-mating
possible
- Attached protection cap
- EMI shielded
- Low-Smoke, Zero-Halogen
(LSZH)

APPLICATIONS

Base Stations
Industrial
Aerospace & Defense

TECHNICAL DOCUMENTS

Protection Class : IP 68
Salt mist : IEC 61300-2-26 : passed
Vibration : IEC 61300-2-1 : passed
Shock : IEC 61300-2-9 : passed

OPTICAL

Insertion loss according to IEC 61300-3-34
Multimode type : $\leq 0.25\text{dB}$ max. $\leq 0.70\text{dB}$
Singlemode type : $\leq 0.30\text{dB}$ max. $\leq 1.00\text{dB}$
Return Loss : Singlemode $\geq 45\text{dB}$

MECHANICAL


Technology : full ceramic ferrule and sleeve
Mechanically robust :

- ODC plug ≤ 800 N tensile load
- ODC socket ≤ 30 N tensile load


Installation torque force : - min. 1Nm - max. 2 Nm.
Operating temperature : -40°C up to +85°C
Mating durability : min. 100 cycles

INTERFACE DIMENSIONS


2 Fiber ODC Plug




4 Fiber ODC Plug



2 Fiber Small Square ODC Socket




2 Fiber Large Square ODC Socket




INTERFACE DIMENSIONS (cont.)


2 Fiber hexagonal ODC Socket



4 Fiber Small Square Socket




4 Fiber Hexagonal Socket




PRODUCT DIMENSIONS

2 Fiber Plug to LC Duplex Assembly



4 Fiber Plug to LC Duplex Assembly



CABLE ASSEMBLY PART NUMBERS

Base Part Number ¹	Description	Fiber Size	Available Sizes
1985834	2 Fiber Plug to LC Duplex Assembly	Singlemode	1 to 99 meters ²
1985835	2 Fiber Plug to LC Duplex Assembly	Multimode (50/125)	
1985836	2 Fiber Plug to LC Duplex Assembly	Multimode (62.5/125)	
1985837	4 Fiber Plug to LC Duplex Assembly	Multimode (50/125)	
1985838	4 Fiber Plug to LC Duplex Assembly	Multimode (62.5/125)	
1985844	2 Fiber Plug to LC Duplex Assembly	Singlemode	100 to 999 meters ³
1985845	2 Fiber Plug to LC Duplex Assembly	Multimode (50/125)	
1985846	2 Fiber Plug to LC Duplex Assembly	Multimode (62.5/125)	
1985847	4 Fiber Plug to LC Duplex Assembly	Multimode (50/125)	
1985848	4 Fiber Plug to LC Duplex Assembly	Multimode (65.5/125)	

¹For complete part numbers, obtain proper customer drawing.


²The length is defined by the dash number (example : 8-1985834-2 is 82 meters long, 1-1985834-5 is 15 meters long)

³The length is defined by the dash number (example : 8-1985844-2 is 820 meters long, 1-1985844-5 is 150 meters long)


Note: Other dust caps (screw type) and connector types, in combination with ODC Plug (or socket), are available upon request.

PRODUCT DIMENSIONS (cont.)

2 Fiber Socket to LC Duplex Assembly



4 Fiber Socket to LC Duplex Assembly



CABLE ASSEMBLY PART NUMBERS

Base Part Number ¹	Description	Fiber Size	Available Sizes
1985839	2 Fiber Socket to LC Duplex Assembly	Singlemode	0.3 to 99 meters ²
1985840	2 Fiber Socket to LC Duplex Assembly	Multimode (50/125)	
1985841	2 Fiber Socket to LC Duplex Assembly	Multimode (62.5/125)	
1985842	4 Fiber Socket to LC Duplex Assembly	Multimode (50/125)	
1985843	4 Fiber Socket to LC Duplex Assembly	Multimode (62.5/125)	

¹For complete part numbers, obtain proper customer drawing.

²The length is defined by the dash number (example : 3-1985839-5 is 3.5 meters long, 1-1985839-6 is 1.6 meters long)

Note: Other dust caps (screw type) and connector types, in combination with ODC Plug (or socket), are available upon request.

FOR MORE INFORMATION

Stefan Borgas, EMEA Product Manager

Phone: (46) 8 50 72 50 44 | E-mail: sborgas@tycoelectronics.com

Yasuo Sasaki, ASIA Director of Fiber Optics

Phone: (81) 44 844 8390 | E-mail: sasaki.yasuo@tycoelectronics.com

Brent Hatfield, Americas Product Manager

Phone: 717-986-7037 | E-mail: brent.hatfield@tycoelectronics.com

Technical Support

Internet:	www.tycoelectronics.com/help
USA:	+1 (800) 522-6752
Canada:	+1 (905) 470-4425
Mexico & Central America:	+52(O) 55-1106-0814
South America:	+55 (O) 11-2103-6000
Germany:	+49 (O) 6251-133-1999
UK:	+44 (O) 8706-080208
France:	+33 (O) 1-3420-8686
Netherlands:	+31 (O) 73-6246-999
China:	+86 (O) 400-820-6015

Part numbers in this brochure are RoHS Compliant*, unless marked otherwise.

*as defined www.tycoelectronics.com/leadfree

Tyco Electronics Corporation, Harrisburg, PA

tycoelectronics.com

© 2010 Tyco Electronics Corporation. All Rights Reserved.

9-1773449 CIS PDF 03/2010

ODC and ODC logo are trademarks of Huber + Suhner AG Corporation.

TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors.

Other products, logos, and Company names mentioned herein may be trademarks of their respective owners.

While Tyco Electronics has made every reasonable effort to ensure the accuracy of the information in this catalog, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult Tyco Electronics for the latest dimensions and design specifications.