


**Part Number: 91525-8450**

0.50mm Pitch LaneLink™ I/O Latch Receptacle, 4 Lane, Cx4 Ethernet, 8 Circuits, Tape and Reel, 2 Solder Posts, Tape and Reel Packaging



Series image - Reference only

Status:	OBSOLETE
Replacement:	918048450 Foam Gasket, 918048451 Metal Gasket
Series:	91525
Category:	I/O Connectors

Mates With Part(s):

[916351020](#), [916351021](#), [916351022](#)

Product Environmental Compliance

EU RoHS: ELV and RoHS Compliant

China RoHS:

REACH SVHC:

Low-Halogen Status: Not Reviewed

Part Detail**General**

Status	Obsolete
Category	I/O Connectors
Series	91525
Application	Wire-to-Board
Component Type	Receptacle
Product Name	InfiniBand*, LaneLink™
Type	N/A

Physical

Circuits (Loaded)	8
Circuits (maximum)	8
Circuits Detail	8 Differential Pair
Color - Resin	Black
Durability (mating cycles max)	250
Lock to Mating Part	Yes
Material - Metal	Brass, Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Orientation	Right Angle
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm, 2.40mm, 4.00mm
Packaging Type	Embossed Tape on Reel
Panel Mount	Yes
Pitch - Mating Interface	0.50mm
Plating min - Mating	0.102µm
Plating min - Termination	3.048µm
Polarized to Mating Part	Yes
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-20°C to +60°C
Termination Interface: Style	Surface Mount
Wire Size AWG	N/A

Electrical

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	0.5A
Shielded	Yes
Voltage - Maximum	30V

Solder Process Data

Lead-free Process Capability	Reflow Capable (SMT only)
Process Temperature max. C	260

Material Info

UPC	822348246700
-----	--------------

Application Tooling

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Previously Available Application Tooling

[Check our list of old tooling that used to be available for this part](#)