


SEVEN SEGMENT DISPLAY – 10.2 mm (0.4 INCH), Dual

DATA SHEET 3544 REV.

Notes: All dimensions are in mm, tolerance is ± 0.25 mm (0.01") unless otherwise specified**Absolute Maximum Ratings $T_a=25^\circ\text{C}$**

Parameter	Green	Unit
Power dissipation per segment	60	mw
Peak forward current per segment*	80	mA
Continuous forward current per segment	15	mA
Reverse voltage per segment	5	V
Operating temperature range	-35~85	$^\circ\text{C}$
Storage temperature range	-35~85	$^\circ\text{C}$
Solder temperature 1/16 inch below seating plane for 3 seconds at 260 $^\circ\text{C}$		

* 1/10 duty cycle 10 ms pulse width

Electro-optical Characteristic: ($T_a=25^\circ\text{C}$)

Part No.		Chip Material	Color	Wavelength (nm)	Iv (mcd) Typ. 20mA	Note
Common Anode	Common Cathode					
LN2004-G-AG	LN2004-G-CG	GaP	Green	572	13	

Features

- 0.40 inch digit height, Gray surface
- Uniformly illuminated segments
- Wide viewing angle
- Easy mounting on PCB or socket

Description

LN2004 series display is fully compatible with industry standard 0.40" package with options of low current (-xxL), common anode (-Axx) and common cathode (-Cxx).