Inductive Proximity Sensors

İ	P	r	O	X



Global Proximity



AccuProx



E56 Pancake



Nonmetallic Tubular



E52 Cube Style



E51, Factory Sealed



3.0	Introduction Quick Reference Guide	V8-T3-2
3.1	iProx Sensors Product Description	V8-T3-10
3.2	E57 Premium+ Series Sensors Product Description	V8-T3-17
3.3	E57 Premium+ Series Short Barrel Sensors Product Description	V8-T3-29
3.4	Global Proximity Sensors Product Description	V8-T3-36
3.5	AccuProx Analog Sensors Product Description	V8-T3-45
3.6	Ferrous Only Tubular Sensors Product Description	V8-T3-51
3.7	Metal Face Sensors Product Description	V8-T3-54
3.8	High Current Output Sensors Product Description	V8-T3-58
3.9	Miniature Short Body Sensors Product Description	V8-T3-61
3.10	E56 Pancake Sensors Product Description	V8-T3-66
3.11	Nonmetallic Tubular Sensors Product Description	V8-T3-71
3.12	E52 Cube Style Sensors Product Description	V8-T3-74
3.13	E52 Rectangular Style Sensors Product Description	V8-T3-78
3.14	E55 Limit Switch Style Sensors with Nonmetallic Housings Product Description	V8-T3-81
3.15	E51 Modular Limit Switch Style Sensors Product Description	V8-T3-83
3.16	E51 Limit Switch Style, Factory Sealed 6P+ Sensors Product Description	V8-T3-92



Unless otherwise noted, the products contained in this section should not be used for functional safety applications. These products were not designed or tested to IEC 60947-5-3 or recommended for functional safety.



For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Quick Reference Guide

Inductive Proximity Sensors

Sensing Application	Sensing Style	Size	Max Range	Product Family	Page
Shielded	Shielded tubular	8 mm	3 mm	Global Proximity Sensors	V8-T3-36
Sensor		12 mm	4 mm	iProx™ Sensors	V8-T3-10
			2 mm	E57 Premium + Series	V8-T3-17, V8-T3-29
			5 mm	Global Proximity Sensors	V8-T3-36
Mounting		18 mm	8 mm	iProx Sensors	V8-T3-10
-			5 mm	E57 Premium + Series	V8-T3-17, V8-T3-29
			8 mm	Global Proximity Sensors	V8-T3-36
		30 mm	15 mm	iProx Sensors	V8-T3-10
			10 mm	E57 Premium + Series	V8-T3-17, V8-T3-29
			15 mm	Global Proximity Sensors	V8-T3-36
Unshielded	Unshielded tubular	8 mm	6 mm	Global Proximity Sensors	V8-T3-36
Sensor		12mm	10 mm	iProx Sensors	V8-T3-10
			10 mm	E57 Premium + Series	V8-T3-17, V8-T3-29
			10 mm	Global Proximity Sensors	V8-T3-36
Target		18 mm	18 mm	iProx Sensors	V8-T3-10
			20 mm	E57 Premium + Series	V8-T3-17, V8-T3-29
			18 mm	Global Proximity Sensors	V8-T3-36
		30 mm	29 mm	iProx Sensors	V8-T3-10
			22 mm	E57 Premium + Series	V8-T3-17, V8-T3-29
			29 mm	Global Proximity Sensors	V8-T3-36
MINIM	Analog tubular	12 mm	8mm	AccuProx™ Analog Sensors	V8-T3-45
		18 mm	15 mm	AccuProx Analog Sensors	V8-T3-45
Analog		30 mm	25 mm	AccuProx Analog Sensors	V8-T3-45
Sensor					
Shielded Sensor Target Mounting	Shielded cube	40 x 40 x 40 mm	20 mm	E52 Cube Style Sensors	V8-T3-74
Unshielded Sensor Target Mounting	Unshielded cube	40 x 40 x 40 mm	40 mm	E52 Cube Style Sensors	V8-T3-74

Inductive Proximity Sensors, continued

Sensing Application	Sensing Style	Size	Max Range	Product Family	Page
Mounting Shielded Sensor	Shielded limit switch	118 x 40 x 40 mm 114 x 39 x 38.4 mm	13 mm	E51 Modular Limit Switch Style Sensors E51 Limit Switch Style, Factory Sealed 6P+ Sensors E55 Limit Switch Style Sensors with Nonmetallic Housings	V8-T3-83, V8-T3-92
Target	Unshielded limit switch	118 x 40 x 40 mm 114 x 39 x 38.4 mm	24 mm	E51 Series E55 Series	V8-T3-83, V8-T3-92
Mounting Unshielded Sensor					
Target Shielded Sensor		79 x 79 x 39 mm	40 mm	E56 Series	V8-T3-66
Unshield Sensor Mounting		79 x 79 x 39 mm 110 x 110 x 41 mm 171.5 x 171.5 x 67.5 mm	100 mm	E56 Series	V8-T3-66

Technical Reference

Inductive Proximity Sensors



General


There are a number of factors which should be considered when applying induction proximity sensors. A detailed discussion of these factors can be found on **Page V8-T12-4**. Presented below are a few of the more important considerations for quick reference.

Mounting

Inductive proximity sensors are available in two classifications: shielded (also known as embeddable or flush mountable) and unshielded (non-embeddable or non-flush mountable). What these terms refer to is the distance to surrounding metal that the device can be mounted. In the case of a shielded sensor the device can be mounted with the sensor completely surrounded by metal.

In the case of an unshielded sensor, a metal free zone must be provided when mounting the sensor. The size of the metal free zone is dependent on both the size of the sensor and the type of sensing range it has, for example, standard or extended.

Mounting Ranges



Standard Range							
Shielded	0	0					
Unshielded	2 x Sn	Cap height					
Extended Rang	je						
Semi-shielded	Sn	d					
Non-embeddable	2 x Sn	Cap height					

Where **a** and **b** are the metal free dimensions.

When mounting the sensors, do not exceed the following recommended torque specifications.

Torque Specifications

Nickel-Plated Brass
er
20 lb-in (2.3 Nm)
er
70 lb-in (7.9 Nm)
er
70 lb-in (7.9 Nm)

Extended Range Sensors

Extended range proximity sensors by Eaton's electrical sector offer sensing distances almost three times greater than conventional devices. They are available in semi-shielded designs: mounted similar to an embeddable sensor—and non-embeddable designs requiring more metal free zone area than conventional unshielded sensors. All are available in a variety of circuits and terminations.

Target Material

When manufacturers of inductive proximity sensors state the sensing range of their devices, they are usually based upon a ferrous target made of carbon-rolled steel (IE FE 360) defined by ISO630. For example, in this product guide the E57LAL18A2 has a sensing range of 5 mm based upon a target of mild steel.

Sensing ranges to targets made of non-ferrous metals have to have a correction factor applied as listed in the table below. To use this table, multiply the sensing distance of the device by the factor given.

Example: The E57LAL18A2 has a sensing range of 5 mm. When used to sense a brass target, the sensing range becomes 2.25 mm (5 mm x 0.45).

Table of Correction Factors

Multiply sensing range of device by factor given below.

Correction Factors

	Sensor Size							
Target	4–8 mm	12 mm	18 mm	30 mm	Limit Switch			
Stainless steel 400	0.90	0.90	1.0	1.0	1.0			
Stainless steel 300	0.65	0.70	0.70	0.75	0.85			
Brass	0.35	0.45	0.45	0.45	0.5			
Aluminum	0.35	0.40	0.45	0.40	0.47			
Copper	0.30	0.25	0.35	0.30	0.40			

Target Size

Often overlooked when applying sensors is the fact that the manufacturer's stated sensing ranges are also dependent upon target size. The table below reflects the standard target sizes which were used to determine sensing ranges.

If targets are the same size or greater than standard, no reduction in sensing distance will occur. However, a smaller target size will result in a decrease in sensing range.

A general rule of thumb is that the target size shall be three times the range or the size of the sensor face, whichever is larger.

Standard Target Size ①

	Standard Sensing Ran	ige	Extended Sensing Range		
Target	Shielded Devices	Unshielded Devices	Semi-Shield Devices	Non-Embeddable Devices	
4 mm	4 mm square	4 mm square	_	_	
5 mm	5 mm square	5 mm square	_	_	
6.5 mm	6.5 mm square	6.5 mm square	_	_	
8 mm	8 mm square	8 mm square	_	_	
12 mm	12 mm square	12 mm square	18 mm square	30 mm square	
18 mm	18 mm square	24 mm square	36 mm square	60 mm square	
30 mm	30 mm square	45 mm square	66 mm square	_	
Limit switch	45 mm square	72 mm square	_	_	

Note

1 Targets are 1 mm thick.

Product Selection Guide

iProx



Page V8-T3-10

Overview

Designed to be the highest performing tubular inductive sensor. Standard features include extended sensing ranges, high noise-immunity, extreme durability and includes Autoconfigure Technology. Advanced features include output delay, speed detection and cloning with ProxView Software.

Applications

Automotive, machine tool, material handling where high sensing performance and inventory consolidation is a priority

Product Features

Auto-configure technology automatically detects a sinking (NPN) or sourcing (PNP) connection and switches the sensor accordingly, without any user intervention Optional computer programming cable and Windows-based ProxView configuration software makes it easy to customize sensors

Clone the sensor to match the characteristics of more than 4,800 competitive models, or configure it to match your specific application needs

Advanced programmable features such as dual outputs, output delay, speed detection and more

Technical Data and Specifications

Current ratings—
AC: 250 mA
DC: 300 mA
Enclosure ratings—
NEMA® 4, 4X, 6, 6P, 12, 13
IEC IP67, IP69K
Construction—
Stainless steel

Approvals

cUL® Listed



E57 Premium+ Series



Page V8-T3-17

Overview

High performance inductive sensors include stainless steel models, extended ranges and right-angle sensing.

Applications

A wide variety of applications including those where customers require AC/DC universal inventory sensors

Product Features

12, 18 and 30 mm diameters
Two- and three-wire AC and DC sensors
360° LED indicators standard
NO or NC outputs
Variety of terminations

Resettable short circuit protected and reverse polarity on select models

Robust stainless steel tubes, shockresistant front caps, polycarbonate end bells, and impact-absorbing potting compound are resistant to physical and environmental abuse in high temperature, high pressure washdown and high shock and vibration applications

Technical Data and Specifications

Current ratings—
AC: 250 mA
DC: 200 mA
Enclosure ratings—
NEMA 4, 4X, 6, 6P, 12, 13
IEC IP6, IP69K7
Construction—
Stainless steel

Approvals

cUL Listed CE (AC/DC and DC-only models)





E57 Premium+ Series Short Barrel



Page V8-T3-29

Overview

Full featured sensors with shorter overall length than standard tubular sensors.

Applications

Automation, robotics, transfer lines, conveyors, material handling

Product Features

360° LFD indicators

Available in 12, 18 and 30 mm diameters Two-wire sensors offer 20–250 Vac or Vdc operation; AC only 20–135 Vac Three-wire models operate on 6–30 Vdc

Same sensing ranges as standard sensors High flex extra long 5m cable or pigtail micro-pin connector

Short circuit protection on AC/DC and DC-only versions

Global Proximity



Page V8-T3-36

Overview

This full-line, tubular proximity sensor family provides a cost-effective solution for high volume OEM use.

Applications

Machine tool detection, press applications, cam detection, material handling, valve and shaft position, automotive assembly

Product Features

8, 12, 18 and 30 mm diameters Two-wire sensors available in AC or DC versions

Three-wire sensors available in DC versions Shielded and unshielded models

LED indicators standard

Cable, micro-connector and nano-connector terminations

Short circuit protection on DC models NO or NC outputs

Technical Data and Specifications

Current ratings—
AC mode—250 mA
DC mode—200 mA
Enclosure ratings—
NEMA 4, 4X, 6, 6P, 12, 13
IEC IP67
Construction—
Stainless steel
Semi-shielded models: nickel plated brass

Approvals

UL[®] Listed CSA[®] Certified CE (AC/DC and DC-only models)







Technical Data and Specifications

Current ratings— AC mode—200 mA DC mode—100 mA Enclosure ratings— IEC IP67, IP69K

Construction— Nickel plated brass 8 mm Nano: stainless steel

Approvals

cCSAus CE (DC-only models)





AccuProx



Page V8-T3-45

Overview

AccuProx sensors feature analog outputs that change linearly as the target moves closer or further from the sensor face.

Ferrous Only Tubular



Page V8-T3-51

Overview

Sensors designed to detect only ferrous metals (steel/iron).

Metal Face



Page V8-T3-54

Overview

Tough sensors with thick stainless steel sensing faces and barrels.

High Current Output



Page V8-T3-58

Overview

DC sensors which can carry extremely large continuous inrush current

Applications

Part positioning, distance, size and thickness measurement, general inspection and error proofing (such as material imperfection or blemish detection), eccentricity or absolute angle detection, identification of different metals

Product Features

Extended linear sensing range of up to 25 mm—three times longer than standard tubular analog inductive sensors

Outputs available in current (4-20 or 0-20 mA) and voltage (0-10V)

High output resolution and repeatability for applications requiring precision sensing performance

Robust stainless steel barrel, shockresistant front cap, polycarbonate end bell and impact-absorbing potting compound Ideal for extreme temperature or high pressure washdown environments

Applications

Workcell applications, automotive and aircraft production

18 mm diameters Two-wire AC or three-wire DC NO or NC outputs Micro- and mini-pin terminations

Applications

Metal cutting operations where damage to sensor face could occur

Applications

Heavy-duty vehicles, cement mixers, lift trucks, front end loaders, farm equipment

Product Features

LED indicators

Product Features

connections

12, 18 and 30 mm diameters Two-wire AC or three-wire DC 20 mil thick stainless steel face 303 stainless steel barrel LED indicator 2-meter cable, micro- and mini-pin

Product Features

30 mm diameter stainless steel housing Solid-state output for 12 ampere continuous, 50 ampere inrush capacity -40° to 158°F (-40° to 70°C) temperature range NO and NC isolated outputs

Heavy gauge SJO cable

Technical Data and Specifications

Current ratings-0-10 Vdc, 0-20 mA, 4-20 mA Enclosure ratings-NEMA 4, 4X, 6, 6P, 13 Construction-Stainless steel

Approvals

cUL Listed



Technical Data and Specifications

Current ratings-AC: 500 mA continuous DC: 200 mA continuous Enclosure ratings-NEMA 4, 4X, 6, 6P, 12, 13 IEC IP67 Construction-

Approvals

Stainless steel

UL Listed **CSA Certified**





Technical Data and Specifications

Current ratings-AC: 500 mA continuous DC: 200 mA continuous Enclosure ratings-NEMA 4, 4X, 6, 6P, 12, 13 IEC IP67 Construction-Stainless steel

Approvals

UL Listed **CSA Certified**





Technical Data and Specifications

Current ratings-Varies by model Enclosure ratings— NEMA 4, 4X, 6, 6P, 12, 13 IEC IP67 Construction-Stainless steel

Approvals

Miniature Short Body

E56 Pancake

Tubular, Nonmetallic Housing

E52 Cube Style



Page V8-T3-61

Overview

Small diameter and short body (4, 5, 6.5 and 8 mm) tubular housings for tight sensing applications.

Applications

Automation equipment, robotics, machine tool, counting, sorting

Product Features

Variety of diameters in stainless steel housings

PVC cable, micro- and nano-pin connections LED indicators standard

Short overall lengths

Short circuit and reverse polarity protection



Page V8-T3-66

Overview

Self-contained sensors capable of sensing up to 3.94 inches (100 mm).

Applications

Oil rig operations, floor conveyors, automotive assembly, overhead cranes

Product Features

40, 50, 70 and 100 mm sensing distances Four-wire DC models have complementary outputs (1 NO/1 NC)

Four-wire DC models use auto-configure technology, which allows the sensor to automatically adapt for NPN or PNP without user intervention

Available in two-wire AC versions Power and output LED indicator Quick disconnect option Short circuit protected in DC Longest sensing distances available



Page V8-T3-71

Overview

Tubular sensors with nonmetallic housings offer high corrosion resistance.

Applications

Food processing lines, high washdown environments

Product Features

12, 18 and 30 mm diameters shielded and unshielded sensing

AC and DC voltages Tough ABS plastic housing Output LED on all models

Normally open or closed outputs



Page V8-T3-74

Overview

A family of industry-standard, cube-sized inductive sensors with long range capabilities.

Applications

Automotive, manufacturing, machinery OEMs

Product Features

Long inductive proximity ranges available (up to 40 mm sensing distance)
Four-wire DC models have complementary outputs (1 NO/1 NC)

Four-wire DC models use auto-configure technology, which allows the sensor to automatically adapt for NPN or PNP without user intervention

Robust design featuring vibration and impact-absorbing potting compound Ideal for extreme temperatures or high pressure washdown environments

Technical Data and Specifications

Current ratings— DC: 200 mA maximum Enclosure ratings— NEMA 4, 4X, 6, 6P, 12, 13 IEC IP67

Construction— Stainless steel

Technical Data and Specifications

Current ratings—
AC: 500 mA continuous
DC: 200 mA continuous
Enclosure ratings—
NEMA 4, 4X, 12, 13
(some models also rated NEMA 6)
IEC IP66

Construction— PPS

Technical Data and Specifications

Current ratings—
AC: 150 mA
DC: 200 mA
Enclosure ratings—
NEMA 3, 3S, 4, 4X, 13
IEC IP66
Construction—

Technical Data and Specifications

Current ratings—
DC: 300 mA maximum
Enclosure ratings—
NEMA 4, 4X, 6, 6P, 12, 13
IEC IP67
Construction—
Zinc alloy/PPS, PL

Approvals

CE

 ϵ

Approvals

cULus Listed



Approvals

ABS plastic

_

Approvals

cULus Listed



E52 Rectangular Style



Page V8-T3-78

Overview

A variety of small rectangular sensors for limited space applications.

Applications

Tight applications where conventional sensor are too large

Product Features

Variety of housing styles R12, R18, Q16, 10 to 30 Vdc NPN and PNP output Short circuit protection

LED indicator for output status

E55 Limit Switch Style, **Nonmetallic Housing**



Page V8-T3-81

Overview

These nonmetallic sensors provide corrosion resistance in a limit switch style housing.

Applications

Food processing lines, high washdown environments

Product Features

5 position head can be top mounted or in any of four side positions Long sensing ranges up to 40 mm Normally open or closed outputs AC voltages Tough PBT resin housing

E51 Limit Switch Style. Factory Sealed 6P +



Page V8-T3-83

Overview

Completely epoxy filled in unitized, one piece limit switch style construction for reliable performance under the most adverse of environmental conditions.

Applications

All corrosive environments: Coolants/ cutting oils, automotive applications

Product Features

One piece housing on switch body/ receptacle

Head and housing totally epoxy encapsulated

Side sensing head can be unfastened and moved to any of four positions Quick disconnect options

Corrosive resistant epoxy coated housing

E51 Limit Switch Style, Modular



Page V8-T3-92

Overview

Modular design allows maximum use of inventories in these limit switch style housings. Solid-state circuitry in a variety of sensing ranges.

Applications

Machine tool, punch presses, automotive, conveyor systems

Product Features

Modular heads, switch bodies, receptacles Shielded or unshielded sensing ranges Solid-state electronics Viton gasket seals LED indicators for power and output status Top and side sensing heads Alternate frequency for side by side

operation Components individually labeled for easy

identification

Technical Data and Specifications

Current ratings-DC: 100 mA maximum Enclosure ratings-NEMA 1, 2, 3, 3S, 4, 12 IEC IP66 Construction-PBT composition housing

Approvals

Technical Data and Specifications

Current ratings— AC: 400 mA Enclosure ratings-NEMA 4, 4X, 6, 12, 13 IEC IP67 Construction-PBT resin

Technical Data and Specifications

Current ratings— AC: 1 ampere continuous DC: 0.6 ampere continuous Enclosure ratings— NEMA 3, 3S, 4, 4X, 6, 6P, 12, 13 IFC IP67

Construction-Die cast zinc Gasket material: Viton®

Technical Data and Specifications

Current ratings— AC: 1 ampere continuous DC: 0.6 ampere continuous Enclosure ratings— NEMA 3, 3S, 4, 4X, 6, 6P, 12, 13 IEC IP67 Class I, Class II, Division 2 Groups A, B, C, D, F and G; Class III

Construction-Die cast zinc Gasket material: Viton

Approvals

UL Listed CSA Certified (most models)



Approvals





Approvals

cUL Listed



Contents

Description	Page
iProx Sensors	
Product Selection	
iProx Sensors	V8-T3-11
Complementary and Dual Output Sensors .	V8-T3-13
Compatible Connector Cables	V8-T3-14
Accessories	V8-T3-14
Technical Data and Specifications	V8-T3-15
Wiring Diagrams	V8-T3-16
Dimensions	V8-T3-16

iProx Sensors

Product Description

The iProx represents the highest performance, most versatile tubular inductive sensor offered by Eaton's electrical sector. By utilizing an embedded microprocessor and exclusive SmartSense™ technology, iProx can sense up to three times farther than typical sensors of its class, while providing an unheard-of level of customization.

Both shielded and unshielded versions of iProx feature extended sensing ranges. This allows the sensor to be mounted farther from the target, thereby reducing the potential for target impacts and increasing the sensing reliability of your application.

The iProx also includes a wide range of advanced features that can be enabled via optional programming tools. Using the ProxView Windows-based software package, an entirely custom sensor can be programmed to perfectly fit an application.

Sensor characteristics, such as sensing range, can be customized down to the nearest tenth of a millimeter. Outputs can be changed from NO to NC. The iProx even features built-in timing delays and speed detection logic—no PLC programming is necessary.

With extended sensing range, quality construction and the ability to adapt to its environment, iProx is the ideal choice for even the most demanding inductive sensing applications.

Application Description Typical Applications

- Automotive
- Machine tool
- Material handling
- Metalworking

Features

- Available in AC two-wire, DC three-wire and unique DC four-wire with complementary (NO-NC) or dual NO outputs
- Reliably detect metal targets at up to three times the range of conventional shielded or unshielded tubular inductive sensors

- Quality construction using a stainless steel barrel, 360-degree dual-color LED indicator, Ryton[®] impact-resistant face cap and vibration-absorbing potting compound
- Auto-configure technology automatically detects a sinking (NPN) or sourcing (PNP) connection and switches the sensor accordingly, without any user intervention
- Exclusive SmartSense embedded microprocessor technology allows for customizable range, band sensing, nuisance metal rejection, timing delays and over/under speed detection
- Optional computer programming cable and Windows-based ProxView configuration software makes it easy to customize sensors
- Withstands high electrical noise (up to 20 V/m)
- Resistant to extreme temperatures (-40°F [-40°C])

Standards and Certifications

- cUL Listed
- CE







DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

iProx Sensors

Note: Custom iProx models can also be ordered directly from the factory with pre-set ranges, outputs and connectors. Consult the Eaton Application Engineers at 1-800-426-9184 for more information.

Two-Wire Sensors

IVVO-VVII	e Sensors						
Operating Voltage	Sensing Range	Shielding	Connection Type ①	NO Output Catalog Number ^②	NC Output Catalog Number ^②		
12 mm Di	meter						
20-132 Vac	4 mm	Shielded	3-pin micro AC connector	E59-M12A105A01-A1 🕢	E59-M12A105A01-A2 🐱		
			3-pin micro AC pigtail ③	E59-M12A105A01P-A1 🙃	E59-M12A105A01P-A2 🙃		
			3-pin mini AC pigtail ^③	E59-M12A105A01PB-A1 ふ	E59-M12A105A01PB-A2		
			2-meter cable	E59-M12A105C02-A1	E59-M12A105C02-A2		
	10 mm	Unshielded	3-pin micro AC connector	E59-M12C110A01-A1 &	E59-M12C110A01-A2 🙃		
			3-pin micro AC pigtail ③	E59-M12C110A01P-A1 ふ	E59-M12C110A01P-A2 🙃		
			3-pin mini AC pigtail ^③	E59-M12C110A01PB-A1 ふ	E59-M12C110A01PB-A2		
			2-meter cable	E59-M12C110C02-A1	E59-M12C110C02-A2		
18 mm Dia	meter						
20-132 Vac	8 mm	Shielded	3-pin micro AC connector	E59-M18A109A01-A1 🙃	E59-M18A109A01-A2 😧		
			3-pin micro AC pigtail ③	E59-M18A109A01P-A1 ₃	E59-M18A109A01P-A2 🐽		
			3-pin mini AC pigtail ^③	E59-M18A109A01PB-A1 ふ	E59-M18A109A01PB-A2		
			2-meter cable	E59-M18A109C02-A1	E59-M18A109C02-A2		
	18 mm	Unshielded	3-pin micro AC connector	E59-M18C118A01-A1 3€	E59-M18C118A01-A2 🕹		
			3-pin micro AC pigtail ③	E59-M18C118A01P-A1 ふ	E59-M18C118A01P-A2 .€		
			3-pin mini AC pigtail ^③	E59-M18C118A01PB-A1 ふ	E59-M18C118A01PB-A2		
			2-meter cable	E59-M18C118C02-A1	E59-M18C118C02-A2		
30 mm Dia	meter						
20-132 Vac	15 mm	Shielded	3-pin micro AC connector	E59-M30A115A01-A1 🐽	E59-M30A115A01-A2 🙃		
			3-pin micro AC pigtail ③	E59-M30A115A01P-A1 ふ	E59-M30A115A01P-A2 🕟		
			3-pin mini AC pigtail ③	E59-M30A115A01PB-A1 🕟	E59-M30A115A01PB-A2		
			2-meter cable	E59-M30A115C02-A1	E59-M30A115C02-A2		
	29 mm	Unshielded	3-pin micro AC connector	E59-M30C129A01-A1 ๋€	E59-M30C129A01-A2 🕟		
			3-pin micro AC pigtail ^③	E59-M30C129A01P-A1 ๋ €	E59-M30C129A01P-A2 🙃		
			3-pin mini AC pigtail ③	E59-M30C129A01PB-A1 €	E59-M30C129A01PB-A2		
			2-meter cable	E59-M30C129C02-A1	E59-M30C129C02-A2		

- $\ensuremath{ \bigodot}$ See listing of compatible connector cables on Page V8-T3-14.
- ① For sensors with custom cable lengths or PUR jackets, contact Application Engineering at 1-800-426-9184.
- ② Sensors are ordered with pre-set outputs from the factory, but can be later programmed either NO or NC using the ProxView software.
- 3 Standard pigtail cable length is 12 in.

Note: Custom iProx models can also be ordered directly from the factory with pre-set ranges, outputs and connectors. Consult the Eaton Application Engineers at 1-800-426-9184 for more information.

Three-Wire Sensors

	Operating Voltage	Sensing Range	Shielding	Connection Type ①	NO Output Catalog Number ②	NC Output Catalog Number ©
Standard Range	12 mm Dia	meter				
	6-48 Vdc	4 mm	Shielded	4-pin micro DC connector	E59-M12A105D01-D1 3	E59-M12A105D01-D2 3
				4-pin micro DC pigtail ^③	E59-M12A105D01P-D1 🔃	E59-M12A105D01P-D2 🕮
Extended Range				2-meter cable	E59-M12A105C02-D1	E59-M12A105C02-D2
		10 mm	Unshielded	4-pin micro DC connector	E59-M12C110D01-D1 🕃	E59-M12C110D01-D2 3
-0				4-pin micro DC pigtail ®	E59-M12C110D01P-D1 ::	E59-M12C110D01P-D2 ::
100				2-meter cable	E59-M12C110C02-D1	E59-M12C110C02-D2
Standard Range	18 mm Dia	meter				
1	6–48 Vdc	8 mm	Shielded	4-pin micro DC connector	E59-M18A108D01-D1 🕃	E59-M18A108D01-D2 🕃
				4-pin micro DC pigtail ③	E59-M18A108D01P-D1 🙃	E59-M18A108D01P-D2 3
Extended Range				2-meter cable	E59-M18A108C02-D1	E59-M18A108C02-D2
Extended hange		18 mm	Unshielded	4-pin micro DC connector	E59-M18C116D01-D1 3	E59-M18C116D01-D2 3
THE STATE OF THE S				4-pin micro DC pigtail ^③	E59-M18C116D01P-D1 🕃	E59-M18C116D01P-D2 3
1				2-meter cable	E59-M18C116C02-D1	E59-M18C116C02-D2
Standard Range	30 mm Dia	meter				
	6–48 Vdc	15 mm	Shielded	4-pin micro DC connector	E59-M30A115D01-D1 😟	E59-M30A115D01-D2 🙃
				4-pin micro DC pigtail ^③	E59-M30A115D01P-D1 😟	E59-M30A115D01P-D2 😟
0.20				2-meter cable	E59-M30A115C02-D1	E59-M30A115C02-D2
Extended Range		29 mm	Unshielded	4-pin micro DC connector	E59-M30C129D01-D1 3	E59-M30C129D01-D2 3
				4-pin micro DC pigtail ③	E59-M30C129D01P-D1 3	E59-M30C129D01P-D2 3
11/1				2-meter cable	E59-M30C129C02-D1	E59-M30C129C02-D2

- ③ See listing of compatible connector cables on Page V8-T3-14.
- $^{\scriptsize \textcircled{\tiny 1}} \ \ \text{For sensors with custom cable lengths or PUR jackets, contact Application Engineering at 1-800-426-9184}.$
- ② Sensors are ordered with pre-set outputs from the factory, but can be later programmed either NO or NC using the ProxView software.
- 3 Standard pigtail cable length is 12 in.

Complementary and Dual Output Sensors

Four-Wire Sensors

	Operating Voltage	Sensing Range	Shielding	Output Type	Connection Type	Complementary Output (1NO-1NC) Catalog Number	Dual NO Output Catalog Number ①
1	12 mm Dia	ameter					
ò	–48 Vdc	4 mm	Shielded	NPN (sinking)	4-pin micro DC connector	E59-M12A105D01-D3NN 🕃	E59-M12A105D01-D1NN ::
					2-meter cable	E59-M12A105C02-D3NN	E59-M12A105C02-D1NN
				PNP (sourcing)	4-pin micro DC connector	E59-M12A105D01-D3PP ::	E59-M12A105D01-D1PP 🕃
					2-meter cable	E59-M12A105C02-D3PP	E59-M12A105C02-D1PP
		10 mm	Unshielded	NPN (sinking)	4-pin micro DC connector	E59-M12C110D01-D3NN 🕃	E59-M12C110D01-D1NN 🙃
					2-meter cable	E59-M12C110C02-D3NN	E59-M12C110C02-D1NN
				PNP (sourcing)	4-pin micro DC connector	E59-M12C110D01-D3PP 🙃	E59-M12C110D01-D1PP ::
					2-meter cable	E59-M12C110C02-D3PP	E59-M12C110C02-D1PP
1	18 mm Dia	ameter					
	6–48 Vdc	8 mm	Shielded	NPN (sinking)	4-pin micro DC connector	E59-M18A108D01-D3NN 🕃	E59-M18A108D01-D1NN ::
					2-meter cable	E59-M18A108C02-D3NN	E59-M18A108C02-D1NN
				PNP (sourcing)	4-pin micro DC connector	E59-M18A108D01-D3PP ::	E59-M18A108D01-D1PP 🙃
					2-meter cable	E59-M18A108C02-D3PP	E59-M18A108C02-D1PP
		18 mm	Unshielded	NPN (sinking)	4-pin micro DC connector	E59-M18C116D01-D3NN 🕃	E59-M18C116D01-D1NN 🙃
					2-meter cable	E59-M18C116C02-D3NN	E59-M18C116C02-D1NN
				PNP (sourcing)	4-pin micro DC connector	E59-M18C116D01-D3PP 🙃	E59-M18C116D01-D1PP 🕃
					2-meter cable	E59-M18C116C02-D3PP	E59-M18C116C02-D1PP
3	30 mm Dia	ameter					
6	6–48 Vdc	15 mm	Shielded	NPN (sinking)	4-pin micro DC connector	E59-M30A115D01-D3NN 🙃	E59-M30A115D01-D1NN ::
					2-meter cable	E59-M30A115C02-D3NN	E59-M30A115C02-D1NN
				PNP (sourcing)	4-pin micro DC connector	E59-M30A115D01-D3PP ::	E59-M30A115D01-D1PP ::
					2-meter cable	E59-M30A115C02-D3PP	E59-M30A115C02-D1PP
		29 mm	Unshielded	NPN (sinking)	4-pin micro DC connector	E59-M30C129D01-D3NN ::	E59-M30C129D01-D1NN 🕃
					2-meter cable	E59-M30C129C02-D3NN	E59-M30C129C02-D1NN
				PNP (sourcing)	4-pin micro DC connector	E59-M30C129D01-D3PP ::	E59-M30C129D01-D1PP :
					2-meter cable	E59-M30C129C02-D3PP	E59-M30C129C02-D1PP

- $\ensuremath{\textcircled{3}}$ See listing of compatible connector cables on Page V8-T3-14.
- ① At this time, iProx Complementary and Dual Output models are not available with auto-sink/source detection. Therefore, PNP (sourcing) and NPN (sinking) models must be ordered separately.

Micro-Style Straight Female

Mini-Style Straight Female

Compatible Connector Cables

Standard Cables ①

Current Rating at 600V	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-Style,	Straight Fe	emale					
_	AC	3-pin, 3-wire	22 AWG	6.0 ft (2m)	2-Red/Black 3-Red/White	CSAS3F3CY2202	CSAS3F3RY2202
_	DC	4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White 3-Blue 4-Black	CSDS4A4CY2202	CSDS4A4RY2202
Mini-Style, S	traight Fer	nale				Catalog Number	
13A	_	3-pin	16 AWG	6 ft (2m)	1-Green 2-Black 3-White	CSMS3F3CY1602	

Accessories

Description	Catalog Number
Step-by-step programming software required to program iProx. Compatible with Microsoft Windows [®] and Windows [®] Mobile devices.	E59SW1
The iProx programming cable is used to program individual iProx sensors, providing a connection between the computer and the sensor. Connects to computer via a serial (RS-232) or USB port. (USB connection requires an adapter which is included with purchase.)	E59RP1
Field applied labels for iProx sensor (100 pcs)	E59LABEL
	Step-by-step programming software required to program iProx. Compatible with Microsoft Windows® and Windows® Mobile devices. The iProx programming cable is used to program individual iProx sensors, providing a connection between the computer and the sensor. Connects to computer via a serial (RS-232) or USB port. (USB connection requires an adapter which is included with purchase.)

Note

 $^{\scriptsize \textcircled{1}}$ For a full selection of connector cables, see Tab 10, section 10.1.

Catalog Number

Starter Kit

iProx Starter Kits

Description

Description



• • • • • • • • • • • • • • • • • • • •	· · · · · · · · · · · · · · · · · · ·					
Interested in custom programming iProx sensors to fit your application?						
These kits include everything needed to get the most out of iProx: a sensor, a programming cable (E59RP1), a micro connector cable (CSDS4A4CY2202) and ProxView software on CD-ROM (E59SW1).						
Starter kit includes:						
12 mm AC unshielded iProx sensor (E59-M12C110A01-A1)	E5912ACKIT					
12 mm DC unshielded iProx sensor (E59-M12C110D01-D1)	E5912DCKIT					
18 mm AC unshielded iProx sensor (E59-M18C118A01-A1)	E5918ACKIT					
18 mm DC unshielded iProx sensor (E59-M18C116D01-D1)	E5918DCKIT					
30 mm AC unshielded iProx sensor (E59-M30C129A01-A1)	E5930ACKIT					
30 mm DC unshielded iProx sensor (E59-M30C129D01-D1)	E5930DCKIT					

Demo Kit

iProx Demonstration Kit



A powered, briefcase demo kit show-casing the capabilities of iProx and AccuProx sensors. Kit includes one 18 mm iProx sensor and one 18 mm AccuProx sensor. A quick disconnect cable and mounting system allow for fast swapping of sensors. Demo kit is powered by two replaceable 9-volt alkaline batteries.

E59DEM01

Catalog Number

Technical Data and Specifications

iProx Sensors

Description	Two-Wire Sensors	Three-Wire Sensors
Input voltage	20-132 Vac	6-48 Vdc
Load current	250 mA	300 mA
Leakage current	≤1.7 mA at 32°F (0°C), 2.0 mA at −40°F (−40°C)	≤150 µA
Voltage drop	<5 Vac	≤2.5 Vdc
Burden current	_	≤15 mA
Protection	None	Auto reset
Switching hysteresis	<15% rated sensing distance	<15% rated sensing distance
Repeat accuracy	Shielded models: <1% sensing distance; Unshielded models: <3% sensing distance	Shielded models: <1% sensing distance; Unshielded models: <3% sensing distance
Surge capacity	3A/30 ms	_
Temperature range	-40° to 158°F (-40° to 70°C)	-40° to 158°F (-40° to 70°C)
Material of construction	303 stainless steel; end bells: polycarbonate; face caps: Ryton [®] ; cable: AWM style 20387 (PVC)	303 stainless steel; end bells: polycarbonate; face caps: Ryton®; cable: AWM style 20387 (PVC)
Vibration and shock	Vibration: 10 to 55 Hz, 1 mm amplitude, IEC 60068-2-6; shock: 30g, 11 ms per IEC 68-2-27	Vibration: 10 to 55 Hz, 1 mm amplitude, IEC 60068-2-6; shock: 30g, 11 ms per IEC 68-2-27
Indicator LED	360° viewable LED	360° viewable LED
Enclosure ratings	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) IP69K ①	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) IP69K ①

Response Time ②

	Two-Wire Sensors	Three-Wire Sei Shielded	nsors		Unshielded		
Description	All Two-Wire Models	12 mm	18 mm	30 mm	12 mm	18 mm	30 mm
Factory default mode	Shipped in "Side by Side Mode" by default (20 V/m)	580 Hz (10 V/m)	390 Hz (10 V/m)	240 Hz (10 V/m)	300 Hz (10 V/m)	150 Hz (10 V/m)	145 Hz (10 V/m)
Side by side ③	30 Hz (10 V/m)	50 Hz (20 V/m)	50 Hz (20 V/m)	50 Hz (20 V/m)	50 Hz (20 V/m)	50 Hz (20 V/m)	50 Hz (20 V/m)
High noise immunity mode	10 Hz (>20 V/m)	10 Hz (>20 V/m)	10 Hz (>20 V/m)	10 Hz (>20 V/m)	10 Hz (>20 V/m)	10 Hz (>20 V/m)	10 Hz (>20 V/m)

Notes

Ryton® is a registered trademark of Phillips Chemical (division of Phillips Petroleum).

- ① Our products conform to NEMA® tests as indicated, however, some severe washdown applications can exceed these NEMA test specifications.
- 2 iProx sensors may be programmed to perform in side by side or high noise immunity applications using the iProx programming cable (E59RP1) and ProxView software (E59SW1).
- (E59SW1). Use the side by side response time parameter when using the iProx Tray Programmer (E59TP1), iProx programming cable (E59RP1) and ProxView software (E59SW1).

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.


iProx Sensors

Operating			Connector Models (Face View Male Shown)			
Voltage	Output	Cable Models	Micro	Mini		
Two-Wire S	Sensors					
20–132 Vac	NO and NC	BN L1 BU Load L2	1 L1	L1 or 1 L2 or Load (-)		
Three-Wire	Sensors					
6–48 Vdc	NO and NC (NPN and PNP) ①	BN +V BK Load BU (-)	(-) (-) (-) (-) (-) (-) (-) (-) (-) (-)	_		
Four-Wire I	Dual Output and Co	omplementary Sensors				
6–48 Vdc	NO and NC (NPN)	BN +V WH Load BU (-) BL Load	(a) (b) (c) (c) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d	_		
	NO and NC (PNP)	3 BN +V WH Load BU (-) BL Load	(-) Load (2) (1) +V (3) (4) Load			

Dimensions


Approximate Dimensions in Inches (mm)

Cable Models



Size	Shielding	A	В	C	D
12 mm	Shielded	2.46 (62.4)	1.98 (50.3)	0.02 (0.5)	0.67 (17)
	Unshielded	2.46 (62.4)	1.64 (41.6)	0.36 (9)	0.67 (17)
18 mm	Shielded	2.54 (64.5)	2.00 (50.9)	0.02 (0.5)	0.94 (24)
	Unshielded	2.54 (64.5)	1.47 (37.4)	0.55 (14)	0.94 (24)
30 mm	Shielded	2.74 (69.6)	2.13 (54.1)	0.03 (0.75)	1.41 (36)
	Unshielded	2.74 (69.6)	1.41 (35.8)	0.75 (19)	1.41 (36)

Micro-Connector Models



Size	Shielding	A	В	С	D
12 mm	Shielded	2.71 (68.7)	1.98 (50.3)	0.02 (0.5)	0.67 (17)
	Unshielded	2.71 (68.7)	1.64 (41.6)	0.36 (9)	0.67 (17)
18 mm	Shielded	2.73 (69.3)	2.00 (50.9)	0.02 (0.5)	0.94 (24)
	Unshielded	2.73 (69.3)	1.47 (37.4)	0.55 (14)	0.94 (24)
30 mm	Shielded	2.92 (74.1)	2.13 (54.1)	0.03 (0.75)	1.41 (36)
	Unshielded	2.92 (74.1)	1.41 (35.8)	0.75 (19)	1.41 (36)

- ① The three-wire DC version of iProx automatically configures itself to NPN or PNP based on field wiring. No user intervention is required.
- $\,^{\odot}\,$ Pin numbers 2 and 4 are internally jumpered together. Either pin may be used.
- $\ ^{\textcircled{3}}$ The complementary (1NO-1NC) output models feature the NC output on pin 2 (white).



ontent	ts		

C

Description	Page
E57 Premium+ Series Sensors	
Product Selection	
E57 Premium+ Sensors	V8-T3-18
Compatible Connector Cables	V8-T3-23
Accessories	V8-T3-23
Technical Data and Specifications	V8-T3-24
Wiring Diagrams	V8-T3-25
Dimensions	V8-T3-26

E57 Premium+ Series Sensors

Product Description

The Premium+ Series Inductive Proximity Sensors by Eaton's electrical sector have improved sensing performance, product durability and selection. This improved line of sensors carries the Premium+ Series name because we have upgraded the design to a rugged stainless steel body, shock-resistant front caps and impact-absorbing potting compound. Plus, the Premium+ Series line now includes a choice of AC, AC/ DC and DC-only, 12, 18 and 30 mm sensors with unmatched noise immunity of greater than 20V/meter.

Features

- New expanded offering of two-wire, three-wire, AC, DC, and AC/DC multiple range sensor models
- Manufactured to take physical and environmental abuse
- Designed with stainless steel barrel and new potting compound for robust, high temperature, high pressure washdown, as well as intense shock and vibration applications
- Unmatched high noise immunity eliminates problems associated with electrical noise (all models >20V/meter)

- 360° output status indicator is visible from any angle and in any light condition
- Resettable short circuit protection and reverse polarity in select models
- Right angle sensing models offer unique problem-solving capabilities
- Wide temperature range -13° to 158°F (-25° to 70°C) on cable, micro-style connections

Standards and Certifications

- cUL Listed
- CE (AC/DC and DC-only models)







A DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

E57 Premium+ Sensors

Two-Wire Sensors

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type ①	NO Output Catalog Number	NC Output Catalog Number
Standard Range	12 mm Dian	neter End Sensing				
	20–250 Vac	2 mm	Shielded	2-meter cable	E57LAL12A2	E57LBL12A2
33		(standard range)		3-pin micro AC connector	E57LAL12A2SA 🕹	E57LBL12A2SA 🏵
200				3-pin micro AC pigtail connector	E57LAL12A2SP ⊙	E57LBL12A2SP ⓐ
Extended Range		4 mm	Unshielded	2-meter cable	E57LAL12A2E	E57LBL12A2E
30		(standard range)		3-pin micro AC connector	E57LAL12A2EA 🖸	E57LBL12A2EA ⓐ
				3-pin micro AC pigtail connector	E57LAL12A2EP 🗈	E57LBL12A2EP ③
T. C. P.	20–132 Vac	6 mm	Semi-shielded	2-meter cable	E57-12LE06-A	E57-12LE06-A1
		(extended range)		3-pin micro AC connector	E57-12LE06-AA 🙃	E57-12LE06-A1A 🙃
				3-pin micro AC pigtail connector	E57-12LE06-AP ⊙	_
		10 mm	Non-embeddable	2-meter cable	E57-12LE10-A	E57-12LE10-A1
		(extended range)		3-pin micro AC connector	E57-12LE10-AA ふ	E57-12LE10-A1A 🔂
				3-pin micro AC pigtail connector	E57-12LE10-AP ⊙	E57-12LE10-A1P 🛈
	40-250 Vac	2 mm	Shielded	2-meter cable	E57SAL12A2	E57SBL12A2
	50/60 Hz ^② 20–250 Vdc	(standard range) 4 mm (standard range)		3-pin micro AC connector	E57SAL12A2SA 🐱	E57SBL12A2SA ๋€
	20-230 Vuc			3-pin mini-connector	E57MAL12A2B1 🕟	_
			Unshielded	2-meter cable	E57SAL12A2E	E57SBL12A2E
				3-pin micro AC connector	E57SAL12A2EA 🙃	E57SBL12A2EA ๋€
Standard Range	18 mm Dian	neter End Sensing				
	20–250 Vac	5 mm (standard range) 8 mm (standard range)	Shielded	2-meter cable	E57LAL18A2	E57LBL18A2
0-37				3-pin micro AC connector	E57LAL18A2SA ふ	E57LBL18A2SA 🕹
211				3-pin micro AC pigtail connector	E57LAL18A2SP €	E57LBL18A2SP む
Extended Range				3-pin mini-connector	E57MAL18A2B1 ⊙	E57MBL18A2B1 ⊙
			Unshielded	2-meter cable	E57LAL18A2E	E57LBL18A2E
1	•			3-pin micro AC connector	E57LAL18A2EA ⊙	E57LBL18A2EA 🔂
				3-pin micro AC pigtail connector	E57LAL18A2EP 🙃	E57LBL18A2EP 🕹
				3-pin mini-connector	E57MAL18A2EB1 🕟	E57MBL18A2EB1 ๋€
	20-132 Vac	12 mm	Semi-shielded	2-meter cable	E57-18LE12-A	E57-18LE12-A1
		(extended range)		3-pin micro AC connector	E57-18LE12-AA ๋€	E57-18LE12-A1A ๋€
				3-pin micro AC pigtail connector	E57-18LE12-AP ๋€	E57-18LE12-A1P 🐱
				3-pin mini-connector	E57-18LE12-AB ふ	E57-18LE12-A1B ₺
		18 mm	Non-embeddable	2-meter cable	E57-18LE20-A	E57-18LE20-A1
		(extended range)		3-pin micro AC connector	E57-18LE20-AA ๋	E57-18LE20-A1A 🙃
				3-pin micro AC pigtail connector	E57-18LE20-AP ふ	E57-18LE20-A1P (3)
				3-pin mini-connector	E57-18LE20-AB ๋	E57-18LE20-A1B ๋
	40-250 Vac	5 mm	Shielded	2-meter cable	E57SAL18A2	E57SBL18A2
	50/60 Hz ^②	(standard range)		3-pin micro AC connector	E57SAL18A2SA 🕟	E57SBL18A2SA €
	20–250 Vdc	8 mm	Unshielded	2-meter cable	E57SAL18A2E	E57SBL18A2E
		(standard range)		3-pin micro AC connector	E57SAL18A2EA 🙃	E57SBL18A2EA 🙃

- See listing of compatible connector cables on Page V8-T3-23.
- ① For cable lengths longer than 2 meters, add the number of the desired length in meters to the end of the listed catalog number (for catalog numbers ending with a number, add an **S** and then the length). Examples for a 5-meter cable: E57-18LE12-A becomes E57-18LE12-A**5**; E57LAL12A2 becomes E57LAL12A2S**5**.
- ② Avoid wiring these AC/DC models in series as the sensors may not perform reliably. Contact Eaton's Applications Engineering at 1-800-426-9184 with questions.

E57 Premium+ Series Sensors

E57SAL30A2EA 🐽

E57SBL30A2EA 🗈

Two-Wire Sensors, continued

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type ①	NO Output Catalog Number	NC Output Catalog Number			
le	18 mm Diameter Right Angle Sensing								
1	20-250 Vac	5 mm	Shielded	2-meter cable	E57RAL18A2	E57RBL18A2			
10				3-pin micro AC connector	E57RAL18A2SA ₃	E57RBL18A2SA €			
				3-pin micro AC pigtail connector	E57RAL18A2SP 🙃	E57RBL18A2SP ₃			
				3-pin mini-connector	E57RAL18A2B1 🔕	E57RBL18A2B1 ④			
		8 mm	Unshielded	2-meter cable	E57RAL18A2E	E57RBL18A2E			
				3-pin micro AC connector	E57RAL18A2EA 🙃	E57RBL18A2EA ๋€			
				3-pin micro AC pigtail connector	E57RAL18A2EP 🙃	E57RBL18A2EP ふ			
				3-pin mini-connector	E57RAL18A2EB1 ③	E57RBL18A2EB1 €			
	30 mm Diameter End Sensing								
	(s 	10 mm (standard range)	Shielded	2-meter cable	E57LAL30A2	E57LBL30A2			
				3-pin micro AC connector	E57LAL30A2SA €	E57LBL30A2SA ↔			
Contract of the Contract of th				3-pin micro AC pigtail connector	E57LAL30A2SP ₃	E57LBL30A2SP ↔			
				3-pin mini-connector	E57MAL30A2B1 ๋€	E57MBL30A2B1 ③			
		15 mm (standard range)	Unshielded	2-meter cable	E57LAL30A2E	E57LBL30A2E			
				3-pin micro AC connector	E57LAL30A2EA ふ	E57LBL30A2EA ๋€			
				3-pin micro AC pigtail connector	E57LAL30A2EP ↔	E57LBL30A2EP ๋€			
				3-pin mini-connector	E57MAL30A2EB1 ⊙	E57MBL30A2EB1 ๋€			
	20-132 Vac	22 mm	Semi-shielded	2-meter cable	E57-30LE22-A	E57-30LE22-A1			
		(extended range)		3-pin micro AC connector	E57-30LE22-AA 🙃	E57-30LE22-A1A 🙃			
				3-pin micro AC pigtail connector	E57-30LE22-AP ③	E57-30LE22-A1P ๋€			
				3-pin mini-connector	E57-30LE22-AB ๋€	E57-30LE22-A1B ⊙			
	40-250 Vac	10 mm	Shielded	2-meter cable	E57SAL30A2	E57SBL30A2			
	50/60 Hz ² 20–250 Vdc	(standard range)		3-pin micro AC connector	E57SAL30A2SA ₃	E57SBL30A2SA €			
		15 mm	Unshielded	2-meter cable	E57SAL30A2E	E57SBL30A2E			
		(standard range)		3-pin micro AC connector	E57SAL30A2EA 🙃	E57SBL30A2EA 🙃			

Notes

- ${ \odot \hspace{-8pt}:\:\:\:}$ See listing of compatible connector cables on Page V8-T3-23.
- ① For cable lengths longer than 2 meters, add the number of the desired length in meters to the end of the listed catalog number (for catalog numbers ending with a number, add an **S** and then the length). Examples for a 5-meter cable: E57-18LE12-A becomes E57-18LE12-A**5**; E57LAL12A2 becomes E57LAL12A2.

3-pin micro AC connector

Avoid wiring these AC/DC models in series as the sensors may not perform reliably. Contact Eaton's Applications Engineering at 1-800-426-9184 with questions.

Shielding

Connection Type ①

E57 Premium+ Series Sensors

Sensing

Range (Sn)

Three-Wire Sensors

Operating

Voltage

Standard Range	
-	-
032	

Company or the Company of the Compan	
Extended Range	
Extenueu nange	
753	

Standard	Range



Extended Range



voitage	naliye (Sil)	Siliciumy	Connection type ©	Catalog Number	Catalog Number
12 mm Dia	meter End Sensing				
6–48 Vdc	2 mm	Shielded	2-meter cable	E57LAL12T110	E57LBL12T110
	(standard range)	(NPN)	4-pin micro DC connector	E57LAL12T110SD ::	E57LBL12T110SD 🕃
			4-pin micro DC pigtail connector	E57LAL12T110SP :::	E57LBL12T110SP 3
		Shielded	2-meter cable	E57LAL12T111	E57LBL12T111
		(PNP)	4-pin micro DC connector	E57LAL12T111SD ::	E57LBL12T111SD ::
			4-pin micro DC pigtail connector	E57LAL12T111SP :::	E57LBL12T111SP 🗓
	4 mm	Unshielded	2-meter cable	E57LAL12T110E	E57LBL12T110E
	(standard range)	(NPN)	4-pin micro DC connector	E57LAL12T110ED 🙃	E57LBL12T110ED :
			4-pin micro DC pigtail connector	E57LAL12T110EP ::	E57LBL12T110EP ::
		Unshielded	2-meter cable	E57LAL12T111E	E57LBL12T111E
		(PNP)	4-pin micro DC connector	E57LAL12T111ED ::	E57LBL12T111ED 😩
			4-pin micro DC pigtail connector	E57LAL12T111EP ::	E57LBL12T111EP :
	6 mm	Semi-shielded	2-meter cable	E57-12LE06-C	E57-12LE06-C1
	(extended range)	(NPN) Semi-shielded (PNP)	4-pin micro DC connector	E57-12LE06-CD 🙃	E57-12LE06-C1D 3
			4-pin micro DC pigtail connector	E57-12LE06-CP 3	E57-12LE06-C1P 3
			2-meter cable	E57-12LE06-B	E57-12LE06-B1
			4-pin micro DC connector	E57-12LE06-BD 😟	E57-12LE06-B1D 3
			4-pin micro DC pigtail connector	E57-12LE06-BP 3	E57-12LE06-B1P 3
	10 mm	Non-embeddable (NPN)	2-meter cable	E57-12LE10-C	E57-12LE10-C1
	(extended range)		4-pin micro DC connector	E57-12LE10-CD 😟	E57-12LE10-C1D 3
			4-pin micro DC pigtail connector	E57-12LE10-CP 3	_
			2-meter cable	E57-12LE10-B	E57-12LE10-B1
		(PNP)	4-pin micro DC connector	E57-12LE10-BD 🙃	E57-12LE10-B1D 3
			4-pin micro DC pigtail connector	E57-12LE10-BP 😩	_
8 mm Dia	meter End Sensing				
i–48 Vdc	5 mm	Shielded	2-meter cable	E57LAL18T110	E57LBL18T110
	(standard range)	(NPN)	4-pin micro DC connector	E57LAL18T110SD 3	E57LBL18T110SD 3
			4-pin micro DC pigtail connector	E57LAL18T110SP ::	E57LBL18T110SP 3
			4-pin mini-connector	E57MAL18T110B1 😃	E57MBL18T110B1 3
		Shielded	2-meter cable	E57LAL18T111	E57LBL18T111
		(PNP)	4-pin micro DC connector	E57LAL18T111SD 3	E57LBL18T111SD 3
			4-pin micro DC pigtail connector	E57LAL18T111SP 🙃	E57LBL18T111SP 3
			4-pin mini-connector	E57MAL18T111B1 🙃	E57MBL18T111B1 3
	8 mm	Unshielded	2-meter cable	E57LAL18T110E	E57LBL18T110E
	(standard range)	(NPN)	4-pin micro DC connector	E57LAL18T110ED ::	E57LBL18T110ED 😩
			4-pin micro DC pigtail connector	E57LAL18T110EP ::	E57LBL18T110EP ::
			4-pin mini-connector	E57MAL18T110EB1 #	E57MBL18T110EB1 😩
		Unshielded	2-meter cable	E57LAL18T111E	E57LBL18T111E
		(PNP)	4-pin micro DC connector	E57LAL18T111ED 🙃	E57LBL18T111ED ::
			4-pin micro DC pigtail connector	E57LAL18T111EP ::	E57LBL18T111EP (#)

NC Output Catalog Number

NO Output Catalog Number

Notes

- $\ensuremath{\textcircled{\$}}$ See listing of compatible connector cables on Page V8-T3-23.
- ① For cable lengths longer than 2 meters, add the number of the desired length in meters to the end of the listed catalog number (for catalog numbers ending with a number, add an S and then the length). Examples for a 5-meter cable: E57-18LE12-A becomes E57-18LE12-A5; E57LAL12A2 becomes E57LAL12A2 S5.

4-pin mini-connector

E57MAL18T111EB1 3

E57MBL18T111EB1 ::

E57 Premium+ Series Sensors

Three-Wire Sensors, continued

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type ①	NO Output Catalog Number	NC Output Catalog Number			
Standard Range	18 mm Diameter End Sensing, continued								
	6-48 Vdc	12 mm	Semi-shielded (NPN)	2-meter cable	E57-18LE12-C	E57-18LE12-C1			
931		(extended range)		4-pin micro DC connector	E57-18LE12-CD 😮	E57-18LE12-C1D 😮			
a per				4-pin micro DC pigtail connector	E57-18LE12-CP :	E57-18LE12-C1P 🕃			
Extended Range				4-pin mini-connector	E57-18LE12-CB 🕃	E57-18LE12-C1B 🕃			
			Semi-shielded	2-meter cable	E57-18LE12-B	E57-18LE12-B1			
The state of the s			(PNP)	4-pin micro DC connector	E57-18LE12-BD 😩	E57-18LE12-B1D 🙃			
				4-pin micro DC pigtail connector	E57-18LE12-BP 🕃	E57-18LE12-B1P 🕃			
				4-pin mini-connector	E57-18LE12-BB 🕃	E57-18LE12-B1B 😮			
		18 mm	Non-embeddable	2-meter cable	E57-18LE20-C	E57-18LE20-C1			
		(extended range)	(NPN)	4-pin micro DC connector	E57-18LE20-CD 🕃	E57-18LE20-C1D 🕃			
				4-pin micro DC pigtail connector	E57-18LE20-CP :	E57-18LE20-C1P 🕃			
				4-pin mini-connector	E57-18LE20-CB 🕃	E57-18LE20-C1B ::			
			Non-embeddable (PNP)	2-meter cable	E57-18LE20-B	E57-18LE20-B1			
				4-pin micro DC connector	E57-18LE20-BD 😩	E57-18LE20-B1D 🙃			
				4-pin micro DC pigtail connector	E57-18LE20-BP 🕃	E57-18LE20-B1P :			
				4-pin mini-connector	E57-18LE20-BB 🕃	E57-18LE20-B1B 😮			
Right Angle	18 mm Diameter Right Angle Sensing								
33 8	6-48 Vdc	5 mm	Shielded (NPN)	2-meter cable	E57RAL18T110	E57RBL18T110			
933				4-pin micro DC connector	E57RAL18T110SD 🙃	E57RBL18T110SD 🙃			
100				4-pin micro DC pigtail connector	E57RAL18T110SP 😀	E57RBL18T110SP 3			
				4-pin mini-connector	E57RAL18T110B1 🙃	E57RBL18T110B1 🙃			
			Shielded (PNP)	2-meter cable	E57RAL18T111	E57RBL18T111			
				4-pin micro DC connector	E57RAL18T111SD 😩	E57RBL18T111SD 😀			
				4-pin micro DC pigtail connector	E57RAL18T111SP 🙃	E57RBL18T111SP 🙃			
				4-pin mini-connector	E57RAL18T111B1 🕃	E57RBL18T111B1 🕃			
		8 mm	Unshielded	2-meter cable	E57RAL18T110E	E57RBL18T110E			
			(NPN)	4-pin micro DC connector	E57RAL18T110ED ::	E57RBL18T110ED ::			
				4-pin micro DC pigtail connector	E57RAL18T110EP 🕃	E57RBL18T110EP 🕃			
				4-pin mini-connector	E57RAL18T110EB1 #	E57RBL18T110EB1 3			
			Unshielded	2-meter cable	E57RAL18T111E	E57RBL18T111E			
			(PNP)	4-pin micro DC connector	E57RAL18T111ED 😩	E57RBL18T111ED (#)			
				4-pin micro DC pigtail connector	E57RAL18T111EP 😩	E57RBL18T111EP :			
				4-pin mini-connector	E57RAL18T111EB1 🗉	E57RBL18T111EB1 🎛			

- $\ensuremath{\textcircled{\textbf{3}}}$ See listing of compatible connector cables on $\ensuremath{\textbf{Page V8-T3-23}}.$
- ① For cable lengths longer than 2 meters, add the number of the desired length in meters to the end of the listed catalog number (for catalog numbers ending with a number, add an **S** and then the length). Examples for a 5-meter cable: E57-18LE12-A becomes E57-18LE12-A**5**; E57LAL12A2 becomes E57LAL12A2**S5**.

Three-Wire Sensors, continued

Standard Range

Extended Range



Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type ①	NO Output Catalog Number	NC Output Catalog Number
30 mm Dian	neter End Sensing				
6–48 Vdc	10 mm	Shielded	2-meter cable	E57LAL30T110	E57LBL30T110
	(standard range)	(NPN)	4-pin micro DC connector	E57LAL30T110SD 😮	E57LBL30T110SD ::
			4-pin micro DC pigtail connector	E57LAL30T110SP 3	E57LBL30T110SP 🙃
			4-pin mini-connector	E57MAL30T110B1 ::	E57MBL30T110B1 🙃
		Shielded	2-meter cable	E57LAL30T111	E57LBL30T111
		(PNP)	4-pin micro DC connector	E57LAL30T111SD :	E57LBL30T111SD ::
			4-pin micro DC pigtail connector	E57LAL30T111SP ::	E57LBL30T111SP 🙃
			4-pin mini-connector	E57MAL30T111B1 🙃	E57MBL30T111B1 🙃
	15 mm (standard range)	Unshielded	2-meter cable	E57LAL30T110E	E57LBL30T110E
		(NPN)	4-pin micro DC connector	E57LAL30T110ED 😩	E57LBL30T110ED ::
			4-pin micro DC pigtail connector	E57LAL30T110EP ::	E57LBL30T110EP ::
			4-pin mini-connector	E57MAL30T110EB1 3	E57MBL30T110EB1 😩
		Unshielded (PNP)	2-meter cable	E57LAL30T111E	E57LBL30T111E
			4-pin micro DC connector	E57LAL30T111ED 😩	E57LBL30T111ED 😩
			4-pin micro DC pigtail connector	E57LAL30T111EP ::	E57LBL30T111EP :
			4-pin mini-connector	E57MAL30T111EB1 🙃	E57MBL30T111EB1 🕃
	22 mm	Semi-shielded (NPN)	2-meter cable	E57-30LE22-C	E57-30LE22-C1
	(extended range)		4-pin micro DC connector	E57-30LE22-CD ::	E57-30LE22-C1D ::
			4-pin micro DC pigtail connector	E57-30LE22-CP :	E57-30LE22-C1P ::
			4-pin mini-connector	E57-30LE22-CB 😩	E57-30LE22-C1B 😮
		Semi-shielded	2-meter cable	E57-30LE22-B	E57-30LE22-B1
		(PNP)	4-pin micro DC connector	E57-30LE22-BD ::	E57-30LE22-B1D 😮
			4-pin micro DC pigtail connector	_	E57-30LE22-B1P 😮
			4-pin mini-connector	E57-30LE22-BB :	E57-30LE22-B1B ::

- ③ See listing of compatible connector cables on Page V8-T3-23.
- ① For cable lengths longer than 2 meters, add the number of the desired length in meters to the end of the listed catalog number (for catalog numbers ending with a number, add an **S** and then the length). Examples for a 5-meter cable: E57-18LE12-A becomes E57-18LE12-A**5**; E57LAL12A2 becomes E57LAL12A2S**5**.

E57 Premium+ Series Sensors

Compatible Connector Cables

Standard Cables ①

Micro-Style Straight Female	
0	

Current Ra at 600V	ating Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-St	yle, Straight F	emale					
=	AC	3-pin, 3-wire	22 AWG	6.0 ft (2m)	2 3 1-Green 2-Red/Black 3-Red/White	CSAS3F3CY2202	CSAS3F3RY2202
	DC	4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White 3-Blue 4-Black	CSDS4A4CY2202	CSDS4A4RY2202

Mini-Style Straight Female



Mini-Sty	yle, Straight Fe	emale		Catalog Number			
13A	_	3-pin	16 AWG	6 ft (2m)	1-Green 2-Black 3-White	CSMS3F3CY1602	
10A	AC/DC	4-pin, 4-wire	16 AWG	6 ft (2m)	1-Black 2-Blue 3 2 3-Brown 4-White	CSMS4A4CY1602	

Accessories

E57 Premium+ Sensors

Description	Reference
Mounting brackets	See Tab 8, section 8.2
Replacement mounting nuts and other accessories	See Tab 8, section 8.3
Connector cables	See Tab 10, section 10.1

Note

 $\ensuremath{^{\circlearrowleft}}$ For a full selection of connector cables, see Tab 10, section 10.1.

Technical Data and Specifications


E57 Premium+ Sensors

Description	Two-Wire AC Sensors	Two-Wire AC/DC Sensors	Three-Wire DC Only Sensors
Operating voltage	20–250 Vac	40–240 Vac ① 20–250 Vdc	6–48 Vdc
Maximum load current	250 mA	250 mA	500 mA at 6-30 Vdc
Switching frequency	20 Hz	60 Hz	12 mm: 800 Hz 18 mm: 500 Hz 30 mm: 300 Hz
Leakage current	1.7 mA maximum at 158°F (70°C)	≤2.0 mA	≤100 µA
Voltage drop	7V maximum	12V at <10 mA ≤4V at >25 mA	<2.5V
Holding current	5 mA minimum	5 mA minimum	_
Burden current	_	_	≤10 mA
Protection	_	Resettable short circuit; overload protection	Auto reset
Switching hysteresis	2 to 20% of rated sensing range	<15% rated sensing distance	<15% rated sensing distance
Repeat accuracy	<3% sensing distance	Shielded models: <1% sensing distance; unshielded and extended range: <3%	Shielded models: <1% sensing distance; unshielded and extended range: <3%
Time delay before availability	_	<200 ms	<200 ms
Output indicator LED	360° viewable LED	360° viewable LED	360° viewable LED
Operating temperature	–13° to 158°F (–25° to 70°C) Mini Conn.: –13° to 122°F (–25° to 50°C)	–13° to 158°F (–25° to 70°C) Mini Conn.: –13° to 122°F (–25° to 50°C)	–13° to 158°F (–25° to 70°C) Mini Conn.: –13° to 122°F (–25° to 50°C)
Enclosure ratings	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) IP69K	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) IP69K	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) IP69K
Shock	30g, 11 ms per IEC 68-2-76	30g, 11 ms per IEC 68-2-76	30g, 11 ms per IEC 68-2-76
Vibration	10 to 55 Hz, 1 mm amplitude	10 to 55 Hz, 1 mm amplitude	10 to 55 Hz, 1 mm amplitude
Housing material	303 stainless steel ^② ; polycarbonate end bells; Ryton [®] front ends	303 stainless steel ^② ; polycarbonate end bells; Ryton [®] front ends	303 stainless steel ©; polycarbonate end bells; Ryton® front ends
Cable	AWM Style 20387 (PVC)	AWM Style 20387 (PVC)	AWM Style 20387 (PVC)

Recommended Mounting Clearances

For unshielded standard range sensors and extended range sensors, clearance must be provided around the sensor when mounting for reliable performance. ("Sn" is the sensing range of the sensor, "d" is the sensor diameter.)

E57 Premium+ Sensors, Mounting



Туре	Shielding	а	b
Standard range	Shielded	0	0
	Unshielded	Cap height	2 x 5n
Extended range	Semi-shielded	d	Sn
	Non-embeddable	Cap height	2 x Sn

Notes

Ryton® is a registered trademark of Phillips Chemical (division of Phillips Petroleum).

- $^{\scriptsize \textcircled{1}}$ 40–240 Vac at <–4°F (<–20°C).
- ② Semi-shielded models are nickel-plated brass.

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

E57 Premium+ Sensors


Operating			Connector Models (Face View Male Sho	wn)
Voltage	Output	Cable Models	Micro	Mini
Two-Wire Sensor	s			
20–250 Vac/dc and AC-only AC wiring example	NO and NC	BN L1 BU Load L2	L2 Load 3 2 L1	L1 (1) Load L2
20–250 Vac/dc DC wiring example	NO and NC (NPN)	BN Load L1 or +V BU L2 or (-)	L2— <u>Load</u> 3 2 L1	_
	NO and NC (PNP)	BN L1 or +V Load L2 or (-)	L2	_
Three-Wire Senso	ors			
6–48 Vdc	NO (NPN)	BN +V BK Load (-)	(-) (2 (1) +V Load Load	+V Load (1 (4) (-)
	NO (PNP)	BN +V BK Load (_)	(-) (2) (1) +V	(-) Load (1 (4) +V
	NC (NPN)	BN +V BK Load (-)	(-) (2) (1) +V	+V Load (1) (4) (-)
	NC (PNP)	BN +V BK Load BU (_)	(-) Load 2 1 +V	(-) Load (1) (4) +V
•				

Dimensions


Approximate Dimensions in Inches (mm)

E57 Premium+ Series Sensors, End Sensing ①2

Cable Models



Connector Models




Size	Shielding	Overall Length A	Threaded Length B	Cap Height C	Nut Width D	Thread Size E
Two-Wire AC	Sensors—Cable Models					
12 mm	Shielded	2.46 (62.4)	1.98 (50.3)	_	0.67 (16.8)	M12 x 1
	Semi-shielded	2.87 (72.8)	2.28 (57.9)	0.06 (1.62)	0.67 (16.8)	M12 x 1
	Unshielded	2.87 (72.7)	1.98 (50.3)	0.36 (9.14)	0.67 (16.8)	M12 x 1
18 mm	Shielded	2.54 (64.5)	2.00 (50.9)	_	0.94 (23.8)	M18 x 1
	Semi-shielded	2.60 (66.1)	1.90 (48.2)	0.10 (2.54)	0.94 (23.8)	M18 x 1
	Unshielded	2.60 (66.0)	1.47 (37.2)	0.56 (14.1)	0.94 (23.8)	M18 x 1
30 mm	Shielded	2.73 (69.3)	1.98 (50.3)	_	1.41 (35.9)	M30 x 1.5
	Semi-shielded	2.67 (67.8)	1.90 (48.2)	0.13 (3.30)	1.41 (35.9)	M30 x 1.5
	Unshielded	2.73 (69.3)	1.49 (37.8)	0.52 (13.26)	1.41 (35.9)	M30 x 1.5
Two-Wire AC	Sensors – Micro-Connec	tor Models				
12 mm	Shielded	2.69 (68.4)	1.98 (50.3)	_	0.67 (16.8)	M12 x 1
	Semi-shielded	3.04 (77.2)	2.28 (57.9)	0.06 (1.62)	0.67 (16.8)	M12 x 1
	Unshielded	3.06 (77.7)	1.98 (50.3)	0.36 (9.14)	0.36 (9.14)	M12 x 1
18 mm	Shielded	2.72 (69.06)	2.00 (50.9)	_	0.94 (23.8)	M18 x 1
	Semi-shielded	2.72 (69.1)	1.90 (48.2)	0.10 (2.54)	0.94 (23.8)	M18 x 1
	Unshielded	2.74 (69.4)	1.47 (37.2)	0.56 (14.1)	0.94 (23.8)	M18 x 1
30 mm	Shielded	2.91 (73.8)	1.98 (50.3)	_	1.41 (35.9)	M30 x 1.5
	Semi-shielded	2.78 (70.6)	1.90 (48.2)	0.13 (3.30)	1.41 (35.9)	M30 x 1.5
	Unshielded	2.91 (73.8)	1.49 (37.8)	0.52 (13.26)	1.41 (35.9)	M30 x 1.5
Two-Wire AC/	DC Sensors—Cable Mod	dels				
12 mm	Shielded	2.45 (62.4)	1.98 (50.3)	_	0.67 (16.8)	M12 x 1
	Unshielded	2.45 (62.4)	1.80 (45.8)	0.20 (5)	0.67 (16.8)	M12 x 1
18 mm	Shielded	2.54 (64.5)	2.00 (50.9)	_	0.94 (23.8)	M18 x 1
	Unshielded	2.54 (64.5)	1.75 (44.4)	0.28 (7)	0.94 (23.8)	M18 x 1
30 mm	Shielded	2.72 (69.3)	1.98 (50.3)	_	1.41 (35.9)	M30 x 1.5
	Unshielded	2.72 (69.3)	1.49 (37.8)	0.52 (13.26)	1.41 (35.9)	M30 x 1.5
Two-Wire AC/	DC Sensors – Micro-Con	nector Models				
12 mm	Shielded	2.69 (68.4)	1.98 (50.3)	_	0.67 (16.8)	M12 x 1
	Unshielded	2.69 (68.4)	1.80 (45.8)	0.20 (5)	0.67 (16.8)	M12 x 1
18 mm	Shielded	2.72 (69.06)	2.00 (50.9)	_	0.94 (23.8)	M18 x 1
	Unshielded	2.72 (69.06)	1.75 (44.4)	0.28 (7)	0.94 (23.8)	M18 x 1
30 mm	Shielded	2.91 (73.8)	1.98 (50.3)	_	1.41 (35.9)	M30 x 1.5
	Unshielded	2.91 (73.8)	1.49 (37.8)	0.52 (13.26)	1.41 (35.9)	M30 x 1.5

- ① These dimensions apply to the Premium+ Series models in this section. Not indicated Premium Series models.
- ② For short barrel model dimensions (E57SAL ...) refer to Page V8-T3-29.


Approximate Dimensions in Inches (mm)

E57 Premium+ Series Sensors, End Sensing ①②

Cable Models, continued



Connector Models, continued




Size	Shielding	Overall Length A	Threaded Length B	Cap Height C	Nut Width D	Thread Size E
Two-Wire AC	Sensors – Mini-Connecto	or Models				
18 mm	Shielded	3.39 (86.1)	2.00 (50.8)	0.02 (0.5)	0.94 (23.8)	M18 x 1
	Semi-shielded	3.39 (86.0)	1.90 (48.2)	0.10 (2.54)	0.94 (23.8)	M18 x 1
	Unshielded	3.39 (86.1)	1.46 (37.0)	0.57 (14.5)	0.94 (23.8)	M18 x 1
30 mm	Shielded	3.39 (86.1)	2.1 (53.3)	0.03 (0.8)	1.41 (35.9)	M30 x 1.5
	Semi-shielded	3.44 (87.4)	1.90 (48.2)	0.13 (3.30)	1.41 (35.9)	M30 x 1.5
	Unshielded	3.39 (86.1)	1.55 (39.4)	0.55 (14.0)	1.41 (35.9)	M30 x 1.5
Three-Wire DO	C Sensors – Mini-Connec	tor Models				
18 mm	Shielded	3.39 (86.1)	2.00 (50.8)	0.02 (0.5)	0.94 (23.8)	M18 x 1
	Semi-shielded	3.39 (86.0)	1.90 (48.2)	0.10 (2.54)	0.94 (23.8)	M18 x 1
	Unshielded	3.39 (86.1)	1.46 (37.0)	0.57 (14.5)	0.94 (23.8)	M18 x 1
30 mm	Shielded	3.39 (86.1)	2.1 (53.3)	0.03 (0.8)	1.41 (35.9)	M30 x 1.5
	Semi-shielded	3.44 (87.4)	1.90 (48.2)	0.13 (3.30)	1.41 (35.9)	M30 x 1.5
	Unshielded	3.39 (86.1)	1.55 (39.4)	0.55 (14.0)	1.41 (35.9)	M30 x 1.5
Three-Wire DO	Sensors—Cable Model	s				
12 mm	Shielded	2.46 (62.4)	1.98 (50.3)	_	0.67 (16.8)	M12 x 1
	Semi-shielded	2.87 (72.8)	2.28 (57.9)	0.06 (1.62)	0.67 (16.8)	M12 x 1
	Unshielded	2.87 (72.7)	1.98 (50.3)	0.36 (9.14)	0.67 (16.8)	M12 x 1
18 mm	Shielded	2.54 (64.5)	2.00 (50.9)	_	0.94 (23.8)	M18 x 1
	Semi-shielded	2.60 (66.1)	1.90 (48.2)	0.10 (2.54)	0.94 (23.8)	M18 x 1
	Unshielded	2.60 (66.0)	1.47 (37.2)	0.56 (14.1)	0.94 (23.8)	M18 x 1
30 mm	Shielded	2.73 (69.3)	1.98 (50.3)	_	1.41 (35.9)	M30 x 1.5
	Semi-shielded	2.67 (67.8)	1.90 (48.2)	0.13 (3.30)	1.41 (35.9)	M30 x 1.5
	Unshielded	2.73 (69.3)	1.49 (37.8)	0.52 (13.26)	1.41 (35.9)	M30 x 1.5
Three-Wire DO	Sensors – Micro-Conne	ector Models				
12 mm	Shielded	2.71 (68.7)	1.98 (50.3)	_	0.67 (16.8)	M12 x 1
	Semi-shielded	3.04 (77.2)	2.28 (57.9)	0.06 (1.62)	0.67 (16.8)	M12 x 1
	Unshielded	3.06 (77.7)	1.98 (50.3)	0.36 (9.14)	0.67 (16.8)	M12 x 1
18 mm	Shielded	2.73 (69.3)	2.00 (50.9)	_	0.94 (23.8)	M18 x 1
	Semi-shielded	2.72 (69.1)	1.90 (48.2)	0.10 (2.54)	0.94 (23.8)	M18 x 1
	Unshielded	2.74 (69.4)	1.47 (37.2)	0.56 (14.1)	0.94 (23.8)	M18 x 1
30 mm	Shielded	2.92 (74.1)	1.98 (50.3)	_	1.41 (35.9)	M30 x 1.5
	Semi-shielded	2.78 (70.6)	1.90 (48.2)	0.13 (3.30)	1.41 (35.9)	M30 x 1.5
	Unshielded	2.92 (74.1)	1.49 (37.8)	0.52 (13.26)	1.41 (35.9)	M30 x 1.5

- ① These dimensions apply to the Premium+ Series models in this section. Not indicated Premium Series models.
- ② For short barrel model dimensions (E57SAL ...) refer to Page V8-T3-29.


Approximate Dimensions in Inches (mm)

E57 Premium+ Series Sensors, Right Angle Sensing

Cable Models



Connector Models



Size	A	nnread B	C C	D D	E E	
Mini-Conne	ctor Models					
18 mm	4.303 (109)	1.97 (50)	0.98 (25)	0.94 (24)	M18 x 1	
Micro-Conn	ector Models					
18 mm	3.65 (93)	1.97 (50)	0.98 (25)	0.94 (24)	M18 x 1	

Contante

V8-T3-34

E57 Premium+ Series Short Barrel Sensors

E57 Premium+ Series Short Barrel Sensors

Contonio	
Description	Page
E57 Premium+ Series Short Barrel Sensors	
Product Selection	
E57 Premium+ Series Short Barrel Sensors	V8-T3-30
Compatible Connector Cables	V8-T3-31
Accessories	V8-T3-32
Technical Data and Specifications	V8-T3-32
Wiring Diagrams	V8-T3-33

Dimensions

E57 Premium+ Series Short Barrel Sensors

Product Description

The new Premium+ Series Short Barrel Inductive Proximity Sensors from Eaton's electrical sector feature the same sensing ranges as our standard length sensors, but in a body with a substantially shorter length. This allows the sensors to be used in applications where mounting space is limited.

Our robust Premium+ Series design has been added to the short barrel line. This means these sensors have been upgraded to include rugged stainless steel barrels, polycarbonate end bells, shock-resistant front cap and potting compound. Plus, the short barrel line now includes a choice of AC, AC/DC and DC-only, 12, 18 and 30 mm sensors. Cable models feature an optional extra long 5-meter cable. Every sensor is designed with 360° LED.

Features

- Manufactured to take physical and environmental abuse
- Designed with stainless steel barrel and impactabsorbing new potting compound for robust, high temperature, high pressure washdown, as well as intense shock and vibration applications
- Unmatched high noise immunity eliminates problems associated with electrical noise (all models >20V/meter)
- 360° output status indicator is visible from any angle and in any light condition

- Resettable short circuit protection in AC/DC and DC models
- Reverse polarity protection in three-wire DC versions
- Small size to fit in tight spaces
- Choice of cable for low cost wiring, or microconnector for quick installation or replacement
- Cable models include an extra long 5-meter cable as option

Standards and Certifications

- cUL Listed
- CE (AC/DC and DC-only models)







A DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578.

For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

E57 Premium+ Series Short Barrel Sensors

Two-Wire Sensors

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type ①	NO Output Catalog Number	NC Output Catalog Number
mm	12 mm Dia	meter				
-	20-250 Vac	2 mm	Shielded	2-meter cable	E57SAL12A4	E57SBL12A4
3	per la company de la company d			3-pin micro AC connector	E57SAL12A4SA ₃	E57SBL12A4SA ふ
24		4 mm	Unshielded	2-meter cable	E57SAL12A4E	E57SBL12A4E
				3-pin micro AC connector	E57SAL12A4EA 🗈	E57SBL12A4EA ふ
	40-250 Vac	2 mm	Shielded	2-meter cable	E57SAL12A2	E57SBL12A2
	50/60 Hz ^② 20–250 Vdc			3-pin micro AC connector	E57SAL12A2SA 🗈	E57SBL12A2SA €
	20 200 100	4 mm	Unshielded	2-meter cable	E57SAL12A2E	E57SBL12A2E
				3-pin micro AC connector	E57SAL12A2EA 🙃	E57SBL12A2EA ふ
mm	18 mm Dia	meter				
	20-250 Vac	5 mm	Shielded	2-meter cable	E57SAL18A4	E57SBL18A4
7/19	pp (F)			3-pin micro AC connector	E57SAL18A4SA ₃	E57SBL18A4SA ふ
17/		8 mm	Unshielded	2-meter cable	E57SAL18A4E	E57SBL18A4E
				3-pin micro AC connector	E57SAL18A4EA ₃	E57SBL18A4EA ⊙
	40-250 Vac	5 mm	Shielded	2-meter cable	E57SAL18A2	E57SBL18A2
	50/60 Hz ^② 20–250 Vdc			3-pin micro AC connector	E57SAL18A2SA 🗈	E57SBL18A2SA 🔕
	20 200 100	8 mm	Unshielded	2-meter cable	E57SAL18A2E	E57SBL18A2E
				3-pin micro AC connector	E57SAL18A2EA 🗈	E57SBL18A2EA ふ
mm	30 mm Dia	meter				
-PA	20-250 Vac	10 mm	Shielded	2-meter cable	E57SAL30A4	E57SBL30A4
				3-pin micro AC connector	E57SAL30A4SA 🙃	E57SBL30A4SA 🕹
		15 mm	Unshielded	2-meter cable	E57SAL30A4E	E57SBL30A4E
				3-pin micro AC connector	E57SAL30A4EA 🙃	E57SBL30A4EA ふ
	40-250 Vac	10 mm	Shielded	2-meter cable	E57SAL30A2	E57SBL30A2
	50/60 Hz ^② 20–250 Vdc			3-pin micro AC connector	E57SAL30A2SA 🗈	E57SBL30A2SA ₃
	20 200 100	15 mm	Unshielded	2-meter cable	E57SAL30A2E	E57SBL30A2E
				3-pin micro AC connector	E57SAL30A2EA 🙃	E57SBL30A2EA 🙃

- See listing of compatible connector cables on Page V8-T3-31.
- ① Cable models are supplied as standard with a 2-meter cable. A 5-meter cable is available by adding S5 to the catalog number. Example: E57SAL12T110 becomes E57SAL12T110S5.
- ② Avoid wiring these AC/DC models in series as the sensors may not perform reliably. Contact Eaton's Applications Engineering at 1-800-426-9184 with questions.

E57 Premium+ Series Short Barrel Sensors

Three-Wire Sensors

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type ①	NO Output Catalog Number	NC Output Catalog Number			
12 mm	12 mm Dia	12 mm Diameter							
	6–48 Vdc	2 mm	Shielded	2-meter cable	E57SAL12T110	_			
3			(NPN)	4-pin micro DC connector	E57SAL12T110SD 😩	_			
			Shielded	2-meter cable	E57SAL12T111	E57SBL12T111			
			(PNP)	4-pin micro DC connector	E57SAL12T111SD 😩	E57SBL12T111SD ::			
		4 mm	Unshielded	2-meter cable	E57SAL12T110E	E57SBL12T110E			
			(NPN)	4-pin micro DC connector	E57SAL12T110ED 3	E57SBL12T110ED 3			
			Unshielded	2-meter cable	E57SAL12T111E	E57SBL12T111E			
			(PNP)	4-pin micro DC connector	E57SAL12T111ED #	E57SBL12T111ED			
3 mm	18 mm Dia	meter							
	6–48 Vdc	5 mm	Shielded	2-meter cable	E57SAL18T110	E57SBL18T110			
2/10	100		(NPN)	4-pin micro DC connector	E57SAL18T110SD 🙃	E57SBL18T110SD 😀			
DI			Shielded (PNP)	2-meter cable	E57SAL18T111	E57SBL18T111			
				4-pin micro DC connector	E57SAL18T111SD #	E57SBL18T111SD (#)			
		8 mm	Unshielded (NPN)	2-meter cable	E57SAL18T110E	E57SBL18T110E			
				4-pin micro DC connector	E57SAL18T110ED 3	E57SBL18T110ED (#)			
			Unshielded (PNP)	2-meter cable	E57SAL18T111E	E57SBL18T111E			
				4-pin micro DC connector	E57SAL18T111ED #	E57SBL18T111ED (#)			
) mm	30 mm Dia	meter							
All I	6–48 Vdc	10 mm	Shielded	2-meter cable	E57SAL30T110	E57SBL30T110			
	- 10		(NPN)	4-pin micro DC connector	E57SAL30T110SD 3	E57SBL30T110SD (#)			
			Shielded	2-meter cable	E57SAL30T111	E57SBL30T111			
-			(PNP)	4-pin micro DC connector	E57SAL30T111SD 😟	E57SBL30T111SD (#)			
		15 mm	Unshielded	2-meter cable	E57SAL30T110E	E57SBL30T110E			
			(NPN)	4-pin micro DC connector	E57SAL30T110ED 3	E57SBL30T110ED (#)			
			Unshielded	2-meter cable	E57SAL30T111E	E57SBL30T111E			
			(PNP)	4-pin micro DC connector	E57SAL30T111ED :	E57SBL30T111ED ::			

Compatible Connector Cables

Standard Cables 2

	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-Style	Micro-Styl	le, Straight Fem	ale				
Straight Female	AC	3-pin, 3-wire	22 AWG	6.0 ft (2m)	② ③ 1-Green 2-Red/Black 3-Red/White	CSAS3F3CY2202	CSAS3F3RY2202
	DC	4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White 3-Blue 4-Black	CSDS4A4CY2202	CSDS4A4RY2202



- 3 See listing of compatible connector cables above.
- Cable models are supplied as standard with a 2-meter cable. A 5-meter cable is available by adding \$5 to the catalog number. Example: E57SAL12T110 becomes E57SAL12T110\$5.
- ② For a full selection of connector cables, see Tab 10, section 10.1.

Accessories

E57 Premium+ Series Short Barrel Sensors

Description	Reference
Mounting brackets	See Tab 8 , section 8.2
Replacement mounting nuts and other accessories	See Tab 8, section 8.3
Connector cables	See Tab 10, section 10.1

Technical Data and Specifications

E57 Premium+ Series Short Barrel Sensors

		Two-Wire AC/DC Sensors		
Description	Two-Wire AC Sensors	AC Operation	DC Operation	Three-Wire DC Sensors
Operating voltage	40-250 Vac	40-250 Vac	20–250 Vdc	6–48 Vdc
Maximum load current	250 mA	200 mA	200 mA	250 mA
Switching frequency	20 Hz	60 Hz 60 Hz		12 mm: 800 Hz 18 mm: 500 Hz 30 mm: 300 Hz
Leakage current	1.7 mA maximum at 70°C	1.7V mA maximum at 120 Vac	≤2.0 mA	100 μA maximum
Voltage drop	7V maximum	≤4V at >25 mA	12V at <10 mA	≤2.5V
Holding current	5 mA minimum	5 mA minimum	5 mA maximum	≤10 mA
Protection	_	Resettable short circuit; overload protection	Resettable short circuit; overload protection	Auto reset
Switching hysteresis	2–20% of rated sensing distance	2-20% of rated sensing distance	2-20% of rated sensing distance	2–20% of rated sensing distance
Repeat accuracy	<3% sensing distance	<3% sensing distance	<3% sensing distance	<3% sensing distance
Output indicator LED	360° viewable LED	360° viewable LED	360° viewable LED	360° viewable LED
Operating temperature	−13° to 158°F (−25° to 70°C) ^①	−13° to 158°F (−25° to 70°C) ^①	−13° to 158°F (−25° to 70°C) ^①	−13° to 158°F (−25° to 70°C) ^①
Enclosure ratings	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)
Shock	30g sine wave, 11 ms per IEC68-2-76	30g sine wave, 11 ms per IEC68-2-76	30g sine wave, 11 ms per IEC68-2-76	30g sine wave, 11 ms per IEC68-2-76
Vibration	10 to 55 Hz, 1 mm amplitude	10 to 55 Hz, 1 mm amplitude	10 to 55 Hz, 1 mm amplitude	10 to 55 Hz, 1 mm amplitude
Material of construction	Stainless steel, polycarbonate end bells, Ryton [®] front cap	Stainless steel, polycarbonate end bells, Ryton [®] front cap	Stainless steel, polycarbonate end bells, Ryton [®] front cap	Stainless steel, polycarbonate end bells, Ryton® front cap
Cable	AWM Style 20387 (PVC)	AWM Style 20387 (PVC)	AWM Style 20387 (PVC)	AWM Style 20387 (PVC)

Notes

 $\label{eq:Ryton} \textbf{Ryton}^{\textcircled{\$}} \text{ is a registered trademark of Phillips Chemical (division of Phillips Petroleum)}.$

① 240 Vac operation is limited to less than 122°F (50°C) in two-wire AC/DC models.

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

E57 Premium+ Series Short Barrel Sensors


Operating Voltage	Output	Cable Models	Micro-Connector Models (Face View Male Shown)
Two-Wire Sensor	s		
20–250 Vac/dc 45/65 Hz DC wiring example	NO and NC (NPN)	BN Load L1 or +V BU L2 or (-)	L2— <u>Load</u> 3 2 L1
	NO and NC (PNP)	BN L1 or +V	L2
20–250 Vac/dc and AC-only AC wiring example	NO and NC	BN L1 BU Load L2	L2 Load 3 2 L1
Three-Wire Senso	ors		
6–48 Vdc	NO (NPN)	BN +V BK Load BU (-)	(-) (2 (1) +V Load
	NO (PNP)	BN +V BK Load (_)	(-) (2) (1) +V
	NC (NPN)	BN +V BK Load (-)	(-) (2) (1) +V
	NC (PNP)	BN +V BK Load (_)	(-) Load (2) (1) +V

Dimensions


Approximate Dimensions in Inches (mm)

E57 Premium+ Series Short Barrel Sensors—Cable Models


12 mm



18 mm



30 mm




Size	Shielding	Overall Length A	Threaded Length B	Cap Height C	Thread Size D
Two-Wire AC	Sensors				
12 mm	Shielded	2.04 (51.7)	1.56 (39.6)	0.02 (0.5)	M12 x 1
	Unshielded	2.04 (51.7)	1.38 (35.1)	0.20 (5)	M12 x 1
18 mm	Shielded	1.39 (35.3)	0.86 (21.82)	0.02 (0.5)	M18 x 1
	Unshielded	1.39 (35.3)	0.60 (15.32)	0.28 (7)	M18 x 1
30 mm	Shielded	1.58 (40.2)	0.99 (25.15)	0.03 (0.8)	M30 x 1.5
	Unshielded	1.77 (44.9)	0.68 (17.27)	0.52 (13.26)	M30 x 1.5
Two-Wire AC	/DC Sensors				
12 mm	Shielded	2.46 (62.4)	1.98 (50.27)	_	M12 x 1
	Unshielded	2.46 (62.4)	1.80 (45.77)	0.20 (5)	M12 x 1
18 mm	Shielded	2.54 (64.5)	2.00 (50.9)	_	M18 x 1
	Unshielded	2.54 (64.5)	1.75 (44.4)	0.28 (7)	M18 x 1
30 mm	Shielded	2.72 (69.3)	2.12 (53.8)	_	M30 x 1.5
	Unshielded	2.72 (69.3)	1.63 (41.4)	0.52 (13.26)	M30 x 1.5
Three-Wire D	C Sensors				
12 mm	Shielded	1.39 (35.3)	0.91 (23.09)	0.02 (0.5)	M12 x 1
	Unshielded	1.39 (35.3)	0.73 (18.59)	0.20 (5)	M12 x 1
18 mm	Shielded	1.39 (35.3)	0.86 (21.82)	0.02 (0.5)	M18 x 1
	Unshielded	1.39 (35.3)	0.60 (15.32)	0.28 (7)	M18 x 1
30 mm	Shielded	1.58 (40.2)	0.84 (21.26)	0.03 (0.8)	M30 x 1.5
	Unshielded	1.77 (44.9)	0.53 (13.46)	0.52 (13.26)	M30 x 1.5

E57 Premium+ Series Short Barrel Sensors


Approximate Dimensions in Inches (mm)

E57 Premium+ Series Short Barrel Sensors—Micro-Connector Models


12 mm



18 mm



30 mm



Size	Shielding	Overall Length A	Threaded Length B	Cap Height C	Thread Size D
Two-Wire AC	Sensors				
12 mm	Shielded	2.27 (57.8)	1.56 (39.6)	0.02 (0.5)	M12 x 1
	Unshielded	2.27 (57.8)	1.38 (35.1)	0.20 (5)	M12 x 1
18 mm	Shielded	1.57 (40.0)	0.86 (21.82)	0.02 (0.5)	M18 x 1
	Unshielded	1.57 (40.0)	0.60 (15.32)	0.28 (7)	M18 x 1
30 mm	Shielded	1.76 (44.8)	0.99 (25.15)	0.03 (0.8)	M30 x 1.5
	Unshielded	1.95 (49.5)	0.68 (17.27)	0.52 (13.26)	M30 x 1.5
Two-Wire AC	DC Sensors				
12 mm	Shielded	2.69 (68.4)	1.98 (50.27)	_	M12 x 1
	Unshielded	2.69 (68.4)	1.80 (45.77)	0.20 (5)	M12 x 1
18 mm	Shielded	2.72 (69.06)	2.00 (50.9)	_	M18 x 1
	Unshielded	2.72 (69.06)	1.75 (44.4)	0.28 (7)	M18 x 1
30 mm	Shielded	2.91 (73.8)	2.12 (53.8)	_	M30 x 1.5
	Unshielded	2.91 (73.8)	1.63 (41.4)	0.52 (13.26)	M30 x 1.5
Three-Wire D	C Sensors				
12 mm	Shielded	1.64 (41.5)	0.91 (23.09)	0.02 (0.5)	M12 x 1
	Unshielded	1.64 (41.5)	0.73 (18.59)	0.20 (5)	M12 x 1
18 mm	Shielded	1.59 (40.3)	0.86 (21.82)	0.02 (0.5)	M18 x 1
	Unshielded	1.59 (40.3)	0.60 (15.32)	0.28 (7)	M18 x 1
30 mm	Shielded	1.77 (45.0)	0.84 (21.26)	0.03 (0.8)	M30 x 1.5
	Unshielded	1.96 (49.7)	0.53 (13.46)	0.52 (13.26)	M30 x 1.5



Contents

Description	Page
Global Proximity Sensors	
Product Selection	
Global Proximity Sensors	V8-T3-37
Compatible Connector Cables	V8-T3-40
Accessories	V8-T3-40
Technical Data and Specifications	V8-T3-41
Wiring Diagrams	V8-T3-42
Dimensions	V8-T3-43

Global Proximity Sensors

Product Description

The Global Proximity Sensor family was created by Eaton's electrical sector with the high volume OEM in mind. It has been optimized to include only those functions necessary for basic, reliable sensing. Why pay for extra features when you don't need them? That's not to say these sensors lack the performance or features you expect. Our DC units are short circuit protected and will sense up to 2000 operations per second. Plus, all sensors include a bright LED indicator to show output status.

There's no need to design your machine around these sensors. The Global family includes models in a variety of diameters so they will fit right where you need them. Select models from 8 mm diameter all the way up to 30 mm, for just the size or sensing range that you require. Need something smaller? Our standard line includes inductive proximity sensors as small as 4 mm in diameter.

The Global Proximity is available in AC or DC, two-wire or three-wire, and NPN or PNP. You can even choose between cable wiring or quick-disconnect connectors. For power handling, our DC units feature a 100 mA load current rating and AC units are rated up to 200 mA.

Features

- The Global Proximity Line features solid performance and a basic feature set for reliable, cost-effective sensing
- Available in a variety of sizes to fit in all of your applications: 8 mm, 12 mm, 18 mm and 30 mm diameters
- DC sensors operate on 10–30 Vdc in two-wire and three-wire (NPN or PNP) configurations
- AC sensors operate on 20–250 Vac in two-wire configuration
- Switching frequency of 2 kHz for DC models
- Shielded and unshielded versions available
- Terminations include:
 - 2-meter cable
 - Micro-connector
 - Nano-connector
- DC units include short circuit protection

Standards and Certifications

- CE (DC models only)
- cCSAus





A DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

Global Proximity Sensors

Two-Wire Sensors

	Operating Voltage	Sensing Range	Shielding	Output Type	Connection Type	NO Output Catalog Number	NC Output Catalog Number
12 mm	12 mm Dia	meter					
	20–250 Vac	2 mm	Shielded	_	2-meter cable	E57-12GS02-A	E57-12GS02-A1
1					3-pin micro AC connector	E57-12GS02-AAB 🔕	E57-12GS02-A1AB 🔕
		4 mm	Unshielded	_	2-meter cable	E57-12GU04-A	E57-12GU04-A1
					3-pin micro AC connector	E57-12GU04-AAB 🕹	E57-12GU04-A1AB 🗈
	10-30 Vdc	2 mm	Shielded	NPN/PNP	2-meter cable	E57-12GS02-D	E57-12GS02-D1
					4-pin micro DC connector	E57-12GS02-DDB 😮	E57-12GS02-D1DB ::
		4 mm	Unshielded	NPN/PNP	2-meter cable	E57-12GU04-D	E57-12GU04-D1
					4-pin micro DC connector	E57-12GU04-DDB ::	E57-12GU04-D1DB 🤀
		8 mm	_	NPN/PNP	2-meter cable	E57-12GE08-D	E57-12GE08-D1
		(extended range)			4-pin micro DC connector	E57-12GE08-DDB 😮	E57-12GE08-D1DB 😆
18 mm	18 mm Dia	meter					
	20-250 Vac	5 mm	Shielded	_	2-meter cable	E57-18GS05-A	E57-18GS05-A1
					3-pin micro AC connector	E57-18GS05-AAB 🔕	E57-18GS05-A1AB 🐼
		8 mm	Unshielded	_	2-meter cable	E57-18GU08-A	E57-18GU08-A1
					3-pin micro AC connector	E57-18GU08-AAB ⊙	E57-18GU08-A1AB ๋
		16 mm			3-pin micro AC connector	E57-18GE16-AAB 🕟	E57-18GE16-A1AB 🐼
	10-30 Vdc	5 mm	Shielded	NPN/PNP	2-meter cable	E57-18GS05-D	E57-18GS05-D1
					4-pin micro DC connector	E57-18GS05-DDB 😟	E57-18GS05-D1DB 3
		8 mm	Unshielded	NPN/PNP	2-meter cable	E57-18GU08-D	E57-18GU08-D1
					4-pin micro DC connector	E57-18GU08-DDB ::	E57-18GU08-D1DB 😮
		16 mm	_	NPN/PNP	2-meter cable	E57-18GE16-D	E57-18GE16-D1
		(extended range)			4-pin micro DC connector	E57-18GE16-DDB 😮	E57-18GE16-D1DB 🙃
30 mm	30 mm Dia	meter					
11	20-250 Vac	10 mm	Shielded	_	2-meter cable	E57-30GS10-A	E57-30GS10-A1
					3-pin micro AC connector	E57-30GS10-AAB 🔕	E57-30GS10-A1AB ๋
		15 mm	Unshielded	_	2-meter cable	E57-30GU15-A	E57-30GU15-A1
					3-pin micro AC connector	E57-30GU15-AAB 🕹	E57-30GU15-A1AB ๋
	10-30 Vdc	10 mm	Shielded	NPN/PNP	2-meter cable	E57-30GS10-D	E57-30GS10-D1
					4-pin micro DC connector	E57-30GS10-DDB 🙃	E57-30GS10-D1DB 3
		15 mm	Unshielded	NPN/PNP	2-meter cable	E57-30GU15-D	E57-30GU15-D1
					4-pin micro DC connector	E57-30GU15-DDB ::	E57-30GU15-D1DB 🤀
		25 mm	_	NPN/PNP	2-meter cable	E57-30GE25-D	E57-30GE25-D1
		(extended range)			4-pin micro DC connector	E57-30GE25-DDB 😟	E57-30GE25-D1DB 😮

Note

 $\textcircled{\ensuremath{\boldsymbol{\mathfrak{a}}}}$ See listing of compatible connector cables on Page V8-T3-40.

Three-Wire Sensors

	Operating Voltage	Sensing Range	Shielding	Output Type	Connection Type	NO Output Catalog Number	NC Output Catalog Number
8 mm	8 mm Diam	neter					
	10-30 Vdc	1 mm	Shielded	NPN	2-meter cable	E57-08GS01-C	E57-08GS01-C1
					3-pin nano-connector	E57-08GS01-CNB 🕟	E57-08GS01-C1NB ③
23					4-pin micro DC connector	E57-08GS01-CDB ::	E57-08GS01-C1DB 😟
				PNP	2-meter cable	E57-08GS01-G	E57-08GS01-G1
					3-pin nano-connector	E57-08GS01-GNB ⊙	E57-08GS01-G1NB 🗈
					4-pin micro DC connector	E57-08GS01-GDB 3	E57-08GS01-G1DB 3
		3 mm	_	NPN	2-meter cable	E57-08GE03-C	E57-08GE03-C1
		(extended range)			3-pin nano-connector	E57-08GE03-CNB ⊙	E57-08GE03-C1NB ⊙
					4-pin micro DC connector	E57-08GE03-CDB ::	E57-08GE03-C1DB 3
				PNP	2-meter cable	E57-08GE03-G	E57-08GE03-G1
					3-pin nano-connector	E57-08GE03-GNB ⊙	E57-08GE03-G1NB ⓒ
					4-pin micro DC connector	E57-08GE03-GDB ::	E57-08GE03-G1DB 33
		2 mm	Unshielded	NPN	2-meter cable	E57-08GU02-C	E57-08GU02-C1
					3-pin nano-connector	E57-08GU02-CNB 🙃	E57-08GU02-C1NB ๋€
					4-pin micro DC connector	E57-08GU02-CDB 33	E57-08GU02-C1DB ::
				PNP	2-meter cable	E57-08GU02-G	E57-08GU02-G1
					3-pin nano-connector	E57-08GU02-GNB ⓒ	E57-08GU02-G1NB ๋€
					4-pin micro DC connector	E57-08GU02-GDB 🔢	E57-08GU02-G1DB 3
		6 mm	=	NPN	2-meter cable	E57-08GE06-C	E57-08GE06-C1
		(extended range)			4-pin micro DC connector	E57-08GE06-CDB ::	E57-08GE06-C1DB 3
				PNP	2-meter cable	E57-08GE06-G	E57-08GE06-G1
					4-pin micro DC connector	E57-08GE06-GDB 😮	E57-08GE06-G1DB 3
12 mm	12 mm Dia	meter					
	10-30 Vdc	2 mm	Shielded	NPN	2-meter cable	E57-12GS02-C	E57-12GS02-C1
THE STATE OF THE S					4-pin micro DC connector	E57-12GS02-CDB 😮	E57-12GS02-C1DB 3
				PNP	2-meter cable	E57-12GS02-G	E57-12GS02-G1
					4-pin micro DC connector	E57-12GS02-GDB 3	E57-12GS02-G1DB 3
		5 mm	_	NPN	2-meter cable	E57-12GE05-C	E57-12GE05-C1
		(extended range)			4-pin micro DC connector	E57-12GE05-CDB ::	E57-12GE05-C1DB 😟
				PNP	2-meter cable	E57-12GE05-G	E57-12GE05-G1
					4-pin micro DC connector	E57-12GE05-GDB ::	E57-12GE05-G1DB 3
		4 mm	Unshielded	NPN	2-meter cable	E57-12GU04-C	E57-12GU04-C1
					4-pin micro DC connector	E57-12GU04-CDB ::	E57-12GU04-C1DB 33
				PNP	2-meter cable	E57-12GU04-G	E57-12GU04-G1
					4-pin micro DC connector	E57-12GU04-GDB 🕃	E57-12GU04-G1DB (#)
		10 mm	=	NPN	2-meter cable	E57-12GE10-C	E57-12GE10-C1
		(extended range)			4-pin micro DC connector	E57-12GE10-CDB (8)	E57-12GE10-C1DB ::
				PNP	2-meter cable	E57-12GE10-G	E57-12GE10-G1
					4-pin micro DC connector	E57-12GE10-GDB ::	E57-12GE10-G1DB 33

Note

 $\ensuremath{\textcircled{\footnotemark}{\foot$

NC Output Catalog Number

Global Proximity Sensors

NO Output Catalog Number

Three-Wire Sensors, continued

18 mm	

Operating Voltage	Sensing Range	Shielding	Output Type
18 mm Dia	meter		
10-30 Vdc	5 mm	Shielded	NPN
			PNP

30 mm



10–30 Vdc	5 mm	Shielded	NPN	2-meter cable	E57-18GS05-C	E57-18GS05-C1
				4-pin micro DC connector	E57-18GS05-CDB 😟	E57-18GS05-C1DB ::
			PNP	2-meter cable	E57-18GS05-G	E57-18GS05-G1
				4-pin micro DC connector	E57-18GS05-GDB ::	E57-18GS05-G1DB ::
	8 mm	=	NPN	2-meter cable	E57-18GE08-C	E57-18GE08-C1
	(extended range)			4-pin micro DC connector	E57-18GE08-CDB ::	E57-18GE08-C1DB ::
			PNP	2-meter cable	E57-18GE08-G	E57-18GE08-G1
				4-pin micro DC connector	E57-18GE08-GDB :	E57-18GE08-G1DB :
	8 mm	Unshielded	NPN	2-meter cable	E57-18GU08-C	E57-18GU08-C1
				4-pin micro DC connector	E57-18GU08-CDB ::	E57-18GU08-C1DB 🙃
			PNP	2-meter cable	E57-18GU08-G	E57-18GU08-G1
				4-pin micro DC connector	E57-18GU08-GDB 😮	E57-18GU08-G1DB 😩
	18 mm	_	NPN	2-meter cable	E57-18GE18-C	E57-18GE18-C1
	(extended range)			4-pin micro DC connector	E57-18GE18-CDB ::	E57-18GE18-C1DB ::
			PNP	2-meter cable	E57-18GE18-G	E57-18GE18-G1
				4-pin micro DC connector	E57-18GE18-GDB ::	E57-18GE18-G1DB ::
30 mm Dia	meter					
10-30 Vdc	10 mm	Shielded	NPN	2-meter cable	E57-30GS10-C	E57-30GS10-C1
				4-pin micro DC connector	E57-30GS10-CDB ::	E57-30GS10-C1DB ::
			PNP	2-meter cable	E57-30GS10-G	E57-30GS10-G1
				5-meter Cable	E57-30GS10-G5	_
				4-pin micro DC connector	E57-30GS10-GDB ::	E57-30GS10-G1DB ::
	15 mm	=	NPN	2-meter cable	E57-30GE15-C	E57-30GE15-C1
	(extended range)			4-pin micro DC connector	E57-30GE15-CDB ::	E57-30GE15-C1DB ::
			PNP	2-meter cable	E57-30GE15-G	E57-30GE15-G1
				4-pin micro DC connector	E57-30GE15-GDB 😟	E57-30GE15-G1DB 😮
	15 mm	Unshielded	NPN	2-meter cable	E57-30GU15-C	E57-30GU15-C1
				4-pin micro DC connector	E57-30GU15-CDB 😩	E57-30GU15-C1DB 🕃
			PNP	2-meter cable	E57-30GU15-G	E57-30GU15-G1
				4-pin micro DC connector	E57-30GU15-GDB ::	E57-30GU15-G1DB 😮
	29 mm	_	NPN	2-meter cable	E57-30GE29-C	E57-30GE29-C1
	(extended range)			4-pin micro DC connector	E57-30GE29-CDB 😮	E57-30GE29-C1DB ::
			PNP	2-meter cable	E57-30GE29-G	E57-30GE29-G1

Connection Type

Note

3 See listing of compatible connector cables on Page V8-T3-40.

Compatible Connector Cables

Standard Cables ①



Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-Styl	e, Straight Fem	ale				
AC	3-pin, 3-wire	22 AWG	6.0 ft (2m)	2.Red/Black 3-Red/White	CSAS3F3CY2202	CSAS3F3RY2202
DC	4-pin, 3-wire	22 AWG	6.0 ft (2m)	1-Brown 2-No Wire 3-Blue 4-Black	CSDS4A3CY2202	CSDS4A3RY2202



Nano-Style, Straight Female								
DC	3-pin	24 AWG	6.0 ft (2m)	3 4 1-Brown 3-Blue 4-Black	CSNS3A3CY2402	CSNS3A3RY2402		

Accessories

Global Proximity Sensors

Description	Reference
Mounting brackets	See Tab 8 , section 8.2
Replacement mounting nuts and other accessories	See Tab 8, section 8.3
Connector cables	See Tab 10, section 10.1

Note

 $^{\ ^{\}textcircled{1}}$ For a full selection of connector cables, see Tab 10, section 10.1.

Global Proximity Sensors

Technical Data and Specifications

Global Proximity Sensors

Description	Two-Wire AC Sensors	Two-Wire DC Sensors	Three-Wire DC Sensors		
Operating voltage	20-250 Vac	10–30 Vdc	10–30 Vdc		
OFF-state leakage	<1.8 mA	<0.8 mA	<0.01 mA		
Maximum load current	200 mA	100 mA	100 mA		
Minimum load current	5 mA	3 mA	_		
Surge current	5A (20 ms)	_	_		
Voltage drop	<8 Vac at 400 mA	<6V	<1.5V		
Switching frequency					
8 mm diameter	_	_	2 kHz (shielded and unshielded)		
12 mm diameter	25 Hz	1 kHz (shielded); 1 kHz (unshielded)	2 kHz (shielded); 1 kHz (unshielded)		
18 mm diameter	25 Hz	1 kHz (shielded); 500 Hz (unshielded)	1 kHz (shielded); 500 Hz (unshielded)		
30 mm diameter	25 Hz	500 Hz (shielded); 200 Hz (unshielded)	300 Hz (shielded); 150 Hz (unshielded)		
Short circuit protection	No	Yes	Yes		
Overload trip point	_	>120 mA	220 mA		
Time delay before availability	_	_	<10 ms		
Transient protection	_	2 kV, 1 ms, 1 kohm	1kV, 0.1 ms, 1 kohm		
Repeat accuracy	Shielded: <1.0%/Unshielded: <3.0% (Sr)	<2.0% (Sr)	<1.0% (Sr)		
Switching hysteresis	<15%	<15%	<15%		
Operating temperature	-13° to 158°F (-25° to 70°C) (32° to 140°F [0° to 60°C] for all extended range models)	-13° to 158°F (-25° to 70°C) (32° to 140°F [0° to 60°C] for all extended range models)	-13° to 158°F (-25° to 70°C) (32° to 140°F [0° to 60°C] for all extended range models)		
Temperature drift	<10% (Sr)	<10% (Sr)	<10% (Sr)		
Protection	IP67, IP69K	IP67, IP69K	IP67, IP69K		
Housing material	Nickel plated brass (stainless steel for 8 mm diameter, nano-connector models)	Nickel plated brass (stainless steel for 8 mm diameter, nano-connector models)	Nickel plated brass (stainless steel for 8 mm diameter, nano-connector models)		
Cable	PVC jacket, 2-meter length	PVC jacket, 2-meter length	PVC jacket, 2-meter length		

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

Global Proximity Sensors


Operating Voltage	Output	Cable Models	Connector Models (Face View Male Shown) Micro	Nano
Two-Wire S	Sensors			
20-250 Vac	NO	BN L1 BU Load L2 Yellow/Green * Intenally connected to housing (use of this wire is optional)	* Internally connected to housin (use of this wire is optional)	_
10–30 Vdc	NO (NPN)	BN Load +V	(-) Load (+V)	_
	NO (PNP)	BN +V BU Load (-)	(-)— <u>Load</u> (+V)	_
Three-Wire				
10-30 Vdc	NO (NPN)	BN +V BK Load BU (-)	(-) (2 (1) +V Load	(-) (-) +V
	NO (PNP)	BN +V BK Load (_)	(-) (2 (1) +V	(-) (-) +V
	NC (NPN)	BN +V BK Load (-)	(<u>-</u>) (2 (1) +V	(-) (-) +V
	NC (PNP)	BN +V BK Load BU (_)	(-) Load 2 1 +V	(-) (4) (1) +V

Dimensions

Approximate Dimensions in mm


Cable Models

Two-Wire Sensors



Catalog Number	Operating Voltage	A	В	С	D	E
E57-12GS02-A	20–250 Vac	M12x1	65	15	50	_
E57-12GU04-A	-	M12x1	60	15	42	8
E57-18GS05-A		M18x1	80	20	60	_
E57-18GU08-A	-	M18x1	80	20	48	12
E57-30GS10-A	-	M30x1.5	80	20	60	_
E57-30GU15-A		M30x1.5	80	20	45	15
E57-12GS02-D	10-30 Vdc	M12x1	50	_	50	_
E57-12GU04-D		M12x1	50	_	42	8
E57-12GE08-D		M12x1	50	_	42	8
E57-12GE08-D1		M12x1	50	_	42	8
E57-18GS05-D		M18x1	55	5	50	_
E57-18GU08-D		M18x1	55	5	38	12
E57-18GE16-D		M18x1	55	5	38	12
E57-18GE16-D1		M18x1	55	5	38	12
E57-30GS10-D		M30x1.5	55	5	50	_
E57-30GU15-D		M30x1.5	55	5	35	15
E57-30GE25-D		M30x1.5	55	5	35	15
E57-30GE25-D1		M30x1.5	55	5	35	15

Three-Wire Sensors




Catalog Number	Operating Voltage	A	В	С	D	E
E57-08GE03-C	10-30 Vdc	M8x1	46	6	40	_
E57-08GE03-G	_	M8x1	46	6	40	_
E57-08GE06-C	_	M8x1	45	_	41	4
E57-08GE06-G	_	M8x1	45	_	41	4
E57-08GS01-C	_	M8x1	45	_	45	_
E57-08GS01-G	_	M8x1	45	_	45	_
E57-08GU02-C	_	M8x1	45	_	41	4
E57-08GU02-G	_	M8x1	45	_	41	4
E57-12GE05-C	=	M12x1	51	2	49	_
E57-12GE05-G	_	M12x1	51	2	49	_
E57-12GE10-C	=	M12x1	50.5	1.7	41	7.8
E57-12GE10-G	=	M12x1	50.5	1.7	41	7.8
E57-12GS02-C	_	M12x1	50	_	50	_
E57-12GS02-G	=	M12x1	50	_	50	_
E57-12GU04-C	=	M12x1	50	_	42	8
E57-12GU04-G	=	M12x1	50	_	42	8
E57-18GE08-C	-	M18x1	67.5	2.5	65	_
E57-18GE08-G	_	M18x1	65.5	2.5	65	_
E57-18GE18-C	-	M18x1	66	2.5	52	11.5
E57-18GE18-G	_	M18x1	66	2.5	52	11.5
E57-18GS05-C	_	M18x1	55	5	50	_
E57-18GS05-G	-	M18x1	55	5	50	_
E57-18GU08-C	_	M18x1	55	5	38	12
E57-18GU08-G	_	M18x1	55	5	38	12
E57-30GE15-C	_	M30x1.5	69	5	64	_
E57-30GE15-G	_	M30x1.5	69	5	64	_
E57-30GE29-C	_	M30x1.5	83	5	64	15
E57-30GE29-G	_	M30x1.5	83	5	64	15
E57-30GS10-C		M30x1.5	55	5	50	_
E57-30GS10-G	-	M30x1.5	55	5	50	_
E57-30GU15-C	_	M30x1.5	55	5	35	15
E57-30GU15-G	_	M30x1.5	55	5	35	15

Approximate Dimensions in mm


Connector Models

Two-Wire Sensors



Catalog Number ^①	Operating Voltage	A	В	С	D	E
E57-12GS02-AAB	20-250 Vac	M12x1	68	16	42	_
E57-12GU04-AAB	_	M12x1	68	16	34	8
E57-18GS05-AAB	_	M18x1	91	20	60	_
E57-18GU08-AAB	-	M18x1	91	20	48	12
E57-18GE16-AAB	_	M18x1	79.2	15	37	11.5
E57-30GS10-AAB	_	M30x1.5	80	20	60	_
E57-30GU15-AAB	_	M30x1.5	91	20	45	15
E57-12GS02-DDB	10-30 Vdc	M12x1	69	16	42	_
E57-12GU04-DDB	_	M12x1	68	16	34	8
E57-12GE08-DDB	_	M12x1	68	10	50	8
E57-12GE08-D1DB	_	M12x1	68	10	50	8
E57-18GS05-DDB	_	M18x1	76	15	61	_
E57-18GU08-DDB	_	M18x1	80	15	49	12
E57-18GE16-DDB	_	M18x1	79	15	52	12
E57-30GS10-DDB		M30x1.5	75	15	60	_
E57-30GU15-DDB	_	M30x1.5	79	15	45	15
E57-30GE25-DDB	_	M30x1.5	78	15	48	15

Three-Wire Sensors



Catalog Number ^①	Operating Voltage	A	В	С	D	E
E57-08GE03-CDB	10–30 Vdc	M8x1	71	26	36	_
E57-08GE03-CNB	_	M8x1	61	19	42	_
E57-08GE03-GDB	_	M8x1	71	26	36	
E57-08GE03-GNB	_	M8x1	61	19	42	_
E57-08GE06-CDB	-	M8x1	70	31	35	4
E57-08GE06-GDB	_	M8x1	70	31	35	4
E57-08GS01-CDB	-	M8x1	70	21	49	_
E57-08GS01-CNB	_	M8x1	60	20	40	_
E57-08GS01-GDB	_	M8x1	70	21	49	
E57-08GS01-GNB	_	M8x1	60	20	40	_
E57-08GU02-CDB	_	M8x1	70	21	45	4
E57-08GU02-CNB	_	M8x1	60	20	36	4
E57-08GU02-GDB	_	M8x1	70	21	45	4
E57-08GU02-GNB	_	M8x1	60	20	36	4
E57-12GE05-CDB	_	M12x1	69	24	45	
E57-12GE05-GDB	_	M12x1	69	24	45	_
E57-12GE10-CDB	_	M12x1	68.5	10.3	36	7.8
E57-12GE10-GDB	_	M12x1	68.5	10.3	36	7.8
E57-12GS02-CDB	_	M12x1	68	16	52	_
E57-12GS02-GDB		M12x1	68	16	52	_
E57-12GU04-CDB		M12x1	68	20	31	8
E57-12GU04-GDB		M12x1	68	20	31	8
E57-18GE08-CDB		M18x1	79	30	49	_
E57-18GE08-GDB	_	M18x1	79	30	49	
E57-18GE18-CDB		M18x1	79.2	15	37	11.5
E57-18GE18-GDB	_	M18x1	79.2	15	37	11.5
E57-18GS05-CDB		M18x1	76	15	61	_
E57-18GS05-GDB	_	M18x1	76	15	61	
E57-18GU08-CDB	_	M18x1	76	15	49	12
E57-18GU08-GDB	_	M18x1	80	15	49	12
E57-30GE29-CDB	_	M30x1.5	79	30	34	15
E57-30GE29-GDB	_	M30x1.5	79	30	34	15
E57-30GS10-CDB	_	M30x1.5	79	15	60	
E57-30GS10-GDB	_	M30x1.5	75	15	60	
E57-30GU15-CDB	_	M30x1.5	75	15	45	15
E57-30GU15-GDB		M30x1.5	75	15	45	15

Note

 $^{^{\}scriptsize \textcircled{1}}$ Normally closed models are dimensionally identical to equivalent normally open models.

AccuProx Analog Sensors



Contents

Description	Page
AccuProx Analog Sensors	
Application Guide	V8-T3-46
Product Selection	
AccuProx Analog Sensors	V8-T3-47
Compatible Connector Cables	V8-T3-47
Technical Data and Specifications	V8-T3-48
Wiring Diagrams	V8-T3-50
Dimensions	V8-T3-50

AccuProx Analog Sensors

Product Description

The AccuProx from Eaton's electrical sector is a high performance analog inductive proximity sensor. The AccuProx family of analog sensors provide unmatched sensing range, linearity and resolution in an affordable and compact tubular package.

Unlike standard inductive sensors, which send an open or close signal upon target presence or absence, AccuProx analog sensors provide an electrical signal that varies in proportion to the position of the metal target within its sensing range. This makes AccuProx ideal for applications requiring precise position sensing and measurement.

The sensing performance of AccuProx sets it apart from traditional analog inductive designs. Utilizing components from the cutting-edge iProx family, AccuProx provides sensing ranges of three to four times that of typical tubular analog inductive sensors—all without compromising accuracy.

Unlike many competitive products, which are often hampered by an "S-shaped" output curve, AccuProx outputs are linear.

AccuProx has the range and precision to solve your most difficult measurement applications.

Application Description

Typical Applications

- Part positioning
- Distance, size and thickness measurement
- General inspection and error proofing, such as material imperfection or blemish detection
- Eccentricity or absolute angle detection
- Identification of different metals

See the Application Guide on **Page V8-T3-46** for more detail.

Features

- Extended linear sensing range of up to 25 millimeters—three times longer than standard tubular analog inductive sensors
- Outputs available in current (4–20 or 0–20 mA) and voltage (0–10V)
- High output resolution and repeatability for applications requiring precision sensing performance
- Robust stainless steel barrel, shock-resistant front cap, polycarbonate end bell and impactabsorbing potting compound
- Ideal for extreme temperature or high pressure washdown environments
- High noise immunity of 20V/m prevents many problems associated with electrical noise

Standards and Certifications

- cUL Listed
- CE







DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578.

For Application Assistance in the U.S. and Canada call 1-800-426-9184.

AccuProx Analog Sensors

Application Guide

Presenting AccuProx— Unmatched Analog Range in a Proven Package

Historically, analog sensors have been limited by very short sensing ranges—as little as one or two millimeters. By utilizing technology first perfected in the iProx family of digital inductive sensors, AccuProx can sense objects as far as 25 millimeters. This extended range can be achieved without making compromises often found in competitive products, such as reduced output accuracy.

AccuProx utilizes many of the proven materials found in other tubular sensor families. The threaded barrel and included mounting nuts are made of stainless steel, which exhibits superior corrosion and abrasion resistance versus nickelplated brass. AccuProx also features a proprietary internal potting compound that absorbs impacts and vibration while sealing out moisture. The materials used in the construction of AccuProx are time-tested and proven to work.

High Output Accuracy


Analog inductive sensors are often used in applications that require a higher level of precision than a standard digital sensor. For example, applications such as part inspection require a sensor that can detect very small variances. AccuProx has been designed with these applications in mind.

Output accuracy is determined by the repeat accuracy, linearity, resolution and response time of the sensor.

Repeat accuracy refers to the variations in sensing distance between successive sensor operations due to component tolerances, where all operating conditions are kept the same. The repeat accuracy of an 18 millimeter, unshielded AccuProx sensor is less than 20 micrometers. See the chart below for a repeat accuracy comparison of AccuProx versus the competition.




Linearity refers to the shape of the output curve. Many competitive analog sensors exhibit a wavy or "S-shaped" output curve. This means that a change in target distance may not always translate into an equivalent change in output, particularly at the innermost and outermost ranges of a non-linear analog sensor. AccuProx features a linear output. See the diagram below for an example of AccuProx versus a non-linear competitive offering.



Resolution refers to the number of "steps" in the sensor output. A higher resolution is ideal because it will allow the sensor to detect smaller changes in target position.

An 18 millimeter, unshielded AccuProx features more than 350 output steps, ensuring consistent performance.


Typical Analog Applications Material Imperfection or Blemish Detection



Eccentricity or Absolute Angle Detection



Saw Blade Deflection



AccuProx Analog Sensors

Product Selection

AccuProx Analog Sensors

Three-/Four-Wire Sensors

	Operating Voltage	Sensing Range ^①	Shielding	Connection Type	Current (0–20 mA) and Voltage (0–10V) Output ② Catalog Number	Current (4— 20 mA) Output Only ② Catalog Number
	12 mm Dia	meter				
-05	15-30 Vdc	0.5–4 mm	Shielded	4-pin micro DC connector	E59-A12A104D01-CV 3	E59-A12A104D01-C1 🕃
3				4-pin micro DC pigtail	E59-A12A104D01P-CV 🕃	E59-A12A104D01P-C1 ::
				2-meter cable	E59-A12A104C02-CV	E59-A12A104C02-C1
12		1–8 mm	Unshielded	4-pin micro DC connector	E59-A12C108D01-CV ::	E59-A12C108D01-C1 😮
				4-pin micro DC pigtail	E59-A12C108D01P-CV 🕃	E59-A12C108D01P-C1 ::
				2-meter cable	E59-A12C108C02-CV	E59-A12C108C02-C1
	18 mm Dia	meter				
-	15–30 Vdc	1–7 mm	Shielded	4-pin micro DC connector	E59-A18A107D01-CV 🕄	E59-A18A107D01-C1 🙃
				4-pin micro DC pigtail	E59-A18A107D01P-CV 🕃	E59-A18A107D01P-C1 🙃
				2-meter cable	E59-A18A107C02-CV	E59-A18A107C02-C1
7		1–15 mm	Unshielded	4-pin micro DC connector	E59-A18C115D01-CV 3	E59-A18C115D01-C1 ::
No.				4-pin micro DC pigtail	E59-A18C115D01P-CV ::	E59-A18C115D01P-C1 ::
				2-meter cable	E59-A18C115C02-CV	E59-A18C115C02-C1
	30 mm Dia	meter				
ALTER .	15-30 Vdc	1–12 mm	Shielded	4-pin micro DC connector	E59-A30A112D01-CV 😀	E59-A30A112D01-C1 ::
70				4-pin micro DC pigtail	E59-A30A112D01P-CV ::	E59-A30A112D01P-C1 33
Stant Con				2-meter cable	E59-A30A112C02-CV	E59-A30A112C02-C1
1)		1–25 mm	Unshielded	4-pin micro DC connector	E59-A30C125D01-CV (3)	E59-A30C125D01-C1 (3)
				4-pin micro DC pigtail	E59-A30C125D01P-CV 3	E59-A30C125D01P-C1 ::
				2-meter cable	E59-A30C125C02-CV	E59-A30C125C02-C1

Compatible Connector Cables

Standard Cables ³

	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-Style	Micro-Sty	le, Straight Fen	nale				
Straight Female	DC	4-pin, 3-wire	22 AWG	6.0 ft (2m)	1-Brown 2-No Wire 3-Blue 4-Black	CSDS4A3CY2202	CSDS4A3RY2202
	DC	4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White 3-Blue 4-Black	CSDS4A4CY2202	CSDS4A4RY2202

- oxdots See listing of compatible connector cables above.
- $^{\odot}$ Published range data is based on a 1 mm thick square target made of Type FE 360 steel per ISO Standard 630.
- ② Models available in custom output configurations (for example, 1–5V, 0–5V). Contact factory for details.
- ③ For a full selection of connector cables, see Tab 10, section 10.1.

Technical Data and Specifications

AccuProx Analog Sensors


Description	12 mm Models Shielded	Unshielded	18 mm Models Shielded	Unshielded	30 mm Models Shielded	Unshielded
Performance						
Analog operating range ①	0.5–4 mm	1–8 mm	1–7 mm	1–15 mm	1–12 mm	1–25 mm
Temperature range	-40° to 158°F (-40° to 70°C)					
Temperature drift	<± 10%	<± 10%	<± 10%	<± 10%	<± 10%	<± 10%
Conformity	<± 10%	<± 10%	<± 10%	<± 10%	<± 10%	<± 10%
Repeat accuracy	<25 µm ②	<20 µm ②	<40 μm ^②	<20 µm ②	<50 μm ②	<30 μm ^②
Minimum repeat accuracy	<3.0% at max. range	<1.1% at max. range	<2.2% at max. range	<1.2% at max. range	<1.2% at max. range	<0.8% at max. range
Recovery time	<1.0 ms	<1.1 ms	<1.5 ms	<2.0 ms	<2.0 ms	<3.0 ms
Response time	200 Hz	100 Hz	200 Hz	100 Hz	140 Hz	100 Hz
Linearity tolerance	<± 1.0% of full scale					
Resolution	23 μm max.	16 μm max.	40 μm max.	21 µm max.	50 μm max.	30 μm max.
Electrical						
Style	AccuProx Analog, three-/four-wire DC					
Operating voltage	15–30 Vdc					
Current output signal	0–20 mA or 4–20 mA by model	0-20 mA or 4-20 mA by model	0-20 mA or 4-20 mA by model	0-20 mA or 4-20 mA by model	0–20 mA or 4–20 mA by model	0-20 mA or 4-20 mA by model
Current output load resistance	400-500 ohms					
Current output ripple content	± 40 μA max.					
Current output minimum change	30 μΑ	20 μΑ	50 μΑ	28 μΑ	66 μΑ	40 μΑ
Voltage output signal ^③	0-10V	0-10V	0-10V	0-10V	0-10V	0-10V
Voltage output load resistance	4.7–5.0 kohm (2.5 mA max.)					
Voltage output ripple content	± 10 mV max.					
Voltage output minimum change	15 mV	10 mV	25 mV	14 mV	33 mV	20 mV
Burden current	<20 mA					
Output LED	Dual-color, 360° viewable					
Short circuit protection	Incorporated 4	Incorporated ④				
Wire breakage protection	Incorporated	Incorporated	Incorporated	Incorporated	Incorporated	Incorporated
Reverse polarity protection	Incorporated	Incorporated	Incorporated	Incorporated	Incorporated	Incorporated
Physical						
Size			See Dimensions	on Page V8-T3-50 .		
Enclosure protection	NEMA 4, 4X, 6, 6P, 13					
Shock	30g half-sine at 11 ms					
Vibration	10–55 Hz, 1 mm amplitude	10-55 Hz, 1 mm amplitude	10–55 Hz, 1 mm amplitude	10-55 Hz, 1 mm amplitude	10–55 Hz, 1 mm amplitude	10–55 Hz, 1 mm amplitude
Housing material	Stainless steel, polycarbonate end bell, polyphenylene sulfide front cap					
Termination	Micro-connector, potted cable, 2m; Pigtail, micro-connector, 2m					

- $^{\odot}$ Published range data is based on a 1 mm thick square target made of Type FE 360 steel per ISO Standard 630.
- $^{\circ}$ The sensor achieves its maximum repeat accuracy after warming up for a period of at least one hour.
- ③ Voltage outputs available on models ending in -CV.
- $\textcircled{$\bullet$ Continuous short-circuits can exceed power dissipation ratings and cause eventual destruction. }$


AccuProx Analog Performance Graphs

Linear Output


12 mm



18 mm




30 mm




Measurement Resolution ①


12 mm



18 mm




30 mm




Output Resolution ^②


12 mm



18 mm



30 mm



- ① Measurement resolution is the sensor's ability to detect a change in target position. The measurement resolution is the finest at the highest point in the curve.
- ② Output resolution is the change in output signal relative to target position. The minimum change in output resolution is defined by the lowest point in the curve.

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.


AccuProx Analog Sensors

Style	Output(s)	Micro-Connector Models	Cable and Pigtail Models
12 mm diameter models ending in -C1 ①	Current: 4–20 mA	(-) (2 (1) +V (3) (4)	BN/1 +V BK/4 Current Output Load
18 and 30 mm diameter models ending in -C1 ①		(-) (2 (1) +V (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	BU/3(-)
Models ending in -CV	Current: 0–20 mA Voltage: 0–10V	Current Output (-) 2 1 +V (2) 1 +V (2) 1 Output	BN/1 +V BK/4 Voltage Output WT/2 Current Output BU/3 (-)

Dimensions


Approximate Dimensions in Inches (mm)

Micro-Connector Models



Size	Shielding	A	В	C	D
12 mm	Shielded	3.05 (77.5)	1.98 (50.3)	0.02 (0.50)	0.67 (17)
	Unshielded	3.05 (77.5)	1.64 (41.6)	0.36 (9)	0.67 (17)
18 mm	Shielded	2.73 (69.3)	2.00 (50.9)	0.02 (0.50)	0.94 (24)
	Unshielded	2.73 (69.3)	1.47 (37.4)	0.55 (14)	0.94 (24)
30 mm	Shielded	2.92 (74.1)	2.13 (54.1)	0.03 (0.75)	1.41 (36)
	Unshielded	2.92 (74.1)	1.41 (35.8)	0.75 (19)	1.41 (36)

Cable and Pigtail Models



Size	Shielding	A	В	C	D
12 mm	Shielded	2.46 (62.4)	1.98 (50.3)	0.02 (0.5)	0.67 (17)
	Unshielded	2.46 (62.4)	1.64 (41.6)	0.36 (9)	0.67 (17)
18 mm	Shielded	2.54 (64.5)	2.00 (50.9)	0.02 (0.5)	0.94 (24)
	Unshielded	2.54 (64.5)	1.47 (37.4)	0.55 (14)	0.94 (24)
30 mm	Shielded	2.74 (69.6)	2.13 (54.1)	0.03 (0.75)	1.41 (36)
	Unshielded	2.74 (69.6)	1.41 (35.8)	0.75 (19)	1.41 (36)

Note

For models ending in -C1 (current output only models), pins 2 and 4 are intentionally connected.
 Do not connect outputs of -C1 models to separate loads—this sensor should only be connected to a single-output load.

V8-T3-53

Ferrous Only Tubular Sensors



Outcits	
Description	Page
Ferrous Only Tubular Sensors	
Product Selection	
Ferrous Only Tubular Sensors	V8-T3-52
Compatible Connector Cables	V8-T3-52
Accessories	V8-T3-52
Technical Data and Specifications	V8-T3-53
Wiring Diagrams	V8-T3-53

Dimensions

Ferrous Only Tubular Sensors

Product Description

These unique Inductive Proximity Sensors have been specially made by Eaton's electrical sector to detect only a specific type of metal. Ferrous Only models will detect only ferrous metals such as steel, iron, nickel or cobalt.

A typical application for Ferrous Only sensors would be in workcell applications where cutting tools, tool pallets and fixtures must be detected for proper workpiece manipulation. The sensors detect ferrous objects while ignoring aluminum.

These sensors are available in a standard 18 mm diameter, and are epoxy filled for shock/ vibration resistance and heat tolerance.

Features

- Ferrous Only sensors detect ferrous metals, such as steel or iron, while ignoring non-ferrous metals
- Selection of two-wire and three-wire, AC/DC and DC-only sensor models
- Wide operating temperature range: -13° to 158°F (-25° to 70°C)

Contante

DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

Ferrous Only Tubular Sensors

Two-Wire Sensors

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number
	18 mm Diam	eter			
_	20-250 Vac/dc	5.0 mm	Shielded	3-pin micro AC connector	E57FAL18A2SA 🕹
	50/60 Hz			3-pin mini-connector	E57FAL18A2B1 🙃

18 mm

Three-Wire Sensors

Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number
18 mm Diar	neter			
10-30 Vdc	5.0 mm	Shielded (PNP)	4-pin micro DC connector	E57FAL18T111SD 🏗

18 mm

Compatible Connector Cables

Standard Cables ①

Standard C	ables 🔍						
Current Rating at 600V	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-Style,	Straight Fe	emale					
	AC	3-pin, 3-wire	22 AWG	6.0 ft (2m)	2 3 1-Green 2-Red/Black 3-Red/White	CSAS3F3CY2202	CSAS3F3RY2202
_	DC	4-pin, 3-wire	22 AWG	6.0 ft (2m)	1-Brown 2-No Wire 3-Blue 4-Black	CSDS4A3CY2202	CSDS4A3RY2202
Mini-Style, S	traight Fer	nale				Catalog Number	
13 A	_	3-pin	16 AWG	6.0 ft (2m)	1-Green 2-Black 3 2 3-White	CSMS3F3CY1602	



Accessories

Mini-Style Straight Female

Ferrous Only Tubular Sensors

Description	Reference
Mounting brackets	See Tab 8, section 8.2
Replacement mounting nuts and other accessories	See Tab 8, section 8.3
Connector cables	See Tab 10, section 10.1

Notes

① For a full selection of connector cables, see **Tab 10**, **section 10.1**.

Technical Data and Specifications

Ferrous Only Tubular Sensors

Description	Two-Wire AC/DC Sensors	Three-Wire DC Sensors		
Operating voltage	20–250 Vac/dc	10–30 Vdc		
Maximum load current	100 mA	100 mA		
Switching frequency	15 Hz	1000 Hz		
Leakage current	2.5 mA maximum	<0.01 mA		
Voltage drop	10V maximum	1.5V maximum		
Holding current	5 mA minimum	_		
Burden current	_	17 mA		
Protection	Transient, power on false pulse suppression	Short circuit protection		
Switching hysteresis	<15% rated sensing distance	<15% rated sensing distance		
Repeat accuracy	<1% sensing distance	<1% sensing distance		
Time delay before availability	<10 ms	<10 ms		
Output indicator LED	Lights when output is ON	Lights when output is ON		
Operating temperature	−13° to 131°F (−25° to 55°C)	-13° to 131°F (-25° to 55°C)		
Enclosure ratings	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)		
Shock 30g sine wave, 11 ms per IEC68-2-76		30g sine wave, 11 ms per IEC68-2-76		
Vibration 10 to 55 Hz, 1 mm amplitude in all three planes		10 to 55 Hz, 1 mm amplitude in all three planes		
Housing material	Stainless steel	Stainless steel		

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

Ferrous Only Tubular Sensors


Connector Models (Face View Male Shown)

Operating Voltage	Output	Micro	Mini
Two-Wire Sensors			
20–250 Vac/dc 50/60 Hz	NO	L2 Load 3 2 L1	L1 (2) (3) Load L2
Three-Wire Sensors	5		
10–30 Vdc	NO (PNP)	_	(-) Load 1 4 +V

Dimensions

Approximate Dimensions in Inches (mm)

Ferrous Only Tubular Sensors



Connector Models

Catalog Number	A	В	C	D		
Two-Wire Models						
E57FAL18A2SA	M18 x 1	3.11 (79)	1.38 (35)	1.73 (44)		
E57FAL18A2B1	M18 x 1	3.90 (99)	1.34 (34)	2.56 (65)		
Three-Wire Models						
E57FAL18T111SD	M18 x 1	3.11 (79)	1.14 (29)	1.97 (50)		



Contents

Description	Page
Metal Face Sensors	
Product Selection	
Metal Face Sensors	V8-T3-55
Compatible Connector Cables	V8-T3-52
Accessories	V8-T3-56
Technical Data and Specifications	V8-T3-56
Wiring Diagrams	V8-T3-57
Dimensions	V8-T3-57

Metal Face Sensors

Product Description

Metal Face Inductive Proximity Sensors by Eaton's electrical sector incorporate tough stainless steel sensing faces in place of the plastic faces found in standard sensors. This provides a higher level of protection for more reliable operation and longer life in harsh environments.

The sensors stand up to abrasion and impact caused by flying metal chips, grit, and misaligned or vibrating targets. In addition, the stainless steel body resists corrosion and chemical attack.

Common sensor diameters, voltage styles and wiring connections make it easy to retrofit your existing, damaged sensors. Solve the problem of damaged sensors permanently with Eaton's Metal Face Sensors.

Features

- Two-wire AC/DC models and three-wire DC models are compatible with your existing wiring
- Common 12 mm, 18 mm and 30 mm housing diameters allow easy changeout of existing damaged sensors
- The 20 mil stainless steel sensing face is thicker than competing units for a higher level of protection
- The stainless steel body is damage and corrosion resistant
- Wide operating temperature range: -13° to 158°F (-25° to 70°C)

A DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

Product Selection

Metal Face Sensors

Two-Wire Sensors

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number
12 mm	12 mm Diame	eter			
	20–250 Vac/dc 50/60 Hz	2 mm	Shielded	3-pin micro AC connector	E57FAL12A2SA-M ๋€
30 mm	30 mm Diame	eter			
	20–250 Vac/dc 50/60 Hz	10 mm	Shielded	3-pin micro AC connector	E57FAL30A2SA-M ③

Three-Wire Sensors

	Tillee-Wile Gensors						
	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number		
12 mm	12 mm Diar	neter					
	10–30 Vdc	2 mm	Shielded (PNP)	4-pin micro DC connector	E57FAL12T111SD-M ⊕		
18 mm	18 mm Dian	neter					
	10–30 Vdc	5 mm	Shielded (PNP)	4-pin micro DC connector	E57FAL18T111SD-M ⊕		

Compatible Connector Cables

Standard Cables ^①

	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Micro-Style	Micro-Styl	e, Straight Fema	ale				
Straight Female	AC	3-pin, 3-wire	22 AWG	6.0 ft (2m)	② ③ 1-Green 2-Red/Black 3-Red/White	CSAS3F3CY2202	CSAS3F3RY2202
	DC	4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White 3-Blue 4-Black	CSDS4A4CY2202	CSDS4A4RY2202

- $\ensuremath{\textcircled{\ensuremath{\mathfrak{a}}}}$ See listing of compatible connector cables above.
- $^{\scriptsize \textcircled{1}}$ For a full selection of connector cables, see Tab 10, section 10.1.

Accessories

Metal Face Sensors

Description	Reference	
Mounting brackets	See Tab 8 , section 8.2	
Replacement mounting nuts and other accessories	See Tab 8, section 8.3	
Connector cables	See Tab 10, section 10.1	

Technical Data and Specifications

Metal Face Sensors

–250 Vac/dc 0 mA Hz	10–30 Vdc 100 mA 2000 Hz	
	2000 Hz	
Hz		
Hz ·		
·	4000 11	
	1000 Hz	
	300 Hz	
mA maximum	600 μA maximum	
V maximum	1.5V maximum	
nA minimum	_	
	17 mA	
nsient, power on false pulse suppression	Short circuit protection	
5% rated sensing distance	<15% rated sensing distance	
% sensing distance	<1% sensing distance	
00 ms	<200 ms	
hts when output is ON	Lights when output is ON	
3° to 131°F (–25° to 55°C)	-13° to 131°F (-25° to 55°C)	
MA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	
g sine wave, 11 ms per IEC68-2-76	30g sine wave, 11 ms per IEC68-2-76	
to 55 Hz, 1 mm amplitude in all three planes	10 to 55 Hz, 1 mm amplitude in all three planes	
3 stainless steel	303 stainless steel	
mils	20 mils	
0 1 3	/ maximum A minimum A sensing distance A sensing distance B minimum B mi	

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

Metal Face Sensors


Operating Voltage	Output	Micro-Connector Models (Face View Male Shown)
Two-Wire Senso	rs	
20–250 Vac/dc 50/60 Hz	NO	L2 Load (3) (2) L1
Three-Wire Sens	sors	
10-30 Vdc	NO (NPN)	(-) (2 (1) +V Load
	NO (PNP)	(-) (2) (1) +V

Dimensions


Approximate Dimensions in Inches (mm)

Metal Face Sensors

Connector Models



Catalog Number	Α	В	C	D	
Two-Wire Models					
E57FAL12A2SA-M	M x 12	2.67 (68)	1.10 (28)	1.58 (40)	
E57FAL30A2SA-M	M x 30	3.70 (94)	1.34 (34)	2.36 (60)	
Three-Wire Models					
E57FAL12T111SD-M	M x 12	2.67 (68)	1.02 (26)	1.65 (42)	
E57FAL18T110SD-M	M x 18	3.11 (79)	1.14 (29)	1.97 (50)	
E57FAL18T111SD-M	M x 18	3.11 (79)	1.14 (29)	1.97 (50)	



Contents

Description	Page
High Current Output Sensors	
Product Selection	V8-T3-59
Accessories	V8-T3-59
Technical Data and Specifications	V8-T3-60
Wiring Diagrams	V8-T3-60
Dimensions	V8-T3-60

High Current Output Sensors

Product Description

Now there is an alternative to limit switches for position sensing on industrial vehicles. High Current Output Sensors feature a continuous output current rating from 2 to 8A. These sensors from Eaton's electrical sector are ideally suited to handle high current loads found on such industrial vehicles as aerial lift trucks, fork lifts, refuse trucks, cement mixers, dump trucks, hook and ladder trucks, front end loaders, farm equipment and hundreds of other vehicles that are constantly subjected to mechanical (shock, vibration, collisions) and environmental (dirt, grease, ice, rain) abuse that create havoc with mechanical devices.

Features

- Solid-state output can handle up to 8A continuous
- Ideal for vehicle use to replace mechanical limit switches, typically required to handle high currents
- · Wide voltage and temperature range covers most vehicle power supplies and operating environments
- Normally Open and Normally Closed isolated outputs
- SJO cable is available in custom lengths
- Dual colored 360° LED indicating light, green as power ON and red as output

DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

High Current Output Sensors

Product Selection

High Current Output Sensors

30 mm

Four-Wire Sensors



Operating Voltage	Sensing Range	Shielding	Output Type	Output Ratin	g <100 ms Pulse	Connection Type ①	Catalog Number
30 mm Dia	meter						
10-55 Vdc	10 mm	Shielded	NO and NC (PNP)	3.5A	20A	2-meter cable	E57-30JS10-H

30 mm

Six-Wire Sensors ②



Operating	Sensing			Output Rating			
Voltage	Range	Shielding	Output Type	Continuous	<100 ms Pulse	Connection Type $^{\scriptsize \textcircled{1}}$	Catalog Number
30 mm Dia	ameter						
10-30 Vdc	10 mm	Shielded	NO and NO, or NC and NC (NPN or PNP)	8A	50A	2-meter cable	E57-30HS10-K

Accessories

High Current Output Sensors

Description	Reference
Mounting brackets	See Tab 8, section 8.2
Replacement mounting nuts and other accessories	See Tab 8, section 8.3

- ^① For additional cable length other than 2-meter, add desired length in meters to listed catalog number. Example: For an E57-30JS10-H with a 5-meter cable, order E57-30JS10-H5.
- $^{\circ}$ 50 Amp surge, 12 Amp at 50% duty cycle and 8 Amp continuous.


Technical Data and Specifications

High Current Output Sensors


Description	Four-Wire Sensors	Six-Wire Sensors
Operating voltage	10 to 55 Vdc	10 to 30 Vdc
Switching rate	250 Hz	100 Hz
Off-state current	100 Aμ maximum	100 Aμ maximum
Voltage drop	1.2V	2.0V
Burden current	10 mA at 55 volts	30 mA at 30 volts
Time delay before availability	<100 ms	<100 ms
Output indicator LED	360° visibility	360° visibility
Output type	Solid-state	Solid-state, isolated
Protection	Transient and power on false pulse	Transient and power on false pulse
Enclosure ratings	NEMA 4, 4X, 6, 6P, 12 and 13 (IEC IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IEC IP67)
Ambient temperature range	-40° to 158°F (-40° to 70°C)	-40° to 158°F (-40° to 70°C)
Barrel material	303 stainless steel	303 stainless steel
Cable	2m standard SJO water resistive (18 AWG)	2m standard SJO water resistive (18 AWG)
Shock	30g sine wave, 11 ms	30g sine wave, 11 ms
Vibration	10 to 55 Hz, 2 mm amplitude in all 3 planes	10 to 55 Hz, 2 mm amplitude in all 3 planes

Wiring Diagrams


Four-Wire-PNP



Six-Wire—NO/NO Output Configuration




Six-Wire—NC/NC Output Configuration



Dimensions

Approximate Dimensions in Inches (mm)

High Current Output Sensors





Contents

Description	Pag
Miniature Short Body Sensors	
Product Selection	
Miniature Short Body Sensors	V8-T3-62
Compatible Connector Cables	V8-T3-63
Accessories	V8-T3-52
Technical Data and Specifications	V8-T3-64
Wiring Diagrams	V8-T3-64
Dimensions	V8-T3-6

Miniature Short Body Sensors

Product Description

These unique Inductive Proximity Sensors by Eaton's electrical sector are designed to be used in extremely small spaces. A wide variety of models are available with housing diameters from 8 mm all the way down to 4 mm, allowing you to choose the one that best fits your application. The sensors are three-wire devices that operate from 10 to 30 Vdc. Both shielded and unshielded versions are available.

Application Description Typical Applications

- Automation equipment
- Robotics
- Machine tool
- Counting
- Sorting

Features

- Small 4, 5, 6.5 and 8 mm diameters for use in applications with limited space for mounting sensors
- Stainless steel housings
- All models include an LED indicator to show output status
- Short circuit and reverse polarity protection
- Rated NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) for high resistance to environmental factors

Standards and Certifications

CE





THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578.

For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

Miniature Short Body Sensors

Three-Wire Sensors

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number	NC Output Catalog Number
4 mm	4 mm Diam	eter (Unthreade	ed)			
	10–30 Vdc	0.8 mm	Shielded	2-meter cable	E57EAL4T110SP	_
			(NPN)	3-pin nano-connector	E57EAL4T110SN 🙃	_
			Shielded	2-meter cable	E57EAL4T111SP	_
			(PNP)	3-pin nano-connector	E57EAL4T111SN ふ	_
	5 mm Diam	eter				
i mm	10-30 Vdc	0.8 mm	Shielded	2-meter cable	E57EAL5T110SP	_
			(NPN)	3-pin nano-connector	E57EAL5T110SN ๋€	_
1			Shielded	2-meter cable	E57EAL5T111SP	_
			(PNP)	3-pin nano-connector	E57EAL5T111SN ⓓ	_
	6.5 mm Dia	meter (Unthrea	ded)			
i.5 mm	10–30 Vdc	1 mm	Shielded	2-meter cable	E57EAL6T110SP	_
			(NPN)	3-pin nano-connector	E57EAL6T110SN 🛈	_
				4-pin micro DC connector	E57EAL6T110SD 33	_
			Shielded (PNP)	2-meter cable	E57EAL6T111SP	_
				3-pin nano-connector	E57EAL6T111SN 🐼	_
				4-pin micro DC connector	E57EAL6T111SD 🕃	_
			Unshielded (NPN) Unshielded	2-meter cable	E57EAL6T110EP	_
				3-pin nano-connector	E57EAL6T110EN 🕟	_
				2-meter cable	E57EAL6T111EP	_
			(PNP)	3-pin nano-connector	E57EAL6T111EN 🙃	_
	8 mm Diam	eter				
mm	10–30 Vdc	1 mm	Shielded	2-meter cable	E57EAL8T110SP	E57EBL8T110SP
			(NPN)	3-pin nano-connector	E57EAL8T110SN ๋€	E57EBL8T110SN ๋€
4				4-pin micro DC connector	E57EAL8T110SD 🕃	E57EBL8T110SD 😩
			Shielded	2-meter cable	E57EAL8T111SP	E57EBL8T111SP
			(PNP)	3-pin nano-connector	E57EAL8T111SN ๋€	E57EBL8T111SN 🙃
				4-pin micro DC connector	E57EAL8T111SD 🕃	E57EBL8T111SD ::
		2 mm	Unshielded	2-meter cable	E57EAL8T110EP	E57EBL8T110EP
		<u></u>	(NPN)	3-pin nano-connector	E57EAL8T110EN 🙃	E57EBL8T110EN ๋€
				4-pin micro DC connector	E57EAL8T110ED 😮	E57EBL8T110ED 🕃
			Unshielded	2-meter cable	E57EAL8T111EP	E57EBL8T111EP
			(PNP)	3-pin nano-connector	E57EAL8T111EN 🙃	E57EBL8T111EN 🔝
				4-pin micro DC connector	E57EAL8T111ED (3)	E57EBL8T111ED (#)

Note

 $\ensuremath{ \bigodot}$ See listing of compatible connector cables on Page V8-T3-63.

Miniature Short Body Sensors

Compatible Connector Cables

Standard Cables®

	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
/licro-Style	Micro-Sty	le, Straight Fe	male				
traight Female	DC	4-pin, 3-wire	22 AWG	6.0 ft (2m)	1-Brown 2-No Wire 3-Blue 4-Black	CSDS4A3CY2202	CSDS4A3RY2202
		4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White 3-Blue 4-Black	CSDS4A4CY2202	CSDS4A4RY2202
ano-Style	Nano-Sty	le, Straight Fe	male				
traight Female	-	3-pin	24 AWG	6.0 ft (2m)	3 4 1-Brown 3-Blue 4-Black	CSNS3A3CY2402	CSNS3A3RY2402

Accessories

Miniature Short Body Sensors

Description	Reference
Mounting brackets	See Tab 8, section 8.2
Replacement mounting nuts and other accessories	See Tab 8, section 8.3
Connector cables	See Tab 10, section 10.1

Note

① For a full selection of connector cables, see **Tab 10**, **section 10.1**.

Technical Data and Specifications

Miniature Short Body Sensors

Description	Three-Wire DC Only Sensors
Operating voltage	10–30 Vdc
Maximum load current	200 mA
Switching frequency	2 kHz
Leakage current	0.01 mA maximum
Voltage drop	1.5V maximum
Burden current	10 mA maximum
Protection	Transient, power on false pulse suppression, auto-reset short circuit
Switching hysteresis	<15% rated sensing distance
Repeat accuracy	<1% sensing distance
Time delay before availability	<50 ms
Output indicator LED	Lights when output is ON
Operating temperature	–13° to 158°F (–25° to 70°C)
Enclosure ratings	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)
Housing material	Stainless steel
Cable	PVC high flex, oil/water resistant, 22 AWG

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

Miniature Short Body Sensors


Operating Voltage	Output	Cable Models	Connector Models (Face View Male Shown) Micro	Nano
Three-Wire	Sensors			
10-30 Vdc	NO (NPN)	BN +V BK Load (-)	(-) (2 (1) +V Load	(-) (4) (1) +V
	NO (PNP)	BN +V BK Load (_)	(-) (2 (1) +V	(-) (-) +V
	NC (NPN)	BN +V BK Load (-)	(-) (2 (1) +V	(-) (-) +V
	NC (PNP)	BN +V BK Load	(-) Load 2 1 +V	(-) (4) (1) +V

Dimensions


Approximate Dimensions in Inches (mm)

Cable Models

Unthreaded Barrel




Threaded Barrel




Size A	Barrel Type	Length B	D	Thread Size	Nut Width F	Connector Diameter G	LED Location
Cable Models							
4 mm	Unthreaded	1.0 (25)	_	_	_	_	L1
5 mm	Threaded	1.0 (25)	0.8 (21)	M5 x 0.5	SW8	_	L1
6.5 mm	Unthreaded	1.8 (45)	_	_	_	_	L2
8 mm	Threaded	1.2 (30)	1.2 (30)	M8 x 1	SW13	_	L2

Connector Models

Unthreaded Barrel



Threaded Barrel



Size A	Barrel Type	Length B	С	D	Thread Size	Nut Width F	Connector Diameter G	LED Location
Nano-Conn	ector Models							
4 mm	Unthreaded	1.6 (40)	0.7 (18)	0.8 (21)	_	_	0.31 (8)	L1
5 mm	Threaded	1.6 (40)	0.7 (18)	0.8 (21)	M5 x 0.5	SW8	0.31 (8)	L1
6.5 mm	Unthreaded	2.4 (60)	1.5 (39)	2.0 (50)	_	_	0.31 (8)	L1
8 mm	Threaded	1.8 (45)	1.0 (25)	1.4 (36)	M8 x 1	SW13	0.31 (8)	L1
Micro-Conr	nector Models							
6.5 mm	Unthreaded	2.9 (70)	1.4 (36)	1.5 (39)	_	_	0.47 (12)	L1
8 mm	Threaded	2.0 (50)	1.6 (40)	1.0 (25)	M8 x 1	SW13	0.47 (12)	L2



Contents

Description	Page
E56 Pancake Sensors	
Product Selection	
E56 Pancake Sensors	V8-T3-67
Compatible Connector Cables	V8-T3-68
Technical Data and Specifications	V8-T3-69
Wiring Diagrams	V8-T3-70
Dimensions	V8-T3-70

E56 Pancake Sensors

Product Description

The E56 Pancake Sensor from Eaton's electrical sector is a high performance inductive proximity sensor. The E56 Pancake provides greater sensing ranges than other inductive sensor package types.

The E56 Pancake family provides convenience and ease of wiring with autoconfigurable, complementary outputs. (Auto-configurable outputs automatically detect an NPN or PNP output configuration and switch the sensor accordingly, without user intervention.) Power and output LEDs make troubleshooting much easier than conventional proximity sensors, which usually only feature output LEDs. These convenience features, combined with the performance of the E56 Pancake, make it an excellent inductive sensing solution for applications requiring an extremely rugged, long-range sensing solution.

Application Description **Typical Applications**

- Heavy-duty trucks, cranes and machinery
- Steel mills
- Pipe and rod manufacturing
- Automotive manufacturing
- Amusement parks

Features

- Longest inductive sensing ranges available (up to 100 mm)
- Three sizes to meet your application needs, with maximum ranges of 50, 70 or 100 mm
- Complementary outputs (1NO/1NC) on four-wire DC models
- Auto-configure output technology on four-wire DC models, which automatically detect how the sensor has been wired (NPN or PNP) and switch the sensor without user intervention
- Small diameter, two-wire AC models feature a selector switch inside the housing, enabling output contacts to be used as either NO or NC
- Robust design featuring vibration and impactabsorbing potting compound
- Ideal for extreme temperatures or high pressure washdown environments

Standards and Certifications

CF





DANGER

THIS SENSOR IS NOT A **SAFETY DEVICE AND IS NOT** INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

E56 Pancake Sensors


Product Selection

E56 Pancake Sensors

Pancake Style

Two-Wire Sensors







DC Four-Wire Sensors

Small Diameter
Caller)

Voltage Type	Output Configuration	Output Contacts	Shielding	Sensing Range	Connector Style	Catalog Number
Small Diame	eter (79 x 79 x 39 ı	mm)				
10-42 Vdc			1.57 in (40 mm)	DC screw	E56ADL40SA	
	autoconfigure ②				DC 4-pin mini	E56ADL40SAE01 3
					DC 4-pin micro	E56ADL40SAD01 :
			Unshielded	1.57 in (40 mm)	DC screw	E56ADL40UA
					DC 4-pin mini	E56ADL40UAE01 :
					DC 4-pin micro	E56ADL40UAD01 🙃
			Unshielded	2 in (50 mm)	DC screw	E56ADL50UA
					DC 4-pin mini	E56ADL50UAE01 :
					DC 4-pin micro	E56ADL50UAD01 🙃
Medium Dia	meter (110 x 110 x	41 mm)				
10-42 Vdc	NPN/PNP autoconfigure ②	1 NO and 1 NC	Unshielded	2.75 in (70 mm)	DC 4-pin mini	E56BDL70UAE01 🙃
					DC 4-pin micro	E56BDL70UAD01 😩
Large Diame	eter (172 x 172 x 6	8 mm)				
10-42 Vdc	NPN/PNP autoconfigure ^②	1 NO and 1 NC	Unshielded	3.94 in (100 mm)	DC 4-pin mini	E56CDL100UAE01 3
					DC 4-pin micro	E56CDL100UAD01 ::




Medium Diameter



- See listing of compatible connector cables on Page V8-T3-68
- ① Includes potentiometer for adjustment of sensing range.
- ² Autoconfigure technology allows the sensor to automatically adapt to NPN or PNP without user intervention.

Compatible Connector Cables

Standard Cables ^①



Note

① For a full selection of connector cables, see Tab 10, section 10.1.

Technical Data and Specifications

Two-Wire

	AC Two-Wire		
Description	Small Diameter	Medium Diameter	Large Diameter
Operating voltage	20-250 Vac	20–250 Vac	20-250 Vac
Load current (maximum)	400 mA	400 mA	400 mA
Off-state leakage	At or above 32°F (0°C): <1.7 mA; below 32°F (0°C): 2.0 mA	At or above 32°F (0°C): <1.7 mA; below 32°F (0°C): 2.0 mA	At or above 32°F (0°C): <1.7 mA; below 32°F (0°C): 2.0 mA
Voltage drop	<10V (5V nominal)	<10V (5V nominal)	<10V (5V nominal)
Outputs	NO or NC (switch selectable)	NO or NC by model	NO or NC by model
Sensing range (maximum)	50 mm	70 mm	100 mm
Range adjustment	Not adjustable	Potentiometer adjustable down to 50% of rated maximum range	Potentiometer adjustable down to 50% of rated maximum range
Standard target size (mild steel)	150 mm	210 mm	300 mm
Frequency of operation	30 Hz	10 Hz	10 Hz
Repeatability	<3%	<3%	<3%
Hysteresis (maximum)	10–15%	10–15%	10–15%
Time delay before availability	300 ms	300 ms	300 ms
Circuit protection	Short circuit protection with auto-reset	Short circuit protection with auto-reset	Short circuit protection with auto-reset
Operating temperature	−13° to 158°F (−25° to 70°C) ①	−13° to 158°F (−25° to 70°C) ^①	−13° to 158°F (−25° to 70°C) ^①
Temperature drift	±10%	±10%	±10%
Enclosure rating	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)
Indicator LEDs	Output status	Output status	Output status
Materials of construction	PPS housing	PPS housing; aluminum baseplate	PPS housing; aluminum baseplate

Four-Wire

DC Four-Wire		
Small Diameter	Medium Diameter	Large Diameter
10-42 Vdc	10-42 Vdc	10-42 Vdc
300 mA	300 mA	300 mA
<25 mA	<25 mA	<25 mA
<150 µA per output	<150 µA per output	<150 μA per output
<2.5V	<2.5V	<2.5V
1 NO/1 NC (complementary)	1 NO/1 NC (complementary)	1 NO/1 NC (complementary)
50 mm	70 mm	100 mm
Not adjustable	Potentiometer adjustable down to 50% of rated maximum range	Potentiometer adjustable down to 50% of rated maximum range
150 mm	210 mm	300 mm
70 Hz	40 Hz	30 Hz
<3%	<3%	<3%
10–15%	10–15%	10–15%
300 ms	300 ms	300 ms
Short circuit protection with auto-reset	Short circuit protection with auto-reset	Short circuit protection with auto-reset
−13° to 158°F (−25° to 70°C) ①	−13° to 158°F (−25° to 70°C) ^①	−13° to 158°F (−25° to 70°C) ①
±10%	±10%	±10%
NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67)
Green: power; Red: output status	Green: power; Red: output status	Green: power; Red: output status
PPS housing	PPS housing; aluminum baseplate	PPS housing; aluminum baseplate
	Small Diameter 10-42 Vdc 300 mA <25 mA <150 µA per output <2.5V 1 NO/1 NC (complementary) 50 mm Not adjustable 150 mm 70 Hz <3% 10-15% 300 ms Short circuit protection with auto-reset -13° to 158°F (-25° to 70°C) ① ±10% NEMA 4, 4X, 6, 6P, 12 and 13 (IP67) Green: power; Red: output status	Small Diameter Medium Diameter 10-42 Vdc 10-42 Vdc 300 mA 300 mA <25 mA


Note

 $[\]odot$ Small diameter DC unshielded models are rated at -40° F (-40° C). All other models can be operated at -40° F (-40° C), but range drift will occur.

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.


E56 Pancake Sensors



Dimensions

Approximate Dimensions in Inches (mm)

E56 Pancake Sensors



Model	A (Depth)	B (Width)	C (Depth)	D (Height)	E (Mounting)	F (Mounting)	G (Diameter)
Small Diameter	Models						
Micro-connector	3.13 (79.0)	3.13 (79.0)	4.32 (110.0)	1.54 (39.0)	2.56 (65.0)	2.56 (65.0)	0.21 (5.0)
Mini-connector	3.13 (79.0)	3.13 (79.0)	4.67 (119.0)	1.54 (39.0)	2.56 (65.0)	2.56 (65.0)	0.21 (5.0)
Screw terminal	3.13 (79.0)	3.13 (79.0)	3.87 (92.0)	1.54 (39.0)	2.56 (65.0)	2.56 (65.0)	0.21 (5.0)
Medium Diame	ter Models						
Micro-connector	4.35 (110.0)	4.35 (110.0)	4.94 (125.4)	1.63 (41.0)	3.625 (92.0)	3.625 (92.0)	0.218 (5.5)
Mini-connector	4.35 (110.0)	4.35 (110.0)	5.29 (134.4)	1.63 (41.0)	3.625 (92.0)	3.625 (92.0)	0.218 (5.5)
Large Diameter	Models						
Micro-connector	6.75 (171.5)	6.75 (171.5)	7.26 (184.4)	2.66 (67.5)	5.875 (149.0)	5.875 (149.0)	0.266 (7.0)
Mini-connector	6.75 (171.5)	6.75 (171.5)	7.61 (193.3)	2.66 (67.5)	5.875 (149.0)	5.875 (149.0)	0.266 (7.0)

Nonmetallic Tubular Sensors



Contents

Description	Page
Nonmetallic Tubular Sensors	
Product Selection	V8-T3-72
Technical Data and Specifications	V8-T3-73
Wiring Diagrams	V8-T3-73
Dimensions	V8-T3-73

Nonmetallic Tubular Sensors

Product Description

E55 Tubular Inductive Proximity Sensors by Eaton's electrical sector are constructed of corrosion resistant PBT plastic. They are ideally suited for wash down applications such as those found in food processing plants. They are available in 12 mm, 18 mm and 30 mm diameters, shielded or unshielded. Shielded units can be embedded in metallic surfaces.

Features

- Models available that operate on two-wire AC or three-wire DC power
- Threaded tubular housings in three diameters allow easy integration into new and existing applications
- Nonmetallic construction offers excellent resistance to corrosion
- Output indicator LED is standard on all models

DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

Product Selection

Nonmetallic Tubular Sensors

Two-Wire Sensors ①

	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number	NC Output Catalog Number				
12 mm	12 mm Diameter									
1	20–250 Vac 50/60 Hz	2 mm	Shielded	2-meter cable	E55CAL12A2	E55CBL12A2				
		4 mm	Unshielded	2-meter cable	E55CAL12A2E	E55CBL12A2E				
18 mm	18 mm Diameter									
1	20–250 Vac 50/60 Hz	5 mm	Shielded	2-meter cable	E55CAL18A2	E55CBL18A2				
		8 mm	Unshielded	2-meter cable	E55CAL18A2E	E55CBL18A2E				
30 mm	30 mm Dia	meter								
1	20–250 Vac 50/60 Hz	10 mm	Shielded	2-meter cable	E55CAL30A2	E55CBL30A2				
	-	15 mm	Unshielded	2-meter cable	E55CAL30A2E	E55CBL30A2E				

Three-Wire Sensors ①

	THICC-VV	ne ocnsors	_			
	Operating Voltage	Sensing Range (Sn)	Shielding	Connection Type	NO Output Catalog Number	NC Output Catalog Number
2 mm	12 mm Dia	meter				
-	10-30 Vdc	2 mm	Shielded (NPN)	2-meter cable	E55CAL12T110	E55CBL12T110
31			Shielded (PNP)	2-meter cable	E55CAL12T111	E55CBL12T111
		4 mm	Unshielded (NPN)	2-meter cable	E55CAL12T110E	E55CBL12T110E
			Unshielded (PNP)	2-meter cable	E55CAL12T111E	E55CBL12T111E
8 mm	18 mm Dia	meter				
	10-30 Vdc	5 mm	Shielded (NPN)	2-meter cable	E55CAL18T110	E55CBL18T110
			Shielded (PNP)	2-meter cable	E55CAL18T111	E55CBL18T111
		8 mm	Unshielded (NPN)	2-meter cable	E55CAL18T110E	E55CBL18T110E
			Unshielded (PNP)	2-meter cable	E55CAL18T111E	E55CBL18T111E
0 mm	30 mm Dia	meter				
	10-30 Vdc	10 mm	Shielded (NPN)	2-meter cable	E55CAL30T110	E55CBL30T110
			Shielded (PNP)	2-meter cable	E55CAL30T111	E55CBL30T111
		15 mm	Unshielded (NPN)	2-meter cable	E55CAL30T110E	E55CBL30T110E
			Unshielded (PNP)	2-meter cable	E55CAL30T111E	E55CBL30T111E
	-					

Note

① For a selection of mounting brackets and other accessories for use with these sensors, see **Tab 8**, **section 8.2**.

Technical Data and Specifications

Nonmetallic Tubular Sensors

Description	Two-Wire AC Models	Three-Wire DC Models		
Operating voltage	20–250 Vac, 50/60 Hz	10-30 Vdc		
Maximum load current	150 mA	200 mA		
Switching frequency				
12 mm	25 Hz	2000 Hz (shielded); 1000 Hz (unshielded)		
18 mm	25 Hz	1000 Hz (shielded); 500 Hz (unshielded)		
30 mm	25 Hz	300 Hz (shielded); 150 Hz (unshielded)		
Protection	_	Short circuit and reverse polarity		
Temperature range	–13° to 158°F (–25° to 70°C)	–13° to 158°F (–25° to 70°C)		
Enclosure material Polybutylene Teraphtalate (PBT)		Polybutylene Teraphtalate (PBT)		
Enclosure rating NEMA 3, 3S, 4, 4X, 13 (IP66)		NEMA 3, 3S, 4, 4X, 13 (IP66)		
Indicator LED	Lights when output is ON			

Wiring Diagrams


Nonmetallic Tubular Sensors

Operating Voltage	Output	Cable Models	Operating Voltage	Output	Cable Models
Two-Wire S	ensors		Three-Wire	Sensors	
20–250 Vac 50/60 Hz	All	BN L1 or +V Load L2 or (-)	10–30 Vdc	NPN	BN +V BK Load (-)
				PNP	BN +V

Dimensions


Approximate Dimensions in Inches (mm)

12 and 18 mm



A	В	Thread Size C
12 mm		
2.17 (55)	1.77 (45)	M12 x 1
18 mm		
2.17 (55)	1.77 (45)	M18 x 1

30 mm



A	В	C C
30 mm		
3.15 (80)	2.36 (60)	M30 x 1.5



Contents

Description	Page
E52 Cube Style Sensors	
Product Selection	
E52 Cube Style Sensors	V8-T3-75
Compatible Connector Cables	V8-T3-75
Technical Data and Specifications	V8-T3-76
Wiring Diagrams	V8-T3-76
Dimensions	V8-T3-77

E52 Cube Style Sensors

Product Description

The E52 Cube Sensor from Eaton's electrical sector is a high performance inductive proximity sensor, providing long sensing ranges in a compact, industry-standard package.

The E52 Cube family features Eaton's Autoconfigure output technology, which automatically detects NPN or PNP wiring states and switches the sensor accordingly, without user intervention. The E52 also utilizes complementary outputs to further reduce the number of models needed to cover a wide array of inductive sensing applications. Individual power and output LEDs make installation and troubleshooting easy. Combine the above features with the range and five-way mounting flexibility of the E52 Cube family, and chances are there's an E52 solution to your sensing needs.

The E52 Cube was designed with the most heavy-duty applications in mind. Some of those applications include automotive manufacturing, aggregate machinery, and metalworking applications. Try the E52 Cube in some your most demanding applications today.

Application Description Typical Applications

- · Automotive manufacturing
- Metalworking
- Machinery OEMs
- Pipe and rod manufacturing
- Block and brick manufacturing equipment
- Amusement parks
- Heavy-duty trucks, cranes and lifts

Features

- Long inductive proximity ranges available (up to 40 mm sensing distance)
- Four-wire DC models have complementary outputs (1NO-1NC)
- Four-wire DC models use auto-configure technology, which allows the sensor to automatically adapt for NPN or PNP without user intervention
- Robust design featuring vibration and impactabsorbing potting compound
- Ideal for extreme temperatures or high pressure washdown environments

Standards and Certifications

• CE





DANGER

THIS SENSOR IS NOT A **SAFETY DEVICE AND IS NOT** INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

E52 Cube Style Sensors

Product Selection

E52 Cube Style Sensors

DC Four-Wire Sensors

	Voltage Type	Output Configuration	Shielding	Output Type	Sensing Range	Connector Style	Catalog Number
Mini-Connector	Cube Packag	ge (40 x 40 x 40 mm)					
	10-48 Vdc	NPN/PNP	Shielded	1 NO and 1 NC	15 mm	DC 4-pin micro	E52Q-DL15SAD01 🙃
		autoconfigure ①				DC 4-pin mini	E52Q-DL15SAE01 🙃
			Unshielded	1 NO and 1 NC	15 mm	DC 4-pin micro	E52Q-DL15UAD01 🙃
						DC 4-pin mini	E52Q-DL15UAE01 ::
E E	10-48 Vdc	NPN/PNP	Shielded	1 NO and 1 NC	20 mm	DC 4-pin micro	E52Q-DL20SAD01 3
		autoconfigure ①				DC 4-pin mini	E52Q-DL20SAE01 ::
Micro-Connector			Unshielded	1 NO and 1 NC	20 mm	DC 4-pin micro	E52Q-DL20UAD01 ::
Micro Connector						DC 4-pin mini	E52Q-DL20UAE01 ::
					25 mm	DC 4-pin micro	E52Q-DL25UAD01 🙃
CIN						DC 4-pin mini	E52Q-DL25UAE01 ::
4					30 mm	DC 4-pin micro	E52Q-DL30UAD01 🙃
						DC 4-pin mini	E52Q-DL30UAE01 ::
\$ A					35 mm	DC 4-pin micro	E52Q-DL35UAD01 🙃
						DC 4-pin mini	E52Q-DL35UAE01 ::
					40 mm	DC 4-pin micro	E52Q-DL40UAD01 😟
						DC 4-pin mini	E52Q-DL40UAE01 ::

Compatible Connector Cables

Standard Cables ²

	Standard C	abics -						
	Current Rating at 600V	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
icro-Style	Micro-Style, S	Straight Fe	male					
aight Female	_	DC	4-pin, 4-wire	22 AWG	6.0 ft (2m)	1-Brown 2-White	CSDS4A4CY2202	CSDS4A4RY2202
					16.4 ft (5m)	3-Blue 4-Black	CSDS4A4CY2205	CSDS4A4RY2205
and the same of th					32.8 ft (10m)	_	CSDS4A4CY2210	CSDS4A4RY2210
ri-Style right Female	Mini-Style, St	traight Fem	nale					
alylit remale	10A	AC/DC	4-pin, 4-wire	16 AWG	6.0 ft (2m)	1-Black 2-Blue	CSMS4A4CY1602	_
					13.1 ft (4m)	3-Brown 4-White	CSMS4A4CY1604	_
					19.7 ft (6m)	_	CSMS4A4CY1606	-

Notes

- $\ensuremath{\textcircled{\textbf{3}}}$ See listing of compatible connector cables above.
- ① Autoconfigure technology allows the sensor to automatically adapt to NPN or PNP without user intervention.
- ② For a full selection of connector cables, see Tab 10, section 10.1.

Technical Data and Specifications


E52 Cube Style Sensors

Description	DC Four-Wire
Operating voltage	10–48 Vdc
Load current (maximum)	300 mA
Burden current	<25 mA
Off-state leakage	<150 µA per output
Voltage drop	<2.5V
Outputs	1 NO/1 NC (complementary)
Standard target size (mild steel)	120 mm
Frequency of operation	100 Hz
Repeatability	<3%
Hysteresis (maximum)	10–15%
Time delay before availability	300 ms
Circuit protection	Short circuit protection with auto-reset
Operating temperature ^①	−25° to 158°F (−25° to 70°C)
Temperature drift	±10%
Enclosure rating	NEMA 4, 4X, 6, 6P, 12 and 13 (IP67, IP68)
Indicator LEDs	Green: power; Red: output status
Material of construction	Zinc alloy housing, PPS, PC

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

E52 Cube Style Sensors




Note

 $^{\odot}$ Will operate at -40° F (-40° C), but range drift will occur.

Dimensions

Approximate Dimensions in Inches (mm)

E52 Cube Style Sensors



Model	Width A	Depth B	Height C	Overall Height D	
Micro-connector	1.57 (40)	1.57 (40)	1.57 (40)	2.725 (69.2)	
Mini-connector	1.57 (40)	1.57 (40)	1.57 (40)	2.965 (75.3)	



Contents

Description	rage
E52 Rectangular Style Sensors	
Product Selection	
E52 Rectangular Style Sensors	V8-T3-79
Compatible Connector Cables	V8-T3-79
Technical Data and Specifications	V8-T3-79
Wiring Diagrams	V8-T3-80
Dimensions	V8-T3-80

E52 Rectangular Style Sensors

Product Description

Rectangular E52 Inductive Proximity Sensors from Eaton's electrical sector feature a small, thin, compact space-saving design for applications where tubular type sensors cannot be used. Sensors are self-contained for direct connection to a logic circuit, relay, counter, programmable controller, and so on.

Features

- Small, low-profile design for use in space restrictive applications
- Three-wire DC operation
- Choose from a variety of sizes, and side or end sensing configurations
- Output indicator included on all models
- Epoxy filled cavities stop fluids from contacting any electrical component
- Convenient mounting holes integrated into each sensor housing

A DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

E52 Rectangular Style Sensors

Product Selection

E52 Rectangular Style Sensors

Three-Wire Models

Voltage	Sensing Range	Frequency	Shielding	Connection Type	NO Output Catalog Number	NC Output Catalog Number
R12 Side S	Sensing					
12-24 Vdc	0.12 in (3 mm)	Standard	Shielded (NPN)	1-meter cable	E52RAL12T110	_
			Shielded (PNP)	_	E52RAL12T111	_
		Alternate	Shielded (NPN)	1-meter cable	E52RAL12T110AF	_
			Shielded (PNP)		E52RAL12T111AF	_
Q16 End S	ensing					
12–30 Vdc	0.20 in (5 mm)	Standard	Unshielded (NPN)	2-meter cable	E52-16QS04-C	E52-16QS04-C1
			Unshielded (PNP)	2-meter cable	E52-16QS04-B	E52-16QS04-B1
R18 Side S	Sensing					
10-30 Vdc	0.16 in (4 mm)	Standard	Unshielded (NPN)	2-meter cable	E52-18RU04-C	E52-18RU04-C1
				3-pin nano-connector	E52-18RU04-CN 🙃	E52-18RU04-C1N
			Unshielded (PNP)	2-meter cable	E52-18RU04-B	E52-18RU04-B1
				3-pin nano-connector	E52-18RU04-BN ๋€	E52-18RU04-B1N (
Q25 End S	ensing					
10–30 Vdc	0.39 in (10 mm)	Standard	Shielded (NPN)	2-meter cable	E52-25QS10-C	E52-25QS10-C1
			Shielded (PNP)	2-meter cable	E52-25QS10-B	E52-25QS10-B1

Compatible Connector Cables

Standard Cables ①

	Otaliaal	a oubics					
	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number
Nano-Style	Nano-Sty	le, Straight Fe	male				
Straight Female	DC	3-pin	24 AWG	6.0 ft (2m)	3 1-Brown 3-Blue 4-Black	CSNS3A3CY2402	CSNS3A3RY2402

Technical Data and Specifications

E52 Rectangular Style Sensors

Description	Specification
Input current	Less than 10 mA
Load current	100 mA maximum
Switching rate	500 operations per second
Circuit protection	Short circuit
Ambient temperature range	–13° to 130°F (–10° to 55°C)
Enclosure rating	NEMA 1, 2, 3, 3S, 4, 12 (IEC IP66)
Enclosure material	PBT composition
Output indicator LED	Lights when output is ON

Notes

- See listing of compatible connector cables above.
- ① For a full selection of connector cables, see **Tab 10**, **section 10.1**.

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

E52 Rectangular Style Sensors


Operating Voltage	Output	Cable Models	Nano-Connector Models (Face View Male Shown)
Three-Wire	e Sensors		
Operating Voltage Three-Wire S	NPN	BN +V BK Load BU (-)	(-) (-) +V
	PNP	BN +V BK Load (_)	(-) Load +V

Dimensions

Approximate Dimensions in Inches (mm) except where noted


E52 Rectangular Style Sensors

R12




Note: Dimensions are mm only.


Q16




Q25



R18





E55 Limit Switch Style Sensors with Nonmetallic Housings

E55 Limit Switch Style Sensors with Nonmetallic Housings





Contents

Description	Page
E55 Limit Switch Style Sensors with Nonmetallic Housings	
Product Selection	V8-T3-81
Technical Data and Specifications	V8-T3-82
Wiring Diagrams	V8-T3-82
Dimensions	V8-T3-82

E55 Limit Switch Style Sensors with Nonmetallic Housings

Product Description

These sensors from Eaton's electrical sector feature PBT resin housings for high resistance to corrosion. The housing is sized to offer a direct replacement for standard limit switches. The unique sensing head is factory assembled for top sensing, but can be easily converted in the field to any one of four side sensing positions. Models are available with sensing ranges from 15 mm to 40 mm. The sensors can be wired for NO or NC operation.

Features

- Nonmetallic housing offers excellent resistance to corrosion
- Same form factor and mounting as standard limit switches for easy retrofit
- Sensor head features five sensing positions (top and all four sides) that can be easily changed in the field
- Long sensing ranges up to 40 mm

DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

Product Selection

E55 Limit Switch Style Sensors

E55 Limit Switch



Two-Wire Sensors

Voltage Type	Sensing Range (Sn)	Shielding	Output	Connection Type	Catalog Number
35-250 Vac	15 mm	Shielded	NO or NC	Terminal wiring	E55BLT1C
	20 mm	Unshielded			E55BLT1D
	30 mm	_			E55BLT1E
	40 mm				E55BLT1F

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578. For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Technical Data and Specifications

E55 Limit Switch Style Sensors

Operating voltage 35–250 Vac Maximum load current 400 mA Switching frequency 25 Hz maximum Leakage current 1.8 mA Voltage drop 8V maximum	
Switching frequency 25 Hz maximum Leakage current 1.8 mA Voltage drop 8V maximum	
Leakage current 1.8 mA Voltage drop 8V maximum	
Voltage drop 8V maximum	
Inrush 5A maximum for 20 ms	
Indicator LEDs Two LEDs: One lights when power is ON, the other lights when outp	ut is ON
Operating temperature -13° to 158°F (-25° to 70°C)	
Enclosure ratings NEMA 4, 4X, 6, 12, 13 (IP67)	
Housing material PBT resin	

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.


E55 Limit Switch Style Sensors

Operating Voltage	Output	Terminal Models
Two-Wire Sensors		
35–250 Vac ①	NO	1 0 0 Load L2
	NC	L1 1 2 Load L2 3 4

Dimensions

Approximate Dimensions in Inches (mm)

E55 Limit Switch Style Sensors



Note

① Switches are shipped as NO configuration. Internal jumpers must be moved to program for NC.

Contents

Deceriation

E51 Modular Limit Switch Style Sensors

E51 Modular Limit Switch Style Sensors



Description	raye
E51 Modular Limit Switch Style Sensors	
Product Selection	
Standard Sensors— Assembled with Terminal Wiring	V8-T3-84
Standard Sensors— Assembled with Receptacles	V8-T3-85
Sensor Heads	V8-T3-85
Sensor Bodies	V8-T3-86

Logic Module

Compatible Connector Cables

Accessories

Technical Data and Specifications

Dimensions

E51 Modular Limit Switch Style Sensors

Product Description

The E51 Inductive Proximity Sensor family from Eaton's electrical sector combines high performance with a familiar limit switch style housing. Modular, plug-in components provide application flexibility, ease of maintenance, less downtime and reduced inventory. Choose from two-wire sensors with AC/DC operation, or four-wire sensors in either AC or DC styles. Connection options include terminal, miniconnector or various lengths of cable.

Choose from standard sensors that detect all types of metallic targets. The next page provides more detail on these sensors.

Features

- Rugged construction is ideal for industrial environments
- Viton gaskets ensure a positive seal and high resistance to industry chemicals
- Direct replacement for worn out limit switches
- Sensor heads and bodies feature captive screws to eliminate loss
- All sensor heads include a selector switch to program output function to either NO or NC
- Sensor bodies feature bifurcated engagement prongs for a reliable connection when plugging into receptacle stabs

- Engagement key between sensor body and receptacle prevents improper assembly
- Sensors accommodate both U.S. and DIN mounting dimensions
- Wiring terminals feature captive pressure plate saddles for #18 to #12 AWG wire. A green screw identified ground terminal is also included
- Logic modules are available to provide additional control functions

Standards and Certifications

- UL Listed
- CSA Certified
- CE (where shown)







V8-T3-86

V8-T3-87

V8-T3-88

V8-T3-88

V8-T3-89

V8-T3-89

V8-T3-90



DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578.

For Application Assistance in the U.S. and Canada call 1-800-426-9184.

Product Selection

Standard Sensors—Assembled with Terminal Wiring

Standard E51 sensors feature long sensing ranges and a choice of top or side sensing heads. Alternate frequency units eliminate interference when mounted close to standard frequency units. Order sensors in component form, as assembled plug-in units, or in a sealed version where the sensor body is factory assembled to an epoxy filled receptacle with tamper-proof screws to ensure a lasting seal.

Assembled Sensor


Assembled Sensors-Standard (with Terminal Wiring)





Sensor Body and Receptacle







E51RC

modules ②

E51RCB

NO and NC complementary E51SPL PNP

E51RN

10-30 Vdc

E51SNL NPN

E51RN

Sensor Heads ①

Top Sensing





Side Sensing



			11000ptaoio =	201101	201110	LUIIIUD	20111114	2011111
Sensing Range	Shielding	Frequency	Sensor Head Only Catalog Number	Assembled S Catalog Nun	Sensors with Head, Ser nber	nsor Body and Rec	eptacle	
Top Sens	ing							
0.51 in (13 mm)	Shielded	Standard	E51DT1	E51ALT1 (€ E51CLT1	E51CNT1	E51PLT1 (€ E51NLT1 (€
(15 11111)		Alternate	E51DT2	E51ALT2 (€ E51CLT2	E51CNT2	E51PLT2 (€ E51NLT2 (€
0.94 in (24 mm)	Unshielded	Standard	E51DT5	E51ALT5 (€ E51CLT5	E51CNT5	E51PLT5 (€ E51NLT5 (€
(24 11111)	Alternate	E51DT6	E51ALT6 (€ E51CLT6	E51CNT6	E51PLT6 (€ E51NLT6 (€	
Side Sen	sing							
0.51 in (13 mm)	Shielded	Standard	E51DS1	E51ALS1 (€ E51CLS1	E51CNS1	E51PLS1 (€ E51NLS1 (€
(10 11111)		Alternate	E51DS2	E51ALS2 (€ E51CLS2	E51CNS2	E51PLS2 (€ E51NLS2 (€
0.94 in (24 mm)	Unshielded	Standard	E51DS5	E51ALS5 (€ E51CLS5	E51CNS5	E51PLS5 (€ E51NLS5 (€
(24 11111)		Alternate	E51DS6	E51ALS6 (€ E51CLS6	E51CNS6	E51PLS6 (€ E51NLS6 (€

E51RA

① All sensor heads feature a programmable output selector switch for NO or NC operation. Operation is as follows:

For This Output Type:	Set Selector Position: "TARGET"	"NO TARGET"	
NO NO	Target present	Target absent	
NC	Target absent	Target present	

- 2 Logic module must be ordered separately, see Page V8-T3-86. These sensor bodies are rated NEMA 4, 4X and 13.
- ® Receptacles feature terminal wiring with a 1/2 in NPT thread at the conduit entrance. Other connection options are available:

Connection Option		Catalog Number	Code Suffix	Example
20 mm thread at the conduit entrance		_	20	E51ALT120
Mini-connector termination with epoxy filled receptacle, see Page V8-T3-87 for	Two-wire, 3-pin connector	CSMS3F3CY1602	P3	E51ALT1P3
additional receptacle options	Four-wire, 5-pin connector	CSMS5D5CY1602	P5	E51CLT1P5
Pre-wired cable with epoxy filled	8 ft long	_	S	E51ALT1S
receptacle	12 ft long	_	S12	E51ALT1S12
	20 ft long	_	S20	E51ALT1S20

E51 Modular Limit Switch Style Sensors

Standard Sensors—Assembled with Receptacles

Sensor body is attached to receptacle with tamper-proof screws.

Assembled Sensors—Standard (with Epoxy Filled Receptacles and Pre-wired Cables)

Sensor Base Type with 8 ft Cable ②





Sensor Heads ①	Sensing Range	Shielding	Frequency	Sensor Head Only Catalog Number	Assembled Catalog Nur		th Head and Sensor Bas	e			
Top Sensing	Top Sens	ing									
	0.51 in (13 mm)	Shielded	Standard	E51DT1	E51ALT16P	C€	E51CLT16P	E51PLT16P	C€	E51NLT16P	C€
*	(13 11111)		Alternate	E51DT2	E51ALT26P		E51CLT26P	E51PLT26P	C€	E51NLT26P	C€
	0.94 in	Unshielded	Standard	E51DT5	E51ALT56P	C€	E51CLT56P	E51PLT56P	C€	E51NLT56P	C€
	(24 mm)		Alternate	E51DT6	E51ALT66P	C€	E51CLT66P	E51PLT66P	C€	E51NLT66P	C€
Side Sensing	Side Sen	sing									
	0.51 in	Shielded	Standard	E51DS1	E51ALS16P	C€	E51CLS16P	E51PLS16P	C€	E51NLS16P	C€
(C) 1	(13 mm)		Alternate	E51DS2	E51ALS26P	C€	E51CLS26P	E51PLS26P	C€	E51NLS26P	C€
	0.94 in	Unshielded	Standard	E51DS5	E51ALS56P	C€	E51CLS56P	E51PLS56P	C€	E51NLS56P	C€
	(24 mm)		Alternate	E51DS6	E51ALS66P	C€	E51CLS66P	E51PLS66P	C€	E51NLS66P	C€

Sensor Heads

Sensor Heads ①

Top Sensing

Side Sensing



Sensing Range	Shielding	Frequency	Target Material	Catalog Number
Top Sensing				
0.51 in (13 mm)	Shielded	Standard	All metals	E51DT1
		Alternate		E51DT2
0.94 in (24 mm)	Unshielded	Standard	All metals	E51DT5
		Alternate		E51DT6
Side Sensing				
0.51 in (13 mm)	Shielded	Standard	All metals	E51DS1
		Alternate		E51DS2
0.94 in (24 mm)	Unshielded	Standard	All metals	E51DS5
		Alternate		E51DS6

Notes

① All sensor heads feature a programmable output selector switch for NO or NC operation. Operation is as follows:

For This Output Type:	Set Selector Position: "TARGET"	"NO TARGET"
NO	Target present	Target absent
NC	Target absent	Target present

② Switch bases feature 8 ft of SOOW-A cable. Other connection options are available:

Connection Option ³	Suffix	Example
Mini-connector mounted on 3 ft (0.9m) pigtail cable	T	E51ALT16PT
Mini-connector mounted to switch base	C	E51ALT16PC
Cable longer than 8 feet, add required length in 1 ft increments to listed catalog number—20 ft maximum	Length in ft	E51ALT16P12 for 12 ft

³ See listing of compatible connector cables on Page V8-T3-88.

Sensor Bodies

AC/DC

Two-Wire Sensors

Operating Voltage	Output	Protection	Output Rating Continuous	Туре	Catalog Nun	ıber
AC/DC						
20–264 Vac/dc, 50/60 Hz	1 output, load powered, NO or NC, programmable from head; off state leakage current: <1.7 mA at 120 Vac/dc, <2.0 mA at 240 Vac	Latching short circuit and overload	0.5A	_	E51SAL ①	C€

	Four-Wire Operating	Sensors				
	Voltage	Output	Protection	Output Rating Continuous	Туре	Catalog Number
AC (E51SCN Shown)	AC					
	120 Vac, 50/60 Hz	2 complementary outputs, line powered, NO and NC	_	1.0A to 158°F (70°C), linearly derated to 0.6A at 176°F (80°C)	_	E51SCL ①
THE P CONTRACTOR OF THE PARTY O				1.0A to 113°F (45°C), linearly derated to 0.3A at 176°F (80°C)	_	E51SCN 23
OC	DC					
	10-30 Vdc	2 complementary outputs, line powered, NO and NC	Reverse polarity	0.6A to 104°F (40°C), linearly derated to 0.36A at 176°F (80°C)	NPN	E51SNL ①
					PNP	E51SPL®

Logic Module

Logic Module (for E51SCN Sensor Body Only)

Description	Timing Range ⁴	Catalog Number		
Adjustable delay between time object is sensed and time switch function occurs	0.15 to 15.0 seconds	E51MTB		
Adjustable delay between time object leaves sensing field and time switch transfers back to non-sensing state				
1	Adjustable delay between time object is sensed and time switch function occurs Adjustable delay between time object leaves sensing field and time switch transfers back to	and time switch function occurs Adjustable delay between time object is sensed and time switch function occurs Adjustable delay between time object leaves sensing field and time switch transfers back to		

Notes

- This sensor body is available in a factory-sealed, non plug-in configuration (with 8-ft cable), add 6P to listed catalog number. Example: E51SAL6P.
- ② Sensor body is black. E51SCN sensor bodies are rated NEMA 4, 4X and 13.
- ③ This sensor accepts logic modules, as seen in chart above.
- $@ \ \ \text{Repeatability of the timing cycle is } \pm 1\% \ \text{at constant voltage, ambient temperature and reset time.}$
- $\ ^{\textcircled{5}}$ Reset time is 25 ms minimum. Rated NEMA 4, 4X and 13.

E51 Modular Limit Switch Style Sensors

Receptacles

Receptacles

					Conduit Entrance 1/2 in NPT	20 mm
	Description	Style	Details	Cable Length	Catalog Number	Catalog Number
urface Mount	Surface Mount					
	Conduit entrance, front or rear mounting	Two-wire, AC/DC	_	_	E51RA	E51RA20
1		Four-wire, AC	Gray	_	E51RC	E51RC20
			Black ①	_	E51RCB	E51RCB20
1		Four-wire, DC	_	_	E51RN	E51RN20
Aini-Connector	Mini-Connector					
	Epoxy filled receptacle with pre-wired mini-connector	Two-wire, AC/DC	3-pin	_	E51RAP3 ๋€	_
		Four-wire, AC	5-pin	_	E51RCP5 ↔	_
		Four-wire, DC	5-pin		E51RNP5 €	_
igtail with	Pigtail with Mini-Connector					
Mini-Connector	Epoxy filled receptacle with mini-connector mounted on 3 ft (0.9m) cable	Two-wire, AC/DC	3-pin	3 ft (0.9m)	E51RAPT3 🗈	_
5		Four-wire, AC	5-pin	3 ft (0.9m)	E51RCPT5 €	_
		Four-wire, DC	5-pin	3 ft (0.9m)	E51RNPT5 ↔	_
re-Wired Cable	Pre-Wired Cable					
And the same	Epoxy filled receptacle with pre-wired 16 gauge,	Two-wire, AC/DC	3-conductor	8 ft (2.4m)	E51RAS	E51RA20S
7	yellow jacketed, type SOOW-A cable. Cable enters through hole threaded for conduit			12 ft (3.6m)	E51RAS12	_
	anough hole anouaca for conduit			20 ft (6m)	E51RAS20	_
		Four-wire, AC	5-conductor	8 ft (2.4m)	E51RCS	E51RC20S
				12 ft (3.6m)	E51RCS12	_
				20 ft (6m)	E51RCS20	_
		Four-wire, DC	5-conductor	8 ft (2.4m)	E51RNS	E51RN20S
				12 ft (3.6m)	E51RNS12	_
				20 ft (6m)	E51RNS20	_

Notes

 $\ensuremath{ \odot } \ensuremath{ \odot }$ See listing of compatible connector cables on Page V8-T3-88.

 $^{^{\}scriptsize\textcircled{\tiny{1}}}$ Black receptacle is for color compatibility with E51SCN sensor body.

E51 Modular Limit Switch Style Sensors

Compatible Connector Cables

Standard Cables ①

Pin Configuration/Wire Colors (Face View Female Shown) Catalog Number Voltage Current Number Rating at 600V Style of Pins Gauge Length Micro-Style, Straight Female 3-pin 16 AWG 6 ft (2m) CSMS3F3CY1602 1-Green 1 2-Black 3-White 10A AC/DC CSMS4A4CY1602 4-pin, 16 AWG 6 ft (2m) 1-Black 2-Blue 3-Brown four-wire (4)(1)4-White 8A 5-pin 16 AWG 6 ft (2m) CSMS5D5CY1602 1-White 2-Red 3-Green

4-Orange 5-Black

Micro-Style Straight Female

Accessories

	E51 Modular Limit Switch Style Sensors				
	Description	Catalog Number			
One Hole	Universal Mounting Bracket				
	One hole, includes mounting hardware, stainless steel	E51KH2			
Two Holes	Two holes, includes mounting hardware, steel	E51KH4			
1)4					
Machine Mounting	Machine Mounting Bracket				
Bracket	Zinc die cast construction	E50KH3			
Stand-Off Mounting	Stand-Off Mounting Bracket				
Bracket	Steel construction	E51KH3			
Remote Sensor Head Assembly	Remote Sensor Head Assembly				



sembly	Remote Sensor Head Assembly				
	Permits mounting sensor head up to 3 ft (0.9m) from sensor body	E51KRM			



Dimensions, see Page V8-T3-90.

 $^{\scriptsize \textcircled{1}}$ For a full selection of connector cables, see Tab 10, section 10.1.

Technical Data and Specifications

E51 Modular Limit Switch Style Sensors

Description	Specification
Output rating (NEMA D150)	
AC/DC models	0.5A continuous
AC models	1A continuous
DC models	0.6A continuous
Protection	Latching short circuit protection on two-wire AC/DC models; DC models: resettable short circuit protection
Switching rate	AC models: 15 Hz; DC models: 50 Hz
Indicator LEDs	Lights when output is ON. One LED for each output
Alternate frequency	Standard and alternate frequencies allow side-by-side operation without interference
Enclosure material	Zinc die cast
Gasket material	Viton
Enclosure ratings	NEMA 3, 3S, 4, 4X, 6, 6P, 12 and 13 (IP67); E51SCN sensor body only: NEMA 4, 4X and 13
Hazardous locations ratings	
Class I	Division II—GRPS ABCD
Class II	Division II—GRPS F and G
Class III	Division 2
Temperature range	−13° to 158°F (−25° to 70°C)
Torque requirements	Switch body screws: 25–30 in-lbs; sensing head screws: 14–18 in-lbs
Vibration	10–55 Hz, 1 mm amplitude
Shock	30g, 11 ms, 1/2 sine wave
Humidity	95% non-condensing
Burden current	<25 mA
OFF-state leakage	DC version: 120 μA; two-wire AC: 1.9 mA maximum; three-wire AC: 1.1 mA
ON-state leakage	<2.5 Vdc
Power-up delay	<150 ms

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.

E51 Modular Limit Switch Style Sensors

Operating Voltage	Output	Terminal and Cable Models	Mini-Connector Models (Face View Male Shown)
Two-Wire Sens	sors		
20–264 Vac or Vdc 50/60 Hz	NO or NC (NO shown, can be changed to NC using switch on sensor head)	White 1 Black Load L2 or +V 0 4 Green 1	L1 or 1
Four-Wire Sen	sors		
120 Vac 50/60 Hz	NO and NC ①	Red 1 Coad Coange Load White L2 Coad Coange L2	L2 Load (1 (5) L1 N.C. Load N.O. $\frac{1}{2}$
10–30 Vdc	NO and NC NPN $^{\scriptsize \textcircled{0}}$	Load Red 1 2 Orange White 4 (-)	(-) (1) (5) (-) (-) (2) (4) (-) (-) (-) (-) (-) (-) (-) (-) (-) (-
	NO and NC PNP ①	Red 1 Coad Coad White Coad White Green (-)	(-) Load 2 3 4 +V Load N.C. Load N.O. ±


① Changing output switch on sensor head will reverse output function (NO becomes NC, and NC becomes NO).

Dimensions


Approximate Dimensions in mm [in]

E51 Modular Limit Switch Style Sensors

Standard Sensors




Sensor with Logic Module




Accessories

Approximate Dimensions in Inches [mm]

Universal Mounting Bracket-One Hole



Universal Mounting Bracket-Two Holes




Note


① Can accommodate both U.S., 29.4 [1.16] x 59.5 [2.34] and DIN, 30 [1.18] x 60 [2.36], mounting dimensions are in mm [in].

Approximate Dimensions in mm [in]

Machine Mounting Bracket





Stand-Off Mounting Bracket



Approximate Dimensions in Inches [mm]

Remote Sensor Head Assembly





Contents

Description	Page
E51 Limit Switch Style, Factory Sealed 6P+ Sensors	
Product Selection	
Unitized Sensors	V8-T3-93
Compatible Connector Cables	V8-T3-93
Accessories	V8-T3-94
Technical Data and Specifications	V8-T3-94
Wiring Diagrams	V8-T3-95
Dimensions	V8-T3-95

E51 Limit Switch Style, Factory Sealed 6P+ Sensors

Product Description

E51 6P+ Inductive Proximity Sensors from Eaton's electrical sector are fully sealed, pre-wired and designed specifically to ensure reliability under the most adverse of environmental conditions. They have been proven to withstand the penetrating properties of dirt, dust, grit, extreme temperatures and humidity. The unitized design eliminates plug-in connections that can lead to reliability problems in rugged environments.

Features

- The one-piece body and sensing head are both epoxy filled to protect internal components from contamination
- The head is hard-wired to the sensor body to ensure trouble-free performance
- Choose from top and side sensing heads
- Side sensing heads can be rotated to any of four positions
- Mounting dimensions allow direct replacement of worn out limit switches
- Rugged zinc die cast construction withstands physical abuse
- Connection options include pre-wired cable, body mounted connector and pigtail connector



DANGER

THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A **SAFETY DEVICE. This sensor** is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safetyrelated use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.

For the most current information on this product, visit our Web site: www.eaton.com

Four-Wire Sensors

E51 Limit Switch Style, Factory Sealed 6P+ Sensors

Product Selection

Unitized Sensors

Assembled Sensor with 8 ft Cable ①

Factory Sealed 6P+ Assembled Sensors



Top Sensing ²



Side Sensing $^{\scriptsize 2}$



		Operating voltage	20–264 Vac/dc		120 Vac	10–30 Vdc	
		Output	NO	NC	NO and NC complementary	NO and NC comp PNP	lementary NPN
Sensing		Assembled Sensor with Head, Sensor Body and Receptacle					
Range	Shielding	Frequency ³	Catalog Numbe	r			
Top Sensing							
0.51 in (13 mm)	Shielded	Standard	E51ALT16PU	E51BLT16PU	E51CLT16PU	E51PLT16PU	E51NLT16PU
		Alternate	E51ALT26PU	E51BLT26PU	E51CLT26PU	E51PLT26PU	E51NLT26PU
0.94 in (24 mm) Unshielde	Unshielded	Standard	E51ALT56PU	E51BLT56PU	E51CLT56PU	E51PLT56PU	E51NLT56PU
		Alternate	E51ALT66PU	E51BLT66PU	E51CLT66PU	E51PLT66PU	E51NLT66PU
Side Sensing	3						
0.51 in (13 mm) S	Shielded	Standard	E51ALS16PU	E51BLS16PU	E51CLS16PU	E51PLS16PU	E51NLS16PU
		Alternate	E51ALS26PU	E51BLS26PU	E51CLS26PU	E51PLS26PU	E51NLS26PU
0.94 in (24 mm)	Unshielded	Standard	E51ALS56PU	E51BLS56PU	E51CLS56PU	E51PLS56PU	E51NLS56PU
		Alternate	E51ALS66PU	E51BLS66PU	E51CLS66PU	E51PLS66PU	E51NLS66PU

Two-Wire Sensors

Compatible Connector Cables

Standard Cables ®



Current Rating at 600V	Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	Catalog Number
Mini-Style, S	Mini-Style, Straight Female					
13A	_	3-pin	16 AWG	6 ft (2m)	1-Green 2-Black 3-White	CSMS3F3CY1602
10A	_	4-pin	16 AWG	6 ft (2m)	1-Black 2-Blue 3 2 3-Brown 4-White	CSMS4A4CY1602
8A	AC/DC	5-pin, 5-wire	16 AWG	6 ft (2m)	1-Black 2-Blue 3-Orange 4-Brown 5-White	CSMS5A5CY1602

① Switch bases feature 8 ft of SOOW-A cable. Other connection options are available:

Connection Option ⁴	Instructions	Example
Mini-connector mounted on 3 ft (0.9m) pigtail cable (3-pin for two-wire sensors; 5-pin for four-wire sensors)	Add the letter T before U	E51ALT16PTU
Mini-connector mounted to switch base (3-pin for two-wire sensors; 5-pin for four-wire sensors)	Add the letter C before U	E51ALT16PCU
Cable longer than 8 ft, add required length in 1 ft increments to listed catalog number—20 ft maximum	Add length in feet to end of catalog number	E51ALT16PU12 ^⑤

- ② Sensor head is hard wired to sensor body and cannot be detached. Side sensing head can be unfastened and rotated to any of four positions.
- Sensor heads feature color coded target symbols: Yellow for standard frequency; Green for alternate frequency.
- See listing of compatible connector cables above.
- ^⑤ For 12 ft.
- © For a full selection of connector cables, see Tab 10, section 10.1.

Accessories

E51 Limit Switch Style, Factory Sealed 6P+ ®

	Description	Catalog Number		
One Hole	Universal Mounting Bracket			
	Includes mounting hardware, stainless steel	E51KH2		
Two Holes	Includes mounting hardware, steel	E51KH4		
Machine Mounting	Machine Mounting Bracket			
Bracket	Zinc die cast construction	E50KH3		
Stand-Off Mounting	Stand-Off Mounting Bracket			
Bracket	Steel construction	E51KH3		
	Dimensions, see Page V8-T3-95.			

Technical Data and Specifications

E51 Limit Switch Style, Factory Sealed 6P+

Description	Specification		
Output rating (NEMA D150)			
AC/DC models	0.5A continuous		
AC models	1A continuous		
DC models	0.6A continuous		
Protection	Latching short circuit protection on two-wire AC/DC and three-wire DC models		
Switching rate	AC models: 15 Hz; DC models: 50 Hz		
Indicator LEDs	Lights when output is ON. One LED for each output		
Alternate frequency	Standard and alternate frequencies allow side-by-side operation without interference		
Enclosure material	Cast metal		
Gasket material	Zinc die cast		
Enclosure ratings	NEMA 3, 3S, 4, 4X, 6, 6P, 12 and 13 (IP68)		
Temperature range	–13° to 158°F (–25° to 70°C)		
Torque requirements	Switch body screws: 25–30 in-lbs; sensing head screws: 14–18 in-lbs		
OFF-state leakage	DC version: 120 μA; two-wire AC: 1.9 mA maximum; three-wire AC: 1.1 mA		
ON-state leakage	<2.5 Vdc		

Note

 $^{^{\}scriptsize \textcircled{1}}$ For a full selection of connector cables, see Tab 10, section 10.1.

Wiring Diagrams

Pin numbers are for reference, rely on pin location when wiring.


E51 Limit Switch Style, Factory Sealed 6P+

Operating Voltage	Output	Cable Models	Mini-Connector Models (Face View Male Shown)				
Two-Wire Se	Two-Wire Sensors						
20–264 Vac or Vdc 50/60 Hz	NO or NC (NO shown)	White 1 2 Black Load L2 or (-)	L1 or (1) L2 (-) (2) (3) Load or +V				
Four-Wire Se	ensors						
120 Vac 50/60 Hz	NO and NC	Red 1 Coad Orange Coad White Green 1 L2	L2 Load 2 4 L1 N.C. Load N.O. =				
10–30 Vdc	NO and NC NPN	Load Red 1 Orange White +V Green 3 4	(-) (5) (Load +V N.O. Load +V				
	NO and NC PNP	Red 1 Orange Load White Load Green (-)	(-) Load (2) (4) +V (1) (5) (1) (5) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1				

Dimensions

Approximate Dimensions in mm [in]

E51 Limit Switch Style, Factory Sealed 6P+




Note


 Can accommodate both U.S., 29.4 [1.16] x 59.5 [2.34] and DIN, 30 [1.18] x 60 [2.36], mounting dimensions. Approximate Dimensions in Inches [mm]

Accessories

Universal Mounting Bracket-One Hole




Universal Mounting Bracket—Two Holes



Approximate Dimensions in mm [in]

Machine Mounting Bracket



Note

 Can accommodate both U.S., 29.4 [1.16] x 59.5 [2.34] and DIN, 30 [1.18] x 60 [2.36], mounting dimensions.

Stand-Off Mounting Bracket

