

Customer Information Sheet

DRAWING No.: D9XXX-XX

SHEET 2 OF 2

IF IN DOUBT - ASK

©

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

PART No.	No. OF CONTACTS	No. OF CENTRE BARS	DIM 'A'	DIM 'B'	DIM 'C'	DIM 'D'
D9206-XX	6	0	7.62	5.08	10.16	7.62
D9208-XX	8	0	10.16	7.62	10.16	7.62
D9214-XX	14	0	17.78	15.24	10.16	7.62
D9216-XX	16	0	20.32	17.78	10.16	7.62
D9218-XX	18	0	22.86	20.32	10.16	7.62
D9220-XX	20	1	25.40	22.86	10.16	7.62
D9222-XX	22	1	27.94	25.40	12.70	10.16
D9224-XX	24	1	30.48	27.94	17.78	15.24
D9228-XX	28	1	35.62	33.02	17.78	15.24
D9232-XX	32	1	40.64	38.10	17.78	15.24
D9240-XX	40	2	50.80	48.26	17.78	15.24
D9248-XX	48	2	60.96	58.42	25.28	22.86
D9264-XX	64	2	81.28	78.74	25.28	22.86
D9724-XX	24	1	30.48	27.94	12.70	10.16
D9922-XX	22	1	27.94	25.40	10.16	7.62
D9924-XX	24	0	30.48	27.94	10.16	7.62
D9948-XX	48	2	60.96	58.42	17.78	15.24

SPECIFICATION:

MATERIAL:

MOULDING = 30% GLASS-FILLED POLYESTER UL94V-0, BLACK
CONTACTS = BRASS

FINISH:

CONTACTS:
01 = 3.5-5.0µ TIN OVER 2µ NICKEL
05 = 0.05-0.10µ GOLD OVER 2µ NICKEL

ELECTRICAL:

CURRENT RATING AT 25°C = 1.5A
CURRENT RATING AT 85°C = 0.25A
CONTACT RESISTANCE (INITIAL) = 15 mΩ MAX
CONTACT RESISTANCE (AFTER CONDITIONING) = 23 mΩ MAX
INSULATION RESISTANCE (INITIAL) = 1,000 MΩ MIN
INSULATION RESISTANCE (AFTER CONDITIONING) = 100 MΩ MIN

ENVIRONMENTAL:

TEMPERATURE RANGE = -55°C TO +125°C

PACKING:

TUBE

FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C004XX (LATEST ISSUE)

ORDER CODE:

D9XXX-XX

PITCH CODE

SEE TABLE


TOTAL No. OF CONTACTS

FINISH


01 - TIN

05 - GOLD


ILLUSTRATION OF
NUMBER OF CENTRE BARS
(SEE TABLE)





0 BARS



1 BAR



2 BARS



NOTES:

1. RECOMMENDED PCB HOLE SIZE
= Ø0.80mm MIN.

WJB	8	03.03.03	7324
NAME	ISS.	DATE	C/NOTE
APPROVED: P. D. COLLINS			
CHECKED: M. G. PLESTED			
DRAWN: J. A. KEIR			
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

HARWIN INC U.S.A. TEL: (812) 542 2546 FAX: (812) 542 2541	HARWIN PLC U.K. TEL: 023 9237 0451 FAX: 023 9231 4590	HARWIN PTE SINGAPORE TEL: 65 6779 4909 FAX: 65 6779 3868
--	--	---

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH:

SEE ABOVE

S/AREA:

mm²

TITLE:

DIL I.C. THROUGH
HEADER ASSEMBLY

DRAWING NUMBER:

D9XXX-XX

SHT
2
OF
2