

**Harvatek Surface Mount LED Data Sheet
HT-110IRAJ-XXXX**

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 1/13

DISCLAIMER.....	3
PRODUCT SPECIFICATIONS	4
ATTENTION: ELECTROSTATIC DISCHARGE (ESD) PROTECTION	4
LABEL SPECIFICATIONS	5
ABSOLUTE MAXIMUM RATING	6
PACKAGE OUTLINE DIMENSION.....	6
RECOMMENDED SOLDERING PATTERN FOR REFLOW SOLDERING	6
ELECTRO-OPTICAL CHARACTERISTICS.....	6
CHARACTERISTICS CURVES.....	7
RADIATION PATTERN	7
PACKAGING	8
TAPE DIMENSION	8
REEL DIMENSION.....	8
PACKING	9
DRY PACK.....	10
REFLOW SOLDERING	11
PRECAUTIONS.....	12
REWORKING.....	12
CLEANING	12
REVISION HISTORY	13

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 2/13

DISCLAIMER

HARVATEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. HARVATEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

HARVATEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of HARVATEK or HARVATEK INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 3/13

Product Specifications

Product	Peak Wavelength	Test Current I_{FP} (mA) $t_p = 20ms$	Radiant Intensity (mW/Sr)	Forward Voltage V_F (V)	Orderable Part Number
HT-110IRAJ	940 nm	100	1.0 min	1.25 typ	HT-110IRAJ-XXXX
	Specification		Material		Quantity
Resin	Water clear		Epoxy resin		
Carrier tape	Per EIA 481-1A specs		Transparent		3000 pcs per reel
Reel	Per EIA 481-1A specs		Plastic / White		
Label	HT standard		Paper		
Packing bag	220x240mm		Aluminum laminated bag/ no-zipper		One reel per bag
Carton	HT standard		Paper		

Others:

Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of I_v , λ_D and V_f . Each reel has a label identifying its specification; the immediate box consists of a product label as well.

Compliance and Certification

RoHS compliant and IS9002, QS9000 and ISO14001 certified.



ATTENTION: Electrostatic Discharge (ESD) protection



The symbol to the left denotes that ESD precaution is needed. ESD protection for GaP and AlGaAs based chips is necessary even though they are relatively safe in the presence of low static-electric discharge. Parts built with AlInGaP, GaN, or/and InGaN based chips are **STATIC SENSITIVE devices**. ESD precaution must be taken during design and assembly.

If manual work or processing is needed, please ensure the device is adequately protected from ESD during the process.

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 4/13

Label Specifications

HARVATEK			Date: yyyy/mm/dd
CUSTOMER P/N: 			
HARVATEK P/N: 		QTY: PCS 	
LOT NO: 		QC	
IV BIN:	COLOR BIN:	VF:	

Harvatek P/N:

H T - 1 1 0 IRAJ - XXXX

Series Name	Emitting Wavelength	Customer Code
HT-110 HT: Harvatek 110: Side-emitting series 3.2 (L) x 1.5 (W) x 1.0 (H) mm	IRAJ: 940 nm Infrared Emitter $I_{FP}=100mA$, $t_p=20ms$	XXXX Customer Product Code (TBD)

Lot P/N:

1 2 3 4 5 6 7 8 9 10
P 1 2 2 3 0 A - D T

Code 1	Code 2	Code 3	Code 4, 5	Code 6, 7	Code 9	Code 10
	Mfg. Year	Mfg. Month	Mfg. Date	Lots	Resin Color	Packaging
Internal Tracing Code	Z: 2000 1: 2001 2: 2002 3: 2003	1: Jan. 2: Feb. 9: Sep. A: Oct. B: Nov. C: Dec.	1~31/ (30)	01~99, A,B,C...	C: Clear D: Diffused	T: Tape & Reel

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.	
Tentative Product	*****			HT-110IRAJ-XXXX	
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 5/13	

Product Features

Absolute Maximum Rating

Parameter	Symbol	Max.	Unit
Power Dissipation	P_D	80	mW
Continuous Forward Current	I_F	50	mA
Reverse Voltage	V_R	5	V
Operating Temperature	T_{OP}	-30 to 80	°C
Storage Temperature	T_{ST}	-40 to 85	°C

* @ $t_P = 10 \mu s$, duty cycle = 1%

Package Outline Dimension

Recommended Soldering Pattern for Reflow Soldering

Unit: mm Tolerance: +/-0.1





Outline Dimension	Solder Pattern
Soldering terminals may shift in the x, y direction.	Unit: mm

Electro-Optical Characteristics



Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage	V_F	—	1.25	1.6	V	$I_F=20mA$
Reverse Current	I_R	—	—	10	uA	$V_R=5V$
Peak Emission Wavelength	λ_P	—	940	—	nm	$I_F=20mA$
Radiant Intensity	I_e	1.0	3.0	—	mW/sr	$I_{FP}=100mA$ $t_P=20ms$
Spectral Wavelength	$\Delta\lambda$	—	50	—	nm	$I_F=20mA$
Emission Angle	$2\frac{1}{2}\theta$	—	140	—	degrees	—

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 6/13

Characteristics Curves




Radiation Pattern



Official Product	Product: HT-110IRAJ-XXXX	Data Sheet No.
Tentative Product	*****	HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	August 20, 2009	Version of 1.0
		Page 7/13

Packaging


Tape Dimension



Part No.	Dim. A	Dim. B	Dim. C	Q'ty/Reel
HT-110IRAJ-XXXX	3.40 ± 0.10	1.70 ± 0.10	1.20 ± 0.10	3K


Unit: mm

Reel Dimension



Official Product	Product: HT-110IRAJ-XXXX	Data Sheet No.
Tentative Product	*****	HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	August 20, 2009	Version of 1.0
		Page 8/13

Packing



5 boxes per carton is available depending on shipment quantity.

	Specification	Material	Quantity
Carrier tape	Per EIA 481-1A specs	Transparent	3000 pcs per reel
Reel	Per EIA 481-1A specs	Plastic / White	
Label	HT standard	Paper	
Packing bag	220x240mm	Aluminum laminated bag/ no-zipper	One reel per bag
Carton	HT standard	Paper	Non-specified
Others:			
Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of I_v , λ_D and V_f . Each reel has a label identifying its specification; the immediate box consists of a product label as well.			


Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 9/13

Dry Pack

All SMD optical devices are **MOISTURE SENSITIVE**. Avoid exposure to moisture at all times during transportation or storage. Every reel is packaged in a moisture protected anti-static bag. Each bag is properly sealed prior to shipment.

Upon request, a humidity indicator will be included in the moisture protected anti-static bag prior to shipment.

The packaging sequence is as follows:




Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 10/13

Reflow Soldering

- Recommended tin glue specifications: melting temperature in the range of 178~192 °C
- The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):

Lead-free Solder Profile



Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 11/13

Precautions

1. Avoid exposure to moisture at all times during transportation or storage.
2. Anti-Static precaution must be taken when handling GaN, InGaN, and AlInGaP products.
3. It is suggested to connect the unit with a current limiting resistor of the proper size. Avoid applying a reverse voltage beyond the specified limit.
4. Avoid operation beyond the limits as specified by the absolute maximum ratings.
5. Avoid direct contact with the surface through which the LED emits light.
6. If possible, assemble the unit in a clean room or dust-free environment.

Reworking

- Rework should be completed within 5 seconds under 260 °C.
- The iron tip must not come in contact with the copper foil.
- Twin-head type is preferred.

Cleaning

Following are cleaning procedures after soldering:

- An alcohol-based solvent such as isopropyl alcohol (IPA) is recommended.
- Temperature x Time should be 50°C x 30sec. or <30°C x 3min
- Ultra sonic cleaning: < 15W/ bath; bath volume ≤ 1liter
- Curing: 100 °C max, <3min

Cautions of Pick and Place

- Avoid stress on the resin at elevated temperature.
- Avoid rubbing or scraping the resin by any object.
- Electro-static may cause damage to the component. Please ensure that the equipment is properly grounded. Use of an ionizer fan is recommended.

Official Product	Product: HT-110IRAJ-XXXX			Data Sheet No.
Tentative Product	*****			HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		August 20, 2009	Version of 1.0	Page 12/13

Revision History

Changes since last revision	Page	Version No.	Revision Date
Initial Release – XXXX		1.0	08-20-2009

Official Product	Product: HT-110IRAJ-XXXX		Data Sheet No.
Tentative Product	*****		HT-110IRAJ-XXXX
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	August 20, 2009	Version of 1.0	Page 13/13