

## NOTES

1 - UNIT INCLUDES V3-1371 BASIC SWITCH WITH PLUNGER  
^ SEAL BOLT (4)

2 LEVER FINISHED WITH AN ELECTROSTATIC POWDER COATING (BLACK)  
3 MEASURED FROM N.O./N.C. TERMINALS TO POINT WHERE ATTACHED TO  
RECEPTACLE PINS

4 WIRE SHALL BE PER MIL-W-22759/16 AWG 20

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

**MICRO SWITCH**  
a Honeywell Division


## ASSEMBLY - TOGGLE SWITCH

CATALOG LISTING

15AT62

---

THIRD ANGLE PROJECTION



DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED  
TOLERANCES ARE

ONE PLACE      (.0)       $\pm .030$

TWO PLACES      (.00)       $\pm .015$

THREE PLACES (.000)  $\pm .005$

ANGLES ±

WEIGHT

ANSI Y14.5M-1982 APPLIES

FED. MFG. CODE 91929

15AT62

DRAWING NUMBER

7

---

PTC/CAD 2D  
DRAWN

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[15AT62](#)