

HCMOS 5x3.2mm 2.5V SMD Oscillator



Model: F540L SERIES

RoHS Compliant / Pb Free

Rev. 5/7/2009

Page 1 of 2

http://www.foxonline.com/need_a_sample.htm

Need a
Sample®

FEATURES

- 2.5V Operation
- HCMOS Output
- Standby Function
- Low Power Consumption
- Tape and Reel (1,000 pcs. STD)

XpressO® Equivalent
FXO-HC52

Why XpressO?
Lower Cost, Faster Delivery, Low Jitter!

• PART NUMBER SELECTION [Learn More](#) - Internet Required

Part Number	Model Number	Frequency Stability ¹	Operating Temperature (°C)	Frequency Range (MHz)
558-Frequency-xxxxx	F540L	±100PPM	-10 ~ +70	1.800 ~ 50.000
559-Frequency-xxxxx	F540LR	±100PPM	-40 ~ +85	1.800 ~ 50.000
560-Frequency-xxxxx	F545L	±50PPM	-10 ~ +70	1.800 ~ 50.000
561-Frequency-xxxxx	F545LR	±50PPM	-40 ~ +85	1.800 ~ 50.000
562-Frequency-xxxxx	F546L	±25PPM	-10 ~ +70	1.800 ~ 50.000
563-Frequency-xxxxx	F546LR	±25PPM*	-40 ~ +85	1.800 ~ 50.000
564-Frequency-xxxxx	F548L	±20PPM*	-10 ~ +70	1.800 ~ 50.000

• ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	1.800 ~ 50.000 MHz
Storage Temperature Range (T _{STG})	-55°C ~ +125°C
Supply Voltage (V _{DD})	2.5V ± 5%
Input Current (I _{DD})	
1.800 ~ 32.000 MHz	10mA
32.000+ ~ 50.000 MHz	12mA
Output Symmetry (50% V _{DD})	45% ~ 55%
Rise Time (10% ~ 90% V _{DD}) (T _R)	5nS
Fall Time (90% ~ 10% V _{DD}) (T _F)	5nS
Output Voltage (V _{OL})	10% V _{DD}
(V _{OH})	90% V _{DD} Min
Output Current (I _{OL})	4mA Min
(I _{OH})	4mA Min
Output Load (HCMOS)	15pF
Standby Current	10µa
Start-up Time (T _s)	10mS
Output Disable Time ²	150nS
Output Enable Time ²	10mS


¹ Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock, and vibration. *Excludes Shock/Vibration

² An internal pullup resistor from pin 1 to pin 4 allows active output if pin 1 is left open.

Drawing is for reference to critical specifications defined by size measurements.

Note: A 0.01µF capacitor should be placed between V_{DD} (Pin 4) and GND (Pin2) to minimize power supply noise.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary. All specifications subject to change without notice.



• ENABLE / DISABLE FUNCTION

INH (Pin 1)	OUTPUT (Pin 3)
OPEN ²	ACTIVE
'1' Level V _{IH} ≥ 70% V _{DD}	ACTIVE
'0' Level V _{IL} ≤ 30% V _{DD}	High Z

HCMOS 5x3.2mm 2.5V SMD Oscillator



Model: F540L SERIES

RoHS Compliant / Pb Free

Rev. 5/7/2009

Page 2 of 2

http://www.foxonline.com/need_a_sample.htm



• TAPE SPECIFICATIONS (millimeters)							
MODEL	A	B	C	D	E	F	STD Reel QTY
F540L Series	Ø1.5	4.0	8.0	5.5	12.0	1.5	1,000

• REEL SPECIFICATIONS (millimeters)							
MODEL	G	H	I	J	K	L	M
F540L Series	2.0	Ø13	Ø21	Ø62	Ø180	13.5	2.0

