

CONFIDENTIAL. THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF COOPER INDUSTRIES, INC. IT IS NOT FOR PUBLIC DISCLOSURE. POSSESSION OF THE INFORMATION DOES NOT CONVEY ANY RIGHT TO LOAN, SELL OR DISCLOSE THE INFORMATION. UNAUTHORIZED REPRODUCTION OR USE OF THE INFORMATION IS PROHIBITED. THIS DOCUMENT IS TO BE RETURNED TO COOPER INDUSTRIES, INC. UPON COMPLETION OF THE PURPOSE FOR WHICH IT IS LOANED OR UPON REQUEST. COPYRIGHT Cooper Industries, Inc. This is an unpublished work. The disclosure of this work is limited to select personnel. Further dissemination or disclosure to the public is PROHIBITED. This unpublished work is protected by Federal Copyright law and all rights thereunder are reserved by Cooper Industries, Inc.	SCALE 1x	UNLESS OTHERWISE SPECIFIED TOLERANCES TO BE: METRIC $\pm .13\text{mm}$ INCHES $\pm .005"$ ANGULAR $\pm 2^\circ$	DATE 9-25-01	NO. BFW 8-80
	TITLE FUSE WIRE		SUP. NO. BFW 7-200 H	
THIRD ANGLE PROJECTION 		DATED 11-16-94		DWG. JPH
INDICATES CRITICAL DIMENSION OR FEATURE 		CK. P.L.		REV. I
"INCHES (OR US UNITS) IS THE PRIMARY UNIT OF MEASURE" METRIC(mm) [INCHES]		PAGE 1 OF 2		AO1111
COOPER Bussmann St. Louis, MO 63178				
C/F NO. 44093		DISTRIBUTION 56		A

ⓐⓑ REVISED &
REDRAWN

MATERIAL:

COMPOSITION: 98.25 - 98.75% LEAD
1.25 - 1.75% ANTIMONY

580°F SOLIDUS
600°F LIQUIDUS

PACKAGING SPEC

PART NUMBER	AMP RATING	DIA.	TOLERANCE ±	FEET PER LB.	SPOOL CONTAINS	TURNS ON SPOOL	SPOOL NO.
BFW 8	8	1.24 .049	.05 .002	109	1 LB.		7788
BFW 10	10	1.40 .055		85			
BFW 15	15	1.73 .068		57			
BFW 20	20	2.08 .082		39			
BFW 25	25	2.39 .094		30			
BFW 30	30	2.62 .103		25			
BFW 35	35	2.87 .113		20.4			
BFW 40	40	3.10 .122		17.7			
BFW 45	45	3.28 .129		15.8			
BFW 50	50	3.48 .137		14			
BFW 60	60	4.01 .158		10.5			
BFW 80	80	4.80 .189		7.4			