



## Features:

- A range of line and hand set insulation piercing plugs designed to accept cordage to BT specification CW1311.
- They are available in 4 and 6 way and are moulded with 'A' polarisation, and sensors etc.
- Designed to allow new style telephones the total flexibility of being moved from socket to socket like any other piece of equipment.
- Equally suitable for other applications using flexible cords, i.e keyboards, hand held controllers and sensors etc.

## Specifications:

Maximum working voltage	: 200V dc.
Current rating	: 250mA dc per contact.
Insulation resistance	: 100M $\Omega$ at 500V dc.
Maximum contact resistance	: <120m $\Omega$ .
Contact life	: 1000 mating cycles.
Contact material	: Gold plated phosphor bronze.
Body material	: Natural polyester.

## Part Number Table

Description	Part Number
Plug, 431A, 4 Way	A006
Plug, 631A, 6 Way	A007
Plug, 430A, 4 Way	A016
Plug, 630A, 6 Way	A015

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-SIGNAL is the registered trademark of the Group. © Premier Farnell plc 2009.