


2-215876-1 Product Details

Share

Print

Email



2-215876-1

TE Internal Number: 2-215876-1

Pending Obsolescence

Search for Replacement Parts

View 3D PDF

PCB Mounted Jacks - Single Port, Multi-port and Stacked

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

• Connector

• Preloaded

• Single Port Configuration

• 1 x 1 Jack Configuration

• Jack Type = RJ25

View all Features

Quick Links

▶ Pricing & Availability

▶ Search for Tooling

▶ Product Feature Selector

▶ Contact Us About This Product

Add to My Part List

Request Sample

Find Similar Products

Buy Product

Documentation & Additional Information	
<div><div>Product Drawings:</div><div><div>• MODULAR JACK, SIDE ENTRY, 6/6 FOR PRINTED CIRCUIT BOARD (PDF, English)</div></div></div> <div><div>Catalog Pages/Data Sheets:</div><div><div>• None Available</div></div></div> <div><div>Product Specifications:</div><div><div>• None Available</div></div></div> <div><div>Application Specifications:</div><div><div>• None Available</div></div></div> <div><div>Instruction Sheets:</div><div><div>• None Available</div></div></div> <div><div>CAD Files: (CAD Format & Compression Information)</div><div><div>• 2D Drawing (DXF, Version L)</div><div>• 3D Model (IGES, Version L)</div><div>• 3D Model (STEP, Version L)</div></div></div>	<div><div>Additional Information:</div><div><div>• Product Line Information</div></div></div> <div><div>Related Products:</div><div><div>• Tooling</div></div></div>
<div>List all Documents</div>	

Product Features (Please use the Product Drawing for all design activity)	
<div><div>Product Type Features:</div><div><div>• Product Type = Connector</div><div>• Jack Type = RJ25</div><div>• PCB Mounting Orientation = Side Entry (Right Angle)</div><div>• PCB Mount Style = Through Hole</div><div>• Termination Method to PC Board = Solder</div><div>• Performance Category = Cat 3</div><div>• LED = Without</div><div>• Grounding Options = Without</div><div>• Panel Stops = Without</div><div>• Keyed = No</div><div>• Profile = Low</div><div>• Color = Black</div><div>• Latch Style = Standard</div></div></div> <div><div>Mechanical Attachment:</div><div><div>• Panel Mount Retention = With</div><div>• Flanged = No</div></div></div> <div><div>Electrical Characteristics:</div><div><div>• Shielded = No</div></div></div> <div><div>Termination Features:</div><div><div>• Solder Tail Contact Plating = Tin over Nickel</div></div></div> <div><div>Dimensions:</div><div><div>• Height (mm [in]) = 11.50 [0.453]</div><div>• PCB Tail Length (mm [in]) = 3.20 [0.126]</div><div>• PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]</div></div></div> <div><div>Body Features:</div><div><div>• Inverted Jack Face = No</div></div></div>	<div><div>Contact Features:</div><div><div>• Contact Plating, Mating Area, Material = Conforms to Product Requirements based on Product Specification 108-19064, Gold or Gold Flash over Palladium Nickel</div><div>• Contact Base Material = Phosphor Bronze</div></div></div> <div><div>Housing Features:</div><div><div>• Housing Material = PA 4.6</div><div>• UL Flammability Rating = UL 94V-0</div></div></div> <div><div>Configuration Features:</div><div><div>• Preloaded = Yes</div><div>• Port Configuration = Single</div><div>• Jack Configuration = 1 x 1</div><div>• Number of Positions = 6</div><div>• Number of Contacts Loaded = 6</div></div></div> <div><div>Industry Standards:</div><div><div>• RoHS/ELV Compliance = RoHS compliant, ELV compliant</div><div>• Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</div><div>• RoHS/ELV Compliance History = Converted to comply with RoHS directive</div></div></div> <div><div>Packaging Features:</div><div><div>• Packaging Method = Loose Piece/Bulk</div><div>• Packaging Quantity = 1,000</div></div></div> <div><div>Product Availability:</div><div><div>• Region = Asia, North America</div></div></div> <div><div>Other:</div><div><div>• Brand = AMP</div><div>• Comment = True positioning of the solder tines may be affected by bulk packaging.</div></div></div>