







Copyright FCI.

PRODUCT NO.
10005639-XXXXX



PART NO.	DIM "A"	DESCRIPTION
10005639-1****	4.00	1.8V
10005639-2****	3.00	2.5V
10005639-3****	5.00	X.XV




spec ref *				dr		Rick Bian	2010/07/08	projection 	mm 	size		A4	scale		0.500
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng				Nickor Zuo	2011/11/30	ecn no ELX-DG-008280-1			
-						chr				Jian Huang	2011/12/02				
-						appr				Pei-Ming Zheng	2011/12/02				
surface			linear	0.X	±0.38		title DDR II 240P V/T DDR II 240P METAL CLIP ASS'Y				dwg no 10005639	rev X			
				0.XX	±0.25										
				0.XXX	±0.13										
-		angular	0°	±2°	www.fci.com		cat. no.		*	Product - Customer Drw				sheet 1 of 4	

Print File - REV C - 2009-06-09

Technical drawing of a connector assembly, showing front and side views with dimensions and callouts.



Front View Dimensions:

- Overall width: 133.35 ± 0.15
- Overall height: 25.4
- Pin #1 (ACK PIN #121) to Pin #64 distance: 63.00
- Pin #64 to Pin #65 distance: 5.00
- Pin #65 to Pin #120 (BACK PIN #240) distance: 55.00
- Pin #1 to Pin #64 distance: 123.0
- Pin #65 to Pin #120 (BACK PIN #240) distance: 123.0
- Pin #120 (BACK PIN #240) to Pin #121 distance: 5.175
- Pin #121 to Pin #122 distance: 5.175
- Pin #122 to Pin #123 distance: 5.175
- Pin #123 to Pin #124 distance: 5.175
- Pin #124 to Pin #125 distance: 5.175
- Pin #125 to Pin #126 distance: 5.175
- Pin #126 to Pin #127 distance: 5.175
- Pin #127 to Pin #128 distance: 5.175
- Pin #128 to Pin #129 distance: 5.175
- Pin #129 to Pin #130 distance: 5.175
- Pin #130 to Pin #131 distance: 5.175
- Pin #131 to Pin #132 distance: 5.175
- Pin #132 to Pin #133 distance: 5.175
- Pin #133 to Pin #134 distance: 5.175
- Pin #134 to Pin #135 distance: 5.175
- Pin #135 to Pin #136 distance: 5.175
- Pin #136 to Pin #137 distance: 5.175
- Pin #137 to Pin #138 distance: 5.175
- Pin #138 to Pin #139 distance: 5.175
- Pin #139 to Pin #140 distance: 5.175
- Pin #140 to Pin #141 distance: 5.175
- Pin #141 to Pin #142 distance: 5.175
- Pin #142 to Pin #143 distance: 5.175
- Pin #143 to Pin #144 distance: 5.175
- Pin #144 to Pin #145 distance: 5.175
- Pin #145 to Pin #146 distance: 5.175
- Pin #146 to Pin #147 distance: 5.175
- Pin #147 to Pin #148 distance: 5.175
- Pin #148 to Pin #149 distance: 5.175
- Pin #149 to Pin #150 distance: 5.175
- Pin #150 to Pin #151 distance: 5.175
- Pin #151 to Pin #152 distance: 5.175
- Pin #152 to Pin #153 distance: 5.175
- Pin #153 to Pin #154 distance: 5.175
- Pin #154 to Pin #155 distance: 5.175
- Pin #155 to Pin #156 distance: 5.175
- Pin #156 to Pin #157 distance: 5.175
- Pin #157 to Pin #158 distance: 5.175
- Pin #158 to Pin #159 distance: 5.175
- Pin #159 to Pin #160 distance: 5.175
- Pin #160 to Pin #161 distance: 5.175
- Pin #161 to Pin #162 distance: 5.175
- Pin #162 to Pin #163 distance: 5.175
- Pin #163 to Pin #164 distance: 5.175
- Pin #164 to Pin #165 distance: 5.175
- Pin #165 to Pin #166 distance: 5.175
- Pin #166 to Pin #167 distance: 5.175
- Pin #167 to Pin #168 distance: 5.175
- Pin #168 to Pin #169 distance: 5.175
- Pin #169 to Pin #170 distance: 5.175
- Pin #170 to Pin #171 distance: 5.175
- Pin #171 to Pin #172 distance: 5.175
- Pin #172 to Pin #173 distance: 5.175
- Pin #173 to Pin #174 distance: 5.175
- Pin #174 to Pin #175 distance: 5.175
- Pin #175 to Pin #176 distance: 5.175
- Pin #176 to Pin #177 distance: 5.175
- Pin #177 to Pin #178 distance: 5.175
- Pin #178 to Pin #179 distance: 5.175
- Pin #179 to Pin #180 distance: 5.175
- Pin #180 to Pin #181 distance: 5.175
- Pin #181 to Pin #182 distance: 5.175
- Pin #182 to Pin #183 distance: 5.175
- Pin #183 to Pin #184 distance: 5.175
- Pin #184 to Pin #185 distance: 5.175
- Pin #185 to Pin #186 distance: 5.175
- Pin #186 to Pin #187 distance: 5.175
- Pin #187 to Pin #188 distance: 5.175
- Pin #188 to Pin #189 distance: 5.175
- Pin #189 to Pin #190 distance: 5.175
- Pin #190 to Pin #191 distance: 5.175
- Pin #191 to Pin #192 distance: 5.175
- Pin #192 to Pin #193 distance: 5.175
- Pin #193 to Pin #194 distance: 5.175
- Pin #194 to Pin #195 distance: 5.175
- Pin #195 to Pin #196 distance: 5.175
- Pin #196 to Pin #197 distance: 5.175
- Pin #197 to Pin #198 distance: 5.175
- Pin #198 to Pin #199 distance: 5.175
- Pin #199 to Pin #200 distance: 5.175
- Pin #200 to Pin #201 distance: 5.175
- Pin #201 to Pin #202 distance: 5.175
- Pin #202 to Pin #203 distance: 5.175
- Pin #203 to Pin #204 distance: 5.175
- Pin #204 to Pin #205 distance: 5.175
- Pin #205 to Pin #206 distance: 5.175
- Pin #206 to Pin #207 distance: 5.175
- Pin #207 to Pin #208 distance: 5.175
- Pin #208 to Pin #209 distance: 5.175
- Pin #209 to Pin #210 distance: 5.175
- Pin #210 to Pin #211 distance: 5.175
- Pin #211 to Pin #212 distance: 5.175
- Pin #212 to Pin #213 distance: 5.175
- Pin #213 to Pin #214 distance: 5.175
- Pin #214 to Pin #215 distance: 5.175
- Pin #215 to Pin #216 distance: 5.175
- Pin #216 to Pin #217 distance: 5.175
- Pin #217 to Pin #218 distance: 5.175
- Pin #218 to Pin #219 distance: 5.175
- Pin #219 to Pin #220 distance: 5.175
- Pin #220 to Pin #221 distance: 5.175
- Pin #221 to Pin #222 distance: 5.175
- Pin #222 to Pin #223 distance: 5.175
- Pin #223 to Pin #224 distance: 5.175
- Pin #224 to Pin #225 distance: 5.175
- Pin #225 to Pin #226 distance: 5.175
- Pin #226 to Pin #227 distance: 5.175
- Pin #227 to Pin #228 distance: 5.175
- Pin #228 to Pin #229 distance: 5.175
- Pin #229 to Pin #230 distance: 5.175
- Pin #230 to Pin #231 distance: 5.175
- Pin #231 to Pin #232 distance: 5.175
- Pin #232 to Pin #233 distance: 5.175
- Pin #233 to Pin #234 distance: 5.175
- Pin #234 to Pin #235 distance: 5.175
- Pin #235 to Pin #236 distance: 5.175
- Pin #236 to Pin #237 distance: 5.175
- Pin #237 to Pin #238 distance: 5.175
- Pin #238 to Pin #239 distance: 5.175
- Pin #239 to Pin #240 distance: 5.175
- Pin #240 to Pin #241 distance: 5.175
- Pin #241 to Pin #242 distance: 5.175
- Pin #242 to Pin #243 distance: 5.175
- Pin #243 to Pin #244 distance: 5.175
- Pin #244 to Pin #245 distance: 5.175
- Pin #245 to Pin #246 distance: 5.175
- Pin #246 to Pin #247 distance: 5.175
- Pin #247 to Pin #248 distance: 5.175
- Pin #248 to Pin #249 distance: 5.175
- Pin #249 to Pin #250 distance: 5.175
- Pin #250 to Pin #251 distance: 5.175
- Pin #251 to Pin #252 distance: 5.175


Prof/E File : REV C : 2009-06-09



Copyright FCI.



RECOMMENDED CIRCUIT BOARD HOLE LAYOUT

spec ref *				dr Rick Bian 2010/07/08		projection 	mm 	size A4	scale 0.500
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng Nickor Zuo 2011/11/30				ecn no ELX-DG-008280-1	
-				chr Jian Huang 2011/12/02					
-				appr Pei-Ming Zheng 2011/12/02				product family	
surface 	linear	0.X	±0.38		title DDR II 240P V/T DDR II 240P METAL CLIP ASS'Y			dwg no 10005639	rev X
		0.XX	±0.25						
		0.XXX	±0.13						
-	angular	0°	±2°	www.fci.com	cat. no. *		Product - Customer Drw		sheet 3 of 4

Print File - REV C - 2009-06-09



Copyright FCI.

10005639 - □ □ □ □ □

PLATING

STYLE : MECHAMICAL KEYING

- 1 : 1.8 VOLT. W/ CENTER KEY#1
- 2 : 2.5 VOLT. W/ LEFT KEY#1
- 3 : X.X VOLT. W/ RIGHT KEY#1

METAL CLIP

- 1 : WITH METAL CLIP + DIM "D"=3.05
- 2 : WITH METAL CLIP + DIM "D"=3.56
- 3 : WITH METAL CLIP + DIM "D"=3.43

TAIL LENGTH

CODE	DIM "B"
0	2.54
1	2.67
2	3.18
3	4.00

COLOR OF HOUSING AND EJECTOR

- 0 : BLACK HOUSING + IVORY EJECTOR
- 1 : BLUE HOUSING + IVORY EJECTOR
- 2 : BLACK HOUSING + BLACK EJECTOR
- 3 : PURPLE HOUSING + IVORY EJECTOR
- 4 : ORANGE HOUSING + IVORY EJECTOR
- 5 : GREEN HOUSING + IVORY EJECTOR
- 6 : RED HOUSING + IVORY EJECTOR
- 7 : IVORY HOUSING + IVORY EJECTOR
- 8 : YELLOW HOUSING + IVORY EJECTOR
- 9 : IVORY HOUSING + BLACK EJECTOR

CODE	CONTACT	SOLDERTAIL	UNDERPLATE
1	10u" (0.25um) MIN. GOLD	100u" (2.54um) MIN. TIN/LEAD	50u" (1.27um) MIN. NICKEL OVERALL
2	15u" (0.38um) MIN. GOLD		
3	30u" (0.76um) MIN. GOLD		
4	3u" (0.076um) MIN. GOLD	100u" (2.54um) MIN. 100% TIN	50u" (1.27um) MIN. NICKEL OVERALL
6LF	10u" (0.25um) MIN. GOLD		
7LF	15u" (0.38um) MIN. GOLD		
8LF	30u" (0.76um) MIN. GOLD	GOLD FLASH	
9LF	3u" (0.076um) MIN. GOLD		
8HLF	30u" (0.76um) MIN. GOLD		

NOTES:

- MATERIAL:
HOUSING: HIGH PERFORMANCE RESINS, GLASS FILLED UL94V-0 RATED.
EJECTOR: HIGH PERFORMANCE RESINS, GLASS FILLED UL94V-0 RATED.
TERMINAL: PHOSPHOR BRONZE.
METAL CLIP: COPPER ALLOY.
- FCI LOGO TO BE APPROXIMATELY LOCATED AS SHOWN ON PRINT.
- PRODUCT SPECIFICATION: GS-12-251.
- PACKAGING SPECIFICATION: GS-14-899.
- CARD THICKNESS APPLIES ACROSS TABS AND INCLUDES PLATING AND/OR METALIZATION.
- 3.00 mm MINIMUM APPLIES TO BOTH 4.00 mm WIDE NOTCH LENGTH AND COMPONENT KEEP-OUT AREA.
- LEADING EDGE OF CONTACT PADS SPECIFIED BY THE KEEP OUT ZONE SHALL BE FREE OF BURRS AND EXTERNAL TIE BARS. FOR OPTIMUM PERFORMANCE, THE TIE BAR IS TO BE ON AN INTERNAL LAYER SO THAT THE REMNANT CANNOT CAUSE CONTACT DAMAGE.
- THE DATE CODE IS SHOWN "MM-DD-YY*" "*" MEANS PRODUCTION LINE CODE.
- THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- THE HOUSING WILL WITH STAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.

spec ref *		dr Rick Bian		2010/07/08		projection mm	size A4	scale 0.500	
tolerance std - -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng Nickor Zuo			2011/11/30		
				chr Jian Huang			2011/12/02		
				appr Pei-Ming Zheng			2011/12/02		
product family						ecn no ELX-DG-008280-1		rel level Released	
surface ✓ -	linear	0.X	±0.38		title DDRII 240P V/T DDRII 240P METAL CLIP ASS'Y			dwg no 10005639	rev X
		0.XX	±0.25						
		0.XXX	±0.13						
	angular	0°	±2°	www.fci.com	cat. no. *		Product - Customer Drw		sheet 4 of 4