

SMALL-SIGNAL AMPLIFIERS (PRO-ELECTRON SERIES)

Type No.	POLARITY	P _D T _A = 25°C (mW)	V _(BR) CBO Volts	V _(BR) CEO Volts	V _(BR) EBO Volts	DC CURRENT GAIN (h _{FE})				V _{CE(SAT)}		f _T Min. (MHz)	C _{cb} Max. (pF)	N.F. Max. (dB)
						Conditions		Limits						
						I _C (mA)	V _{CE} Volts	Min.	Max.	I _C (mA)	Max. Volts			
BC182A	NPN	300	60	50	6	2	5	120	220	100	0.60	150	5	10
BC182B	NPN	300	60	50	6	2	5	180	460	100	0.60	150	5	10
BC212A	PNP	300	60	50	5	2	5	120	220	100	0.60	200	6	10
BC212B	PNP	300	60	50	5	2	5	180	460	100	0.60	200	6	10
BC237A	NPN	300	50	45	6	2	5	120	220	10	0.20	150	4.5	10
BC237B	NPN	300	50	45	6	2	5	180	460	10	0.20	150	4.5	10
BC238A	NPN	300	30	20	5	2	5	120	220	10	0.20	150	4.5	10
BC238B	NPN	300	30	20	5	2	5	180	460	10	0.20	150	4.5	10
BC238C	NPN	300	30	20	5	2	5	380	800	10	0.20	150	4.5	10
BC239B	NPN	300	30	20	5	2	5	180	460	10	0.20	150	4.5	4
BC239C	NPN	300	30	20	5	2	5	380	800	10	0.20	150	4.5	4
BC307A	PNP	300	45	45	5	2	5	120	220	10	0.20	150	6	10
BC307B	PNP	300	45	45	5	2	5	180	460	10	0.20	150	6	10
BC308A	PNP	300	25	25	5	2	5	120	220	10	0.20	150	6	10
BC308B	PNP	300	25	25	5	2	5	180	460	10	0.20	150	6	10
BC308C	PNP	300	25	25	5	2	5	380	800	10	0.20	150	6	10
BC309B	PNP	300	20	20	5	2	5	180	460	10	0.20	150	6	4
BC309C	PNP	300	20	20	5	2	5	380	800	10	0.20	150	6	4
BC413B	NPN	300	45	30	5	2	5	180	460	10	0.6	250	2.5	2.5
BC413C	NPN	300	45	30	5	2	5	380	800	10	0.6	250	2.5	2.5
BC414B	NPN	300	50	45	5	2	5	180	460	10	0.6	250	2.5	2.5
BC414C	NPN	300	50	45	5	2	5	380	800	10	0.6	250	2.5	2.5
BC415A	PNP	300	45	35	5	2	5	120	220	10	0.6	200	4.5	2.0
BC415B	PNP	300	45	35	5	2	5	180	460	10	0.6	200	4.5	2.0
BC415C	PNP	300	45	35	5	2	5	380	800	10	0.6	200	4.5	2.0
BC416A	PNP	300	50	45	5	2	5	120	220	10	0.6	200	4.5	2.0
BC416B	PNP	300	50	45	5	2	5	180	460	10	0.6	200	4.5	2.0
BC416C	PNP	300	50	45	5	2	5	380	800	10	0.6	200	4.5	2.0
BC327-16	PNP	300	45	45	5	100	1	100	250	500	0.7	100	12	—
BC327-25	PNP	300	45	45	5	100	1	160	400	500	0.7	100	12	—
BC327-40	PNP	300	45	45	5	100	1	250	630	500	0.7	100	12	—
BC328-16	PNP	300	25	25	5	100	1	100	250	500	0.7	100	12	—
BC328-25	PNP	625	25	25	5	100	1	160	400	500	0.7	100	12	—
BC328-40	PNP	625	25	25	5	100	1	250	630	500	0.7	100	12	—
BC337-16	NPN	625	45	45	5	100	1	100	250	500	0.7	100	12	—
BC337-25	NPN	625	45	45	5	100	1	160	400	500	0.7	100	12	—
BC337-40	NPN	625	45	45	5	100	1	250	630	500	0.7	100	12	—
BC338-16	NPN	625	25	25	5	100	1	100	250	500	0.7	100	12	—
BC338-25	NPN	625	25	25	5	100	1	160	400	500	0.7	100	12	—
BC338-40	NPN	625	25	25	5	100	1	250	630	500	0.7	100	12	—
BC167A	NPN	300	50	45	6	2	5	125	260	10	0.20	150	4.5	10
BC167B	NPN	300	50	45	6	2	5	240	500	10	0.20	150	4.5	10
BC168A	NPN	300	30	20	5	2	5	125	260	10	0.20	150	4.5	10
BC168B	NPN	300	30	20	5	2	5	240	500	10	0.20	150	4.5	10
BC168C	NPN	300	30	20	5	2	5	450	900	10	0.20	150	4.5	10
BC169B	NPN	300	30	20	5	2	5	240	500	10	0.20	150	4.5	4
BC169C	NPN	300	30	20	5	2	5	450	900	10	0.20	150	4.5	5
BC257A	PNP	300	45	45	5	2	5	125	260	10	0.20	150	6	10
BC257B	PNP	300	45	45	5	2	5	240	500	10	0.20	150	6	10
BC258A	PNP	300	25	25	5	2	5	125	260	10	0.20	150	6	10
BC258B	PNP	300	25	25	5	2	5	240	500	10	0.20	150	6	10
BC258C	PNP	300	25	25	5	2	5	450	900	10	0.20	150	5	10
BC259B	PNP	300	20	20	5	2	5	240	500	10	0.20	150	6	4
BC259C	PNP	300	20	20	5	2	5	450	900	10	0.20	150	6	4



TO-92
Formed
to
TO-18
(CBE
Pinning)



TO-92
Package
(ECB
Pinning)