

- Products Overview
- Product Search**
- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFHSTT Heat Sh.
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Current refinements (click  to remove) Search Tips

Part Number > HSTT25-48-Q6

Your search criteria matched only one product, shown below



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05 -48-QC). Contact customer service for additional color information.

Meets the material performance only of Mil Spec AMS-DTL-23053/5 Class 1(Colors), Class 2 (Clear)

Part Number	HSTT2548-Q6
RoHS Compliancy Status	Compliant
Part Description	Thin Wall Polyolefin Heat Shrink
Material	Flame retardant polyolefin cross-linked except clear
Color	Blue
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 1 (material performance only)
UL Recognized	E122770
Length (ft.)	4
Length (m)	1.2
CE Compliant	No
Max. Recovered I.D. (In.)	0.125
Max. Recovered I.D. (mm)	3.2
Min. Expanded I.D. (In.)	0.250
Min. Expanded I.D. (mm)	6.4
Nominal Diameter (In.)	0.250
Nominal Diameter / Size	0.250
Nominal Recovered Wall Thickness (In.)	0.025
Nominal Recovered Wall Thickness (mm)	0.6
Pricing Description	Heat Shrink Thin, .25"(6.4mm) Dia, Blue
Shrink Ratio	2:1
Temperature Range	-67°F– 275°F (-55°C– 135°C)
Type	Heat Shrink
Min. Order UOM	PC
Min. Order Qty.	25
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.