


Wirewound Resistors, Commercial Power, Four Terminal, Low Value




FEATURES

- Low Inductance
- Extremely low resistance values
- Current sensing
- Low temperature coefficients
- High power to size ratio
- Ceramic cases are available with circuit board stand-offs (designated with a -3 model ending)
- Superior surge capability
- Complete welded construction
- Special inorganic potting compound and ceramic case provide high thermal conductivity in a fireproof package



RoHS*
COMPLIANT

SCHEMATIC



STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	HISTORICAL MODEL	POWER RATING $P_{40^{\circ}\text{C}}$ W	RESISTANCE RANGE Ω $\pm 5\%$ STANDARD, $\pm 3\%$ AVAILABLE	WEIGHT (TYPICAL) g
CPSL03...5	CPSL-3-5	3	0.01 - 0.10	4.0
CPSL03...3	CPSL-3-3	3	0.01 - 0.10	4.2
CPSL05...5	CPSL-5-5	5	0.01 - 0.10	5.2
CPSL05...3	CPSL-5-3	5	0.01 - 0.10	5.4
CPSL07...5	CPSL-7-5	7	0.01 - 0.10	7.6
CPSL10...5	CPSL-10-5	10	0.01 - 0.10	10.2
CPSL15...5	CPSL-15-5	15	0.01 - 0.10	18.9

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	CPSL RESISTOR CHARACTERISTICS
Temperature Coefficient	ppm/ $^{\circ}\text{C}$	± 100 maximum
Short Time Overload	-	5 x rated power for 5 seconds
Maximum Working Voltage	V	$(P \times R)^{1/2}$
Operating Temperature Range	$^{\circ}\text{C}$	- 65/+ 275
Terminal Strength	lb	10 minimum
Dielectric Withstanding Voltage	V_{AC}	1000

GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: CPSL05R0500JB143 (preferred part numbering format)

C P S L 0 5 R 0 5 0 0 J B 1 4 3

GLOBAL MODEL

CPSL03
CPSL05
CPSL07
CPSL10
CPSL15

VALUE

R = Decimal
R1000 = 0.10 Ω

TOLERANCE

F = $\pm 1.0\%$
G = $\pm 2.0\%$
H = $\pm 3.0\%$
J = $\pm 5.0\%$
K = $\pm 10\%$

PACKAGING

E14 = Lead (Pb)-free bulk
E31 = Lead (Pb)-free four layer bulk
B14 = Tin/lead bulk
B31 = Tin/lead four layer bulk

SPECIAL

Dash Number)
(up to 3 digits)
From 1-999 as applicable

Historical Part Number example: CPSL-5-3 0.05 Ω 5% B14 (will continue to be accepted)

CPSL-5-3

0.05 Ω

5%

B14

HISTORICAL MODEL


RESISTANCE VALUE

TOLERANCE CODE

PACKAGING

* Pb containing terminations are not RoHS compliant, exemptions may apply

DIMENSIONS



GLOBAL MODEL	DIMENSIONS in inches [millimeters]					
	A* ± 0.031 [0.794]	B ± 0.031 [0.794]	C ± 0.031 [0.794]	D ± 0.031 [0.794]	E ± 0.001 [0.025]	F ± 0.063 [1.59]
CPSL03...5	0.875 [22.22]	0.313 [7.94]	0.313 [7.94]	-	0.036 [0.914]	0.563 [14.30]
CPSL03...3	0.875 [22.22]	0.313 [7.94]	0.313 [7.94]	0.375 [9.52]	0.036 [0.914]	0.563 [14.30]
CPSL05...5	0.875 [22.22]	0.375 [9.52]	0.344 [8.73]	-	0.036 [0.914]	0.563 [14.30]
CPSL05...3	0.875 [22.22]	0.375 [9.52]	0.344 [8.73]	0.438 [11.11]	0.036 [0.914]	0.563 [14.30]
CPSL07...5	1.391 [35.32]	0.375 [9.52]	0.344 [8.73]	-	0.036 [0.914]	1.000 [25.40]
CPSL10...5	1.875 [47.62]	0.375 [9.52]	0.344 [8.73]	-	0.036 [0.914]	1.375 [34.93]
CPSL15...5	1.875 [47.62]	0.500 [12.70]	0.500 [12.70]	-	0.036 [0.914]	1.375 [34.93]

* Potting compound may extend outside of ceramic case up to 0.060 [1.52] maximum per side.


MATERIAL SPECIFICATIONS

Element: Self-supporting copper-nickel alloy or nickel-chrome alloy, depending on resistance value

Body: Steatite ceramic case with inorganic potting compound

Terminals: Tinned copper

Part Marking: Dale, Model, Wattage, Value, Tolerance, Date Code



PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Thermal Shock	- 55 °C to + 275 °C, 5 cycles, 30 minute dwell time	± (5.0 % + 0.05 Ω) ΔR
Short Time Overload	5 x rated power for 5 seconds	± (4.0 % + 0.05 Ω) ΔR
Dielectric Withstanding Voltage	1000 V _{rms} for one minute	± (2.0 % + 0.05 Ω) ΔR
Low Temperature Operation	- 65 °C, full rated working voltage for 45 minutes	± (3.0 % + 0.05 Ω) ΔR
Bias Humidity	75 °C, 90 % - 100 % RH, 240 hours	± (5.0 % + 0.05 Ω) ΔR
Load Life	1000 hours at rated power, + 40 °C, 1.5 hours "ON", 0.5 hours "OFF"	± (5.0 % + 0.05 Ω) ΔR
Terminal Strength	5 to 10 second 10 pound pull test, torsion test - 3 alternating directions, 360° each	± (1.0 % + 0.05 Ω) ΔR
Resistance to Solder Heat	Terminal immersed 3.5 seconds in molten solder at 1/8" to 3/16" from body	± (1.0 % + 0.05 Ω) ΔR



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.