



- 1 HOUSING: PBT, UL 94V-0 RATED, COLOR-BLACK
CONTACTS: COPPER ALLOY PER ASTM B103
- 2 MOLDED CIRCUIT #1 IDENTIFIER IN LOCATION SHOWN.
- 3 0.00076[.000030] MIN GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] TIN-LEAD IN AREA E, ALL OVER 0.00127[.000050] MIN NICKEL.
- 4 0.00076[.000030] MIN GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] TIN IN AREA E, ALL OVER 0.00127[.000050] MIN NICKEL.
- 5 USE WITH #20-#22 AWG WIRE SIZE, .050 MAX INSULATION DIA., .015 MAX INSULATION WALL THICKNESS.
- 6 CONTACT IDENTIFICATION NUMBER "3" LOCATED IN THIS AREA.
- 7 AMP TRADEMARK (EITHER SIDE).
- 8 OBSOLETE PART NUMBER.
- 9 ROHS 2002/95/EC COMPLIANT.
- 10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

4 9	81.28	31	64	8-102448-0
4 9	76.20	29	60	7-102448-8
4 9	68.58	26	54	7-102448-5
4 9	63.50	24	50	7-102448-3
4 9	50.80	19	40	6-102448-8
4 9	43.18	16	34	6-102448-5
4 9	40.64	15	32	6-102448-4
4 9	38.10	14	30	6-102448-3
4 9	35.56	13	28	6-102448-2
4 9	33.02	12	26	6-102448-1
4 9	30.48	11	24	6-102448-0
4 9	27.94	10	22	5-102448-9
4 9	25.40	9	20	5-102448-8
4 9	22.86	8	18	5-102448-7
4 9	20.32	7	16	5-102448-6
4 9	17.78	6	14	5-102448-5
4 9	15.24	5	12	5-102448-4
4 9	12.70	4	10	5-102448-3
4 9	10.16	3	8	5-102448-2
4 9	7.62	2	6	5-102448-1
FINISH	B	A	NO. OF POSN	PART NO.

SUPERSEDED BY 1-102448-8	3	91.44	35	72	8	3-102448-4
SUPERSEDED BY 1-102448-3	3	88.90	34	70	8	3-102448-3
SUPERSEDED	3	86.36	33	68	8	3-102448-2
SUPERSEDED	3	83.82	32	66	8	3-102448-1
10 OBSOLETE	3	81.28	31	64		3-102448-0
SUPERSEDED BY 1-102448-3	3	78.74	30	62	8	2-102448-9
10 OBSOLETE	3	76.20	29	60		2-102448-8
SUPERSEDED BY 1-102448-3	3	73.66	28	58	8	2-102448-7
SUPERSEDED	3	71.12	27	56	8	2-102448-6
SUPERSEDED BY 1-102448-1	3	68.58	26	54	8	2-102448-5
SUPERSEDED BY 1-102448-1	3	66.04	25	52	8	2-102448-4
	3	63.50	24	50		2-102448-3
SUPERSEDED BY 1-102448-0	3	60.96	23	48	8	2-102448-2
SUPERSEDED BY 1-102448-0	3	58.42	22	46	8	2-102448-1
SUPERSEDED	3	55.88	21	44	8	2-102448-0
SUPERSEDED BY 102448-8	3	53.34	20	42	8	1-102448-9
	3	50.80	19	40		1-102448-8
SUPERSEDED BY 102448-7	3	48.26	18	38	8	1-102448-7
SUPERSEDED BY 102448-7	3	45.72	17	36	8	1-102448-6
10 SUPERSEDED BY 6-102448-5	3	43.18	16	34		1-102448-5
10 OBSOLETE	3	40.64	15	32		1-102448-4
	3	38.10	14	30		1-102448-3
10 OBSOLETE	3	35.56	13	28		1-102448-2
	3	33.02	12	26		1-102448-1
	3	30.48	11	24		1-102448-0
10 OBSOLETE	3	27.94	10	22		102448-9
	3	25.40	9	20		102448-8
	3	22.86	8	18		102448-7
	3	20.32	7	16		102448-6
	3	17.78	6	14		102448-5
	3	15.24	5	12		102448-4
	3	12.70	4	10		102448-3
10 SUPERSEDED BY 5-102448-2	3	10.16	3	8		102448-2
10 OBSOLETE	3	7.62	2	6		102448-1
FINISH	B	A	NO. OF POSN	PART NO.		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DTN: S. SHUEY 30DEC91
 CHK: M. RIDER 06JAN92
 APVD: R. FFLIX 07JAN92

STE TE Connectivity

AMPMODU MT, RCPT ASSY, STANDARD PRESSURE CONTACTS FOR 20-22 AWG WIRE SIZE

PRODUCT SPEC: 108-25015
 APPLICATION SPEC: 114-25032

SIZE: A1
 WEIGHT: 100779
 CUSTOMER DRAWING

SCALE: 4:1
 SHEET: 1 of 1
 REV: S